

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2004 OCT 7 AM 11 38

1. Type of Well
GAS

5. Lease Number
RECEIVED SF-078461

070 FARMINGTON, NM
6. If Indian, All. or
Tribe Name

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

7. Unit Agreement Name

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

8. Well Name & Number
Filan 7

API Well No.
30-045-21177

4. Location of Well, Footage, Sec., T, R, M

1180' FSL, 1840' FEL, Sec. 5, T-27-N, R-8-W, NMPM

10. Field and Pool
So Blanco Pictured Cliffs

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

Notice of Intent

☒ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☐ Other

13. Describe Proposed or Completed Operations

09/13/04 MIRU. ND WH. NU BOP. TIH w/gauge ring to 2194'. TOOH. TIH w/2-7/8" CIBP set @ 2194'. TIH w/70 jts 1-1/4" IJ tubing workstring. Load csg and circulate well with 10 bbls water. Attempt to PT csg to 500 PSI, Leak, 1 BPM @ 500 psi.

Plug #1: Pump 11 sxs Type III cmt (15 Cu ft) @ 2194' to 1748' inside csg to isolate the Pictured cliffs perforations. TOOH to 1128'. WOC.

09/14/04 TIH, tag top of cmt @ 1945'. Circ out 1.5 bbl cmt. Attempt to PT csg to 500#, bled down to 0# in 5 seconds. Plug #2: Pump 8 sxs Type III cement (11 cu ft) inside casing from 1945' to 1851' to cover Fruitland top. TOOH w/tubing. WOC. TIH, tag cmt @ 1851'. Circ w/water. TOOH to 1510'. Circ w/city water. Plug 2: Pump 12 sxs Type III cmt (16 cu ft) inside csg from 1510' to 1023' to cover the Kirtland and Ojo Alamo tops. TOOH w/tbg. WOC.

09/15/04 TIH, tag plug @ 1023'. Attempt to PT csg to 500#, bled down to 0# in 5 seconds. TOOH. TIH, Set CIBP @ 210'. Perforate 3 holes @ 193'. Est circulation out bradenhead w/9 bbl water. Circ bradenhead clean w/20 bbls water. Plug #3: Pump 64 sxs Type III cement

84 cu ft) down csg from 193' to surface. Circ 1 bbl cmt to surface. WOC. ND BOP. Dig out WH, cut off. Cmt down 15' in csg and at surface in annulus. Mix 15 sxs Type III cmt to fill csg, Install P&A marker. RD, Release Rig. (Matt Warren, BLM on location.

Well Plugged & Abandoned 09/15/04

14. I hereby certify that the foregoing is true and correct.

Signed Frances Bond Title Regulatory Specialist Date 10/05/04
fsb

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

ACCEPTED FOR RECORD

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

OCT 07 2004

NMOC

FARMINGTON FIELD OFFICE
BY gmm