submitted in lieu of Form 3160-5

UNITED STATES

DEPARTMENT	OF	THE	INTERI	OR
BUDEAU OF	T.A.Y	מא תנ	NAGEME	שימ

	and Repozts on Wells
1. Type of Well GAS	7.00 FARMINOTON NM6. Tribe Name
	7. Unit Agreement
Name of Operator BURLINGTON RESCURCES OIL & GAS CO	200 × 122 ×
PO Box 4289, Farmington, NM 87	8 Well Name & Num Johnston Federa 499 (505) 326-9700 9 API Well No. 30-045-30969
4. Location of Well, Footage, Sec., 2485'FNL, 615'FWL, Sec.12, T-30-	T, R, M 10% Field and Pool
	TE NATURE OF NOTICE, REPORT, OTHER DATA
Type of Submission Notice of Intent	Type of Action _ Abandonment Change of Plans _ Recompletion New Construction
X Subsequent Report	Plugging Back Non-Routine Fracturing Casing Repair Water Shut off
Final AbandonmentX	Altering Casing Conversion to Injection Other - casing, & cement
3. Describe Proposed or Complete	d Operations
9/2/04 Drill to TD @ 7222'. 9/3/04 TOOH. TIH w/169 jts 4 9 sxs Premium Lit CD-32, 6.25 pps L Premium Lite w/0. 1% fluid loss (58 cmt to surface. N 9/5/04 RU W/L. TIH w/gauge r @ 6700-5500', CBL	
9/2/04 Drill to TD @ 7222'. 9/3/04 TOOH. TIH w/169 jts 4 9 sxs Premium Lit CD-32, 6.25 pps L Premium Lite w/0. 1% fluid loss (58 cmt to surface. N 9/5/04 RU W/L. TIH w/gauge r @ 6700-5500', CBL	Circ hole clean1/2" 10.5# J-55 ST&C csg, set @ 7219'. Cmtd w/ e HS Scavenger cmt w/0.25 pps celloflake, 0.3% CM-1, 1% fluid loss (28 cu. ft.). Tail w/297 sxs 25 pps celloflake, 0.3% CD-32, 6.25 pps LCM-1, 8 cu. ft.). Displaced w/115 bbls fresh wtr. No D BOP. NU WH. RD. Rig released. ing to 7208'. Ran CBL-GR-CCL @ 7206-6700', GR-CCL -GR-CCL @ 5500-1000', GR-CCL @ 1000' to surface. hoe @ 2855'. RD W/L.
9/2/04 Drill to TD @ 7222'. 9/3/04 TOOH. TIH w/169 jts 4 9 sxs Premium Lit CD-32, 6.25 pps L Premium Lite w/0. 1% fluid loss (58 cmt to surface. N 9/5/04 RU W/L. TIH w/gauge r @ 6700-5500', CBL	Circ hole clean1/2" 10.5# J-55 ST&C csg, set @ 7219'. Cmtd w/ e HS Scavenger cmt w/0.25 pps celloflake, 0.3% CM-1, 1% fluid loss (28 cu. ft.). Tail w/297 sxs 25 pps celloflake, 0.3% CD-32, 6.25 pps LCM-1, 8 cu. ft.). Displaced w/115 bbls fresh wtr. No D BOP. NU WH. RD. Rig released. ing to 7208'. Ran CBL-GR-CCL @ 7206-6700', GR-CCL -GR-CCL @ 5500-1000', GR-CCL @ 1000' to surface. hoe @ 2855'. RD W/L.
9/2/04 Drill to TD @ 7222'. 9/3/04 TOOH. TIH w/169 jts 4 9 sxs Premium Lit CD-32, 6.25 pps L Premium Lite w/0. 1% fluid loss (58 cmt to surface. N 9/5/04 RU W/L. TIH w/gauge r @ 6700-5500', CBL TOC @ 2250', 7" s	Circ hole clean1/2" 10.5# J-55 ST&C csg, set @ 7219'. Cmtd w/ e HS Scavenger cmt w/0.25 pps celloflake, 0.3% cM-1, 1% fluid loss (28 cu. ft.). Tail w/297 sxs 25 pps celloflake, 0.3% CD-32, 6.25 pps LCM-1, 8 cu. ft.). Displaced w/115 bbls fresh wtr. No D BOP. NU WH. RD. Rig released. ing to 7208'. Ran CBL-GR-CCL @ 7206-6700', GR-CCL -GR-CCL @ 5500-1000', GR-CCL @ 1000' to surface. hoe @ 2855'. RD W/L.
9/2/04 Drill to TD @ 7222'. 9/3/04 TOOH. TIH w/169 jts 4 9 sxs Premium Lit CD-32, 6.25 pps L Premium Lite w/0. 1% fluid loss (58 cmt to surface. N 9/5/04 RU W/L. TIH w/gauge r @ 6700-5500', CBL TOC @ 2250', 7" s	Circ hole clean1/2" 10.5# J-55 ST&C csg, set @ 7219'. Cmtd w/ e HS Scavenger cmt w/0.25 pps celloflake, 0.3% cM-1, 1% fluid loss (28 cu. ft.). Tail w/297 sxs 25 pps celloflake, 0.3% CD-32, 6.25 pps LCM-1, 8 cu. ft.). Displaced w/115 bbls fresh wtr. No D BOP. NU WH. RD. Rig released. ing to 7208'. Ran CBL-GR-CCL @ 7206-6700', GR-CCL -GR-CCL @ 5500-1000', GR-CCL @ 1000' to surface. hoe @ 2855'. RD W/L.
9/2/04 Drill to TD @ 7222'. 9/3/04 TOOH. TIH w/169 jts 4 9 sxs Premium Lit CD-32, 6.25 pps L Premium Lite w/0. 1% fluid loss (58 cmt to surface. N 9/5/04 RU W/L. TIH w/gauge r @ 6700-5500', CBL TOC @ 2250', 7" s	Circ hole clean1/2" 10.5# J-55 ST&C csg, set @ 7219'. Cmtd w/ e HS Scavenger cmt w/0.25 pps celloflake, 0.3% cM-1, 1% fluid loss (28 cu. ft.). Tail w/297 sxs 25 pps celloflake, 0.3% CD-32, 6.25 pps LCM-1, 8 cu. ft.). Displaced w/115 bbls fresh wtr. No D BOP. NU WH. RD. Rig released. ing to 7208'. Ran CBL-GR-CCL @ 7206-6700', GR-CCL -GR-CCL @ 5500-1000', GR-CCL @ 1000' to surface. hoe @ 2855'. RD W/L.
9/2/04 Drill to TD @ 7222'. 9/3/04 TOOH. TIH w/169 jts 4 9 sxs Premium Lit CD-32, 6.25 pps L Premium Lite w/0. 1% fluid loss (58 cmt to surface. N 9/5/04 RU W/L. TIH w/gauge r @ 6700-5500', CBL TOC @ 2250', 7" s	Circ hole clean1/2" 10.5# J-55 ST&C csg, set @ 7219'. Cmtd w/ e HS Scavenger cmt w/0.25 pps celloflake, 0.3% CM-1, 1% fluid loss (28 cu. ft.). Tail w/297 sxs 25 pps celloflake, 0.3% CD-32, 6.25 pps LCM-1, 8 cu. ft.). Displaced w/115 bbls fresh wtr. No D BOP. NU WH. RD. Rig released. ing to 7208'. Ran CBL-GR-CCL @ 7206-6700', GR-CCL -GR-CCL @ 5500-1000', GR-CCL @ 1000' to surface. hoe @ 2855'. RD W/L. egoing is true and correct. ACCEPTED FOR RE