Form 3160- 5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-013

OMB No. 1004-,0135 Expires: November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

NIM - 0468126 65 If Indian, Allottee, or Tribe Name

abar	idoned well. Use Form 316	0-3 (APD) for such p	roposals. 🕦 🗸 💮	[نــ-		
SUBMIT IN TRIPL	ICATE- Other Instruc	tions on the rev	erse side	7.0 if Unit or 0	CA. Agreement Design	ation
1. Type of Well Oil Well X Gas Well	Other	070 FARMU	STON HM	8. Well Nam	ne and No.	
2. Name of Operator			MAR STRUCTURE		Callow 1S	
Coleman Oil & Gas, Inc				9. API Well	No.	
3a. Address		3b. Phone No. (inclu	ide area code)		30-045-32549	
P.O. Drawer 3337, Farmington, NM 87499 505-327-0356			10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Basin Fruitland Coal		
				11. County of	or Parish, State	
1790' FNL and 1980' FEL SEC 27, T29N, R12W, NMPM				San	Juan	NM
12. CHECK APPROP	PRIATE BOX(S) TO IND	CATE NATURE OF	NOTICE, REPORT	r, or oth	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent	Acidize	Deepen	Production (Start/	Resume)	Water Shut-off	
	Altering Casing	Fracture Treat	Reclamation		Well Integrity	
X Subsequent Report	Casing Repair	New Construction	Recomplete		Other	
	Change Plans	Plug and abandor	n Temporarily Aband	lon		
Final Abandonment Notice	Convert to Injection	Plug back	Water Disposal			
13. Describe Proposed or Completed 0 If the proposal is to deepen direction Attack the Bond under which the	onally or recomplete horizontally	r, give subsurface location	ns and measured and true	vertical depth	s or pertinent markers	and sands.

SPUD WELL OCTOBER 7, 2004 @ 11:00 AM. DRILLED 8 3/4" HOLE TO 140 FT. KB. RAN 3 JTS OF 7" 20# J-55 ST&C NEW CASING. RAN A TOTAL FOOTAGE OF 126.08 FT. AND LANDED @ 131.08 FT. KB. CEMENTED W/ 75 SACKS CLASS B W/ 2% CALCIUM CHLORIDE AND 1/4# PER SACK CELLOFLAKE. CIRCULATED 7 BARRELS OF CEMENT TO RESERVE PIT. NIPPLED UP BOP AND MANIFOLD. PRESSURE TESTED BOP, MANIFOLD AND CASING TO 750 PSIG. DRILLED 6 1/4" HOLE TO 1260 FT. KB. TD WELL @ 1260 FT.KB. @ 3:00 PM ON OCTOBER 11, 2004. RAN A TOTAL OF 32 JTS 4 1/2" 10.50#/FT ST&C J-55. LANDED CASING AT 1250.56 FT. KB. CEMENTED W/ 75 SACKS CLASS G W/ 3% D79 AND 1/4# PER SACK D29. TAILED W/ 50 SACKS CLASS G 50/50 POZ W/ 2% GEL D20, 5# PER SACK D24 GILSONITE, .1% D46, 1% S-1 AND1/4# PER SACK D29. CIRCULATED 10 BARRELS OF CEMENT TO SURFACE.

following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notice shall be filed only after all requirements, including reclamantion, have been completed, and the operator has

NO OPEN HOLE LOGS RAN.

determined that the site is ready for final inspection.)

NO OF LIVIOLE LOGGITAIN.		
14. I hereby certify that the foregoing is true and correct. Name (Printed/ Typed)	Title	
MICHAEL T. HANSON	ENGINEER	
Signature Manhaul T. Jano	October 26, 2004	ACCEPTED FOR RECORD
THIS SPACE FOR FE	DERAL OR STATE OFFICE USE	
Approved by	Title	
Conditions of approval, if any are attached. Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon.		FARMINGTON FIELD OFFICE BY

Title 18 U.S.C. Section 1001 AND Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitiousor fraudulent statements or representations as to any matter within its jurisdiction.