

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

070 FARMINGTON NM

5. Lease Designation and Serial No.

NM 10089

6. If Indian, Allotted or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Mary Anne #1

9. API Well No.

30 045 05121

10. Field and Pool, or Exploratory Area

Bisti Lower Gallup

11. County or Parish, State

San Juan, NM

1. Type of Well



Oil

Well



Gas

Well



Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325 - 1821

Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 660' FWL (SW/4 SW/4)

Unit M, Sec. 9, T24N, R9W, NMPM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION



Notice of Intent



Subsequent Report



Final Abandonment Notice

TYPE OF ACTION



Abandonment



Recompletion



Plugging Back



Casing Repair



Altering Casing



Other



Change of Plans



New Construction



Non-Routine Fracturing



Water Shut-Off



Conversion to Injection



Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows:

Set 2-7/8" cement retainer at 4400'. Pump 124 cu ft Class B below retainer. Gallup plug 4400'-4900'. Spot 12 cu ft Class B plug 2710'-2340' to cover Mesaverde top. Perforate 2-7/8" at 1700', 50' below Pictured Cliffs top. Set cement retainer at 1650'. Pump 257 cu ft Class B below retainer and spot 14 cu ft on top of retainer. Pictured Cliffs/Fruitland plug 1700'-1270'. (Following step was amended from initial approval by Steve Mason) Set retainer at 850'. Pump 117 cu ft Class B below retainer and into hole in casing at 916'. Spot 7 cu ft plug on top of retainer. Ojo Alamo plug 916'-700'. Perforate at 359'. Pump 162 cu ft Class B through hole and circulate 5 bbls to surface. Surface plug surface - 359'. Set dry hole marker. Job complete 10/1/2004.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander
John Alexander

Vice-President

Date

10/07/2004

(This space for Federal or State office use)

ACCEPTED FOR RECORD

Approved by

Title

Date

OCT 20 2004

Conditions of approval, if any:

FARMINGTON FIELD OFFICE

BY *Sm*

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMUCD