

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

## Sundry Notices and Reports on Wells

2004 OCT 25 PM 2 50

## 1. Type of Well

GAS

RECEIVED

070 FARMINGTON NM

## Lease Number

NMSF-065546-A

If Indian, All. or

Tribe Name

Unit Agreement Name

## 2. Name of Operator

**BURLINGTON**

RESOURCES OIL &amp; GAS COMPANY

## 3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

## 4. Location of Well, Footage, Sec., T, R, M

660' FNL, 660' FWL, Sec.19, T-28-N, R-10-W, NMPM

## Well Name &amp; Number

Brink #2

## API Well No.

30-045-07381

## 10. Field and Pool

Basin Fruitland Coal

## 11. County and State

San Juan Co, NM

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

## Type of Action

☐ Notice of Intent☒ Abandonment☐ Change of Plans☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging Back☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection☐ Other -

## 13. Describe Proposed or Completed Operations

10/13/04 MIRU. Dig out WH. Well pressure:130# csg, 25# tbq and BH zero. Blow well down. NU BOP and test. TOH with 1-1/4" EUE tbq. Round trip 3-1/2" gauge ring to 1676'. RU wireline truck. Set 3-1/2" CR at 1676'. TIH with tbq to CIBP. Load csg with 18 bbls wtr and est clean circ. Sting into CR. Attempt to pressure test csg annulus, leak 1 bpm at 600#. Then est rate below CR of 2 bpm at 1300#, est circ out csg. Shut in csg valve. **Plug #1** with CR at 1676', mix and pump 19 sxs Type III cmt (26 cf), squeeze 10 sxs below CR and leave 9 sxs inside the csg above CR up to 1445' to fill the FTC perfs and cover the Fruitland top. TOH and WOC.

10/14/04 TIH and tag cmt @ 1517'. PT to 500#; held OK. TOH with tbq. Perf 4 holes @ 977'. Pump down the 3-1/2" csg and est rate into sqz holes 1 bpm at 200#. **Plug #2** mix & pump 164 sxs Type III cmt (216 cf), sqz 150 sxs outside the 3-1/2" and 6-5/8" csqs from 977' to 690' to cover the Kirtland & Ojo Alamo tops; and leave 14 sxs inside the 3-1/2" csg @ 640'. Perf 3 holes at 119'. Est circ to surface out the bradenhead and 3-1/2" x 6-5/8" annulus. **Plug #3** with 85 sxs Type III cmt (112 cf) pump down the 3-1/2" csg from 119' to surface, first circ good cmt out the bradenhead and then out the annulus. Shut in & WOC. ND BOP. Dig out and cut off WH. Found cement at surface in 3-1/2" csg and the bradenhead annulus; also found it down 30' in the 3-1/2" x 6-5/8" annulus. Install P&A marker with 20 sxs cmt. RD. Rig released. Jim Wright, BR, and Virgil Lucero, BLM, were on location.

The well was plugged and abandoned on 10/14/04.

## 14. I hereby certify that the foregoing is true and correct.

Signed Tammy Jones Title Regulatory Specialist Date 10/25/04

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

Date ACCEPTED FOR RECORD

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

OCT 26 2004

NMOC

FARMINGTON FIELD OFFICE  
BY Jim