

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)5. LEASE DESIGNATION AND SERIAL NO.
NM 11299 (terminated)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

30-029-20551
7. UNIT AGREEMENT NAME
EAST PUERTO CHIQUITO
MANGOS

8. FARM OR LEASE NAME

9. WELL NO.

24 (A-9)

10. FIELD AND POOL, OR WILDCAT

Puerto Chiquito Mangos East

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 9, T-26N, R-1E

12. COUNTY OR PARISH

13. STATE

Rio Arriba New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER Dry hole

2. NAME OF OPERATOR

BENSON-MONTIN-GREER DRILLING CORP.

3. ADDRESS OF OPERATOR

221 Petroleum Center Building, Farmington NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface

270' FNL, 825' FEL, Sec. 9, T-26N, R-1E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7080' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugging operations:

2-25-81 Moved in B-M-G Rig 13 to plug and abandon well.

3- 2-81 Spotted bottom hole cement plug 10 sacks (2 bbls. slurry) down 2-3/8" tubing set 1 foot above PBTD. (Cement plug from 1796' to 1575').
Pulled tubing open ended at 545'. Spotted 25 sacks (5 bbls. slurry) down 2-3/8" tubing. Circulated cement to surface. (Cement plug from 545' to surface).

3- 4-81 Erected dry hole marker. Cleaned location and moved off.

NOTE: Per telephone 2/27/81 Virgil L. Stoabs, B-M-G, to Bruce Wamsley, U.S.G.S. Engineer - verbal approval to plug well as above.

Per telephone 3-30-81 Virgil L. Stoabs, B-M-G, to Jim Sims, U.S.G.S. District Engineer, Farmington. Requested by Mr. Sims to explain on Sundry Notice the sequence of events and dates that resulted in failure of operator to comply with attachment to Notice of Intention to Abandon as approved March 23, 1981.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Vice-President

DATE

7-20-82

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

APR 16 2003

*See Instructions on Reverse Side

/s/ Brian W. Davis