Submit 3 Copies to Appropriate District Office

## State of New Mexico Inergy, Minerals and Natural Resources Departmen

PN

Form C-103 Revised 1-1-89

DIGIDIOTI	V				**	
DISTRICT I P.O. Box 1980, Hobbs, NM 88240  OIL CONSERVATION DIVISION 2040 Pacheco Story 2425			WELL API NO.			
DISTRICT II	2040 Pa	icheco St	52 (4 (3 (6) S)	30-045-05394		
P.O. Drawer DD, Artesia, NM 8821	o Santa Fe,	NM SVSO		5. Indicate Ty	pe of Lease STATE X	FEE 🗌
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87	<b>/</b> 410		OCT 2004	State Oil & E 6597	Gas Lease No.	
SUNDRY NOTICES AND REPORTS ON WELL'S DIV.						
(DO NOT USE THIS FORM FOR PORPOSALS TO DRILL OR TO DEBEEN OR PLUG BACK TO A  DIFFERENT RESERVOIR. USE "APPLICATION FOR DEBUT"  (FORM C-101) FOR SUCH PROPOSALS)						Vame
1. Type of Well:	Central Bisti U	Init				
OIL GAS C						
2. Name of Operator	J OTHER			8. Well No.		
Elm Ridge Resources, Inc.				#44		
3. Address of Operator				9. Pool name or Wildcat		
PO Box 156 Bloomfield, NM 87413				Bisti Lower Gallup		
4. Well Location						
Unit Letter F	1980 Feet From Thε_	North	Line and	1979	Feet From The	West Line
Section 16	Township 25N	Range 12W	7	NMPM		San Juan County
	10. Elevation	•	ther DF, RKB, RT,	GR, etc.)		
		6245			<u> XIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII</u>	
	Appropriate Box to	o Indicat	1	•	•	
NOTICE OF INTENTION TO:				SUBSEQUE	NT REPORT (	)F:
PERFORM REMEDIAL WORK	PLUG AND ABANDON		REMEDIAL WOR	ĸ	ALTERING CAS	ing 🗌
TEMPORARILY ABANDON	CHANGE PLANS		COMMENCE DRI	LLING OPNS.	PLUG AND ABA	ANDONMENT X
PULL OR ALTER CASING	] .		CASING TEST AN	ND CEMENT JOB		
OTHER:		_ 🔲	OTHER:			🗆
12. Describe Proposed or Completed Oper	rations (Clearly state all pertinent de	tails, and give p	ertinent date, including	estimated date of start	ing any proposed	
work) SEE RULE 1103.						
Elm Ridge Resources, Inc. Plug and Abandoned the above referenced well as of 10/8/2004 as follows:						
Plug 1) Set retainer @ 3523'. Pumped 55 sks under retainer and 17 sks on top. Plug2) Shot 2 holes @						
1925'. Set retainer @ 1873'. Pumped 55 sks. Under retainer and left 18 sks on top. Plug 3) Shot 2 holes						
@ 1550'. Set retainer @ 1493'. Pump 55 sks under retainer and 17 sks on top. Plug 4) Shot 2 holes @						
1200'. Set retainer @ 1145'. Pumped 55 sks under and 17 sks on top. Plug 5) Shot 2 holes @ 870'. Set						
retainer @ 828'. Pumped 40 sks on top of retainer set plug from 870' - 670' inside casing. Plug 6) Shot 2						
holes @ 275'. Pumped 155 sks of cement inside and out. Circulated cement to surface. All witnessed by						
Inspector Bruce Martin.						
- (h.						
SIGNATURE	y Marky		TITLE Pro	dcution Assista	nt DATE	10/22/04
TYPE OR PRINT NAME	Amy Mackey				TELEPHONE NO. 50:	5-632-3476 ext. 201
(This space for State Use)	/20				R, DIST. & OCT	2 5 2004
APPROVED BY V	Manueva		TITLE		DATE	
CONDITIONS OF APPROVAL, IF A	NY:					