

PN

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells


1. Type of Well
GAS

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1030' FSL, 840' FEL, Sec. 36, T-32-N, R-9-W, NMPM, San Juan County

API # (assigned by OCD)
30-045-24200
5. Lease Number
6. State Oil&Gas Lease #
E-3150-11
7. Lease Name/Unit Name
San Juan 32-9 Unit
8. Well No.
63A
9. Pool Name or Wildcat
Blanco Mesaverde
10. Elevation:



Type of Submission	Type of Action
☐ Notice of Intent	☒ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☐ Other -
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

8-17-04 MIRU. Dig out WH. Install new bradenhead valve. SDON.
8-18-04 ND WH. NU BOP. TOO H w/197 jts 2 3/8" tbgs. TIH w/csg scraper to 5384'. TOO H.
TIH w/cmt retainer, set @ 5371'. SDON.
8-19-04 PT tbgs to 1300 psi, OK. Load hole w/80 bbl wtr. PT csg to 500 psi, OK. Plug #1:
pump 12 sx Type III cmt on top of cmt retainer inside csg @ 5198-5371' to
isolate Mesaverde interval. Displace w/20 bbl wtr. TOO H to 3848'. Load csg
w/wtr. Plug #2: pump 71 sx Type III cmt inside csg @ 2801-3848' to cover
Pictured Cliffs & Fruitland tops. Displace w/11 bbl wtr. TOO H. TIH, perf 3 sqz
holes @ 1970'. Attempt to establish injection. (Verbal approval to change
plans from Henry Villanueva, OCD). Plug #3: pump 30 sx Type III cmt inside
csg @ 1578-2020' to cover Kirtland & Ojo Alamo tops. Displace w/6 bbl wtr.
TOO H. Load csg w/wtr. Pump 12 sx Type III cmt outside csg through sqz holes.
Displaced to 1758'. WOC. SDON.
8-20-04 TIH, tag TOC @ 1660'. TOO H. TIH, perf 3 sqz holes @ 690'. Establish injection
to 1000 psi. Reperf 3 sqz holes @ 640'. Attempt to establish injection.
(Verbal approval to change procedure from Henry Villanueva, OCD). TOO H. TIH,
perf 3 sqz holes @ 530'. Attempt to establish injection. TIH to 740'. Plug #4:
pump 17 sx Type III cmt inside csg @ 490-740' to cover Nacimiento top. TOO H.
Load csg w/wtr. Sqz 3 sx Type III cmt outside csg. Pressured up to 1000 psi.
Displace to 490'. TOO H. TIH, perf 3 sqz holes @ 278'. Establish circ down csg,
out bradenhead & 7" annulus. Plug #5: pump 100 sx Type III cmt down csg & out
bradenhead. Circ 2 bbl cmt out 7" annulus & bradenhead. ND BOP. Cut off WH.
Install dry hole marker w/20 sx Type III cmt. RD. Rig released.

Well plugged and abandoned 8-20-04

SIGNATURE Nancy Oltmanns Senior Staff Specialist September 23, 2004

(This space for State Use)

Approved by H. Villanueva Title DEPUTY OIL & GAS INSPECTOR, DIST. 10 Date NOV - 5 2004

11-5-04