## NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1

## Revised 11/16/98 NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST Operator Williams Production Lease Name Rosa Well No\_109 Location of Well:Unit Letter G Sec 7 Twp 3 N Rge 5 W API # 30-0 392.352.000 NAME OF RESERVOIR OR POOL TYPE OF PROD. METHOD OF PROD. PROD.MEDIUM (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper Completion R.SA 109 GAILUP Completion GAC PRE-FLOW SHUT-IN PRESSURE DATA Hour, date shut-in Upper Length of time shut-in SI press. Psig Completion Stabilized? (Yes or No) 4-10-03 1000 Lower Completion 4-10-03 1000 Commenced at (hour, date)\* 4- 14-03 Zone producing (Upper or Lower): Lower LAPSED TIME **PRESSURE** PROD. ZONE (hour,date) SINCE. REMARKS Upper Completion Lower Completion 4-15-03 24/25 Production rate during test BOPD based on\_ \_\_\_\_\_Bbls. in\_\_\_\_\_Hours\_\_\_\_\_Grav.\_\_\_\_GOR MCFPD; Tested thru (Orifice or Meter): MID-TEST SHUT-IN PRESSURE DATA Upper Hour, date shut-in Length of time shut-in Completion St press psig Stabilized? (Yes or No) Hour, date shut-in Lower Length of time shut-in Completion

SI press. psig

Stabilized? (Yes or No)

## FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lowr):	
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion		PROD. ZONE	REMARKS
				•	
			·		
<u> </u>					
Production ra	ate during test				
Oil:BOPD based on Gas:MCFPD:To			Bt	ols. inHour	sGravGOR
Gas:	·····	MC	FPD:Tested thru	(Orfice or Meter):	
Remarks:					
I hereby certi	fy that the inform	mation herein co	ontained is true a	nd complete to the b	es of my knowledge.
Approved		20	Operate	or Williams	PRODUCTION
New Mexico O	il Conservation D	ivision	Ву _	fullians	
By Charl	ii Kerr	_	Title	Tech H	
DEPUTY OIL & GAS HISPECTOR, DIST. &3				4-17-07	
Title			Date -	7-17-05	<del></del>

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage lest shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice; once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azlec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).