

SUBMIT IN DUPLICATE
(Other instructions on
reverse side)FORM APPROVED
OMB NO. 1004-0137
Expires: February 28, 1995UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

5. LEASE DESIGNATION AND SERIAL NO.

NM-16057

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.

High Dollar Com #90

9. API Well No.

30-045-30770

10. FIELD AND POOL, OR WILDCAT

Basin Fruitland Coal

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Unit N

Sec. 8, T30N, R14W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

1.a. TYPE OF WELL:

OIL

WELL

☐

GAS

WELL

☒

DRY

☐

OTHER

☐

b. TYPE OF COMPLETION:

NEW

☒

WORK

☐

DEEP-

☐

PLUG

☐

DIFF.

☐

CENTR.

☐

OTHER

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface 675' FSL & 1335' FWL (SE/4 SW/4)

At top prod. interval reported below

same

At total depth

same

14. PERMIT NO.

DATE ISSUED

15. DATE SPUNDED

12/10/2001

16. DATE T.D. REACHED

12/13/2001

17. DATE COMPL.

(Ready to prod.)

12/4/2002

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

5511' GL

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

1140'

21. PLUG BACK T.D., MD & TVD

1086'

22. IF MULTIPLE COMPL.,
HOW MANY*23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

TD

24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD)*

810'-970' (Fruitland Coal)

26. TYPE ELECTRIC AND OTHER LOGS RUN

GR-CCL-CNL

25. WAS DIRECTIONAL SURVEY MADE

no

27. WAS WELL CORED

no

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
7"	20#	125'	8-3/4"	50 sx Class "B" neat w/1/4# celloflake	
4-1/2"	10.5#	1135'	6-1/4"	60 sx Lodense & 1/4# celloflake/sx. Tail with 60 sx neat w/1/4#	
				celloflake/sx. Displace w/17-1/2 H2O.	
				194 cu ft total cement	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SBT (MD)
					2-3/8"	1002'	NA

31. PERFORATION RECORD (Interval, size and number)

810'-816'; 956'-970' w/4 spf (total 80 holes)

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
810'-970'	150 gals formic acid; 45,000# 20/40 Brady
	sand; 20,000# 20/40 resin sand; 32,400 gals
	AmBor Max 1020

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping - size and type of pump)					WELL STATUS (Producing or shut in)	
N/A		flowing					shut in	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL - BBL.	GAS - MCF.	WATER - BBL.	GAS - OIL RATIO	
12/9/2002	24 hrs	1/2"	→	0	90 (est)	95 (est)	N/A	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24 - HOUR RATE	OIL - BBL.	GAS - MCF.	WATER - BBL.	OIL GRAVITY - API (CORR.)		
N/A	170	→	0	90 (est)	95 (est)	N/A		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)


vented - to be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED



Title Vice-President

Date

FARMINGTON FIELD OFFICE

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof: cored intervals; and all drill-stem, tests, including depth interval tested on used, time tool open, flowing and shut-in pressures, and recoveries):

38.

GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP		TRUE VERT. DEPTH
					MEAS. DEPTH		
				Ojo Alamo	---		
				Kirtland	surface		
				Fruitland	645'		
				Pictured Cliffs	976'		
				Total Depth	1140'		