

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

FORM APPROVED
OMB NO. 1004-0135
Expires: November 30, 2000

5. Lease Serial No.
NMSF078284

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.
NMNM78416B

8. Well Name and No.
SAN JUAN 29-6 UNIT 75M

9. API Well No.
PHIL 10-6339-27553-00-X1 39-27553

10. Field and Pool, or Exploratory
BASIN DAKOTA
BLANCO MESAVERDE

11. County or Parish, and State
RIO ARriba COUNTY, NM

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
CONOCOPHILLIPS COMPANY
Contact: CHRIS GUSTARTIS
E-Mail: CHRISTINA.GUSTARTIS@CONOCO

3a. Address
P O BOX 2197 WL 6106
HOUSTON, TX 77252

3b. Phone No. (include area code)
Ph: 832.486.2463

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Sec 23 T29N R6W SESE 10FSL 655FEL
36.70394 N Lat, 107.42499 W Lon

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Drilling Operations
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Casing was set in this well as per the attached wellbore schematic.



14. I hereby certify that the foregoing is true and correct.
**Electronic Submission #51903 verified by the BLM Well Information System
For CONOCOPHILLIPS COMPANY, sent to the Farmington
Committed to AFMSS for processing by ADRIENNE BRUMLEY on 12/17/2004 (05AXB0500SE)**

Name (Printed/Typed) CHRIS GUSTARTIS

Title AUTHORIZED REPRESENTATIVE

Signature (Electronic Submission)

Date 12/15/2004

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By **ACCEPTED**

ADRIENNE BRUMLEY
Title PETROLEUM ENGINEER

Date 12/17/2004

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Farmington

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

NMCOO

END OF WELL SCHEMATIC

Well Name: San Juan 29-6 #75M
 API #: 30-039-27553
 Location: 10' FSL & 655' FEL
Sec. 23 - T29N - R6W
Rio Arriba County, NM
 Elevation: 6448' GL (above MSL)
 Dri Rig RKB: 13' above Ground Level
 Datum: Dri Rig RKB = 13' above GL

11" 3M x 7 1/16" 5M Tubing Head
 11" 3M x 11" 3M Casing Spool
 9-5/8" 8 RD x 11" 3M Casing Head

Spud: 6-Dec-04
 Spud Time: 19:00
 Date TD Reached: 13-Dec-04
 Release Dri Rig: 14-Dec-04
 Release Time: 0:00

Surface Casing Date set: 7-Dec-04
 Size 9 5/8 in
 Set at 227 ft # Jnts: 5
 Wt. 32.3 ppf Grade H-40
 Hole Size 12 1/4 in Conn STC
 Excess Cmt 125 %
 T.O.C. SURFACE Csg Shoe 227 ft
 TD of 12-1/4" hole 227 ft

Notified BLM @ 08:12 hrs on 03-Dec-04
 Notified NMOCD @ 08:16 hrs on 03-Dec-04

Intermediate Casing Date set: 10-Dec-04
 Size 7 in 85 jts
 Set at 3648 ft 0 pups
 Wt. 20 ppf Grade J-55
 Hole Size 8 3/4 in Conn STC
 Excess Cmt 150 % Top of Float Collar 3603 ft
 T.O.C. SURFACE Bottom of Casing Shoe 3648 ft
 Pup @ ft TD of 8-3/4" Hole 3651 ft
 Pup @ ft
 Notified BLM @ 12:15 hrs on 09-Dec-04
 Notified NMOCD @ 12:15 hrs on 09-Dec-04

Production Casing: Date set: 13-Dec-04
 Size 4 1/2 in 185 jts
 Set at 7860 ft 2 pups
 Wt. 11.6 ppf Grade N-80
 Hole Size 6 1/4 in Conn LTC
 Excess Cmt 50 % Top of Float Collar 7858 ft
 T.O.C. (est) Bottom of Casing Shoe 7860 ft
 Marker Jt @ 4964 ft TD of 8-3/4" Hole 7861 ft
 Marker Jt @ 7513 ft
 Marker Jt @ ft
 Notified BLM @ 10:15 hrs on 12-Dec-04
 Notified NMOCD @ 10:15 hrs on 12-Dec-04

Top of Float Collar 7858 ft
 Bottom of Casing Shoe 7860 ft

TD of 8-3/4" Hole: 7861 ft

Surface Cement

Date cmt'd: 7-Dec-04
 Lead : 150 sx Class G Cement
+ 3% S001 Calcium Chloride
+ 0.25 lb/sx D029 Cellophane Flakes
1.16 cuft/sx, 174.0 cuft slurry at 15.8 ppg
 Displacement: bbls fresh wtr
 Bumped Plug at:
 Final Circ Press: 118 psi @ 0.4 bpm
 Returns during job:
 CMT Returns to surface: trace
 Floats Held: No floats used
 W.O.C. for 8.00 hrs (plug bump to start NU BOP)
 W.O.C. for 13.50 hrs (plug bump to test csg)

Intermediate Cement

Date cmt'd: 10-Dec-04
 Lead : 390 sx Class G Cement
+ 0.25 lb/sx D029 Cellophane Flakes
+ 3% D079 Extender
+ 0.20% D046 Antifoam
+ 10.00 lb/sx Phenoseal
2.72 cuft/sx, 1060.8 cuft slurry at 11.7 ppg
 Tail : 220 sx 50/50 POZ : Class G Cement
+ 0.25 lb/sx D029 Cellophane Flakes
+ 2% D020 Bentonite
+ 1.50 lb/sx D024 Gilsonite Extender
+ 2% S001 Calcium Chloride
+ 0.10% D046 Antifoam
+ 6 lb/sx Phenoseal
1.31 cuft/sx, 292.6 cuft slurry at 13.5 ppg
 Displacement: 146.1 bbls
 Bumped Plug at: 11:00 hrs w/ 1510 psi
 Final Circ Press: 1025 psi @ 2 bpm
 Returns during job: YES
 CMT Returns to surface: 35 bbls
 Floats Held: X Yes No
 W.O.C. for 6.00 hrs (plug bump to start NU BOP)
 W.O.C. for 9.50 hrs (plug bump to test csg)

Production Cement

Date cmt'd: 13-Dec-04
 Cement : 465 sx 50/50 POZ : Class G Cement
+ 0.25 lb/sx D029 Cellophane Flakes
+ 3% D020 Bentonite
+ 1.00 lb/sx D024 Gilsonite Extender
+ 0.25% D167 Fluid Loss
+ 0.15% D065 Dispersant
+ 0.10% D800 Retarder
+ 0.10% D046 Antifoam
+ 3.5 lb/sx Phenoseal
1.45 cuft/sx, 674.25 cuft slurry at 13.0 ppg
 Displacement: 122 bbls
 Bumped Plug: 17:30 hrs w/ 2150 psi
 Final Circ Press: 1650 psi @ 2.0 bpm
 Returns during job: None Planned
 CMT Returns to surface: None Planned
 Floats Held: X Yes No

Schematic prepared by:
 Michael P. Neuschafer, Drilling Engineer
 15-December-2004

COMMENTS:

9-5/8" Surf: No float equipment was run. Ran a guide shoe and an aluminum baffle plate 1 jt above the guide shoe @ 186'.
 Displaced top wiper plug with water. Shut in casing head and WOC before backing out landing jt.

Total:

7" Intermediate DISPLACED W/ 146.1 BBLs. FRESH WATER.
 CENTRALIZERS @ 3638', 3560', 3474', 3387', 3301', 3215', 206', 77', 38'.
 TURBOLIZERS @ 2701', 2658', 2615', 2572', 2528'.

Total: 9
 Total: 5

4-1/2" Prod. NONE.