

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
OMB No. 1004-0135  
Expires July 31, 1996

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Elm Ridge Resources, Inc.

3a. Address

PO Box 156, Bloomfield, NM 87413

3b. Phone No. (include area code)

505-635-3476

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

900' FNL & 900' FEL Sec. 15-T23N-R8W

5. Lease Serial No.

NMNM-18463

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or N

2 06

8. Well Name and No.

Federal 15 #41

9. API Well No.

30-045-24578 24678

10. Field and Pool, or Exploratory Area

Nageezi Gallup

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize <input type="checkbox"/> Deepen <input type="checkbox"/> Production (Start/Resume) <input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing <input type="checkbox"/> Fracture Treat <input type="checkbox"/> Reclamation <input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair <input type="checkbox"/> New Construction <input checked="" type="checkbox"/> Recomplete <input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans <input type="checkbox"/> Plug and Abandon <input type="checkbox"/> Temporarily Abandon
	<input type="checkbox"/> Convert to Injection <input type="checkbox"/> Plug Back <input type="checkbox"/> Water Disposal

13. Describe Proposed or Completed Operations (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports shall be filed within 30 days Following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once Testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Elm Ridge Resources Inc. Plug and Abandon the above reference well on 12-21-04 as follows: (see attached) .



14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Amy Mackey

Title

Production Technician

Signature

Date

December 23, 2004

THIS SPACE FOR FEDERAL OR STATE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

ACCEPTED FOR RECORD

JAN 04 2005

NMOCP

FARMINGTON FIELD OFFICE  
BY *Sm*

Plugs for the **Federal 15-41** as follows:

Plug 1) Set cement retainer @ 5160'. Pump 60 sks of cement on top of retainer and 60 sks under retainer.

Plug 2) Set 150' balanced plug @ 3030' – 2880'. Pumped 18 sks of cement.

Plug 3) Set 150' balanced plug @ 2370 – 2220'. Pumped 18 sks of cement.

Plug 4) Set 277' balanced plug @ 1577' – 1300'. Pumped 33 sks of cement.

Plug 5) Set 314' balanced plug @ 1134' – 820'. Pumped 36 sks of cement.

Plug 6) Set 165' balanced plug @ 652' – 487'. Pumped 19 sks. of cement.

Plug 7) Set 50' balanced plug @ 50' – Surface. Pumped 22 sks of cement.

All witnessed by BLM Inspector **Matthew Warren**.