Submit 3 Copies To Appropriate District	State of New Mex	ico		Form	C-103
Office	Energy, Minerals and Natura	-			4, 2004
<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240	Lifeigy, witherars and water		VELLAPI NO.	1716101	1 4, 2004
District II	OH CONGERNALENON			045-32359	
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION I	1.5	. Indicate Type o		
District III	1220 South St. Franc	is Dr.	STATE	FEE 🛛	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 875	505	State Oil & Gas		
1220 S. St. Francis Dr., Santa Fe, NM	,	0	. State Off & Gas	Lease IVO.	
87505					
	ES AND REPORTS ON WELLS		Lease Name or	Unit Agreement l	Vame
(DO NOT USE THIS FORM FOR PROPOSAL			Elliott	Gas Com D	
DIFFERENT RESERVOIR. USE "APPLICAT	FION FOR PERMIT" (FORM ©-101) FOR	CSUCH			
PROPOSALS.) 1. Type of Well:		2 8	. Well Number		
Oil Well Gas Well 🛛 O	ther 🗆 🔑 FED 2	005 🔄 l	1 C		
	Gro Constant				
2. Name of Operator	E OLCON	R 80000 TUR 1	. OGRID Numbe	er	
BP AMERICA PRODUCTION CO	V 17 6-18-18-18-18-18-18-18-18-18-18-18-18-18-		00778	*****	
3. Address of Operator	Variation.	1 - Ť	0. Pool name or		
P.O. BOX 3092 HOUSTON, TX 7	7079-2064	B B	lanco Mesaverd	e	
4. Well Location	411 M 6	38 12			
	200				
Unit Letter L: 2035	feet from the <u>South</u> line	e and <u>745</u> fee	t from the West	line	ĺ
	1				
Section 09		Range 09W	NMPM_SA	AN JUAN C	ounty
	11. Elevation (Show whether DR, I	RKB, RT, GR, etc.)			
	6158				
Pit or Below-grade Tank Application (For pi	t or below-grade tank closures, a form C	2-144 must be attached)			
Pit Location: ULSectTwpRng_	Pit typeDepth to Groundwater	Distance from near	est fresh water well	_	
1					i
Distance from nearest surface water	Relow-grade Tank Location III. S	lect Twn Rns	, ,		
Distance from nearest surface water		SectTwpRn	;		
Distance from nearest surface water		SectTwpRn	 ;		
		SectTwpRn	; ;		
feet from theline andfe	eet from theline			Data	
feet from theline andfe	propriate Box to Indicate Na	ture of Notice, Re	port or Other l		
feet from theline andfe 12. Check Ap NOTICE OF INT	propriate Box to Indicate Na	ture of Notice, Re	port or Other I	PORT OF:	
feet from theline andfe	propriate Box to Indicate Na	ture of Notice, Re	port or Other I		NG 🗆
12. Check Ap NOTICE OF INTI	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON	ture of Notice, Re SUBSE REMEDIAL WORK	eport or Other I	PORT OF: ALTERING CASI	NG 🗆
12. Check Ap NOTICE OF INTI	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON	ture of Notice, Re	eport or Other I	PORT OF: ALTERING CASI PLUG AND	NG 🗆
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK TEMPORARILY ABANDON	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS	ture of Notice, Re SUBSE REMEDIAL WORK COMMENCE DRILL	eport or Other I	PORT OF: ALTERING CASI	NG 🗆
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS	ture of Notice, Re SUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND	eport or Other I	PORT OF: ALTERING CASI PLUG AND	NG 🗆
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS	ture of Notice, Re SUBSE REMEDIAL WORK COMMENCE DRILL	eport or Other I	PORT OF: ALTERING CASI PLUG AND	NG 🗆
12. Check Ap NOTICE OF INTE PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS	ture of Notice, Re SUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB	eport or Other 1 EQUENT REF NG OPNS.	PORT OF: ALTERING CASI PLUG AND	
12. Check Ap NOTICE OF INTIPERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING OTHER:	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION	ture of Notice, Re SUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & S	eport or Other I	PORT OF: ALTERING CASI PLUG AND ABANDONMENT	
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or complete	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ded operations. (Clearly state all per	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & Sectionent details, and g	eport or Other I	PORT OF: ALTERING CASH PLUG AND ABANDONMENT s, including estim	□ ⊠
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & Sectionent details, and g	eport or Other I	PORT OF: ALTERING CASH PLUG AND ABANDONMENT s, including estim	□ ⊠
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion.	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all per plant). SEE RULE 1103. For Multiple	ture of Notice, Re SUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & S ertinent details, and g	eport or Other I	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co	□ □ ated date mpletion
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HO	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all per plant). SEE RULE 1103. For Multiple Cole & DRILL TO 150'. RU & RUN 9 9	ture of Notice, Re SUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & S ertinent details, and g	eport or Other I	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co	□ □ ated date mpletion
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HO YIELD 1.270 CLASS €. CIRC 10 bbls CMT	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all per plant). SEE RULE 1103. For Multiple Cole & DRILL TO 150'. RU & RUN 9.5 TO SURFACE.	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILLI CASING TEST AND CEMENT JOB OTHER: SPUD & S ertinent details, and g completions: Attac	EPORT OF Other I	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co	ated date mpletion
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOW YIELD 1.270 CLASS © CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all per points). SEE RULE 1103. For Multiple TO SURFACE. PSI LOW. TST OK. DRILL OUT CM1	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILLI CASING TEST AND CEMENT JOB OTHER: SPUD & SI ertinent details, and get Completions: Attact 5/8" 32# H-40 ST&C CSG	EPORT OF Other I	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 '-2555'. TIH & L/	ated date mpletion
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOW YIELD 1.270 CLASS © CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553". TIH & CMT 7	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all per points). SEE RULE 1103. For Multiple TO SURFACE. PSI LOW. TST OK. DRILL OUT CM1	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILLI CASING TEST AND CEMENT JOB OTHER: SPUD & SI ertinent details, and get Completions: Attact 5/8" 32# H-40 ST&C CSG	EPORT OF Other I	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 '-2555'. TIH & L/	ated date mpletion
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HO YIELD 1.270 CLASS €. CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553". TIH & CMT 7 TO SURFACE	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all periods). SEE RULE 1103. For Multiple DLE & DRILL TO 150'. RU & RUN 9.5 TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT "CSG; LEAD 260 sx 11.7 PPG CLS G CO.	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & SE ertinent details, and ge Completions: Attact 5/8" 32# H-40 ST&C CSG	EPORT OF Other I	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 '-2555'. TIH & L/ CLS G. CIRC 18 bb	ated date mpletion
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOVIELD 1.270 CLASS €. CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553". TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 `TIH & LAND 4 ½" 11.6#, J-55 LT&	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ded operations. (Clearly state all period). SEE RULE 1103. For Multiple Cole & DRILL TO 150'. RU & RUN 9 5 TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT " CSG; LEAD 260 sx 11.7 PPG CLS GO IN& 250 PSI LOW FOR 15 MIN - OK. C CSG @5553'. TIH & CEMENT 4 ½"	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & Section the Section of the Secti	EPORT OF Other I	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05.	ated date mpletion 2 PPG AND 7", is CMT
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOVIELD 1.270 CLASS €. CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553'. TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 `TIH & LAND 4 ½" 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ded operations. (Clearly state all period). SEE RULE 1103. For Multiple TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT "CSG; LEAD 260 sx 11.7 PPG CLS GO IN& 250 PSI LOW FOR 15 MIN - OK. C CSG @5553'. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG REL	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & S ertinent details, and ge Completions: Attact 5/8" 32# H-40 ST&C CSG T120' = 141'. TIH & DRI CMT; TAIL w/65 sx 13.5 TIH & DRILL 6 ½" HO CSG; CMT WITH 190 s 102/15/05.	EPORT OF Other I	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520	ated date mpletion 2 PPG AND 7",
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOW YIELD 1.270 CLASS € CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553". TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 TIH & LAND 4 ½" 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI I hereby certify that the information ab	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ded operations. (Clearly state all period). SEE RULE 1103. For Multiple TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT "CSG; LEAD 260 sx 11.7 PPG CLS GO IN& 250 PSI LOW FOR 15 MIN - OK. C CSG @5553'. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG REL ove is true and complete to the bese	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & S ertinent details, and g completions: Attact 5/8" 32# H-40 ST&C CSC T120' - 141'. TIH & DRI CMT; TAIL w/65 sx 13.5 TIH & DRILL 6 ½" HO CSG; CMT WITH 190 s 102/15/05. st of my knowledge a	EPORT OF Other IDEQUENT REFOREMENT IN THE PORT IN THE	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520 r certify that any pit	ated date mpletion 2 PPG AND 7", Is CMT
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOVIELD 1.270 CLASS €. CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553'. TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 `TIH & LAND 4 ½" 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ded operations. (Clearly state all period). SEE RULE 1103. For Multiple TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT "CSG; LEAD 260 sx 11.7 PPG CLS GO IN& 250 PSI LOW FOR 15 MIN - OK. C CSG @5553'. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG REL ove is true and complete to the bese	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & S ertinent details, and g completions: Attact 5/8" 32# H-40 ST&C CSC T120' - 141'. TIH & DRI CMT; TAIL w/65 sx 13.5 TIH & DRILL 6 ½" HO CSG; CMT WITH 190 s 102/15/05. st of my knowledge a	EPORT OF Other IDEQUENT REFOREMENT IN THE PORT IN THE	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520 r certify that any pit	ated date mpletion 2 PPG AND 7", Is CMT
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOVIELD 1.270 CLASS €. CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553'. TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 TIH & LAND 4 ½" 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI I hereby certify that the information ab grade tank has been/will be constructed or clo	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ded operations. (Clearly state all period). SEE RULE 1103. For Multiple OLE & DRILL TO 150'. RU & RUN 9.5 TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT "CSG; LEAD 260 sx 11.7 PPG CLS GO IN & 250 PSI LOW FOR 15 MIN - OK. C CSG @5553'. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG REL ove is true and complete to the besised according to NMOCD guidelines	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD &	EQUENT REF ING OPNS. ET REPORT ive pertinent date: h wellbore diagra G TO 142'. CEMENT LL 8 %" HOLE 141 PPG YIELD 1.310 O xs LITECRETE; 9.5 and belief. I furthe an (attached) alterna	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520 r certify that any pit ative OCD-approved	ated date mpletion 2 PPG AND 7", Is CMT
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOW YIELD 1.270 CLASS € CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553". TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 TIH & LAND 4 ½" 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI I hereby certify that the information ab	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ded operations. (Clearly state all period). SEE RULE 1103. For Multiple OLE & DRILL TO 150'. RU & RUN 9.5 TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT "CSG; LEAD 260 sx 11.7 PPG CLS GO IN & 250 PSI LOW FOR 15 MIN - OK. C CSG @5553'. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG REL ove is true and complete to the besised according to NMOCD guidelines	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD & S ertinent details, and g completions: Attact 5/8" 32# H-40 ST&C CSC T120' - 141'. TIH & DRI CMT; TAIL w/65 sx 13.5 TIH & DRILL 6 ½" HO CSG; CMT WITH 190 s 102/15/05. st of my knowledge a	EPORT OF Other IDEQUENT REFOREMENT IN THE PORT IN THE	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520 r certify that any pit ative OCD-approved	ated date mpletion 2 PPG AND 7", Is CMT
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½ SURFACE HE YIELD 1.270 CLASS €. CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553 TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 TIH & LAND 4 ½ 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI I hereby certify that the information ab grade tank has been/will be constructed or clossing the constr	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all period). SEE RULE 1103. For Multiple DLE & DRILL TO 150°. RU & RUN 9.5 TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT "CSG; LEAD 260 sx 11.7 PPG CLS GO IN& 250 PSI LOW FOR 15 MIN - OK. C CSG @5553°. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG REL ove is true and complete to the bessed according to NMOCD guidelines TITLE Report Complex	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD &	EQUENT REF ING OPNS. ET REPORT ive pertinent date: h wellbore diagra G TO 142'. CEMENT IPPG YIELD 1.310 of xs LITECRETE; 9.5 and belief. I furthe an (attached) alterna	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520 or certify that any pit ative OCD-approved	ated date mpletion 2 PPG AND 7", is CMT or below-plan
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOVIELD 1.270 CLASS €. CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553'. TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 TIH & LAND 4 ½" 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI I hereby certify that the information ab grade tank has been/will be constructed or clo	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all period). SEE RULE 1103. For Multiple DLE & DRILL TO 150°. RU & RUN 9.5 TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT "CSG; LEAD 260 sx 11.7 PPG CLS GO IN& 250 PSI LOW FOR 15 MIN - OK. C CSG @5553°. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG REL ove is true and complete to the bessed according to NMOCD guidelines TITLE Report Complex	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILL CASING TEST AND CEMENT JOB OTHER: SPUD &	EQUENT REF ING OPNS. ET REPORT ive pertinent date: h wellbore diagra G TO 142'. CEMENT IPPG YIELD 1.310 of xs LITECRETE; 9.5 and belief. I furthe an (attached) alterna	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520 or certify that any pit ative OCD-approved	ated date mpletion 2 PPG AND 7", Is CMT
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HO YIELD 1.270 CLASS €. CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553'. TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 `TIH & LAND 4 ½" 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI I hereby certify that the information ab grade tank has been/will be constructed or clo SIGNATURE	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all period). SEE RULE 1103. For Multiple OLE & DRILL TO 150'. RU & RUN 9: TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT "CSG; LEAD 260 sx 11.7 PPG CLS G ON 250 PSI LOW FOR 15 MIN - OK. C CSG @5553'. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG REL ove is true and complete to the best of seed according to NMOCD guidelines TITLE Reg	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILLI CASING TEST AND CEMENT JOB OTHER: SPUD & SI Pertinent details, and go completions: Attact S/8" 32# H-40 ST&C CSO T120' - 141'. TIH & DRI CMT; TAIL w/65 sx 13.5 TIH & DRILL 6 1/4" HO CSG; CMT WITH 190 s 02/15/05. st of my knowledge a l, a general permit or gulatory Analyst hlavacl@bp.com	EQUENT REF ING OPNS. ET REPORT ive pertinent date: h wellbore diagra G TO 142'. CEMENT IPPG YIELD 1.310 of xs LITECRETE; 9.5 and belief. I furthe an (attached) alterna	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520 or certify that any pit ative OCD-approved	ated date mpletion 2 PPG AND 7", is CMT or below-plan
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½ SURFACE HE YIELD 1.270 CLASS €. CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553 TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 TIH & LAND 4 ½ 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI I hereby certify that the information ab grade tank has been/will be constructed or clossing the constr	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all period). SEE RULE 1103. For Multiple OLE & DRILL TO 150'. RU & RUN 9 5 TO SURFACE. PSI LOW. TST OK. DRILL OUT CM1" CSG; LEAD 260 sx 11.7 PPG CLS GO IN& 250 PSI LOW FOR 15 MIN - OK. C CSG @5553'. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG REL ove is true and complete to the besised according to NMOCD guidelines TITLE Report of the complete in the	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILLICASING TEST AND CEMENT JOB OTHER: SPUD & Section the details, and gecompletions: Attack 5/8" 32# H-40 ST&C CSC 120' - 141'. TIH & DRICMT; TAIL w/65 sx 13.5 TIH & DRILL 6 1/4" HO CSG; CMT WITH 190 sc 102/15/05. Set of my knowledge a a, a general permit or gulatory Analyst hlavacl@bp.com	EPORT OF Other INCOMENT REFORE TET REPORT Tive pertinent dates the wellbore diagram TO 142'. CEMENT LL 8 ¾" HOLE 141 PPG YIELD 1.310 of the content of	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520 r certify that any pit ative OCD-approved 02/21/05 none No. 281-36	ated date mpletion 2 PPG AND 7", is CMT or below-plan
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOVIELD 1.270 CLASS © CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553'. TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 `TIH & LAND 4 ½" 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI I hereby certify that the information ab grade tank has been/will be constructed or clo SIGNATURE Type or print name Cherry Hlava (This space for State use)	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ded operations. (Clearly state all performs). SEE RULE 1103. For Multiple OLE & DRILL TO 150'. RU & RUN 9.5 TO SURFACE. PSI LOW. TST OK. DRILL OUT CMT "CSG; LEAD 260 sx 11.7 PPG CLS GO IN & 250 PSI LOW FOR 15 MIN - OK. C CSG @5553'. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG RELOVE is true and complete to the best of the best of the perform of the performance of the perf	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILLI CASING TEST AND CEMENT JOB OTHER: SPUD & SI Pertinent details, and go completions: Attact S/8" 32# H-40 ST&C CSO T120' - 141'. TIH & DRI CMT; TAIL w/65 sx 13.5 TIH & DRILL 6 1/4" HO CSG; CMT WITH 190 s 02/15/05. st of my knowledge a l, a general permit or gulatory Analyst hlavacl@bp.com	EQUENT REF ING OPNS. ET REPORT ive pertinent date: h wellbore diagra G TO 142'. CEMENT LL 8 %" HOLE 141 PPG YIELD 1.310 O LE 2555' - 5555 TD xs LITECRETE; 9.5 and belief. I furthe an (attached) alterna DATE (Teleph	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520 or certify that any pit ative OCD-approved	ated date mpletion 2 PPG AND 7", is CMT or below-plan
12. Check Ap NOTICE OF INTI PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/08/05 MIRU & SPUD 13 ½" SURFACE HOVIELD 1.270 CLASS €. CIRC 10 bbls CMT PRES TEST CSG TO 1500 PSI HIGH & 250 20# J-55 ST&C CSG @2553'. TIH & CMT 7 TO SURFACE PRES TEST CSG TO 850 PSI HIGH F/30 MI 02/14/05 `TIH & LAND 4 ½" 11.6#, J-55 LT& RETURNS 5 bbl CMT. CIRC CMT OFF LI I hereby certify that the information ab grade tank has been/will be constructed or clo SIGNATURE	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS MULTIPLE COMPLETION ed operations. (Clearly state all period). SEE RULE 1103. For Multiple OLE & DRILL TO 150'. RU & RUN 9 5 TO SURFACE. PSI LOW. TST OK. DRILL OUT CM1" CSG; LEAD 260 sx 11.7 PPG CLS GO IN& 250 PSI LOW FOR 15 MIN - OK. C CSG @5553'. TIH & CEMENT 4 ½" NER TOP.ND BOP; NU WH. RIG REL ove is true and complete to the besised according to NMOCD guidelines TITLE Report of the complete in the	ture of Notice, ReSUBSE REMEDIAL WORK COMMENCE DRILLICASING TEST AND CEMENT JOB OTHER: SPUD & Section the details, and gecompletions: Attack 5/8" 32# H-40 ST&C CSC 120' - 141'. TIH & DRICMT; TAIL w/65 sx 13.5 TIH & DRILL 6 1/4" HO CSG; CMT WITH 190 sc 102/15/05. Set of my knowledge a a, a general permit or gulatory Analyst hlavacl@bp.com	EPORT OF Other INCOMENT REFORE TET REPORT Tive pertinent dates the wellbore diagram TO 142'. CEMENT LL 8 ¾" HOLE 141 PPG YIELD 1.310 of the content of	PORT OF: ALTERING CASI PLUG AND ABANDONMENT s, including estim am of proposed co T CSG w/100 SXS 15 ' - 2555'. TIH & L/ CLS G. CIRC 18 bb ON 02/13/05. 50 ppg YIELD 2.520 r certify that any pit ative OCD-approved 02/21/05 none No. 281-36	ated date mpletion 2 PPG AND 7", is CMT or below-plan