Form 3160-5 (September 2001)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135
Expires: January 31, 2004

j.	Lease	Serial No.

CHADDY	NOTICES AND RE	DODTS ON	WELL	• /	NMSF-	079065		
	is form for proposals				6. If India	n, Allottee or Tril	be Name	
abandoned w	ell. Use Form 3160 - 3 (	(APD) for suc	ch propo	sals.	N/A	•		
SUBMIT IN TRIPLICATE- Other instructions on reverse side.						7. If Unit or CA/Agreement, Name and/or No.		
1. Type of Well Gas Well Other						NA  8. Well Name and No.		
Name of Operator Lance Oil &	Gas Company, Inc.				F-RPC	C 19 #2Y		
Address		3b. Phone No.	. (include an	ea code)		5-32766		
P. O. Box 70, Kirtlan	505-598-56	5601			10. Field and Pool, or Exploratory Area  West Kutz PC/Basin Fruitland Coal			
Location of Well (Footage, Sec.,	T., R., M., or Survey Description)				<u> </u>	or Parish, State		
688' FNL & 836' FWL, Section	n 19, T29N-R13W					•		
						nan County, N		
12. CHECK A	PPROPRIATE BOX(ES) TO	O INDICATE N	NATURE	OF NOTICE	, REPORT, O	R OTHER DA	ATA	
TYPE OF SUBMISSION	,		TYPE	OF ACTION				
	Acidize	Deepen	֟֝֟֟֟֟֟֓֓֓֓֟		(Start/Resume)	Water Sh		
Notice of Intent	Alter Casing	Fracture Tre	····	Reclamation		Well Inte	grity oud & csg cmt	
Subsequent Report	Casing Repair Change Plans	New Constr		Recomplet	e Iv Abandon		urface casing	
Final Abandonment Notice	Convert to Injection	Plug Back	Carioun C	Water Dis	•			
If the proposal is to deepen din Attach the Bond under which the following completion of the intesting has been completed. Find determined that the site is read 1/2/05 MIRU American I below conductor pipe. W	ectionally or recomplete horizonta the work will be performed or pro- volved operations. If the operation inal Abandonment Notices shall be by for final inspection.) Drilling Company (ADC) Rig (ater washed out dirt around to	ally, give subsurface wide the Bond No. on results in a multip ie filed only after al over conductor the conductor pi	ce locations a on file with iple completi ill requirement	and measured a BLM/BIA. R ion or recomple nts, including r d well @ 1:00	nd true vertical dep equired subsequent stion in a new intervectamation, have be o p.m. Drill new	ths of all pertiner reports shall be val, a Form 3160 een completed, ar 12-1/4" hole to	nt markers and zones. filed within 30 days 4 shall be filed once and the operator has 55', approx 15'	
If the proposal is to deepen din Attach the Bond under which the following completion of the intesting has been completed. Find determined that the site is read 1/2/05 MIRU American I below conductor pipe. W 1/8/05 RU ADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", ceme BOP's. Rig moved off loo Wash & ream from 603'	ectionally or recomplete horizonta the work will be performed or pro- volved operations. If the operation inal Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig (ater washed out dirt around to 1.12-1/4"hole to 150', TD for si & condition hole. Cement 8-5/ cement @ 90', drill 7-7/8" hole to 788'. Drill 7-7/8" hole from to 788'. Drill 7-7/8" hole from	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg. 8° csg with 125 ele in cement to 17/05 Drill 7-7/8° CC Rig #204 moven to 905'. 2/1/05	on file with iple completi ill requirement ill requirement ill requirement in pipe. Spusipe. PU &:  sx STD cm 120'. 1/11- " hole to 75 yed in & loo 5 Drill 7-7/8	and measured a BLM/BIA. R ion or recomple nts, including n d well @ 1:00 shut down. R at @ 15.6 lb, o 15/05 Rig dow cation prep'd " hole to 116	nd true vertical dep equired subsequent stion in a new intervectamation, have be 0 p.m. Drill new dig down rig, prej displaced w/6 bb wn for repairs to n until 1/28/05, w to accomodate s 64'. Circ & condi	ths of all pertiner reports shall be aval, a Form 3160 cen completed, and 12-1/4" hole to p to reset cond is H20, 9 bbis of kelly block assettle continued to the base. 1/31/tion hole. TOO	nt markers and zones. filed within 30 days 4 shall be filed once and the operator has  35', approx 15' uctor pipe.  cant back to pits. sembly. o be secure with 05 RIH to 603'. OH, LD drill string.	
If the proposal is to deepen din Attach the Bond under which the following completion of the intesting has been completed. Fidetermined that the site is read 1/2/05 MIRU American I below conductor pipe. W 1/8/05 RU ADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", cems BOP's. Rig moved off loc Wash & ream from 603' Run esg tools and run 27 bbls H20 and bumped plus	ectionally or recomplete horizonta the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig fater washed out dirt around it 12-1/4"hole to 150', TD for size condition hole. Cement 8-5/4 cement @ 90', drill 7-7/8" hole ent & formation, to 320'. 1/17 cation on 1/28/05. 1/30/05 ADC or 788'. Drill 7-7/8" hole from jts 5-1/2" csg to 1150'. Cement ag w/800 psi, 7 bbls cmt back to	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg.  78" csg with 125 cle in cement to 17/05 Drill 7-7/8" CR ig #204 moven to 905". 2/1/05 ent csg w/90 sx ty	on file with iple completi ill requirement ill	and measured a BLM/BIA. R ion or recomple ints, including r d well @ 1:00 shut down. R at @ 15.6 lb, ( 15/05 Rig dov 50'. Rig dov to 116 '' hole to 116 @ 12 lbs/gal	nd true vertical depequired subsequent tion in a new intervectamation, have been proposed by the control of the	ths of all pertiner reports shall be a val, a Form 3160 cen completed, at 12-1/4" hole to p to reset cond is H20, 9 bbls of kelly block as tell continued to the base. 1/31 tion hole. TOC il @ 13 bbls/ga	nt markers and zones. filed within 30 days 4 shall be filed once and the operator has  35', approx 15' uctor pipe.  cant back to pits.  sembly. o be secure with 05 RIH to 603'. bH, LD drill string. I, displaced w/27.3	
If the proposal is to deepen din Attach the Bond under which the following completion of the intesting has been completed. Fidetermined that the site is read 1/2/05 MIRU American I below conductor pipe. W 1/8/05 RU ADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", cem BOP's. Rig moved off loc Wash & ream from 603' Run csg tools and run 27	ectionally or recomplete horizonta the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig fater washed out dirt around it 12-1/4"hole to 150', TD for size condition hole. Cement 8-5/4 cement @ 90', drill 7-7/8" hole ent & formation, to 320'. 1/17 cation on 1/28/05. 1/30/05 ADC or 788'. Drill 7-7/8" hole from jts 5-1/2" csg to 1150'. Cement ag w/800 psi, 7 bbls cmt back to	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg.  78" csg with 125 cle in cement to 17/05 Drill 7-7/8" CR ig #204 moven to 905". 2/1/05 ent csg w/90 sx ty	on file with iple completi ill requirement ill	and measured a BLM/BIA. R ion or recomple ints, including r d well @ 1:00 shut down. R at @ 15.6 lb, ( 15/05 Rig dov 50'. Rig dov to 116 '' hole to 116 @ 12 lbs/gal	nd true vertical depequired subsequent tion in a new intervectamation, have been proposed by the control of the	ths of all pertiner reports shall be a val, a Form 3160 cen completed, at 12-1/4" hole to p to reset cond is H20, 9 bbls of kelly block as tell continued to the base. 1/31 tion hole. TOC il @ 13 bbls/ga	nt markers and zones. filed within 30 days 4 shall be filed once and the operator has  35', approx 15' uctor pipe.  cant back to pits.  sembly. o be secure with 05 RIH to 603'. bH, LD drill string. I, displaced w/27.3	
If the proposal is to deepen din Attach the Bond under which the following completion of the intesting has been completed. Fidetermined that the site is read 1/2/05 MIRU American below conductor pipe. W 1/8/05 RU ADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", cems BOP's. Rig moved off loc Wash & ream from 603' the Run csg tools and run 27 bbls H20 and bumped plates.	ectionally or recomplete horizonta the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig fater washed out dirt around it 12-1/4"hole to 150', TD for size condition hole. Cement 8-5/4 cement @ 90', drill 7-7/8" hole ent & formation, to 320'. 1/17 cation on 1/28/05. 1/30/05 ADC or 788'. Drill 7-7/8" hole from jts 5-1/2" csg to 1150'. Cement ag w/800 psi, 7 bbls cmt back to	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg.  78" csg with 125 cle in cement to 17/05 Drill 7-7/8" CR ig #204 moven to 905". 2/1/05 ent csg w/90 sx ty	on file with iple completi ill requirement ill	and measured a BLM/BIA. R ion or recomple ints, including r d well @ 1:00 shut down. R at @ 15.6 lb, ( 15/05 Rig dov 50'. Rig dov to 116 '' hole to 116 @ 12 lbs/gal	nd true vertical depequired subsequent tion in a new intervectamation, have been proposed by the control of the	ths of all pertiner reports shall be a val, a Form 3160 cen completed, at 12-1/4" hole to p to reset cond is H20, 9 bbls of kelly block as tell continued to the base. 1/31 tion hole. TOC il @ 13 bbls/ga	at markers and zones. filed within 30 days 4 shall be filed once and the operator has  a 35', approx 15' uctor pipe.  cent back to pits. fiembly. be be secure with a RIH to 603'. bH, LD drill string. displaced w/27.3 b).	
If the proposal is to deepen din Attach the Bond under which of following completion of the in testing has been completed. Fi determined that the site is read  1/2/05 MIRU American I below conductor pipe. W 1/8/05 RU ADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", cems BOP's. Rig moved off loo Wash & ream from 603' Run csg tools and run 27 bbls H20 and bumped plu Rig released 2/2/05 @ 140  4. I hereby certify that the for	ectionally or recomplete horizontal the work will be performed or provolved operations. If the operation in Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig (ater washed out dirt around to 12-1/4"hole to 150', TD for see condition hole. Cement 8-5/cement @ 90', drill 7-7/8" hole ent & formation, to 320'. 1/17-ation on 1/28/05. 1/30/05 ADd to 788'. Drill 7-7/8" hole from jts 5-1/2" csg to 1150'. Cemeng w/800 psi, 7 bbls cmt back to the condition of the complete the condition of the complete the comple	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg.  78" csg with 125 cle in cement to 17/05 Drill 7-7/8" CR ig #204 moven to 905". 2/1/05 ent csg w/90 sx ty	on file with iple completi ill requirement ill	and measured a BLM/BIA. R ion or recomple ints, including r d well @ 1:00 shut down. R at @ 15.6 lb, ( 15/05 Rig dov 50'. Rig dov to 116 '' hole to 116 @ 12 lbs/gal	nd true vertical depequired subsequent tion in a new intervectamation, have been proposed by the control of the	ths of all pertiner reports shall be a val, a Form 3160 cen completed, at 12-1/4" hole to p to reset cond is H20, 9 bbls of kelly block as tell continued to the base. 1/31 tion hole. TOC il @ 13 bbls/ga	at markers and zones. filed within 30 days 4 shall be filed once and the operator has  a 35', approx 15' uctor pipe.  cent back to pits. fiembly. be be secure with a RIH to 603'. bH, LD drill string. displaced w/27.3 b).	
If the proposal is to deepen din Attach the Bond under which the following completion of the intesting has been completed. Fidetermined that the site is read 1/2/05 MIRU American I below conductor pipe. W 1/8/05 RU ADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", cem BOP's. Rig moved off low Wash & ream from 603' to Run csg tools and run 27 bbls H20 and bumped planting released 2/2/05 @ 1460.	ectionally or recomplete horizontal the work will be performed or provolved operations. If the operation in Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig (ater washed out dirt around to 12-1/4"hole to 150', TD for see condition hole. Cement 8-5/cement @ 90', drill 7-7/8" hole ent & formation, to 320'. 1/17-ation on 1/28/05. 1/30/05 ADd to 788'. Drill 7-7/8" hole from jts 5-1/2" csg to 1150'. Cemeng w/800 psi, 7 bbls cmt back to the condition of the complete the condition of the complete the comple	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg.  8" csg with 125 old in cement to 17/05 Drill 7-7/8" IC Rig #204 moven to 905'. 2/1/05 ent csg w/90 sx ty to pits. WOC,	ce locations a on file with iple completi ill requirement ill	and measured at BLM/BIA. Rion or recomplents, including not be should be sho	nd true vertical depequired subsequent stion in a new intervectamation, have been purely by me to provide the prov	ths of all pertiner reports shall be a val, a Form 3160 cen completed, at 12-1/4" hole to p to reset cond is H20, 9 bbls of kelly block as tell continued to the base. 1/31 tion hole. TOC il @ 13 bbls/ga	at markers and zones. filed within 30 days 4 shall be filed once and the operator has  a 35', approx 15' uctor pipe.  cent back to pits. fiembly. be be secure with a RIH to 603'. bH, LD drill string. displaced w/27.3 b).	
If the proposal is to deepen din Attach the Bond under which of following completion of the in testing has been completed. Fi determined that the site is read  1/2/05 MIRU American I below conductor pipe. W 1/8/05 RU ADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", ceme BOP's. Rig moved off loc Wash & ream from 603' of Run csg tools and run 27 bbls H20 and bumped pla  Rig released 2/2/05 @ 140  4. Thereby certify that the for Name (Printed/Typed)  Jo Becksted	ectionally or recomplete horizontal the work will be performed or provolved operations. If the operation in Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig (ater washed out dirt around to 12-1/4"hole to 150', TD for see condition hole. Cement 8-5/cement @ 90', drill 7-7/8" hole ent & formation, to 320'. 1/17-ation on 1/28/05. 1/30/05 ADd to 788'. Drill 7-7/8" hole from jts 5-1/2" csg to 1150'. Cemeng w/800 psi, 7 bbls cmt back to the condition of the complete the condition of the complete the comple	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg.  8" csg with 125 old in cement to 17/05 Drill 7-7/8" IC Rig #204 moven to 905'. 2/1/05 ent csg w/90 sx ty to pits. WOC,	ce locations a on file with iple completi ill requirement pipe. Spusipe. PU &: sx STD cm 120'. 1/11- " hole to 75 yed in & loo 5 Drill 7-7/8 ype 3 lead (Csg shoe so	and measured a BLM/BIA. R ion or recomple ints, including r d well @ 1:00 shut down. R at @ 15.6 lb, ( 15/05 Rig dov 50'. Rig dov to 116 '' hole to 116 @ 12 lbs/gal	nd true vertical depequired subsequent stion in a new intervectamation, have been purely by me to accomodate stide of shoe track in the first shoe tra	ths of all pertiner reports shall be a val, a Form 3160 cen completed, at 12-1/4" hole to p to reset cond is H20, 9 bbls of kelly block as tell continued to the base. 1/31 tion hole. TOC il @ 13 bbls/ga	at markers and zones. filed within 30 days 4 shall be filed once and the operator has  a 35', approx 15' uctor pipe.  cent back to pits. fiembly. be be secure with a RIH to 603'. bH, LD drill string. displaced w/27.3 b).	
If the proposal is to deepen din Attach the Bond under which the following completion of the intesting has been completed. Fidetermined that the site is read  1/2/05 MIRU American I below conductor pipe. W 1/8/05 RU ADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", ceme BOP's. Rig moved off low Wash & ream from 603' the Run csg tools and run 27 bbls H20 and bumped plate Rig released 2/2/05 @ 140  4. Thereby certify that the form Name (Printed/Typed)	ectionally or recomplete horizontal the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig (ater washed out dirt around to 12-1/4"hole to 150", TD for sit is condition hole. Cement 8-5% cement @ 90", drill 7-7/8" hole ent & formation, to 320". 1/17 (action on 1/28/05. 1/30/05 ADC to 788". Drill 7-7/8" hole from jts 5-1/2" (sag to 1150". Cement g w/800 psi, 7 bbls cmt back to 100 hrs.	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg. 78" csg with 125 ble in cement to 17/05 Drill 7-7/8" C Rig #204 moven to 905'. 2/1/05 ent csg w/90 sr ty to pits. WOC,	on file with iple completi ill requirement ill	and measured at BLM/BIA. Rion or recomplents, including not be shut down. Rut @ 15.6 lb, days at a 15.05 Rig down action prep'd hole to 116 @ 12 lbs/gal et @ 1150' with a 115	nd true vertical depequired subsequent stion in a new intervectamation, have been provided by the provided by	ths of all pertiner reports shall be val, a Form 3160 cen completed, and 12-1/4" hole to p to reset cond is H20, 9 bbls of kelly block asset continued to base. 1/31/tion hole. TOO if @ 13 bbls/ga (9' RKB to GI	at markers and zones. filed within 30 days 4 shall be filed once and the operator has  a 35', approx 15' uctor pipe.  cent back to pits. fiembly. be be secure with a RIH to 603'. bH, LD drill string. displaced w/27.3 b).	
If the proposal is to deepen din Attach the Bond under which to following completion of the in testing has been completed. Fi determined that the site is read  1/2/05 MIRU American I below conductor pipe. W 1/8/05 RU ADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", ceme BOP's. Rig moved off loc Wash & ream from 603' t Run csg tools and run 27 bbls H20 and bumped pla Rig released 2/2/05 @ 140  4. I hereby certify that the fore Name (Printed/Typed) Jo Becksted	ectionally or recomplete horizontal the work will be performed or provolved operations. If the operation in Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig (ater washed out dirt around to 12-1/4"hole to 150', TD for see condition hole. Cement 8-5/cement @ 90', drill 7-7/8" hole ent & formation, to 320'. 1/17-ation on 1/28/05. 1/30/05 ADd to 788'. Drill 7-7/8" hole from jts 5-1/2" csg to 1150'. Cemeng w/800 psi, 7 bbls cmt back to the condition of the complete the condition of the complete the comple	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg. 78" csg with 125 ble in cement to 17/05 Drill 7-7/8" C Rig #204 moven to 905'. 2/1/05 ent csg w/90 sr ty to pits. WOC,	on file with iple completi ill requirement ill	and measured at BLM/BIA. Rion or recomplents, including not be shut down. Rut @ 15.6 lb, days at a 15.05 Rig down action prep'd hole to 116 @ 12 lbs/gal et @ 1150' with a 115	nd true vertical depequired subsequent stion in a new intervectamation, have been provided by the provided by	ths of all pertiner reports shall be val, a Form 3160 cen completed, at 12-1/4" hole to p to reset cond is H20, 9 bbls of kelly block asset continued to base. 1/31/tion hole. TOO il @ 13 bbls/ga (9' RKB to GL	at markers and zones. filed within 30 days 4 shall be filed once and the operator has  a 35', approx 15' uctor pipe.  cent back to pits. fiembly. be be secure with a RIH to 603'. bH, LD drill string. displaced w/27.3 b).	
If the proposal is to deepen din Attach the Bond under which to following completion of the in testing has been completed. Fi determined that the site is read  1/2/05 MIRU American I below conductor pipe. W 1/8/05 RU ADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", ceme BOP's. Rig moved off loc Wash & ream from 603' t Run csg tools and run 27 bbls H20 and bumped plu Rig released 2/2/05 @ 140  4. I hereby certify that the for Name (Printed/Typed) Jo Becksted  Signatur	ectionally or recomplete horizontal the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig (ater washed out dirt around to 12-1/4"hole to 150", TD for sit is condition hole. Cement 8-5% cement @ 90", drill 7-7/8" hole ent & formation, to 320". 1/17 (action on 1/28/05. 1/30/05 ADC to 788". Drill 7-7/8" hole from jts 5-1/2" (sag to 1150". Cement g w/800 psi, 7 bbls cmt back to 100 hrs.	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg. 78" csg with 125 ble in cement to 17/05 Drill 7-7/8" C Rig #204 moven to 905'. 2/1/05 ent csg w/90 sr ty to pits. WOC,	on file with iple completi ill requirement ill	and measured a BLM/BIA. R ion or recomple ints, including r d well @ 1:00 shut down. R at @ 15.6 lb, o 15/05 Rig dow cation prep'd by hole to 116 @ 12 lbs/gal et @ 1150' wi	nd true vertical depequired subsequent stion in a new intervectamation, have be p.m. Drill new dig down rig, predisplaced w/6 bbwn for repairs to n until 1/28/05, w to accomodate s 4'. Circ & condi & 84 sx type 3 taith 6' shoe track distributed in the street of the st	ths of all pertiner reports shall be val, a Form 3160 cen completed, and 12-1/4" hole to p to reset cond is H20, 9 bbis of kelly block assell continued to the base. 1/31/tion hole. TOO il @ 13 bbis/ga (9' RKB to GI	at markers and zones. filed within 30 days 4 shall be filed once and the operator has  a 35', approx 15' uctor pipe.  cent back to pits. fiembly. be be secure with a RIH to 603'. bH, LD drill string. displaced w/27.3 b).	
Attach the Bond under which to following completion of the intesting has been completed. Find the strength of the intesting has been completed. Find the strength of the intesting has been completed. Find the intesting has been completed. Find the intesting has been completed. Find the intesting has been conductor pipe. William 18/05 RUADC rig. Drill 1/9/05 RIH to 150', circ & WOC. 1/10/05 RIG, Tag 1/16/05 Drill 7-7/8", ceme BOP's. Rig moved off low Wash & ream from 603' Run csg tools and run 27 bbls H20 and bumped plus Rig released 2/2/05 @ 140.  4. I hereby certify that the form Name (Printed/Typed)  Jo Becksted	ectionally or recomplete horizonta the work will be performed or provolved operations. If the operation inal Abandonment Notices shall be y for final inspection.)  Drilling Company (ADC) Rig (ater washed out dirt around to 12-1/4"hole to 150', TD for se & condition hole. Cement 8-5/ cement @ 90', drill 7-7/8" hole to 788'. Drill 7-7/8" hole from jts 5-1/2" csg to 1150'. Cemen g w/800 psi, 7 bbls cmt back to 100 hrs.  THIS SPACE FOR	ally, give subsurface vide the Bond No. on results in a multiple filed only after all over conductor the conductor pisurf csg.  8° csg with 125 ble in cement to 17/05 Drill 7-7/8° IC Rig #204 moven to 905'. 2/1/05 ent csg w/90 sr ty to pits. WOC, of the pits work work work work work work work work	ce locations a on file with iple completi ill requirement pipe. Spusipe. PU &: sx STD cm sx STD cm 120'. 1/11- " hole to 75 yed in & loo 5 Drill 7-7/8 ype 3 lead (Csg shoe so	and measured at BLM/BIA. Rion or recompletes, including ride well @ 1:00 shut down. Rit @ 15.6 lb, do 15.05 Rig down cation prep'd "hole to 116 @ 12 lbs/gal et @ 1150' with a mpliance Adm	nd true vertical depequired subsequent ston in a new intervectamation, have be to p.m. Drill new lig down rig, predisplaced w/6 bb wn for repairs to a until 1/28/05, w to accomodate s 4'. Circ & condi & 84 sx type 3 taith 6' shoe track of the subsequent stone in the stone track of the stone track	ths of all pertiner reports shall be reports shall be ral, a Form 3160 cen completed, and 12-1/4" hole to p to reset cond is H20, 9 bbls of kelly block asset cell continued to base. 1/31/tion hole. TOO il @ 13 bbls/ga (9' RKB to GI	at markers and zones. Filed within 30 days 4 shall be filed once and the operator has a 35', approx 15' uctor pipe.  The community of the security of the secu	

(Instructions on page 2)