

**OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

OPERATOR ConocoPhillips CO
FARMINGTON, NM 87401
PHONE. 599-3400

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFICE

LOCATION INFORMATION

API Number **3003930892**

WELL NAME OR PIPELINE SERVED: **SAN JUAN 30-5 UNIT / 38P** LEGAL LOCATION: **18-30N-05W** INSTALLATION DATE: **5/24/2011**

PPCO. RECTIFIER NO.: **FM879** ADDITIONAL WELLS: **SJ 30-5-: 206A, 89N, 38P**

TYPE OF LEASE: LEASE NUMBER: **SF-78994**

GROUND BED INFORMATION

TOTAL DEPTH: **300'** CASING DIAMETER: **8"** TYPE OF CASING: **PVC** CASING DEPTH: **20'** CASING CEMENTED ☒

TOP ANODE DEPTH: **167'** BOTTOM ANODE DEPTH: **275'**

ANODE DEPTHS: **167', 179', 191', 203', 215', 227', 239', 251', 263', 275'**

AMOUNT OF COKE: **45 BAGS**

WATER INFORMATION

WATER DEPTH (1): WATER DEPTH (2):

GAS DEPTH: CEMENT PLUGS:

OTHER INFORMATION

TOP OF VENT PERFORATIONS: **160'** VENT PIPE DEPTH: **300'**

REMARKS:



IF ANY OF THE ABOVE INFORMATION IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE. UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

*- LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER

Wednesday, Nove

Page 1 of 1

COMPANY: Conoco Phillips
 COMPANY REP.: Randy Smith
 LOCATION: SAN JUAN 30-5 UNIT / 38P
 JOB NO.: 140739
 FOREMAN: Ron Luna
 DRILLER: Darrel Ferrier

DATE: 5/24/2011
 DIA. HOLE: 7 7/8"
 DEPTH: 300
 COKE TYPE: SW
 # OF COKE: 45 BAGS
 # OF BENTONITE: 0

CASING: SCH 40 PVC
 DIAMETER: 8"
 CASING DEPTH: 20'
 # OF ANODES: 10
 ANODE TYPE: 2284Z
 ANODE LEAD: HWMPE #8



RECTIFIER MFG: _____
 MODEL: _____
 SERIAL #: _____
 V-DC: _____ A-DC: _____

WELL LOG										ANODE PLACEMENT			
DEPTH FT.	DRILLERS LOG - SOIL TYPE	VOLTS	AMPS	COMMENTS / ANODE #	DEPTH FT.	DRILLERS LOG - SOIL TYPE	VOLTS	AMPS	COMMENTS / ANODE #	ANODE NO.	ANODE DEPTH	AMPS W/O COKE	AMPS W/ COKE
0	CASING	13.30			250	SANDY SHALE		2.30	251'-Anode #3	1	275	2.60	5.70
5	CASING				255	SANDY SHALE		2.50		2	263	2.30	6.60
10	CASING				260	SANDY SHALE		2.20		3	251	2.40	7.20
15	CASING				265	SANDY SHALE		2.70	263'-Anode #2	4	239	2.30	7.00
20	CASING				270	SANDY SHALE		2.60		5	227	2.80	7.60
25	GRAY SANDSTONE				275	SANDY SHALE		2.50	275'-Anode # 1	6	215	2.80	7.40
30	GRAY SANDSTONE				280	SANDY SHALE		2.50		7	203	3.00	8.00
35	GRAY SANDSTONE				285	SANDY SHALE		2.30		8	191	3.30	8.20
40	GRAY SANDSTONE				290	SANDY SHALE				9	179	2.10	6.70
45	GRAY SANDSTONE				295	SANDY SHALE				10	167	2.70	6.60
50	GRAY SANDSTONE				300	SANDY SHALE				11			
55	GRAY SANDSTONE				305					12			
60	GRAY SANDSTONE				310					13			
65	GRAY SANDSTONE				315					14			
70	GRAY SANDSTONE				320					15			
75	SHALE				325					16			
80	SHALE		2.30		330					17			
85	SHALE		2.40		335					18			
90	SHALE		2.60		340					19			
95	SHALE		3.20		345					20			
100	SHALE		3.00		350					21			
105	SANDY SHALE		2.30		355					22			
110	SANDY SHALE		2.40		360					23			
115	SANDY SHALE		2.50		365					24			
120	SANDY SHALE		2.60		370					25			
125	SANDY SHALE		2.50		375								
130	SANDY SHALE		2.50		380								
135	SANDY SHALE		2.40		385								
140	SANDY SHALE		2.20		390								
145	SANDY SHALE		1.90		395								
150	SANDY SHALE		2.50		400								
155	SHALE		2.10		405								
160	SHALE		2.10		410								
165	SHALE		2.40	167'-Anode #10	415								
170	SHALE		2.40		420								
175	SHALE		1.90		425								
180	SHALE		2.20	179'-Anode #9	430								
185	SHALE		2.60		435								
190	SHALE		3.10	191'-Anode #8	440								
195	SHALE		2.80		445								
200	SHALE		2.90		450								
205	SHALE		3.00	203'-Anode #7	455								
210	SHALE		2.80		460								
215	SHALE		2.60	215'-Anode # 6	465								
220	SHALE		2.00		470								
225	SHALE		2.50	227'-Anode #5	475								
230	SHALE		3.20		480								
235	SHALE		2.60		485								
240	SHALE		1.90	239'-Anode #4	490								
245	SANDY SHALE		2.00		495								
										TOTAL VOLTS: 13.30			
										TOTAL AMPS: 26.30			
										0.51 OHMS			
										SITE ELEVATION:			
										WATER CONDUCTIVITY:			
										ADDITIONAL COMMENTS:			
										NO POSITIVE CABLE			
										COKE LEVEL: 146 FT			
										EXTRA CASING USED: N/A			