
In Lieu of Form 3160 (June 1990)

UNITED STATES DEPARTMENT OF INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICE AND REPORTS ON WELLS

TO DRILL" for permit for such proposals



FORM APPROVED Budget Bureau No 1004-0135 Expires: March 31, 1993

JUN 09 2011

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION

Lease Designation and Serial No. NMSF-078767

-armington Field Office

If Indian, Allottee or Tribe Name

		urear	u of Land Manageme	nı
	SUBMIT IN TRII	PLICATE	7.	If Unit or CA, Agreement Designation Rosa Unit
1	Type of Well Oil Well Gas Well X Other		8.	Well Name and No Rosa Unit 019D
2.	Name of Operator WILLIAMS PRODUCTION COMPANY		9.	API Well No 30-039-30781
3.	Address and Telephone No. PO Box 640 Aztec, NM 87410-0640 505-634-42	208	10.	Field and Pool, or Exploratory Area BLANCO MV/BASIN DK/BASIN MC
4.	Location of Well (Footage, Sec., T., R., M, or Su SURF 1980' FSL & 660' FWL BHL: \$40" FSL & 694' FWL SEC 24 31N 6W	rvey Description)	11.	County or Parish, State Rio Arriba, New Mexico
	803 CHECK APPROPRIATE	BOX(s) TO INDICATE NATURE O	F NOTICE, REPORT, OR	OTHER DATA
	TYPE OF SUBMISSION		TYPE OF ACTION	ON

TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent X Subsequent Report Final Abandonment	Abandonment Recompletion Plugging Back Casing Repair Altering Casing X Other <u>REALLOCATION</u>	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note Report results of multiple completion on Well Completion or Recompletion Report and Log form)		


Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Williams E&P has run Protechnic's Completion profiler tool for allocation purposes on the Rosa Unit #19D. Based on the results obtained, Williams proposes the following allocation:

	Mesaverde Mancos Dakota	49% 39% 12%			107 84 25	Mcf/d Mcf/d Mcf/d	STORY OF THE CENTED STORY	\\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\.\
	Total	100%			216	Mcf/d	/ ox 1/0 /	
14	I hereby certify that the fore		Title <u>Dri</u>	lling Suprv	D	ate <u>6/9/11</u>		
	(This space for Federal or St Approved by	Henrit	Title	Geo			Date <u>6-10-1</u>	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Williams Production Company Rosa Unit #19D



MEASUREDSOLUTIONS





Company | Williams Production Company

Well Name | Rosa Unit #19D

Field | Blanco Mesaverde/Basin Dakota

Location | Rio Arriba County, New Mexico

Customer Name | Michael Andrews

Date of Survey | May 26, 2011

Date of Analysis | June 1, 2011

Logging Engineer | Loren Healy

Analyst | Cole Hutchings

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful misconduct on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.





Table of Contents

Survey Objectives	_ 4
Logging Procedures	_ 4
Well Information	
Tool String	_ 6
Well Log History	
Results	
Analysis Summary	. 13
Brief Description of Process	14
Model Results With Recorded Data	
Production Rates At Surface Conditions	_ 16
Flow Model at Downhole Conditions With Comparison of Theoretical Response to Recorded Data	17
Overlay of all Log Data	_ 18
Apparent Fluid Velocity Derived from Spinner	_ 19
Spinner Calibration Plots Relationship between R.P.S. and Fluid Velocity (fpm)	_ 20
Well Information	_ 21
Parameters used for Analysis	_ 21
Definitions	22





Survey Objectives

- Identify the source of water production.
- · Identify gas producing intervals.
- Quantitative production profile.

Logging Procedures

Date	Time	Comment
05/26	06:20	Arrive on location
05/26	05:00	Gauge run start
05/26	06:00	Gauge run stop
05/26	07:17	Program Completion Profile String
05/26	07:37	Start GIH pass
05/26	07:57	Stop GIH pass
05/26	08:18	Start logging passes
05/26	11:39	Stop logging passes
05/26	11:45	Start out of well pass
05/26	12:05	Stop out of well pass
05/26	12:14	Start download
05/26	12:38	Stop download
05/26	12:50	Rig down

Interval Logged:

[From 5,300 to 8,111 ft.]

60 ft/min 90 ft/min 120 ft/min





Well Information

Casing: 5.5" 17.0 lb/ft surface to 8,164 ft PBTD: 8,157 ft Tubing: 2.375" 4.7 lb/ft surface to 5,254 ft Perforations: 5,353; 5,359; 5,361; 5,369; 5,387; 5,393; 5,405; 5,407; 5,419; 5,427; 5,439; 5,455; 5,462; 5,478; 5,492; 5,494; 5,496; 5,498; 5,522; 5,524; 5,542; 5,544; 5,566; 5,568; 5,570; 5,576; 5,578; 5,580; 5,582; 5,584; 5,586; 5,588; 5,590; 5,592; 5,594; 5,596; 5,598; 5,600; 5,602; 5,604; 5,606; 5,608; 5,628; 5,630; 5,632; 5,634; 5,636; 5,638; 5,640; 5,642; 5,644; 5,646; 5,648; 5,714; 5,716; 5,718; 5,720; 5,722; 5,726; 5,728; 5,730; 5,732; 5,734 ft (Stage 5 – Cliffhouse/Menefee) 5,816; 5,820; 5,824; 5,828; 5,832; 5,836; 5,840; 5,844; 5,848; 5,852; 5,856; 5,860; 5,864; 5,868; 5,872; 5,876; 5,880; 5,884; 5,888; 5,892; 5,896; 5,900; 5,904; 5,908; 5,912; 5,916; 5,920; 5,924; 5,928; 5,932; 5,936; 5,940; 5,950; 5,954; 5,960; 5,964; 5,968; 5,980; 5,982; 5,996; 5.998: 6.000: 6.012: 6.014: 6.016: 6.021: 6.040: 6.042: 6.044: 6.046: 6,058; 6,060; 6,068; 6,070; 6,072; 6,079; 6,088; 6,090; 6,092; 6,103; 6,116; 6,118; 6,120; 6,136; 6,139; 6,147; 6,164; 6,168 ft (Stage 4 – Point Lookout) 6,960; 6,970; 6,980; 6,990; 7,000; 7,010; 7,020; 7,030; 7,040; 7,050; 7,060; 7,070; 7,080; 7,090; 7,100; 7,110; 7,120; 7,130; 7,140; 7,150; 7,160; 7,170; 7,180; 7,190; 7,200; 7,210; 7,220 ft (Stage 3 – Upper Mancos) 7,272; 7,282; 7,292; 7,299; 7,308; 7,318; 7,328; 7,338; 7,348; 7,356; 7,365; 7,374; 7,386; 7,397; 7,407; 7,414; 7,424; 7,434; 7,444; 7,531; 7,543; 7,563; 7,703; 7,711; 7,717; 7,725; 7,734 ft (Stage 2 – Lower Mancos) 8,031; 8,035; 8,039; 8,043; 8,047; 8,051; 8,055; 8,059; 8,063; 8,069; 8,077; 8,081; 8,085; 8,089; 8,093; 8,097; 8,101; 8,105; 8,113; 8,117; 8,121; 8,125; 8,129; 8,133; 8,147; 8,149 ft (Stage 1 – Dakota)





Flowing tubing pressure at the time of logging: 70 psi

Daily average surface production reported at the time of logging:

gas: 215 Mscf/d water: N/A bpd

Tool String

The 1 11/16" Completion Profiler string comprised the following sensors:

Battery housing; RS-232/CCL; Memory/CPU; Gamma Ray; Pressure/Temperature Combo; Centralizer; Induction Collar Locator; Fluid Density; Centralizer; Spinner Flowmeter.

Well Log History

Log Date	Type of Survey
05/21/10	Completion Profiler





Results

The following table summarizes the production from each producing zone.

				GAS / WATER PR	ODUCTION F			
Zone	Inte	rvals	Q-Gas	Qp-Gas	Percent of	Q-Water	Qp-Water	Percent of
	feet		MCFD	MCFD	Total	BFPD	BFPD	Total
Surface	to	5353	216 Mcf/d		100 %	2 bpd	-	100 %
1. 187	,	∵Stage 5	- Cliffhouse/Mene	fee 🎎 💯 🚕	9.%	* 1 K 7 K 8		\$#@9\%\\ <u>\</u>
5353	to	5734	216 Mcf/d	19 Mcf/d		2 bpd	0 bpd	
		ِيَّارُ Stag	e 4 Point Lookout		41.%			41%
5816	to	6168	197 Mcf/d	88 Mcf/d		2 bpd	1 bpd	
i. : . ડૂર્નું કે	Sagi fo	ှိ Stag	e 3 ∹Upper Mancos	A Company of the State of the S	10,%	The state of the s	The state of the s	10.%
6960	to	7220	109 Mcf/d	22 Mcf/d		1 bpd	0 bpd	
7 July 383	ig no	∵\ Stage	è 2∷ Lower Mancos		28 %	1 20 C WE	Commence of the second	28,%
7272	to	7734	87 Mcf/d	62 Mcf/d		1 bpd	1 bpd	
	98	<u></u> Ærtbijs	tage 1 - Dakota		12%			12 %
8031	to	8105	25 Mcf/d	25 Mcf/d		0 bpd	0 bpd	
, Flow C	Öntr	ibution fi	ròm Below Log Dei	oth[[§#§#]*\	{\}0% ≥%			() () () () () () () () () ()
8111	to	Below	0 Mcf/d		0 %	0 bpd		0 %