RECEIVED

Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR JUN 13 2011

FORM APPROVED OM B No 1004-0137 Expires March 31, 2007

BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLES Field Office			5 Lease Senal No
			NM-052931
Do not use t	his form for proposals to drill of vell. Use Form 3160-3 (APD) for	i ^u i6areofh <i>e</i> irdManagem	26: If Indian, Allottee or Tribe Name Navajo
SUBMIT IN TRIPLICATE- Other instructions on reverse side.			7 If Unit or CA/Agreement, Name and/or No
1 Type of Well ☐ ☐ Gas Well ☐ ☐ Other			8 Well Name and No.
2 Name of Operator BC&D Operating C/O Nacogdoches O&G Inc.			Hanson #08 9 API Well No
3a Address 816 North Street, Nacogdoche	3b Phone	No. (include area code)	30-031-20044 10 Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec.,			Hospah
330' FWL & 330' FSL Section	• • •		11 County or Parish, State McKinley County, New Mexico
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, RI			EPORT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION			
If the proposal is to deepen dire Attach the Bond under which the following completion of the invitesting has been completed. Find determined that the site is ready 9-1-2010- Placed bottom p 5-04-2011-RIH with 2 3/8' 600'. Pump 95 Sks @ 14.8 Pump 30 more Sks @15.6 5-6-2011- RIH with 2 3/8'' 15 jts, no cement on pipe.	Change Plans Convert to Injection Plug Back ed Operation (clearly state all pertinent details, in ectionally or recomplete horizontally, give subsur- the work will be performed or provide the Bond N volved operations If the operation results in a mu- nal Abandonment Notices shall be filed only after v for final inspection.) olug to sufficiently cover the Gallup sand. F 'WS to tag bottom plug at 1091.66'. POOL PPG for outside annulus plug. Top zone of PPG down Braden head. Allow to set up to WS to 620', Mix and Pump 49 Sks @15.3 RIH with WS with 15 jts, Mix and Pump 2	nstruction Recomplete Abandon Temporarily Abandon k Water Disposal Cluding estimated starting date of an face locations and measured and true lituple completion or recompletion in rall requirements, including reclamate rule requirements. Pumped 51 sacks @15.3 PPG for the with WS, GIH with WS and Flarank 20 sks. Mix and Pump 65 to do inside plug. Ppg. Pull tubing up hole 12 jts, 6 Sks, POOH with WS, LD.	Well Integrity Other y proposed work and approximate duration thereof evertical depths of all pertinent markers and zones d subsequent reports shall be filed within 30 days in a new interval, a Form 3160-4 shall be filed once titon, have been completed, and the operator has r a total fillup of 408'. Packer, set packer at 557.15'. Squeeze holes at Sks, pump down Braden head. Mix and mix and pump 24 Sks, no cement to top. Pull n 5.5'' casing. Job shut down by BLM due-to-
14 I hereby certify that the foreg Name (Printed/Typed) Mike Allen	going is true and correct	Title VP Engineering	14 01 (10) 201)
Signature		Date 06/	(10/2011 C.
	THIS SPACE FOR FEDERAL	OR STATE OFFICE U	JSE MACHINET AND
			JUN 1 3 2011
	ttached Approval of this notice does not warra or equitable title to those rights in the subject le conduct operations thereon		PARAMETON PIELD-OFFICE 997S
Title 18 USC Section 1001 and Title States any false, fictitious or fraudule	43 USG Section 1212, make it a crime for any ent statements or representations as to any matter	person knowingly and willfully to rwithin its jurisdiction	make to any department or agency of the United .

(Instructions on page 2)