

#122 = 30-045-29253

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator MERIDIAN CO Location: Unit B Sec 31 Twp 32 Rng 6

Name of Well/Wells or Pipeline Serviced ALLISON Com #122

Elevation _____ Completion Date _____ Total Depth _____ Land Type _____

Casing Strings, Sizes, Types & Depths 60' of 8" PVC SURFACE
CASING

If Casing Strings are cemented, show amounts & types used With 15
SACKS NEAT CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 85' FRESH WATER

Depths gas encountered: NA

Ground bed depth with type & amount of coke breeze used: 353' DEEP
with 4,750 lbs of Asbury 218R COKE breeze

Depths anodes placed: 325, 260, 250, 240, 230, 220, 210, 200, 190, 180, 170, 145, 135

Depths vent pipes placed: 353' 125, 116

Vent pipe perforations: bottom 240

Remarks: _____

RECEIVED
FEB 19 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	2917-w		P/L NAME (S), NUMBER (S)		ALLISON Com #122		
NO #	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME	
0088		11.05	22.8	484	5-10-96	MRW	
REMARKS (PLEASE FOR CONSTRUCTION LOG)							
B31-32-6 60' 8" CASING 5/9/96 ¹⁵ bags							
WATER 80' Drilled 360' LOGGED 353' PERFORATED 240							
95 bags							

DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *		
95	2.7		295	1.4		490			685				
100	2.7		300	1.1		495			690				
105	2.8		305	1.1		500			695				
110	2.4		310	1.1		505			700				
115	2.8		315	1.1		510			ANODE	DEPTH	NO	FULLY	
120	3.1		320	1.5		515			*		COKE	COK. D	
125	3.2		325	1.8+		520			1	325	2.0	3.5	
130	3.0		330	1.4		525			2	260	2.7	4.3	
135	2.7		335	1.3		530			3	250	3.1	5.1	
140	2.2		340	1.2		535			4	240	2.9	5.0	
145	1.9		345	1.2		540			5	230	2.5	4.8	
150	1.8		350	1.0		545			6	220	2.7	5.2	
155	1.7		355		353'	550			7	210	2.7	5.4	
160	1.8		360			555			8	200	3.1	5.7	
165	2.6		365			560			9	190	2.9	5.5	
170	2.6		370			565			10	180	2.8	5.4	
175	2.7		375			570			11	170	2.7	4.8	
180	2.7		380			575			12	145	2.9	4.6	
185	2.6		385			580			13	135	3.2	5.4	
190	2.7		390			585			14	125	3.3	5.4	
195	2.9		395			590			15	115	2.6	4.9	
200	2.7		400			595			16				
205	2.6		405			600			17				
210	2.6		410			605			18				
215	2.6		415			610			19				
220	2.4		420			615			20				
225	2.3		425			620			21				
230	2.5		430			625			22				
235	2.6		435			630			23				
240	2.8		440			635			24				
245	2.9		445			640			25				
250	2.7		450			645			26				
255	2.6		455			650			27				
260	1.4		460			655			28				
265	1.0		465			660			29				
270	1.0		470			665			30				
275	.9		475			670							
280	.9		480			675							
285	1.1		485			680							

DISTRIBUTION - original - separate CPS FILE
 COPY - Division Corrosion Supervisor
 COPY - Region Corrosion Specialist