<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505

### State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.
For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

12620	
39-07	183

### Pit Below-Grade Tank or

RECEIVED

39-07183 Drama	It, Delow Grade It		By OCD at 11:32 am, Jan 27, 2015
Propo	sed Alternative Method Permit or	<u>: Closure Plan Applic</u>	ation
Type of action:	Below grade tank registration		
-	Permit of a pit or proposed alternative me		
	Closure of a pit, below-grade tank, or prop Modification to an existing permit/or regis		
	Closure plan only submitted for an existing		pit, below-grade tank,
or proposed alte			
Instructions: Ple	ase submit one application (Form C-144) per indivi	idual pit, below-grade tank or al	ternative request
	quest does not relieve the operator of liability should of the operator of its responsibility to comply with any of		
1.	,	TP C	,
Operator: <u>Burlington Resources</u>	OGRID#:	14538	
Address: PO BOX 4289, I	armington, NM 87499		<del> </del>
	7-4 Unit NP 2		
API Number: <u>3003907183</u>	OCD Permit Number:		
U/L or Qtr/Qtr <u>K (NESW)</u>	Section <u>5</u> Township <u>27N</u> Range <u>4W</u>	_ County: _Rio Arriba	
	e <u>36.59938000</u> •N Longitude <u>-107.2766</u>		
Surface Owner: X Federal X State	Private Tribal Trust or Indian Allotment	CD NAD83 36.5995 10	7.2773
2. Pit: Subsection F, G or J of 19	15 17 11 NMAC		
Temporary: Drilling Works		losed Prior to Closure	Plan Approval
	avitation P&A Multi-Well Fluid Manageme		Iling Fluid  yes  no
	Thicknessmil LLDPE HDPE		5
Park-new no.	InicknessiniiLLDFE HDFE	□ FVC □ Oulei	
String-Reinforced	Dokan	. ILL Dimensions I	- W - D
Liner Seams: Welded Facto	ry Other Volume:	:bbl Dimensions: L	x Wx D
3.	THE REPORT OF THE PARTY WAS A SECOND TO SECOND THE PARTY OF THE PARTY		
Below-grade tank: Subsection			
	bbl Type of fluid: <u>Produced Water</u>		
Tank Construction material:			
The same of the sa	k detection 🛛 Visible sidewalls, liner, 6-inch lift a	and automatic overflow shut-off	
☐ Visible sidewalls and liner ☐	Visible sidewalls only   Other		
Liner type: Thickness4	mil  HDPE PVC Other	LLDPE	
4.			
Alternative Method:			

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, linstitution or church)  Four foot height, four strands of barbed wire evenly spaced between one and four feet  Alternate. Please specify	ospital,
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other  Monthly inspections (If netting or screening is not physically feasible)	
Signs: Subsection C of 19.15.17.11 NMAC  12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers  Signed in compliance with 19.15.16.8 NMAC	
Variances and Exceptions:  Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	table source
General siting  Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - □ NM Office of the State Engineer - iWATERS database search; □ USGS; ☑ Data obtained from nearby wells  Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells  Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☒ No ☐ NA ☐ Yes ☐ No ☒ NA
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality  Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No
<ul> <li>Within an unstable area. (Does not apply to below grade tanks)</li> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> <li>Within a 100-year floodplain. (Does not apply to below grade tanks)</li> <li>FEMA map</li> </ul>	<ul><li>☐ Yes ☐ No</li><li>☐ Yes ☐ No</li></ul>
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ⊠ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 300 fect from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No
application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No
Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole,	
or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	1cs 1vo
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Permanent Pit or Multi-Well Fluid Management Pit	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa	
lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of	,
initial application NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 N	NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do	
<ul> <li>attached.</li> <li>Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC</li> <li>Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.5</li> </ul>	9 NMAC
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC ☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19, and 19.15.17.13 NMAC	.15.17.9 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:	
11.  Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC	
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.	cuments are
☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC	
<ul> <li>Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC</li> <li>A List of wells with approved application for permit to drill associated with the pit.</li> </ul>	
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19	0.15.17.9 NMAC
and 19.15.17.13 NMAC  ☐ Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC ☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC	
Previously Approved Design (attach copy of design) API Number: or Permit Number:	

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the description is a check mark in the box, that the description is a check mark in the box, that the description is a check mark in the box, that the description is a check mark in the box, that the description is a check mark in the box, that the description is a check mark in the box, that the description is a check mark in the box, that the description is a check mark in the box, that the description is a check mark in the box, that the description is a check mark in the box is a check mark in the box.	ocuments are
### Authorized Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC    Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC    Climatological Factors Assessment	
Proposed Closure: 19.15.17.13 NMAC  Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.  Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well Fl	uid Management Pit
Alternative  Proposed Closure Method: Waste Excavation and Removal  Waste Removal (Closed-loop systems only)  On-site Closure Method (Only for temporary pits and closed-loop systems)  In-place Burial On-site Trench Burial  Alternative Closure Method	uid wanagement i it
14.  Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be a closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	nttached to the
15. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.  Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	.11 NMAC 15.17.11 NMAC
Operator Application Certification:  I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believed.	
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan)  Closure Plan (only) OCD Conditions (see attachment)	
18. OCD Approval: Permit Application (including closure plan)  Closure Plan (only) OCD Conditions (see attachment)	
18.  OCD Approval: Permit Application (including closure plan)  Closure Plan (only)  OCD Conditions (see attachment)	
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature:  Title: Environmental Specialst  OCD Permit Number:  Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	Apr 15, 2015
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature:  Title: Environmental Specialst  OCD Permit Number:  OCD Permit Number:  19.  Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.  Closure Completion Date: 10/12/10	Apr 15, 2015
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)  OCD Representative Signature:  Title: Environmental Specialst  OCD Permit Number:  Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC  Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	Apr 15, 2015 g the closure report. t complete this

22.	
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure belief. I also certify that the closure complies with all applicable closure require	
Name (Print): Kenny Davis	Title: Staff Regulatory Technician
Signature:	Date: <u>12/3/14</u>
e-mail address: kenny.r.davis@conocophillips.com	Telephone: 505-599-4045

## Burlington Resources Oil Gas Company, LP San Juan Basin Below Grade Tank Closure Report

Lease Name: SJ 27-4 Unit NP2

API No.: 3003907183

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure of the below-grade tank referenced above. All proper documentation regarding closure activities is being included with the C-144.

#### General Plan:

- 1. BR shall close a below-grade tank within 60 days of cessation of operations per Subsection G.4 of 19.15.17.13 NMAC. This will include a) below-grade tanks that do not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC within five years, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC; b) an earlier date that the division requires because of imminent danger to fresh water, public health or the environment. For any closure, BR will file the C144 Closure Report as required.
- 2. The below-grade tank referenced above was permitted and closed within 60 days of cessation of the below-grade tanks operation.
- 3. BR shall remove liquids and sludge from a below-grade tank prior to implementing a closure method and shall dispose of the liquids and sludge in a division-approved facility. The facilities to be used will be Basin Disposal (Permit #NM-01-005), JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) and Envirotech Land Farm (Permit #NM-01-011). The liner after being cleaned well (Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC) will be disposed of at the San Juan County Regional Landfill located on CR 3100.
  - All recovered liquids were disposed of at Basin Disposal (Permit #NM-01-005) and any sludge or soil required to be removed to facilitate closure was hauled to Envirotech Land Farm (Permit #NM-01-011) and JFJ Landfarm % IEI (Permit #NM-01-0010B). The liner was cleaned per Subsection D, Paragraph 1, Subparagraph (m) of 19.15.9.712 NMAC was disposed of at the San Juan County Regional Landfill located on CR 3100.
- 4. BR Will receive prior approval to remove the below-grade tank and dispose of it in a division-approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves.
  - The below-grade tank was disposed of in a division-approved manner.
- 5. If there is any on-site equipment associated with a below-grade tank, then BR shall remove the equipment, unless the equipment is required for some other purpose.
  - All on-site equipment associated with the below-grade tank was removed.
- 6. BR will test the soils beneath the below-grade tank to determine whether a release has occurred. COPC shall collect, at a minimum, a five point, composite sample; collect individual grab samples from any area that is wet, discolored or showing other evidence of a release; and analyzed for the constituents listed in Table I of 19.15.17.13 NMAC. COPC shall notify the division of its results on form C-141.

7. A five point composite sample was taken of the below-grade tank using sampling tools and all samples tested per Subsection B of 19.15.17.1 3(B)(1)(b). (Sample results attached).

Components	Tests Method	Limit (mg/kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	100
Chlorides	EPA 300.1	250

8. If BR or the division determines that a release has occurred, then BR shall comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC, as appropriate.

A release was not determined for the above referenced well.

If the sampling program demonstrates that a release has not occurred or that any release does not exceed the
concentrations specified in Table I of 19.15.17.13 NMAC, then BR shall backfill the excavation with compacted,
non-waste containing, earthen material; construct a division-prescribed soil cover; recontour and re-vegetate the
site.

The below-grade tank area passed all requirements of Paragraph (4) of Subsection E of 19.15.17.13 NMAC and was backfilled with compacted, non-waste containing, earthen material.

- 10. Notice of Closure will be given prior to closure to the Aztec Division office between 72 hours and one week via email or verbally. The notification of closure will include the following:
  - i. Operator's name
  - ii. Location by Unit Letter, Section, Township, and Range. Well name and API number.

Notification is missing due to employee turnovers. ConocoPhillips has reviewed our internal processes and has updated them to include the required 72 hour notification.

11. The surface owner shall be notified of BR's closing of the below-grade tank 72 hours, but not more than one week, prior to closure as per the approved closure plan via certified mail, return receipt requested.

The closure process notification to the landowner not found. COPC was not aware that the original notification sent at the time of Permitting was not the only closure notification required.

ConocoPhillips has reviewed our internal processes and has updated them to include the required 72 hour notification.

12. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.

The below-grade tank area was re-contoured to match fit, shape, line, form and texture of the surrounding area. Re-shaping, including drainage control, to prevent ponding and erosion. Natural drainages were unimpeded and water bars and/or silt traps were placed in areas where needed to prevent erosion on a large scale. Final recontour has a uniform appearance with smooth surface, fitting the natural landscape.

13. BR Shall seed the disturbed areas the first favorable growing season following closure of a below-grade tank. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved

methods. BLM stipulated seed mixes will used on federally regulated lands and division-approved seed mixtures (administratively approved if required) will be utilized on all State or private lands. A uniform vegetative cover has been established that reflects a life-form ratio of plus or minus fifty percent (50%) of pre- disturbance levels and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels, excluding noxious weeds. If alternate seed mix is required by the state, private owner or tribe, it will be implemented with administrative approval if needed. COPC will repeat seeding or planting will be continued until successful vegetative growth occurs.

Provision 13 was accomplished through complying with BLM seeding requirements as allowed by the BLM/OCD MOU.

14. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material, with chloride concentrations less than 600 mg/kg as analyzed by EPA Method 300.0, to establish vegetation at the site, or the background thickness of topsoil, whichever is greater.

The below-grade tank area was backfilled and more than four feet of cover was achieved and the cover included one foot of suitable material to establish vegetation at the site.

- 15. All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of the below-grade tank. Closure report will be filed on C-144 and incorporate the following:
  - Soil Backfilling and Cover Installation (See Report)
  - Re-vegetation application rates and seeding techniques (See Report)
  - Photo documentation of the site reclamation (Included as an attachment)
  - Confirmation Sampling Results (Included as an attachment)
  - Proof of closure notice (Included as an attachment)

Closure Documentation was not submitted within the 60 day requirement due to employee turnovers. ConocoPhillips has reviewed our internal processes and has updated them to ensure closure documentation is submitted with the 60 day time frame.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

### State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-141 Revised October 10, 2003

Submit 2 Copies to appropriate District Office in accordance with Rule 116 on back side of form

### Release Notification and Corrective Action

	OPERATOR	Initial	Report	
Name of Company Burlington Resources	Contact Kenny Davis			
Address 3401 East 30th St, Farmington, NM	Telephone No.(505) 599-4045			
Facility Name: San Juan 27-4 Unit NP 2	Facility Type: Gas Well			
Surface Owner Federal Mineral Owner	Federal	Lease No	o.SF-080673	
LOCATIO	N OF RELEASE			
5 to 100 Million and 91 to 100 Million and 90 Million and 91 to 100 Million and 91 to 10	AND THE PROPERTY OF THE PROPER	/West Line	County	
K 5 27N 4W 1650 South	(HE-11) - 10 - 10 - 10 - 10 - 10 - 10 - 10	SE COLL MODERN NEWSCOTTON	Rio Arriba	
	<u>0</u> Longitude <u>-107.27667000</u>			
	OF RELEASE			
Type of Release BGT Closure Summary	Volume of Release N/A	A SECRETARION CONTRACTOR AND ADDRESS.	ecovered N/A	
Source of Release: NONE	Date and Hour of Occurrence N/A	Date and F	Iour of Discovery N/A	
Was Immediate Notice Given?  ☐ Yes ☐ No ☒ Not Required	If YES, To Whom? N/A			
By Whom? N/A	Date and Hour N/A			
Was a Watercourse Reached?	If YES, Volume Impacting the Wa	atercourse.		
N/A ☐ Yes ☒ No	N/A			
If a Watercourse was Impacted, Describe Fully.* N/A				
Describe Cause of Problem and Remedial Action Taken.* N/A				
			,	
Describe Area Affected and Cleanup Action Taken.*				
BGT Closure: NO RELEASE FOUND UPON REMOVAL				
I hereby certify that the information given above is true and complete to				
regulations all operators are required to report and/or file certain release				
public health or the environment. The acceptance of a C-141 report by the				
should their operations have failed to adequately investigate and remedia or the environment. In addition, NMOCD acceptance of a C-141 report				
federal, state, or local laws and/or regulations.	does not reneve the operator of respon	iisioiiity 101 co	impliance with any other	
	OIL CONSER	VATION	DIVISION	
	OIL COLUBBIA	VIIIIOIV	DIVIDIOIV	
Signature:				
	Approved by District Supervisor:			
Printed Name: Kenny Davis		1		
Title: Staff Regulatory Technician	Approval Date:	Expiration D	Date:	
E-mail Address: Kenny.r.davis@conocophillips.com	Conditions of Approval:		Attached	
700 500 101			radion []	
Date: 12/4/14 Phone: (505) 599-4045	)			
* Attach Additional Sheets If Necessary				



December 9, 2010

Project Number 92115-1460

Ms. Kelsi Harrington ConocoPhillips 3401 East 30<sup>th</sup> Street Farmington, New Mexico 87401

Phone: (505) 599-3403

RE: BELOW-GRADE TANK CLOSURE DOCUMENTATION FOR THE SAN JUAN 27-4 UNIT NP #2 (HBR) WELL SITE, RIO ARRIBA COUNTY, NEW MEXICO

Dear Ms. Harrington,

Enclosed please find the field notes and analytical results for below-grade tank (BGT) closure activities conducted at the San Juan 27-4 Unit NP #2 (hBr) well site located in Section 5, Township 27 North, Range 4 West, Rio Arriba County, New Mexico. Upon Envirotech personnel's arrival on October 12, 2010, one (1) five (5)-point composite sample was collected from directly beneath the BGT; see attached *Field Notes*. The sample was analyzed in the field for total petroleum hydrocarbons (TPH) using USEPA Method 418.1, for organic vapors using a photoionization detector (PID) and for chlorides. Additionally, the sample was placed into a four (4)-ounce glass jar, capped headspace free, and transported on ice, under chain of custody, to Envirotech's Analytical Laboratory to be analyzed for benzene and BTEX using USEPA Method 8021 and for total chlorides using USEPA Method 4500. The sample returned results below the regulatory limits for all constituents analyzed, confirming a release did not occur; see attached *Analytical Results*. Envirotech, Inc. recommends no further action in regards to this incident.

We appreciate the opportunity to be of service. If you have any questions or require additional information, please contact our office at (505) 632-0615.

Respectfully submitted, ENVIROTECH, INC.

Scott Genzales

Senior Environmental Technician sgonzales@envirotech-inc.com

Enclosures:

Field Notes

Analytical Results

Cc:

Client File 92115

PAGE NO: OF  DATE STARTED:  0 -    DATE FINISHED:  0 -	2-10		RONMENT. 5796 U.S ARMINGT	AL SCIENT S. HIGHWA ON, NEW I	CH INC TISTS & ENGI LY 64 - 3014 MEXICO 8740		ENVIRON SPECIALI	ST: 5G 59944989
		EDODE		NE: (505) 6	- Delivery		LONG: - /	07.2773514
May 17 11					SURE VE	ERIFICA	TION	
LOCATION: NAME: < LEGAL ADD: UNIT:	SAN JUAN	distance.			TEMP PIT:		NENT PIT:	BGT: X
QTR/FOOTAGE: /450	K 11 50	SEC:	CN ITTY		7N	RNG: 4	W	PM: NMPM
	3 4 /1050	W	CNIY: 7	Rio Arrib	1A	ST: NM		
EXCAVATION APPROX:		FT. X		FT. X		FT. DEEP	CUBIC YA	RDAGE: -
DISPOSAL FACILITY: LAND OWNER:				REMEDI/	TION METH	OD: -		
CONSTRUCTION MATER	Federal		API:	NELVE E STATE	mil me	BGT/PIT	VOLUME:	120661
LOCATION APPROXIMA					WITH LEAK		N: NO	
DEPTH TO GROUNDWAT		54	FT. 31	50	FROM WEL	LHEAD		
TEMPORARY PIT - C		00 '	DET DEE	D 3 2 Cm 11				
BENZENE ≤ 0.2 mg/kg, B	TEX < 50 mg/k	O GBU % DD.	O ED ACTIO	NI (0016) = 6	0.0 // 70011		NEW ASSESSMENT	
	1211 20 mg n	s, dro a Dr	OFRACIO	C S (C108) NI	uu mg/kg, TPH	$(418.1) \le 250$	0 mg/kg, CHL	ORIDES ≤ 500 mg/k
TEMPORARY PIT - C	ROUNDWA'	TER≥100 FE	ET DEEP					
BENZENE ≤ 0.2 mg/kg, B	IEX ≤ 50 mg/k <sub>i</sub>	g, GRO & DRO	FRACTION	$N(8015) \le 50$	00 mg/kg, TPH (	418.1) ≤ 250	mg/kg, CHL	ORIDES ≤ 1000 mg/
X PERMANENT PIT OF	RBGT							
BENZENE ≤ 0.2 mg/kg,	BTEX ≤ 50 mg	/kg, TPH (418.	1) ≤ 100 mg/	kg, CHLORI	DES ≤ 250 mg/	kg		
					D 418.1 ANAL			
	TIME	SAMPLE I.D.	LAB NO.	WEIGHT (g	mL FREON	DILUTION	READING	CALC. (mg/kg)
	11:10	700 SID		-	eal is my	1 9 11 2	202	(mg/s5)
	11.32	Spt. Comp	2	5	20	. 4	6	24
			3	- 3			-	
		7.5x .100	4			2 - 2 -		
			5					
	-							10,50
PERIM	ETER		FIELD C	HLORIDES	S RESULTS		PRO	FILE.
0.7					x			
1		)	SAMPLE ID	READING	CALC.			
IM WIL								
mul		~ 1		1.4	(mg/kg) 2 3			<del>*</del>
met	v -	>>2	Spl. Comp	1.4	33 3		3	* Ser
mu	X	为之		1.4				· S
[mu]	X 36	72		1.4		į.		
MH	₩ 	7		1.4		į.	X	Y.
MH-	36	72	Spl. Comp	1.4 PID RESUL	33	i u	. X	× 1
	36	2	Spl. Comp	PID RESUL	TS RESULTS	; ; (°	X	
	BG (63		Spl. Comp	PID RESUL	TS RESULTS (mg/kg)	; ;;	. X x	
	36		Spl. Comp	PID RESUL	TS RESULTS	; ( (	X	
	136 63		Spl. Comp	PID RESUL	TS RESULTS (mg/kg)	; (°	. X X	X
	BG 63	7	Spl. Comp	PID RESUL	TS RESULTS (mg/kg)	; ;;	· X X	X
	36		Spl. Comp	PID RESUL	TS RESULTS (mg/kg)	; ;;	X X	X.
	A5	NOTES:	Spl. Comp	PID RESUL	TS RESULTS (mg/kg)	; (° ()	X X	
LAB SAMPLES SAMPLE ID ANALYSIS	S ]	NOTES:	Spl. Comp  P  SAMP  Spl. Com	PID RESUL	TS RESULTS (mg/kg) ND	; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;	X X	Y.
LAB SAMPLES SAMPLE ID ANALYSIS BENZENE	S ]	NOTES:	Spl. Comp  P  SAMP  Spl. Com	PID RESUL	TS RESULTS (mg/kg)	toned	X X	
LAB SAMPLES SAMPLE ID ANALYSIS BENZENE BTEX	S RESULTS	NOTES:	Spl. Comp  P  SAMP  Spl. Com	PID RESUL	TS RESULTS (mg/kg) ND	doned	X X	
LAB SAMPLES SAMPLE ID ANALYSIS BENZENE	S RESULTS	NOTES:	Spl. Comp  P  SAMP  Spl. Com	PID RESUL	TS RESULTS (mg/kg) ND	doned	X X	
LAB SAMPLES SAMPLE ID ANALYSIS BENZENE BTEX GRO & DRO	S RESULTS	NOTES:	Spl. Comp  P  SAMP  Spl. Com	PID RESUL	TS RESULTS (mg/kg) ND	doned	X X	X



### **EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS**

Client:

ConocoPhillips

92115-1460

Sample No.:

1

Project #: Date Reported:

10/22/2010

Sample ID: Sample Matrix:

**BGT** Composite

Soil

Date Sampled: Date Analyzed:

10/12/2010 10/12/2010

Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Total Petroleum Hydrocarbons** 

24

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

San Juan 27-4 Unit NP #2 (hBr)

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Scott Gonzales

Printed

Sarah Rowland, EIT

Printed



# CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal. Date:

12-Oct-10

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
TPH	100		
	200	202	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

Scall Con C	10/22/2010
CAnalyst	Date
Scott Gonzales Print Name	
50h Roll	10/22/2010
Review	Date

Sarah Rowland, EIT

Print Name



### **Field Chloride**

Client:

ConocoPhillips

1

Sample No.: Sample ID:

**BGT Composite** 

Sample Matrix:

Soil

Preservative:

Cool

Condition:

Cool and Intact

Project #:

92115-1460

Date Reported:

10/22/2010

Date Sampled:

10/12/2010

Date Analyzed:

10/12/2010

Analysis Needed:

Chloride

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Field Chloride** 

33

33.0

ND = Parameter not detected at the stated detection limit.

References:

"Standard Methods for the Examination of Water and Wastewater", 18th ed., 1992

Hach Company Quantab Titrators for Chloride

Comments:

San Juan 27-4 Unit NP #2 (hBr)

Analyst

Scott Gonzales

Printed

Review

Sarah Rowland, EIT

Printed



### **EPA METHOD 8021** AROMATIC VOLATILE ORGANICS

Client: Sample ID: Laboratory Number: Chain of Custody: Sample Matrix: Preservative: Condition:	ConocoPhillips 5 Pt Comp. 56165 10512 Soil Cool Intact		Project #: Date Reported: Date Sampled: Date Received: Date Analyzed: Date Extracted: Analysis Requested: Dilution:		92115-1460 10-18-10 10-12-10 10-12-10 10-15-10 10-13-10 BTEX 10
Parameter		Concentration (ug/Kg)		Det. Limit (ug/Kg)	
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene		ND 2.6 1.9 17.7 7.5		0.9 1.0 1.0 1.2 0.9	
Total BTEX		29.7			

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	the second secon
Fluorobenzene  1,4-difluorobenzene  Bromochlorobenzene		Percent Recovery
	1,4-difluorobenzene	103 % 104 % 117 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

29.7

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

San Juan 27-4 NP #2



### **EPA METHOD 8021** AROMATIC VOLATILE ORGANICS

Client: Sample ID: Laboratory Number: Sample Matrix: Preservative: Condition:	N/A 1015BBLK QA/QC 56161 Soil N/A N/A		Project #: Date Reported: Date Sampled: Date Received: Date Analyzed: Analysis: Dilution:	N/A 10-18-10 N/A N/A 10-15-10 BTEX			
Calibration and Detection Limits (ug/L)	I-Cal RF:	C-Cal RF: Accept. Ra	%Diff. nge 0 - 15%	Blank Conc	Detect.		
Benzene Toluene Ethylbenzene o,m-Xylene o-Xylene	4.2758E+005 5.4569E+005 4.9768E+005 1.1859E+006 4.5154E+005	4.2844E+005 5.4678E+005 4.9868E+005 1.1883E+006 4.5244E+005	0.2% 0.2% 0.2% 0.2% 0.2%	ND ND ND ND	0.1 0.1 0.1 0.1		

Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff.	Accept Range	Detect. Limit
Benzene	ND	ND	0.0%	0 - 30%	0.9
Toluene	4.0	3.6	10.0%	0 - 30%	1.0
Ethylbenzene	ND	ND	0.0%	0 - 30%	1.0
p,m-Xylene	4.1	3.5	14.6%	0 - 30%	1.2
o-Xylene	1.8	1.8	0.0%	0 - 30%	0.9

Splke Conc. (ug/Kg)	Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Range
Benzene	ND	500	532	106%	39 - 150
Toluene	4.0	500	535	106%	46 - 148
Ethylbenzene	ND	500	538	108%	32 - 160
p,m-Xylene	4.1	1000	1,080	108%	46 - 148
p-Xylene	1.8	500	542	108%	46 - 148

ND - Parameter not detected at the stated detection limit.

Dilution: Spike and spiked sample concentration represent a dilution proportional to sample dilution.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 56161-56162, 56165, 56169-56170, 56175

Analyst



### Chloride

		1000	
Client:	ConocoPhillips	Project #:	92115-1460
Sample ID:	5 Pt Comp	Date Reported:	10-13-10
Lab ID#:	56165	Date Sampled:	10-12-10
Sample Matrix:	Soil	Date Received:	10-12-10
Preservative: Condition:	Cool	Date Analyzed:	10-13-10
Condition:	Intact	Chain of Custody:	10512

Parameter

Concentration (mg/Kg)

**Total Chloride** 

5

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

San Juan 27-4 NP #2

Analyst

### CHAIN OF CUSTODY RECORD

10512

Client:			Project Name /						F					4 41			de.		100	4 6		°= (- )
ConocoP	illips		SAN JU	02	7-4	NP #2						200		ANA	LYSIS	/ PAI	RAME	TERS				
Client Address:			Sampler Name	•	1/ 7/ 707	ESCO., OF E.				X		1	T	Т	_	_		W. T				
		1	Snott	6	2.120/25				15	20	000				1		1	1				
Client Phone No.:			Client No.:		sa raies			alekso.	1 8	bo	80	Ses	-		ے	1		1 1				
			92115-	141.	.1				18	et	1 \$	Met	18	1	三	1	10	ш	1	1	0	ton
Sample No./	Sample	Sample	1211	170	Sample	No./Volum	o la		3	18	(Me	00	2	1	wit	1	418	2	- 1		Ö	T E
Identification	Date	Time	Lab No.		Matrix	of Container				BTEX (Method 8021)	VOC (Method 8260)	RCRA 8 Metals	Cation / Anion	RC.	TCLP with H/P	PAH	TPH (418.1)	CHLORIDE			Sample Cool	Sample Intact
Spt. Comp	10-12-10	11:45	56165	Solid				V	2	-	>	E	O	œ	F	2	F	0	+	+		T
				Soil Solid	Sludge Aqueous		$\forall$		4	T .									+	+	Y	4
			Solid	Sludge Aqueous		$\dagger\dagger$	+	GX GX	191	1015	C						+	+	$\vdash$		-	
	,			Soil Solid	Sludge Aqueous		$\dagger \dagger$	$\dagger$		10/1	ang	Cu	<u>م</u>					+	+	-		
				Soil Solid	Sludge Aqueous		$\forall$							$\dashv$				+	+	-		
				Soil Solid	Sludge Aqueous		H	$\dagger$					-	+		-		+	+	$\vdash$		
				Soil Solid	Sludge Aqueous		H	$\top$						+	+	$\dashv$	-	+	+		-	
				Soil Solid	Sludge Aqueous		H	$\forall$			$\dashv$	-	+	+	$\dashv$	+	$\dashv$	+	+	$\dashv$	4	_
				Soil Solid	Sludge Aqueous		$\Box$	$\dagger \dagger$			-	+	+	+	$\dashv$	$\dashv$	$\dashv$	+	+	$\dashv$	$\dashv$	
				Soil Solid	Sludge Aqueous		$\parallel$	$\dagger \dagger$	7		+	$\dashv$	1	$\dashv$	+	+	$\dashv$	+	+	-	$\dashv$	_
elinquished by: (Sign	eture)	7_		1	Date	Time	Re	ceived	l by: (	Signa	ture)								Da	ite	Tin	ne
elinquished by: (Signa	ature)				10-12-10	14:00	Rec	ceived	by: (	Signal	ture)								10.0	2.10	14:	00
elinquished by: (Signa	ature)						Red	ceived	by: (8	Signat	ure)								+	_		_
•																				- 1		
				-	3	And	alyti	call	Lab	orat	огу											
			5796 US	Highway	64 • Farming	ton, NM 8740	01 • 50	5-632-	0615	• lab@	enviro	tech-li	nc.com	16								





