District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

THE DOWN THAT I ATTEMPT OF	EIVED ollins at 8:02 am, Apr 05, 2016
Type of action: Below grade tank registration Permit of a pit or proposed alternative method Closure of a pit, below-grade tank, or proposed alternative method Modification to an existing permit/or registration Closure plan only submitted for an existing permitted or non-permitted pit, below or proposed alternative method	·grade tank,
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative re	quest
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, greenvironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, references to the operator of its responsibility to comply with any other applicable governmental authority's rules, references to the operator of its responsibility to comply with any other applicable governmental authority's rules, references to the operator of its responsibility to comply with any other applicable governmental authority's rules, references to the operator of its responsibility to comply with any other applicable governmental authority's rules, references to the operator of its responsibility to comply with any other applicable governmental authority's rules, references to the operator of its responsibility to comply with any other applicable governmental authority's rules, references to the operator of its responsibility to comply with any other applicable governmental authority is rules.	ound water or the egulations or ordinances.
Operator: Burlington Resources Oil & Gas Company, LP OGRID #: 14538 Constituents Exceed Standard	dards outline
Address: PO BOX 4289, Farmington, NM 87499 by 19.15.17.13 NMAC. Ple	ase submit a
Facility or well name: SAN JUAN 27-4 UNIT 120 separate C-141 under 19.1	
API Number:30-039-22122 OCD Permit Number:	0.20 1111111
U/L or Qtr/Qtr K (NESW) Section 34 Township 27N Range 4W County: Rio Arriba	BGT CLOSED
Center of Proposed Design: Latitude <u>36.52683817 ∘N</u> Longitude <u>-107.2420966 ∘W</u> NAD: □1927 ⊠ 1983	PRIOR TO
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment	CLOSURE
2.	PLAN APPROVAL
Pit: Subsection F, G or J of 19.15.17.11 NMAC	ALLICOVAL
Temporary: Drilling Workover	
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A ☐ Multi-Well Fluid Management ☐ Low Chloride Drilling Fluid	***************************************
☐ Lined ☐ Unlined Liner type: Thicknessmil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other	
String-Reinforced	
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L_x W_x D_	
3. Below-grade tank: Subsection I of 19.15.17.11 NMAC	
Volume: MAX 120 bbl Type of fluid: Produced Water	
Tank Construction material: Metal	
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off	
∀ Visible sidewalls and liner Visible sidewalls only Other	
Liner type: Thicknessmil	
4.	
Alternative Method:	
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consi	deration of approval.

institution or church)

Alternate. Please specify

Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital,

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)

Four foot height, four strands of barbed wire evenly spaced between one and four feet

4							
6. Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)							
☐ Screen ☐ Netting ☐ Other							
☐ Monthly inspections (If netting or screening is not physically feasible)							
7.							
Signs: Subsection C of 19.15.17.11 NMAC							
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers							
☐ Signed in compliance with 19.15.16.8 NMAC							
8.							
<u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.							
Please check a box if one or more of the following is requested, if not leave blank:							
☐ Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.							
Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.							
9.							
Siting Criteria (regarding permitting): 19.15.17.10 NMAC	. 11						
Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptate material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	otable source						
General siting							
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.	☐ Yes ☐ No						
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	⊠ NA						
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells							
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	☐ Yes ☐ No						
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) - Written confirmation or verification from the municipality; Written approval obtained from the municipality							
Within the area overlying a subsurface mine. (Does not apply to below grade tanks) - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division							
Within an unstable area. (Does not apply to below grade tanks) - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society Topographic map							
Society; Topographic map Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map							
Below Grade Tanks							
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured							
from the ordinary high-water mark).	☐ Yes ☑ No						
- Topographic map; Visual inspection (certification) of the proposed site							
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site							
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)							
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	☐ Yes ☐ No						
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 							
Vithin 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock vatering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. IM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site							

Within 100 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pit Non-low chloride drilling fluid								
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site								
Within 300 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Permanent Pit or Multi-Well Fluid Management Pit								
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.								
 NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 								
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NI Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	nments are NMAC 5.17.9 NMAC							
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc. attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.1 and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.19 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number:	15.17,9 NMAC							

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	documents are						
 attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 							
 □ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC □ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC □ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC □ Quality Control/Quality Assurance Construction and Installation Plan □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC 							
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan 							
Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC							
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.							
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative	luid Management Pit						
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial							
Alternative Closure Method							
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. ☐ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC ☐ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC ☐ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) ☐ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC ☐ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC ☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC							
15.							
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.							
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA						
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NA							
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells Yes No NA							
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No						
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence to the time of initial application. - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site							
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No						
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance							

- Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No							
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division								
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map								
Within a 100-year floodplain. - FEMA map Yes \[\] N								
16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC								
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believes.	ief.							
Name (Print): Title:								
Signature: Date:								
e-mail address: Telephone:								
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 7/12/2	See Front Page							
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	See Front Page							
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 7/12/2	See Front Page 2016 g the closure report.							
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 7/12/2 Title: Compliance Officer OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not	See Front Page 2016 g the closure report.							
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 7/12/2 Title: Compliance Officer OCD Permit Number: 19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed.	See Front Page 2016 g the closure report. t complete this							

22.
Operator Closure Certification:
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
Name (Print) <u>Crystal Walker</u> Title: <u>Regulatory Coordinator</u>
Signature:
e-mail address: <u>crystal.walker@cop.com</u> Telephone: (505) 326-9837

Burlington Resources Oil & Gas Company San Juan Basin: New Mexico Assets

Below Grade Tank Closure Report

Lease Name: San Juan 27-4 Unit 120

API No.: 30-039-22122

In accordance with Rule 19.15.17.13 NMAC, the following information describes the closure of the below-grade tank referenced above. All proper documentation regarding closure activities is being included with the C-144.

General Plan Requirements:

1. Prior to initiating any BGT closure, except in the case of an emergency, BR will notify the surface owner of the intent to close the BGT by certified mail no later than 72 hours or one week before closure and a copy of this notification will be included in the closure report. In the case of an emergency, the surface owner will be notified as soon as practical.

The surface owner notification was not found.

- Notice of closure will be given to the District Division office between 72 hours and one week of the scheduled closure via email or phone. The notification of closure will include the following:
 - a. Operators Name
 - b. Well Name and API Number
 - c. Location

Notification was not found.

3. All liquids will be removed from the BGT following cessation of operation. Produced water will be disposed of at one of COP's approved Salt Water Disposal facilities or at a District Division approved facility.

All recovered liquids were disposed of at an approved SWD facility or an approved District Division facility within 60 days of cessation of operation.

4. Solids and sludge's will be shoveled and/or vacuumed out for disposal at one of the District Division approved facilities, depending on the proximity of the BGT site: Envirotech Land Farm (Permit #NM-01-011), JFJ Land Farm % Industrial Ecosystems Inc. (Permit #NM-01-0010B), and Basin Disposal (Permit #NM-01-005).

Any sludge or soil required to be removed to facilitate closure was transported to Envirotech Land Farm (Permit # NM-01-011) and/or JFJ Landfarm % IEI (Permit# NM-01-0010B).

5. BR will obtain prior approval from District Division to dispose, recycle, reuse, or reclaim the BGT and provide documentation of the disposition of the BGT in the closure report. Steel materials will be recycled or reused as approved by the District Division. Fiberglass tanks will be empty, cut up or shredded, and EPA cleaned for disposal as solid waste. Liner materials will be cleaned without soils or contaminated material for disposal as solid waste. Fiberglass tanks and liner materials will meet the conditions of 19.15.35 NMAC. Disposal

will be at a licensed disposal facility, presently San Juan County Landfill operated by Waste Management under NMED Permit SWM-052426.

The below-grade tank was disposed of in a division-approved manner. The liner was cleaned per 19.15.35.8.C(1)(m) NMAC and disposed of at the San Juan County Regional Landfill located on CR 3100.

6. Any equipment associated with the BGT that is no longer required for some other purpose, following the closure, will be removed.

All on-site equipment associated with the below-grade tank was removed.

- 7. Following removal of the tank and any liner material, BR will test the soils beneath the BGT as follows:
 - a. At a minimum, a five-point composite sample will be taken to include any obvious stained or wet soils or any other evidence of contamination.
 - b. The laboratory sample shall be analyzed for the constituents listed in Table I of 19.15.17.13.

A five point composite sample was taken of the below-grade tank using sampling tools and all samples tested per Table I of 19.15.17.13 and the results are attached.

8. If the District Division and/or BR determine there is a release, BR will comply with 19.15.17.13.C.3b.

A release was not determined for the above referenced well.

9. Upon completion of the tank removal, pursuant to 19.15.17.13.C.3c, if all contaminant concentrations are less than or equal to the parameters listed in Table I of 19.15.17.13 NMAC, the excavation will be backfilled with non-waste earthen material compacted and covered with a minimum of one foot top soil or background thickness whichever is greater and to existing grade. The surface will be re-contoured to match the native grade and to prevent ponding.

The tank removal area passed all requirements of Table I of 19.15.17.13 NMAC and was backfilled with compacted, non-waste containing, earthen material which included at least one foot of suitable material to establish vegetation at the site.

10. For those portions of the former BGT area no longer required for production activities, BR will seed the disturbed area the first favorable growing season after the BGT is covered. Seeding will be accomplished via drilling on the contour whenever practical, or by other District Division-approved methods. BR will notify the District Division when reclamation and re-vegetation is complete.

Reclamation of the BGT shall be considered complete when:

- Vegetative cover reflects a life form ratio of +/- 50% of pre disturbance levels.
- Total percent plant cover of at least 70% of pre-disturbance levels (Excluding noxious weeds) OR
- Pursuant to 19.15.17.13.H.5d BR will comply with obligations imposed by other applicable federal or tribal agencies in which there re-vegetation and reclamation

requirements provide equal or better protection of fresh water, human health and the environment.

Provision 10 will be accomplished pursuant to 19.15.17.H.5d and notification will be submitted upon completion.

11. For those portions of the former BGT area required for production activities, reseeding will be done at well abandonment, and following the procedure noted above.

The former BGT is not required for production activities and reseeding was completed on 5/6/2013 per the procedure noted above.

Closure Report:

All closure activities will include proper documentation and will be submitted to OCD within 60 days of the BGT closure on a Closure Report using District Division Form C-144. The Report will include the following:

- Proof of Closure Notice (surface owner and District Division) (Not Attached)
- Backfilling & cover installation (See Report)
- Confirmation Sampling Analytical Results (Attached)
- Application Rate & Seeding techniques (See Report)
- Photo Documentation of Reclamation (Attached)

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

* Attach Additional Sheets If Necessary

State of New Mexico Energy Minerals and Natural Resources

19

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-141 Revised October 10, 2003

Submit 2 Copies to appropriate District Office in accordance with Rule 116 on back side of form

Release Notification and Corrective Action

						OPERA:	TOR		Initia	ıl Report	\bowtie	Final Report
Name of Company Burlington Resources, a Wholly Owned Subsidiary of ConocoPhillips Company						Contact S	helly Cook-Co	wden				
						Telephone No. 505-324-5140						
						Facility Type: Gas Well API#3003922122						
Surface Owner: Forest Mineral Owner:						Fadaval			Lanca	lo. NMSF	0006	75
Surface Ow.	ner. Fores	ı		Willeral O	wher, i	rederai			Lease N	O. NIVISE	- 0000	/5
LOCATIO						OF REI	LEASE					
Unit Letter	Section	Township	Range	Feet from the	North/South Line Feet from the East/West Line County							
K	34	027N	004W	1560'	5	South 1595' West				Rio Arr	iba	
Latitude 36.5272 ° N Longitude -107.242333 ° W												
Type of Relea	aga Haka	ourn.		NAI	UKE	OF RELI	Release – Unkn	NOW I	Volume R	agazianad		
Source of Rel			ank				lour of Occurrence			Hour of Disc	overv .	_
Bource of Re	icase - Der	ow Grade 1	ATTIC			Unknown	our or occurrence		August 19		20 (01)	
Was Immedia	ate Notice (1,120,120	Yes [No 🛭 Not Red	quired	If YES, To	Whom?	'	· ·			
By Whom?						Date and Hour						
Was a Watero	course Read		v 5	Lar		If YES, Vo	lume Impacting t	he Wate	rcourse.			
			Yes 🛚	No								
If a Watercou		•										
Describe Cause of Problem and Remedial Action Taken.* Below grade tank closure activities.												
Describe Area Affected and Cleanup Action Taken.*The below grade tank sample results were above regulatory standard by USEPA method 418.1 for TPH and Organic Vapors, confirming a release. The sample was then transported to the lab and analytical results were below the regulatory standards set forth in the NMOCD Guidelines for Remediation of Leaks, Spills and Release; therefore no further action is required.												
I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.												
		U.					OIL CONS	SERV	ATION	DIVISIO	N	
	~ ~		0									
Signature:	Zheovey (Cook-On	ode									
Printed Name					1	Approved by District Supervisor:						
Title: Field E	nvironment	al Specialist			1	Approval Dat	e:	E	Expiration I	Date:		
E-mail Addre	ss: Shelly.	g.Cook-Cowd	en@Conc	coPhillips.com	(Conditions of	Approval:			Attached		
Date: October	r 21, 2011		Pho	ne: 505-324-5140								



October 13, 2011

Project Number 92115-1914

Phone: (505) 599-3403

Ms. Kelsi Harrington Conoco Phillips 3401 East 30th Street Farmington, New Mexico 87401

RE: BELOW-GRADE TANK CLOSURE DOCUMENTATION FOR THE SAN JUAN 27-4 #120 (HBR) WELL

SITE, RIO ARRIBA COUNTY, NEW MEXICO

Dear Ms. Harrington,

Enclosed please find the field notes and analytical results for below-grade tank (BGT) closure activities performed at the San Juan 27-4 #120 (hBr) well site located in Section 34, Township 27 North, Range 4 West, Rio Arriba County, New Mexico. Prior to Envirotech's arrival on August 19, 2011, the BGT had been removed. One (1) five (5)-point composite sample was collected from beneath the former BGT. The sample was analyzed in the field for total petroleum hydrocarbons (TPH) using USEPA Method 418.1, for organic vapors using a photoionization detector (PID), and for chlorides. Additionally, the sample was placed into a four (4)-ounce glass jar, capped headspace free, and transported on ice, under chain of custody, to Envirotech's Analytical Laboratory to be analyzed for benzene and BTEX using USEPA Method 8021 and for total chlorides using USEPA Method 4500. The sample returned results below the regulatory standards for benzene, BTEX and chlorides but above the regulatory standard of 100 parts per million (ppm) TPH using USEPA Method 418.1, confirming a release did occur.

A brief site assessment was conducted and the regulatory standards were determined to be 1000 ppm TPH and 1000 ppm organic vapors due to horizontal distance to surface water between 200 and 1,000 feet, pursuant to New Mexico Oil Conservation Division (NMOCD) Guidelines for Remediation of Spills, Leaks, and Releases. The sample from beneath the former BGT returned results below the regulatory standards for TPH using USEPA Method 418.1; see attached *Analytical Results*. Envirotech, Inc. recommends no further action in regards to this incident.

We appreciate the opportunity to be of service. If you have any questions or require additional information, please contact our office at (505) 632-0615.

Respectfully submitted,

ENVIROTECH, INC.

John Rollins

Environmental Technician irollins@envirotech-inc.com

Enclosures: Analytical Results

Field Notes

Cc: Client File 92115

							-4	
PAGE NO: OF		3 en	viro	tech		100	IMENTAL SPECIALIST:	
DATE STARTED: 8/19/11	// 5796 U.S. Hwy 64, Farmington, NM 87401						52683817	
DATE FINISHED: 8/19/11	PHONE: (505) 632-0615						07.2420966	
FIELD REPORT: BGT / PIT CLOSURE VERIFICATION								
LOCATION: NAME: SS 27-9	/	WELL#:/	20	TEMP PIT:	PERMAN	NENT PIT:	BGT:X	
LEGAL ADD: UNIT: K	SEC: 3 </td <td></td> <td>TWP: 27</td> <td></td> <td>RNG: YW</td> <td></td> <td>PM: MA</td>		TWP: 27		RNG: YW		PM: MA	
QTR/FOOTAGE: 1563 FSL + 159	5 FUK-	CNTY:	V Arcide	-	ST: NN			
EXCAVATION APPROX: FT. X — FT. X — FT. DEEP CUBIC YARDAGE: —								
DISPOSAL FACILITY:	rr. A			TION METHO		CODIC 17	ARDAGE;	
LAND OWNER:		API:	KEMEDIA	HON WETH	BGT / PIT	VOI IIME		
CONSTRUCTION MATERIAL:			WALLED V	WITH LEAK D			111	
LOCATION APPROXIMATELY:					And in case of the last of the	··· Simbo	/ Sing Le	
DEPTH TO GROUNDWATER:	98.4	FT. 24	20	FROM WELL	HEAD			
TEMPORARY PIT - GROUNDWAT		ET DEED						
BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/			N (8015) < 50	n mo/ko TPH (418 1) < 2500	ma/ka CHI	OPIDES < 500 mg/kg	
			11 (0015) 3 50	ongag, IIII (410.1) \$ 2500	mg/kg, Crit	CONTDES 2 200 HIG/Kg	
TEMPORARY PIT - GROUNDWAT	Appropriate the second of the	**************************************	Carlo Service Control Control					
BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/l	cg, GRO & DRO	FRACTION	$1(8015) \le 50$	0 mg/kg, TPH (4	118.1) ≤ 2500	mg/kg, CHL	ORIDES ≤ 1000 mg/kg	
PERMANENT PIT OR BGT								
BENZENE ≤ 0.2 mg/kg, BTEX ≤ 50 mg/	kg, TPH (418.1)	≤ 100 mg/kg	, CHLORIDI	ES ≤ 250 mg/kg				
			FIEL	D 418.1 ANAL	vere			
TIME	SAMPLE I.D.	LAB NO.	WEIGHT (g		DILUTION	READING	CALC. (mg/kg)	
10:05	So o STD		-		-	8/6	Crizo. (inglig)	
سي يردنه	BGT.	1	5	30	4	37	148	
		2						
		<u>3</u>						
		5						
		6					***	

DED IN CERED							200-200-200-20	
PERIMETER			HLORIDES	RESULTS		PRO	OFILE	
1 /		SAMPLE ID	READING	CALC.	1			
	<u>.</u>	BET	ND	(mg/kg)				
,		100.	700	NO				
				la dow		3	$\langle \chi \rangle$	
1 / $^{\prime}$						(XX		
n61	-					(XX		
	-	F	ID RESUL	TS				
	H	7		RESULTS		TXXXX		
	1	SAMP	LEID	(mg/kg)	•	TXXX	*	
		136	Ť	ND		, , ,		
	-							
	}-					,		
	ŀ				XSSA	ple por	\sim	
LAB SAMPLES	NOTES:							
SAMPLE ID ANALYSIS RESULTS								
BENZENE								
BTEX								
GRO & DRO CHLORIDES							I	
C. L.								
	WORKORDER	.#		WHO ORDERE	ED			

Client:				ENVIT (505) 632-0615 8 U.S. Hwy 64, Fa	(800) 362-11	879	Project No.	115-1914
FIELD REPORT: S	PILL CL	OSURE V	ERIFIC	ATION			PAGE N	0: / OF /
								TARTED: 8/19/11
QUAD/UNIT: K SEC: 3-1 TWP: 2.7 1/RNG: -1/1 PM: 1/10 CNTW 0/1 CT 1/20								
QTR/FOOTAGE: 15-60 F		595 FWL	CONTRA	CTOR:	CIVI 1. Ja	4 31: ////		NMENTAL JIST: 5/C
EXCAVATION APPROX:		FT. X						
DISPOSAL FACILITY:		11. A		FT. X REMEDIAT	ION METH	FT. DEEP	CUBIC Y	ARDAGE:
LAND USE:			LEASE:			LAND OW	NER.	-
CAUSE OF RELEASE:	36T R	moral		MATERIAL	RELEASED	BGT	Mederi	<u> </u>
SPILL LOCATED APPROXI	MATELY:	96.4		10°	FROM IN	"Il head		
DEPTH TO GROUNDWATE NMOCD RANKING SCORE	: 16	NEAREST	WATER SO	URCE:シ/	<u> </u>	NEAREST		WATER: 654
SOIL AND EXCAVATION I	ESCRIPTIO	N·	NMOCD 7	TPH CLOSUR	E STD: /	000	PPM	
SAMPLE DESCRIPTION 200 STD 65T	TIME /0:05	SAMPLE I.D.	LAB NO.	WEIGHT (g)	mL FREON	DILUTION	READING 2/6 37	CALC. ppm
					_		-	
SPILL PERI	METER		SALEN D	OVM RESULTS			SPILL F	PROFILE
1			SAMPLE ID GGT	FIELD HEADS				
N/		_				f	1 1	
10		ļ	I	AB SAMPLE	2	(C	x x Y	
BET			SAMPLE ID	ANALYSIS	TIME			
						1	KKY	t
						X= 54	mole,	aint
AVEL NOTES:C	CALLED OUT				NSITE:			



CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

-	
Cal	11000
1	Date:

19-Aug-11

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
TPH	100		
	200	216	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

	9/12/2011
Analyst	Date
John Rollins	
Print Name	
Toni Melnight	9/12/2011
Review	Date
Toni Mcknight, EIT	

Print Name



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

ConocoPhillips

1

Sample No.: Sample ID:

Sample Matrix:

Preservative:

BGT Soil Cool

Condition: Cool and Intact

Project #:

92115-1914

Date Reported:

9/12/2011

Date Sampled: Date Analyzed: 8/19/2011 8/19/2011

Analysis Needed:

TOU 440

eded: TPH-418.1

Parameter	(mg/kg)	(mg/kg)
	Concentration	Limit
		Det.

Total Petroleum Hydrocarbons

148

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

San Juan 27-4 #120

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

John Rollins

Printed

Review

Toni Mcknight, EIT

Printed



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client	O		
Client:	ConocoPhillips	Project #:	92115-1907
Sample ID:	BGT	Date Reported:	08-22-11
Laboratory Number:	59342	Date Sampled:	08-19-11
Chain of Custody:	12396	Date Received:	08-19-11
Sample Matrix:	Soil	Date Analyzed:	08-22-11
Preservative:	Cool	Date Extracted:	08-20-11
Condition:	Intact	Analysis Requested:	BTEX
		Dilution:	10

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	ND	0.9	
Toluene	ND	1.0	
Ethylbenzene	ND	1.0	
p,m-Xylene	6.8	1.2	
o-Xylene	1.4	0.9	
Total BTEX	8.2		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery		
	Fluorobenzene	89.7 %		
	1,4-difluorobenzene	100 %		
	Bromochlorobenzene	81.6 %		

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

San Juan 27-4 #120

Arralyst

Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A		Project #:		N/A	
Sample ID:	0822BBLK QA/QC		Date Reported:		08-22-11	
Laboratory Number:	59342		Date Sampled:		N/A	
Sample Matrix:	Soil		Date Received:		N/A	
Preservative:	N/A		Date Analyzed:		08-22-11	
Condition:	N/A		Analysis:		BTEX	
			Dilution:		10	
Calibration and	I-Cal RF:	C-Cal RF:	%Diff,	Blank	Detect.	
Detection Limits (ug/L)		Accept, Rai	nge 0 - 15%	Conc	Limit	
Benzene	2.0549E+006	2.0591E+006	0.2%	ND	0.1	
Toluene	2.8377E+006	2.8434E+006	0.2%	ND	0.1	
Ethylbenzene	2.9315E+006	2.9374E+006	0.2%	ND	0.1	
p,m-Xylene	7.9261E+006	7.9419E+006	0.2%	ND	0.1	
o-Xylene	2.8558E+006	2.8615E+006	0.2%	ND	0.1	

Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff.	Accept Range	Detect, Limit
Benzene	ND	ND	0.0%	0 - 30%	0.9
Toluene	ND	ND	0.0%	0 - 30%	1.0
Ethylbenzene	ND	ND	0.0%	0 - 30%	1.0
p,m-Xylene	6.8	6.7	1.5%	0 - 30%	1.2
o-Xylene	1.4	1.2	14.3%	0 - 30%	0.9

Spike Conc. (ug/Kg)		Sample	Amount Spiked	Spiked Sample	% Recovery	Accept Range
Benzene		ND	500	449	89.9%	39 - 150
Toluene	(*)	ND	500	486	97.1%	46 - 148
Ethylbenzene		ND	500	496	99.2%	32 - 160
p,m-Xylene		6.8	1000	1,000	99.3%	46 - 148
o-Xylene		1.4	500	492	98.0%	46 - 148

ND - Parameter not detected at the stated detection limit.

Dilution: Spike and spiked sample concentration represent a dilution proportional to sample dilution.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using

Photolonization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

59311-59317, 59342

Review



Chloride

Client:

ConocoPhillips

Project #:

92115-1907

Sample ID:

BGT

Date Reported:

08/22/11

Lab ID#:

59342

Date Sampled:

08/19/11

Sample Matrix:

Soil

Date Received:

08/19/11

Preservative:

Cool

Date Analyzed:

08/22/11

Condition:

Intact

Chain of Custody:

12396

Parameter

Concentration (mg/Kg)

Total Chloride

60

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

San Juan 27-4 #120

Analyst

Review

12396

CHAIN OF CUSTODY RECORD

Sample Intact JE:91 11/61/8 Sample Cool ANALYSIS / PARAMETERS CHLORIDE (1.814) H9T HA9 TCLP with H/P **BCI** Cation / Anion RCRA 8 Metals Received by: (Signature) Received by: (Signature) Received by: (Signature) VOC (Method 8260) (TEX (Method 8021) (3108 bodteM) H9T No./Volume Preservative of HgC, HG Co. 16:30 Time 10/2 Sludge Aqueous Sludge Aqueous Aqueous Sludge Aqueous Sludge Aqueous Aqueous Aqueous Aqueous Aqueous Aqueous Date Sludge Sludge Sludge Sludge Sludge Sludge Sample Matrix 92115-1907 Ser Sur 27-4 Project Name / Location: Solid Soil Solid Soil Soil Soil Soil Solid Soil Solid Soil Soil Soil Solid Sampler Name: 59342 Lab No. Client No.: Sample 10:30 Sample 11/6/8 *18115H* Date Relinquished by: (Signature) Relinquished by: (Signature) Relinquished by: (Signature) Client Phone No.: Sample No./ Identification Client Address:

envirotech Analytical Laboratory 5796 US Highway 64 • Farmington, NM 87401 • 505-632-0615 • lab@envirotech-inc.com

ACCENT Printing • Form 28-0807



