Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

5. Lease Serial No. NMNM6681

abandoned well. Use form 3160-3 (APD) for such proposals.					6. If Indian, Allottee or Tribe Name EASTERN NAVAJO		
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No. NMNM135229A		
1. Type of Well					8. Well Name and No. NORTH ALAMITO UNIT 524H		
				9. API Well No. 30-043-21342-00-X1			
3a. Address	(include area code) 10. Field and Pool or Exploratory Area						
1 ROAD 3263 AZTEC, NM 87410	-3476 WILDCAT BASIN MANCOS						
4. Location of Well (Footage, Sec., T.			11. County or Parish, State				
Sec 31 T23N R7W NWSW 20 36.181549 N Lat, 107.621872			SANDOVAL COUNTY, NM				
12. CHECK THE AF	PPROPRIATE BOX(ES) TO) INDICAT	E NATURE OI	F NOTICE, 1	REPORT, OR OTHI	ER D	OATA
TYPE OF SUBMISSION	TYPE OF ACTION						
☐ Notice of Intent	☐ Acidize	☐ Deep	□ Deepen		☐ Production (Start/Resume)		Vater Shut-Off
_	☐ Alter Casing ☐ Hydraulic Fracturing ☐ Re		☐ Reclama	Reclamation		Well Integrity	
Subsequent Report	☐ Casing Repair	☐ New	Construction	☐ Recomplete		☑ Other Drilling Operations	
☐ Final Abandonment Notice			and Abandon		rarily Abandon		ing Operations
BP	☐ Convert to Injection ☐ Plug Back ☐ W		☐ Water D	Vater Disposal			
following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi Intermediate Casing & Cemen 3/7/20 to 3/8/20: MIRU ad 920 install 11 inch 5K Cameron we rams, HCR, pipe rams, kill valvopening safety valve and insidinch surface casing to 1500 his Services). Drill 8.75 inch hole to 43/10/20: Drill 8.75 inch hole to casing set at 5619 ftKB. Float Test good & recorded on char FW spacer with 7% KCL at 8.3	pandonment Notices must be filed on all inspection. It I. NU 11 inch 3K BOP on preal line and TIW ves, check valve, lower Kelly le BOP valve 250 low 5 min, gh 30 min. All tested good & to 2021 ftKB 1403 ftKB. S629 ftKB. RU casing crew. Collar set at 5575 ftKB. RU It. Cement with 55% excess of 3 ppg, followed by 50 bbls (7)	e-set 9.625 250 low 5 i 7, choke ma 3000 high recorded c Run 133 jt BJ cement on both lead	aquirements, including a surface and a surfa	e casing with 10 min. PT bes, full ore-set 9.625 ty Wilson J55 LTC osi on lines.	OCD Receiv 3/16/2020	d the	operator has
14. I hereby certify that the foregoing is	Electronic Submission #507	ATING LL¢,	sent to the Farn	nington	•		
Name (Printed/Typed) SHAW-MA	Title REGUL	ATORY SPE	CIALIST				
Signature (Electronic S	Submission)		Date 03/13/20	020			
	THIS SPACE FOR	FEDERAI	OR STATE	OFFICE US	SE .		
Approved By ACCEPTED			JOE KILLIN TitlePETROLE			Date 03/16/2020	
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conductive to conduct the applicant the applicant to conduct the applicant the ap	Office Farmington						
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s				willfully to mal	ke to any department or a	gency	of the United

Additional data for EC transaction #507134 that would not fit on the form

32. Additional remarks, continued

weighted spacer, followed by LEAD: 160 bbls (383 sx) 12.3 ppg, 2.34 yield, 13.4 gps. TAIL: 68 bbls (255 sx) 13.5 ppg, 1.49 yield, 7.24 gps. Displaced with 213 bbls FW. Drop plug. Bump plug at 2390 psi & hold for 5 min. Check floats. Floats held. 50 bbls good cement back to surface. TOC: surface BOC: 5619 ftKB