

Submit 1 Copy To Appropriate District Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OCD Received
5/13/2020

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-045-31012
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name JAKE PAPA
8. Well Number #001
9. OGRID Number 371838
10. Pool name or Wildcat BISTI LOWER GALLUP

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator DJR OPERATING, LLC	
3. Address of Operator 1 ROAD 3263, AZTEC, NM 87410	
4. Well Location: Unit Letter: <u>M</u> Footages: <u>795</u> feet from the <u>SOUTH</u> line and <u>1000</u> feet from the <u>WEST</u> line Section: <u>32</u> Township <u>25N</u> Range <u>11W</u> NMPM <u>SAN JUAN</u> County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6880' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

The subject well was Plugged & Abandoned on May 8, 2020 per the attached End of Well Report, wellbore diagram, and marker.

Approved for plugging of wellbore only. Liability under bond is retained pending Receipt of C-103 (Subsequent Report of Well Plugging) which may be found @ OCD web page under forms www.emnrd.state.us/oed

PNR ONLY

Spud Date:

10/20/2002

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shaw-Marie Ford TITLE Regulatory Specialist DATE 05/13/2020

Type or print name Shaw-Marie Ford E-mail address: sford@djrlc.com PHONE: 505-632-3476

For State Use Only

APPROVED BY: Brandon Parrell TITLE District Supervisor DATE 7/7/20

Conditions of Approval (if any):

AV

Plug and Abandonment End of Well Report

for

DJR Operating, LLC

Jake Papa # 1

API # 30-045-31012

SW/SW, Unit M, Sec. 32, T25N, R11W

San Juan County, NM

3-10-2020:

MIRU prep rig. Pull rods and tubing.

5-5-2020:

Brandon Powell, NMOCD notified of P&A operations to begin 5-7-2020.

5-7&8-2020:

Run bit and scraper to 4706'. TOOH, TIH with 4 ½" cement retainer, set at 4706'. Load and roll the hole. Test casing to 600 psi, good test.

PLUG 1; Gallup, mix and pump balanced plug with 16 sx Class G cement from 4706' to 4495'. Pull up to 3635'.

PLUG 2; Mancos, mix and pump balanced plug with 12 sx Class G cement from 3635' to 3477'. Pull up to 1759'

PLUG 3; Mesa Verde, mix and pump balanced plug with 12 sx Class G cement from 1759' to 1601'. Pull up to 1434'.

PLUG 4; Chacra, Pictured Cliffs and Fruitland, mix and pump balanced plug with 46 sx Class G cement from 1434' to 827'. Pull up to 482'.

PLUG 5; Kirtland to surface, mix and pump 42 sx Class G cement until cement returns were seen in the 8 5/8" x 4 ½" casing annulus at surface.

Cut off WH, watch for cement fallback, weld P&A marker in place. Top off with Class G cement. Released rig.

Note: All cement was Class G cement mixed at 15.8 ppg, yield 1.15 cu ft / sx.

No NMOCD inspector available on location.

As P&A'd WBD, marker photo and coordinates are attached.

Post P&A Wellbore Diagram
DJR Operating, LLC
Jake Papa # 1
API # 30-045-31012
SW/SW, Unit M, Sec 32, T25N, R11W
San Juan County, NM

GL 6440'

KB 6452'

Spud Date 10/20/2002

SURF CSG

Hole size	<u>12.25</u>
Csg Size:	8.625
Wt:	24#
Grade:	J-55
ID:	8.097
Depth	350
cap cf/ft:	0.3576
TOC:	Surf

FORMATION TOPS

Nacimiento	Surface
Kirtland	432'
Fruitland	930'
Pictured Cliffs	1188'
Chacra	1384'
Mesa Verde	1705'
Mancos	3585'
Gallup	4617'

**Plug 5: 482' to surface, Kirtland to surface
42 sx Class G cement, circulated to surface.**

**Plug 4: 1434' to 827', Chacra, Pictured
Cliffs and Fruitland, 46 sx Class G cement**

**Plug 3: Mesa Verde 1759' to 1601', 12 sx
Class G cement**

**Plug 2: Mancos, 3635' to 3477', 12 sx Class
G cement**

DV tool 3605'

Plug 1: Gallup, 4706' to 4495', 16 sx Class G cement

CR 4706'
Perfs 4744-4848'

PBTD	4915'
TD	4970'

