This form is not to be used for reporting packer leakage tests in Southeast New Mexico

ΚP

Oil Conservation Division

OCD Received 4/27/2020

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator Hilcorp Energy Company					Lease Name JICARILLA A							Well No. 10	
Location of Well: Unit Letter O			Sec	:23						API	# 30-039-20117		
Name of Reservoir or Pool				ol	Type of Prod				Method of Prod			Prod Medium	
Upper Completion PC				Gas				Flow			Tubing		
Lower Completion MV				Gas				Flow			Tubing		
				Pre	-Flow S	Shut-In	Pressu	re Data	ì				
Upper Hour, Date, Shut-In								SI Press. PSIG			Stabilized?(Yes or No)		
Completion 4/20/2020				Length of Time Shut-In						57	Yes		
Lower Hour, Date, Shut-In				106				SI Pres	s. PSIG		Stabilized?(Yes or No)		
Completion 4/20/2020										279	Yes		
Flow Test No. 1 Commenced at: 4/24/2020 Zone Producing (Upper or Lower): LOWER													
Time		Lapsed Time			PRES		SSURE		Prod Zone				
(date/time) Since*			Upp	Upper zone		wer zone Temp		perature			Remarks	
4/24/2020 12:00 AM		0			57	279							
4/24/2020 10:38 AM 10			57		26								
Production rate	during	test											
Oil:BPOD Based on:B			Bbl	_Bbls. InHr			Grav.			GOR			
GasMCFPD; Test thru (Orifice or Meter)													
				Mic	d-Test S	Shut-In	Pressu	re Data	1				
Upper Hour, Date, Shut-In Completion						f Time Shut-In		SI Press. PSIG			Stabilized?(Yes or No)		
Lower Hour, Date, Shut-In Completion		1						SI Press. PSIG			Stabilized?(Yes or No)		

(Continue on reverse side)

Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at:		Zone Producing (Upper or Lower)								
Time	Lapsed Time	PRES	SURE	Prod Zone						
(date/time)	Since*	Upper zone	Lower zone	Temperature	Remarks					
Production rate du Oil:BF	POD Based on:	Bbls. In	Hrs.	Gra	v. GOR					
Gas	MCFPD; Test the	nru (Orifice or M	leter)							
Remarks:										
I hereby certify tha	t the information herein o	contained is true	and complete	to the best of my	knowledge.					
Approved: Sept 3	3	20 20	Operat	or: Hilcorp Ene	rgy Company					
New Mexico Oil	Conservation Division		By:	Gilberto Lovato						
N/	ne Arbil		_							
By:	are between		Title:	Multi-Skilled Op	erator					
Title: District III	Geologist		Date:	Date: Friday, April 24, 2020						

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for
- 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3