Received by OCD: 7/28/2020 11:04:33 AM District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Page 1 FormC-1- Revised April 3, 20 For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.
BGT 2	Pit, Below-Grade Tank, or	
Proposed Alte	rnative Method Permit or Closure I	Plan Application
Closur	of a pit or proposed alternative method e of a pit, below-grade tank, or proposed alternat cation to an existing permit/or registration e plan only submitted for an existing permitted o	
Instructions: Please submit or	e application (Form C-144) per individual pit, below	-grade tank or alternative request
environment. Nor does approval relieve the operator of	t relieve the operator of liability should operations result f its responsibility to comply with any other applicable g	
1. Operator: Enduring Resources, LLC	OGRID #:	372286
Address: 200 Energy Court, Farmington, New	Mexico 87401	
Facility or well name: John Charles 2		
API Number:	OCD Permit Number:	
11/4 O: 10: E G :: 10	Township 27N Range 9W County:	San Juan
U/L or Qtr/Qtr <u>E</u> Section <u>13</u>	r /	
Center of Proposed Design: Latitude <u>36.577854</u>		834 NAD83
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private 2	Longitude Longitude	
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private 2 2. <u>Pit:</u> Subsection F, G or J of 19.15.17.11 NM Temporary: Drilling Workover Permanent Emergency Cavitation 1 Lined Unlined Liner type: Thickness String-Reinforced	Longitude <u>-107.745</u> Tribal Trust or Indian Allotment IAC P&A Multi-Well Fluid Management L mil LLDPE HDPE PVC 0	834 NAD83
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private 2 <u>2.</u> <u>Pit:</u> Subsection F, G or J of 19.15.17.11 NM Temporary: Drilling Workover Permanent Emergency Cavitation 1 Lined Unlined Liner type: Thickness	Longitude <u>-107.745</u> Tribal Trust or Indian Allotment IAC P&A Multi-Well Fluid Management L mil LLDPE HDPE PVC 0	834NAD83
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private 2. Pit: Subsection F, G or J of 19.15.17.11 NM Temporary: Drilling Workover Permanent Emergency Cavitation Lined Unlined Liner type: Thickness String-Reinforced Liner Seams: Welded Factory Other 3. <u>Below-grade tank</u> : Subsection I of 19.15.17 Volume: 12 bbl Type of Tank Construction material: Steel Secondary containment with leak detection Visible sidewalls and liner Visible sidew	Longitude	834 NAD83 ow Chloride Drilling Fluid yes ow Chloride Drilling Fluid yes 1 Dimensions: Lx Wx D verflow shut-off
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private 2 2. Pit: Subsection F, G or J of 19.15.17.11 NM Temporary: Drilling Workover Permanent Emergency Cavitation I Lined Unlined Liner type: Thickness String-Reinforced Liner Seams: Welded Factory Other 3. <u>Below-grade tank</u> : Subsection I of 19.15.17 Volume: 12 bbl Type of Tank Construction material: Steel Secondary containment with leak detection [Visible sidewalls and liner Visible sidew	Longitude	834 NAD83 ow Chloride Drilling Fluid yes ow Chloride Drilling Fluid yes 1 Dimensions: Lx Wx D verflow shut-off
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private 2 2. Pit: Subsection F, G or J of 19.15.17.11 NM Temporary: Drilling Workover Permanent Emergency Cavitation I Lined Unlined Liner type: Thickness String-Reinforced Liner Seams: Welded Factory Other 3. <u>Below-grade tank</u> : Subsection I of 19.15.17 Volume: 12 bbl Type of Tank Construction material: Steel Secondary containment with leak detection [Visible sidewalls and liner Visible sidew Liner type: Thickness	Longitude	834 NAD83 ow Chloride Drilling Fluid yes ow Chloride Drilling Fluid yes 1 Dimensions: Lx Wx D verflow shut-off
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private State Private State Private Private Private Private Private Private Private Private Drilling Workover Permanent Drilling Workover Permanent Emergency Cavitation I Lined Unlined Liner type: Thickness String-Reinforced Liner Seams: Welded Factory Other 3. Below-grade tank: Subsection I of 19.15.17 Volume: 12 bbl Type of Tank Construction material: Steel Secondary containment with leak detection Visible sidewalls and liner Visible sidew Liner type: Thickness mill 4. Alternative Method:	Longitude	834 NAD83 ow Chloride Drilling Fluid yes no ther 1 Dimensions: Lx Wx D verflow shut-off
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private 2. Pit: Subsection F, G or J of 19.15.17.11 NM Temporary: Drilling Workover Permanent Emergency Cavitation Lined Unlined Liner type: Thickness String-Reinforced Liner Seams: Welded Factory Other 3. <u>Below-grade tank</u> : Subsection I of 19.15.17 Volume: 12bbl Type of Tank Construction material: Steel Secondary containment with leak detection Visible sidewalls and liner Visible sidew Liner type: Thicknessmil 4. <u>Alternative Method</u> :	Longitude	834 NAD83 ow Chloride Drilling Fluid yes no ther 1 Dimensions: Lx Wx D verflow shut-off
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private 2. Pit: Subsection F, G or J of 19.15.17.11 NM Temporary: Drilling Workover Permanent Emergency Cavitation Lined Unlined Liner type: Thickness String-Reinforced Liner Seams: Welded Factory Other 3. <u>Below-grade tank</u> : Subsection I of 19.15.17 Volume: 12 bbl Type of Tank Construction material: Steel Secondary containment with leak detection [Visible sidewalls and liner Visible sidew Liner type: Thicknessmil 4. <u>Alternative Method</u> : Submittal of an exception request is required. Ex	Longitude	834 NAD83 ow Chloride Drilling Fluid yes no ther
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private 2. Pit: Subsection F, G or J of 19.15.17.11 NM Temporary: Drilling Workover Permanent Emergency Cavitation Lined Unlined Liner type: Thickness String-Reinforced Liner Seams: Welded Factory Other 3. <u>Below-grade tank</u> : Subsection I of 19.15.17 Volume: 12 bbl Type of Tank Construction material: <u>Steel</u> Secondary containment with leak detection Visible sidewalls and liner Visible sidew Liner type: Thickness mill 4. <u>Alternative Method</u> : Submittal of an exception request is required. Ex 5. Fencing: Subsection D of 19.15.17.11 NMAC (A	Longitude	834 NAD83 ow Chloride Drilling Fluid yes no ther
Center of Proposed Design: Latitude <u>36.577854</u> Surface Owner: Federal State Private 2. Pit: Subsection F, G or J of 19.15.17.11 NM Temporary: Drilling Workover Permanent Emergency Cavitation Lined Unlined Liner type: Thickness String-Reinforced Liner Seams: Welded Factory Other 3. <u>Below-grade tank</u> : Subsection I of 19.15.17 Volume: 12 bbl Type of Tank Construction material: Steel Secondary containment with leak detection Visible sidewalls and liner Visible sidew Liner type: Thickness mill 4. <u>Alternative Method</u> : Submittal of an exception request is required. Ex <u>5.</u> Fencing: Subsection D of 19.15.17.11 NMAC (A Chain link, six feet in height, two strands of ba	Longitude	834 NAD83 ow Chloride Drilling Fluid yes no ther

•

Monthly inspections (If netting or screening is not physically feasible)

🛛 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

7.

8.

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

- Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.
- Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.

General siting

Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank. - □ NM Office of the State Engineer - iWATERS database search; □ USGS; ☑ Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	🗌 Yes 🗌 No
Below Grade Tanks	
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗍 No
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗋 Yes 🗋 No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial	🗌 Yes 🗌 No
 application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No

Received by OCD: 7/28/2020 11:04:33 AM	Page 3 of 1
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Temporary Pit Non-low chloride drilling fluid	
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	□ Yes □ No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No
Permanent Pit or Multi-Well Fluid Management Pit	
 Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	Yes No
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.	
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No
10. Temporary Pits Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection R of 10, 15, 17, 0 N	MAC

Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are
attached.
Hudroscologie Benert (Belew ende Tenke), beerd was the requirements of Benerus (4) of Scheretier, D. of 10, 15, 17, 0 NR (4, C)

Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC

Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC

Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC

Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC

Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC

Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC

Previously Approved Design (attach copy of design) API Number: ______ or Permit Number: _______ or Permit Number: ________ or Permit Number: _______ or Permit Number: ________ or Permit Number: __________ or Permit Number: ________ or Permit Number: ________ or Permit Number: _______ or Permit Number: _______ or Permit Number: _______ or Permit Number: ________ or Permit Number: ________ or Permit Number: ________ or Permit Number: ________ or Permit Number: _______ or Permit Number: _______ or Permit Number: _______ or Permit Number: _______ or Permit Number: _________ or Permit Number: __________ or Permit Number: ________ or Permit Number: _______ or Permit Number: ________ or Permit Number: ________ or Permit Number: ________ or Permit Number: __________ or Permit Number: ________ or Permit Number: ________ or Permit Number: ______________ or Permit Number: _________ or Permit Number: ________ or Permit Number: _______________ or Permit Number: __________ or Permit Number: __________

11.

Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC

Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.

Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC

Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC

A List of wells with approved application for permit to drill associated with the pit.

Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC

Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC

Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC

Previously Approved Design (attach copy of design) API Number:

or Permit Number;

12.	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the</i>	e documents are
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H2S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of 19.15.17.9 NMAC and 19.15.17.13 NMAC	e documents are
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F Alternative Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems)	Iuid Management Pit
In-place Burial On-site Trench Burial Alternative Closure Method	
 ^{14.} Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	
15. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. I 19.15.17.10 NMAC for guidance.	rce material are Please refer to
Ground water is less than 25 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ Yes □ No □ NA
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗋 Yes 🗌 No
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

Received by OCD: 7/28/2020 11:04:33 AM	Page 5 of 11
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	
Within a 100-year floodplain.	Yes No
- FEMA map	Yes No
 16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure play a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannel Soil Cover Design - based upon the appropriate requirements of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC 	11 NMAC 15.17.11 NMAC
17.	
Operator Application Certification:	
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli	ef.
Name (Print): James McDaniel Title: HSE Supervisor	
Signature: Date: Date:	
e-mail address: jmcdaniel@enduringresources.com Telephone: 505-636-9731	
18. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date: Approval Date:	2020
Title: Environmental Specialist OCD Permit Number: BGT 2	
19. Closure Report (required within 60 days of closure completion): 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:	the closure report. complete this
Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-lo If different from approved plan, please explain.	op systems only)
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please intermark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure for private land only) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude Longitude NAD: [1927	

.

.

22. Operator Closure Certification:

true, accurate and complete to the best of my knowledge and l conditions specified in the approved closure plan.
Title:
Date:
Telephone:

_

.

.

Enduring Resources, LLC Below Grade Tank Closure Plan

Well Name:John Charles 2API Num.:30-045-06480Description:Section 13, Township 27N, Range 9W, San Juan County

In accordance with Rule 19.15.17.13 NMAC the following information describes the closure requirements of below-grade tanks on Enduring Resources, LLC. (Enduring) locations. This is Enduring's standard procedure for all below-grade tanks. A separate plan will be submitted for any below-grade tank which does not conform to this plan.

General Plan

- 1. Enduring will obtain approval of this closure plan prior to commencing closure of the below grade tank at this location pursuant to 19.15.17.13.C (1) NMAC
- 2. Enduring will notify the surface owner by certified mail, return receipt requested, that the operator plans closure operations at least 72 hours, but no more than one week, prior to any closure operation. Notice will include:
 - a. Well Name
 - b. API
 - c. Well Location

*Enduring will notify government agencies by email of closure activities.

- 3. Enduring will notify the NMOCD Aztec Office by email that the operator plans closure operations at least 72 hours, but no more than one week, prior to any closure operation. Notice will include:
 - a. Well Name
 - b. API
 - c. Well Location
- 4. Within 60 days of cessation of operations, Enduring will remove all liquids and sludge from below grade tanks prior to implementing closure activities, and will dispose of the liquids and sludge at a division approved facility. Approved facilities and waste steams include:
 - a. Soils, tank bottoms, produced sands, pit sludge and other exempt wastes impacted by petroleum hydrocarbon will be disposed of at: Envirotech: Permit #NM01-0011 and IEI: Permit #NM01-0010B
 - b. Produced water will be disposed of at: Basin Disposal: Permit #NM01-005, Agua Moss: Permit #NM-009, and Enduring owned disposal wells.
- 5. Within six (6) months of cessation of operations, Enduring will remove the below grade tank and dispose of it in a division approved facility, or recycle, reuse or reclaim it in a manner that the appropriate district office approves. If there is any equipment associated with a below grade tank,

then the operator shall remove the equipment, unless the equipment is required for some other purpose.

6. Enduring will collect a closure sample of the soil beneath the location of the below grader tank or liner that is being closed. The closure sample will consist of a five-point composite sample to include any obvious stained or wet soils, or other evidence of contamination. The closure sample will be analyzed for all constituents listed in Table I below, including DRO+GRO, chlorides, TPH (C6-C36), benzene and BTEX.

		Table I Soils Impacted by a Release	
Minimum depth below any point within the horizontal boundary of the release to ground water less than 10,000 mg/l TDS	Constituent	Method*	Limit**
≤ 50 feet	Chloride***	EPA 300.0 or SM4500 Cl B	600 mg/kg
	TPH (GRO+DRO+MRO)	EPA SW-846 Method 8015M	100 mg/kg
	BTEX	EPA SW-846 Method 8021B or 8260B	50 mg/kg
	Benzene	EPA SW-846 Method 8021B or 8260B	10 mg/kg
51 feet-100 feet	Chloride***	EPA 300.0 or SM4500 Cl B	10,000 mg/kg
	TPH (GRO+DRO+MRO)	EPA SW-846 Method 8015M	2,500 mg/kg
	GRO+DRO	EPA SW-846 Method 8015M	1,000 mg/kg
	BTEX	EPA SW-846 Method 8021B or 8260B	50 mg/kg
	Benzene	EPA SW-846 Method 8021B or 8260B	10 mg/kg
>100 feet	Chloride***	EPA 300.0 or SM4500 Cl B	20,000 mg/kg
	TPH (GRO+DRO+MRO)	EPA SW-846 Method 8015M	2,500 mg/kg
	GRO+DRO	EPA SW-846 Method 8015M	1,000 mg/kg
	BTEX	EPA SW-846 Method 8021B or 8260B	50 mg/kg
	Benzene	EPA SW-846 Method 8021B or 8260B	10 mg/kg

- 7. Enduring will close this BGT based on the requirements for groundwater over 100 feet.
- 8. If any contaminant concentration is higher than the parameters listed in Table I above, additional delineation may be required based on review of the results. Enduring will receive division approval prior to proceeding with additional closure activities. If all contaminant concentrations

are less than, or equal to, the parameters listed in Table I above, the operator can proceed to backfill with non-waste containing, uncontaminated earthen material.

- 9. After closure has occurred, Enduring will reclaim the former BGT area, if it is no longer being utilized for the continued extraction of oil and gas, by substantially restoring the surface area to the condition that existed prior to oil and gas operations. Enduring will construct the soil cover to the site's existing grade and prevent ponding of water and erosion of the cover materials. The soil cover shall consist of the background thickness of topsoil, or one foot of suitable materials to establish vegetation at the site, whichever is greater. All areas will be reclaimed as early as practicable, and as close to their original condition or land use as possible. They shall be maintained in such a way as to control dust and to minimize erosion.
- 10. Enduring will complete reclamation in accordance with the requirements listed in NMAC 19.15.17.13.H(5).

(a) Enduring will reclaim all areas disturbed by the closure below-grade tanks, except areas reasonably needed for production operations or for subsequent drilling operations, shall be reclaimed as early and as nearly as practicable to their original condition or their final land use and shall be maintained to control dust and minimize erosion to the extent practicable.

(b) Enduring will ensure that topsoils and subsoils are replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns. The disturbed area then shall be reseeded in the first favorable growing season following closure of the below-grade tank.

(c) Enduring will consider reclamation of disturbed areas no longer in use complete when all ground surface disturbing activities at the site have been completed, and a uniform vegetative cover has been established that reflects a life-form ratio of plus or minus fifty percent (50%) of pre-disturbance levels and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels, excluding noxious weeds.

(d) Re-vegetation and reclamation obligations imposed by other applicable federal or tribal agencies on lands managed by those agencies shall supersede these provisions and govern the obligations of any operator subject to those provisions, provided that the other requirements provide equal or better protection of fresh water, human health and the environment.

(e) The operator shall notify the division when reclamation and re-vegetation are complete

- 11. Within 60 days of closure of the below-grade tank, Enduring will submit a closure report to the Aztec office of the NMOCD. Closure report will be filed on form C-144 and include the following:
 - Proof of closure notice to division and surface owner;
 - Confirmation sampling analytical results;
 - Soil backfilling and cover installation;
 - Photo documentation of the site reclamation.
 - Alternative Table I groundwater criteria request, groundwater information, and received approval (If Needed)

Mr. Cory Smith Oil Conservation Division 1000 Rio Brazos Rd. Aztec, New Mexico 87410 Email: cory.smith@state.nm.us Phone (505) 334-6178 Ext 115

Re: Variance Request for 19.15.17 NMAC Table I and Table II

Mr. Smith,

Please accept this letter as a variance request as outlined in 19.15.17.15(A) NMAC. Enduring Resources, LLC (Enduring) would like to request the replacement of USEPA Method 418.1 for the analysis of Total Petroleum Hydrocarbons (TPH) for USEPA Method 8015M, measuring carbon ranges C6-C36, for all sampling associated with closures and confirmations samples in relation to 19.15.17 NMAC, both in Table I and Table II (2103) and the 'pit rule' passed in 2008. Enduring is requesting this variance on the grounds that USEPA Method 418.1 is an outdated analytical method that reports a full range of hydrocarbons from C5 through C40 (*Reference: American Petroleum Institute*).

The attached table demonstrates the carbon ranges, and the typical hydrocarbon products that can be found in those ranges. As you can see, lube oil ranges from C28-C35. Analytical Method USEPA 418.1 extends past lube oils from C35 through C40. This range of hydrocarbons is above the range that can reasonably be expected to be found in our field in both drilling pits and beneath below grade tanks. USEPA Method 8015M (GRO/DRO + extended analysis) will report hydrocarbons ranging from C6-C10 for GRO, C10- C28 for DRO, and C28-C36 for extended analysis. This information was provided by Environmental Science Corporation Laboratories. As the information demonstrates, the 8015M analytical method reports as low as C6, reporting lower than USEPA Method 418.1. Utilizing analytical method 8015M, lighter range hydrocarbons will be reported instead of higher range, heavy hydrocarbons that may not be reasonably expected to be found in our field. Utilization of USEPA Method 8015M will better protect groundwater resources by identifying lighter, more mobile hydrocarbons that USEPA Method 418.1 cannot identify. The heavier range hydrocarbons, C36-C40, that are not identified by USEPA Method 8015M are not a mobile form of hydrocarbon, and are not a threat to human health and the environment. With your acceptance of this variance request, Enduring Resources will begin utilizing USEPA Method 8015M in place of USEPA Method 418.1 for all sampling activities associated with 19.15.17 NMAC, both from the rules passed in 2008 and 2013.

Respectfully Submitted,

James McDaniel, CHMM #15676 HSE Supervisor Enduring Resources, LLC

Carbon Ranges of Typical Hydrocarbons

Hydrocarbon Carbon Range Condensate C2-C12 Aromatics C5-C7 Gasoline C7-C11 Kerosene C6-C16 Diesel Fuel C8-C21 Fuel Oil #1 C9-C16 Fuel Oil #2 C11-C20 Heating Oil C14-C20 Lube Oil C28-C35

