
submitted in lieu of Form 3160-5

UNITED STATES

DEPARTMENT OF THE INTERIOR



AUG 17 2011

BUREAU OF LAND M	AUG I	AUG 1 / 2011		
Sundry Notices and Reports	on Wells		rarmington l 3ureau of Land	Field Office
1. Type of Well GAS		03.2A.2526223	5. Lease I	Number 19146 an, All. or
2. Name of Operator BURLINGTON		20 RECEIVED 30 PECEIVED 30 PEC	7. Unit A	greement Name
RESCURCES OIL & O 3. Address & Phone No. of Operator	GAS COMPANY LP	E OII CUAIS DIN 112.	8. Well N San Ju	ame & Number an 20S
PO Box 4289, Farmington, NM 87499 (505) 326-9700			9. API W	ell No.
4. Location of Well, Footage, Sec., 7	Γ, R, M		30-045	
Surface: Unit K (NESW), 1880' FSL & 1840' FWL, Section 35, T29N, R9W, NMPM				nd Pool Fruitland Coal
BH: Unit K (NESW), 2463'	FSL & 1839' FWL, Se	ection 35, T29N, R9W, NMPN		y and State an, NM
12. CHECK APPROPRIATE BOX T	O INDICATE NATU	RE OF NOTICE, REPORT,	OTHER DATA	
Type of Submission Type of Notice of Intent	Action Abandonment Recompletion	Change of Plans New Construction	X Other –	Cathodic
X Subsequent Report Final Abandonment	Plugging Casing Repair Altering Casing	Non-Routine Fracturing Water Shut off Conversion to Injection		
1 mar / touridoinfient				
Attached is a drawing for the placemen	t of the cathodic ground	l, rectifier and cable for the sub	ject well.	
14. I hereby certify that the foregoin	g is true and correct.			
Signed Intst Turney	Denise J	ourney Title: Staff Reg	ulatory Technician	Date 8-16-1
(This space for Federal or State Office APPROVED BY	use) Title		Data	
CONDITION OF APPROVAL, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person kind the United States any false, fictitious or fraudulent statements or it.	owingly and willfully to make any depa	ACCE	ACCEPTED FOR RECORD	
			AUG 1 8 2011	
		FARMI	NGTON FIELD OF	FICE



San Juan #20 S

Section 35, T29N, R9W, N.M.P.M., San Juan County, NM

			COPC Pipeline Negative Cable Positive Cable WFS Pipeline Separator	
#20 S 73'			Meter Run ☐ Rectifier ☐ Ground Bed Wellhead	
36.40829N 107.45293W		·		
		Drill ground bed approximately 112' South of #20 wellhead at staked location. Install Solar rectifier at staked location. Install cable to new ground bed and to #20 and 20 S wellheads at lengths below; #20 S Cables: Negative:145' Positive: 65' Total Ditch: 210'		

By: Dwayne Horton Date: 03/02/2011