UNITED STATES DEPARTMENT OF THE INTERIOR



| BUREAU OF LAND MANAGEMENT | ^{JUL} 26 2011 |
|--|--|
| Sundry Notices and Reports on Wells | Bureau of I and Managember 5. Lease Number |
| 1. Type of Well GAS 1. Type of Well | SF-079382 6. If Indian, All. or Tribe Name 7. Unit Agreement Name |
| 2. Name of Operator BURLINGTON 2. Name of Operator S. A. Control S. Contro | San Juan 30-6 Unit |
| RESCURCES OIL & GAS COMPANY LP 3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700 | 8. Well Name & Number San Juan 30-6 Unit 77M |
| PO Box 4289, Farmington, NM 87499 (505) 326-9700 | 9. API Well No. |
| 4. Location of Well, Footage, Sec., T, R, M | 30-039-31001 |
| Surface: Unit J (NWSE), 1450' FSL & 2170' FEL, Section 24, T30N, R7W, N | 10. Field and Pool IMPM Blanco MV/Basin DK |
| BH: Unit N (SESW), 840' FSL & 2565' FWL, Section 24, T30N, R7W, NMPM | 11. County and State Rio Arriba, NM |
| X Subsequent Report Plugging Non-Routine F Casing Repair Water Shut off Casing Casing Conversion to 13. Describe Proposed or Completed Operations | |
| 7/15/11 MIRU AWS 920. NU BOPE. PT 9 5/8" csg to 600#/30min. Test OK. 7/16/11 TIH w/ 8 ¾" bit. Tag cmt @ 199' & DO. Drilled ahead to 3,584' – Inter TD reached 7. set @ 3,569', w/ ACP @ 3,020' & stage tool @ 3,017'. RU to cmt. 1st stage: Pre-flush w/ 10 to (57cf-10bbl=3.02 yld) Premium Lite w/ .25 pps cello-flake, 0.3% CACL2, 0.4% FL-52, 5 pps Ldisplaced w/ 30 bbls FW. Lead w/ 15 sx (32cf-6 bbls=2.13 yld) Premium Lite w/ .25 pps cello-bentonite, & 0.4% SMS. Tail w/ 76 sx (105cf-19bbls=1.38 yld) Type III cmt w/ 0.1% CACL2, Open stage tool. Circ 18 bbls cmt to surface. Plug down @ 00:03 hrs on 7/21/11. 2nd stage: Pumped scavenger 19 sx (57cf-10 bbls=3.02 yld) Premium Lite cmt. w/ .25 pps cello-flake, 0.3% & 0.4% SMS. Lead w/ 330 sx (703cf-125bbls=2.13 yld) Premium Lite cmt w/ .25 pps cello-flake, 0.3% & 0.4% SMS. Drop plug and displaced w/ 119 bbls FW. Bump plug & close stage to hrs on 7/21/11. WOC. TIH w/ 6 ¼" bit. Tag cmt. @ 3,010' & MO. DO stage tool @ 3,017' & to 1500#/30 min. Test OK. Drilled ahead to 7,836' (TD) – TD reached 7/23/11. Circ hole. 7/2 4 ½", 11.6#, L-80 csg., set @ 7,835'. RU to cmt. Pre-flush w/ 10 bbl CW & 2 bbl FW. Pumpe w/ 0.3% CACL2, .25 pps cello-flake, 0.4% FL-52, 5 pps LCM-1, 8% bentonite, & 0.4% SMS. Lite w/ 0.3% CACL2, .25 pps cello-flake, 0.4% FL-52, 5 pps LCM-1, 8% bentonite, & 0.4% SMS. Lite w/ 0.3% CACL2, .25 pps cello-flake, 0.4% FL-52, 5 pps LCM-1, 8% bentonite, & 0.4% SMS. Bump plug. Plug down @ 16:59 hrs on 7/24/11. RD cmt. WOC. ND BOPE | bbl GW & 2 bbls FW. Pumped scavenger 19sx CM-1, 8% bentonite, & 0.4% SMS. Drop plug an flake, 0.3% CACL2, 0.4% FL-52, 5 pps LCM-1, 8. 25 pps cello-flake, & .02% FL-52. Bump plug. re-flush w/ 10 bbls FW, 10 bbls GW, & 10 bbls FW CACL2, 0.4% FL-52, 5 pps LCM-1, 8% bentonice, 0.3% CACL2, 0.4% FL-52, 5 pps LCM-1, 8% bol. Circ 29 bbls cmt to surface. Plug down @ 02 ACP @ 3,020' @ 10:30 hrs. on 7/21/11. PT 7'' cs 4/11 TIH w/ 183 jts (17 jts. BT&C & 166 jts LT&C ded scavenger 9sx (27cf-5bbls=3.02 yld) Premium I Lead w/ 294 sx (582cf-104 bbls=1.98 yld) Premium IS. Drop plug and displaced w/ 122 bbls FW (1st.) |
| PT will be conducted by Completion Rig. Results & TOC will appear on next report. | ACCEPTED FOR RECORD |
| 14. I hereby certify that the foregoing is true and correct. | JUL 2 8 2011 |
| Signed Denise Journey Title:Re | gulatory FARMINGTON FIELTIZ SHIPICE BY S |
| (This space for Federal or State Office use) APPROVED BYTitle CONDITION OF APPROVAL, if any: | Date |

NMOCD A