RECEIVED

Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR

SEP 07 2011

FORM APPROVED OM B No 1004-0137 Expires: March 31, 200

	SUNDRY NOTICES AND REPORTS ON WELL Sand Manage Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE- Other instructions on reverse side.				Navajo		
1 Typ	1 Type of Well ☐ ☐ Gas Well ☐ ☐ Other				8 Well No	ame and No.	
2. Nam	2. Name of Operator BC&D Operating C/O Nacogdoches Oil & Gas Inc.				Hanso	in #03.	
3a Ad		·		Phone No (include area code)		API Well No. 30-031-05528	
	1			36-560-4747		nd Pool, or Exploratory Area h-Gallup	
	ation of Well (<i>Footage, Se</i>		· p		11 County	or Parish, State	
	12. CHECK	APPROPRIATE BOX(ES) TO		RE OF NOTICE, RI	EPORT, OF	R OTHER DATA	
TYF	PE OF SUBMISSION		TY	PE OF ACTION			
✓ Sı	Notice of Intent Subsequent Report	Acidize Alter Casing Casing Repair Change Plans	Deepen Fracture Treat New Construction Plug and Abandon	Production (Star Reclamation Recomplete Temporarily Aba	ŕ	Water Shut-Off Well Integrity Other	
$\supset \bigsqcup_{F_1}$	Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal			
If the At foliates	the proposal is to deepen d ttach the Bond under which bllowing completion of the	Irrectionally or recomplete horizontal h the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be	lly, give subsurface location ride the Bond No. on file wo results in a multiple comp	vith BLM/BIA Required eletion or recompletion in	vertical depth d subsequent r a new interva	ns of all pertinent markers and zones. reports shall be filed within 30 days al, a Form 3160-4 shall be filed once	
If At follows del	the proposal is to deepen detach the Bond under which ollowing completion of the sting has been completed etermined that the site is real B-16-11 - RIH with WS B-17-11 - RIH with WS,	Irrectionally or recomplete horizontal h the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be	lly, give subsurface location ide the Bond No. on file we results in a multiple comp filed only after all requires the @ 15.2 lbs for botton WS – Mix and Pump 70	ns and measured and true vith BLM/BIA Required eletion or recompletion in ments, including reclama m plug. LD WS. 6 sacks @ 15.2 ppg fo	vertical depth d subsequent r a new interva tion, have been r annulus pl	ns of all pertinent markers and zones, reports shall be filed within 30 days it, a Form 3160-4 shall be filed once in completed, and the operator has	
If At follows del	the proposal is to deepen detach the Bond under which ollowing completion of the sting has been completed etermined that the site is real B-16-11 - RIH with WS B-17-11 - RIH with WS,	Irrectionally or recomplete horizontal hithe work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be add for final inspection) to 1573' – Mix and Pump 43 sact tag bottom plug @ 1212' – LD,	lly, give subsurface location ide the Bond No. on file we results in a multiple comp filed only after all requires the @ 15.2 lbs for botton WS – Mix and Pump 70	ns and measured and true vith BLM/BIA Required eletion or recompletion in ments, including reclama m plug. LD WS. 6 sacks @ 15.2 ppg fo	vertical depth d subsequent r a new interva tion, have been r annulus pl	ns of all pertinent markers and zones, reports shall be filed within 30 days it, a Form 3160-4 shall be filed once in completed, and the operator has	
If At follows del	the proposal is to deepen detach the Bond under which ollowing completion of the sting has been completed etermined that the site is real B-16-11 - RIH with WS B-17-11 - RIH with WS,	Irrectionally or recomplete horizontal hithe work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be add for final inspection) to 1573' – Mix and Pump 43 sact tag bottom plug @ 1212' – LD,	lly, give subsurface location ide the Bond No. on file we results in a multiple comp filed only after all requires the @ 15.2 lbs for botton WS – Mix and Pump 70	ns and measured and true vith BLM/BIA Required eletion or recompletion in ments, including reclama m plug. LD WS. 6 sacks @ 15.2 ppg fo	vertical depth d subsequent r a new interva tion, have been r annulus pl	ns of all pertinent markers and zones, reports shall be filed within 30 days it, a Form 3160-4 shall be filed once in completed, and the operator has lug and inside plug. RCUD SEP 9 '11	
If At follows del	the proposal is to deepen detach the Bond under which ollowing completion of the sting has been completed etermined that the site is real B-16-11 - RIH with WS B-17-11 - RIH with WS,	Irrectionally or recomplete horizontal hithe work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be add for final inspection) to 1573' – Mix and Pump 43 sact tag bottom plug @ 1212' – LD,	lly, give subsurface location ide the Bond No. on file we results in a multiple comp filed only after all requires the @ 15.2 lbs for botton WS – Mix and Pump 70	ns and measured and true vith BLM/BIA Required eletion or recompletion in ments, including reclama m plug. LD WS. 6 sacks @ 15.2 ppg fo	vertical depth d subsequent r a new interva tion, have been r annulus pl	ns of all pertinent markers and zones. reports shall be filed within 30 days il, a Form 3160-4 shall be filed once in completed, and the operator has lug and inside plug. round. Weld on PA Marker. RCVD SEP 9 11	
If At follows detection as a second s	The proposal is to deepen detach the Bond under which ollowing completion of the sting has been completed, etermined that the site is real in the sting has been completed. B-16-11 - RIH with WS and B-17-11 - RIH with WS, B-31-11 - Tag Cement (and the sting has been completed by the sting has been completed.	Irrectionally or recomplete horizontal hithe work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be add for final inspection) to 1573' – Mix and Pump 43 sact tag bottom plug @ 1212' – LD,	lly, give subsurface location ide the Bond No. on file was results in a multiple comp filed only after all requires the action of the substrate of the substrat	ns and measured and true with BLM/BIA Required eletion or recompletion in ments, including reclama m plug. LD WS. 6 sacks @ 15.2 ppg for a will cut off casing a	vertical depth d subsequent r a new interva tion, have been r annulus pl	ns of all pertinent markers and zones. reports shall be filed within 30 days it, a Form 3160-4 shall be filed once in completed, and the operator has lug and inside plug. round. Weld on PA Marker. RCVD SEP 9 '11 OIL CONS. DIV.	
If At follows test detection and the state of the state o	The proposal is to deepen detach the Bond under which ollowing completion of the sting has been completed, etermined that the site is real in the sting has been completed. B-16-11 - RIH with WS and B-17-11 - RIH with WS, B-31-11 - Tag Cement (and the sting has been completed) white Allen Mike Allen	Irrectionally or recomplete horizontal h the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be addy for final inspection) to 1573' – Mix and Pump 43 sact tag bottom plug @ 1212' – LD, 117', mix and pump 21 Sks @	lly, give subsurface location ide the Bond No. on file was results in a multiple comp filed only after all requires the angle of the substantial substantial file. WS – Mix and Pump 76 14.8 ppg, cement to top	ns and measured and true with BLM/BIA Required eletion or recompletion in ments, including reclama m plug. LD WS. 6 sacks @ 15.2 ppg for a backs will cut off casing a property of the control of the con	vertical depth d subsequent r a new interva tion, have been r annulus pl	ns of all pertinent markers and zones. reports shall be filed within 30 days it, a Form 3160-4 shall be filed once in completed, and the operator has lug and inside plug. round. Weld on PA Marker. RCVD SEP 9 '11 OIL CONS. DIV.	
If At follows test detection and the state of the state o	The proposal is to deepen detach the Bond under which ollowing completion of the sting has been completed, etermined that the site is real in the sting has been completed. B-16-11 - RIH with WS and B-17-11 - RIH with WS, B-31-11 - Tag Cement (and the sting has been completed by the sting has been completed.	Inectionally or recomplete horizontal high the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be addy for final inspection.) to 1573' – Mix and Pump 43 sact tag bottom plug @ 1212' – LD, with the control of	lly, give subsurface location ide the Bond No. on file was results in a multiple comp filed only after all requires the action of the substantial subs	ns and measured and true with BLM/BIA Required solution or recompletion in ments, including reclama m plug. LD WS. 6 sacks @ 15.2 ppg for p. Will cut off casing a property of the control	vertical depth d subsequent r a new intervation, have been r annulus plat 3' below gr	ns of all pertinent markers and zones, reports shall be filed within 30 days at a Form 3160-4 shall be filed once in completed, and the operator has a lug and inside plug. RCVD SEP 9 '11 DIL CONS. DIV. DIST. 3	
If At follows test detection and the state of the state o	The proposal is to deepen detach the Bond under which ollowing completion of the siting has been completed, etermined that the site is real in the same of the siting has been completed. B-16-11 - RIH with WS and B-17-11 - RIH with WS, B-17-11 - RIH with WS, B-31-11 - Tag Cement (and the same (Printed/Typed) Mike Allen mature	Irrectionally or recomplete horizontal h the work will be performed or provinvolved operations. If the operation Final Abandonment Notices shall be addy for final inspection) to 1573' – Mix and Pump 43 sact tag bottom plug @ 1212' – LD, 117', mix and pump 21 Sks @	lly, give subsurface location ide the Bond No. on file was results in a multiple comp filed only after all requires the action of the substantial subs	ns and measured and true with BLM/BIA Required pletion or recompletion in ments, including reclama in plug. LD WS. 6 sacks @ 15.2 ppg for a building reclama in plug. LD WS. 6 sacks @ 15.2 ppg for a building reclama in plug. LD WS. 6 sacks @ 15.2 ppg for a building reclama in plug. LD WS. 6 sacks @ 15.2 ppg for a building reclama in plug. LD WS. 6 sacks @ 15.2 ppg for a building reclama in plug. LD WS.	vertical depth d subsequent r a new intervation, have been r annulus plant 3' below gr	ns of all pertinent markers and zones. reports shall be filed within 30 days it, a Form 3160-4 shall be filed once in completed, and the operator has lug and inside plug. round. Weld on PA Marker. RCVD SEP 9 '11 OIL CONS. DIV.	

(Instructions on page 2)