$\frac{District\ l}{1625\ N}\ French\ Dr\ ,\ Hobbs,\ NM\ 88240$ 1301 W Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

2	lel	$\mathcal{L}^{C}$

$\sim$	n, Below-Grade Tank, or	.•
Proposed Alternative Method Pe	ermit or Closure Plan Appli	cation
☐ Modification to an existing perr	stem, below-grade tank, or proposed a	Iternative method
below-grade tank, or proposed alternative method	an emoting permitted or non-permitted	a p.i., c.eeea teep eyettiii,
Instructions: Please submit one application (Form C-144) per indi-	vidual pit, closed-loop system, below-grad	e tank or alternative request
Please be advised that approval of this request does not relieve the operator of liabil nvironment. Nor does approval relieve the operator of its responsibility to comply		
Operator: Koch Exploration Company, LLC	OGRID#: 12807	RCVD DEC 12 '08
Address: PO Box 489, Aztec, NM 87410		OIL CONS. DIV.
Facility or well name: <u>Dryden 2</u> (BGT Proposed Closure)		DIST. 3
API Number: <u>30-045-24232</u> OC		
U/L or Qtr/Qtr <u>L</u> Section <u>22</u> Township <u>28N</u>		
Center of Proposed Design: Latitude <u>36° 38' 40" N</u>		
Surface Owner: $\boxtimes$ Federal $\square$ State $\square$ Private $\square$ Tribal Trust or Indian All-	otment	•
2.  □ Pit: Subsection F or G of 19.15.17.11 NMAC  Temporary: □ Drilling □ Workover □ Permanent □ Emergency □ Cavitation □ P&A □ Lined □ Unlined Liner type Thicknessmil □ LLDPE □ String-Reinforced Liner Seams: □ Welded □ Factory □ Other		
☐ Closed-loop System:       Subsection H of 19.15.17.11 NMAC         Type of Operation:       ☐ P&A       ☐ Drilling a new well       ☐ Workover or Drilling intent)         ☐ Drying Pad       ☐ Above Ground Steel Tanks       ☐ Haul-off Bins       ☐ Other         ☐ Lined       ☐ Unlined       Liner type: Thickness      mil       ☐ LLD         Liner Seams:       ☐ Welded       ☐ Factory       ☐ Other	r PE	
4. Subsection I of 19.15.17.11 NMAC  Volume:bbl Type of fluid:		
Tank Construction material:		
<ul> <li>□ Secondary containment with leak detection □</li> <li>□ Visible sidewalls and liner □ Visible sidewalls only □ Other</li> </ul>		
visible sidewalls and filler   visible sidewalls only   Other		

Alternative Method: Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)  Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church)	hospital,
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	
7.  Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)  Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
<ul> <li>Signs: Subsection C of 19.15.17.11 NMAC</li> <li>12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers</li> <li>Signed in compliance with 19.15.3.103 NMAC</li> </ul>	
9.  Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.  Please check a box if one or more of the following is requested, if not leave blank:  Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau of consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	office for
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying above-grade tanks associated with a closed-loop system.	priate district pproval.
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applies to temporary, emergency, or cavitation pits and below-grade tanks)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No ☐ NA
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  (Applies to permanent pits)  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No ☐ NA
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area.  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain FEMA map	☐ Yes ☐ No

Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are
attached.  Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC
and 19.15.17.13 NMAC  Previously Approved Design (attach copy of design) API Number: or Permit Number:
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9  Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design)  API Number:
Previously Approved Operating and Maintenance Plan API Number:(Applies only to closed-loop system that use
above ground steel tanks or haul-off bins and propose to implement waste removal for closure)
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17 9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan  Emergency Response Plan  Oil Field Waste Stream Characterization  Monitoring and Inspection Plan  Erosion Control Plan  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Proposed Closure: 19.15.17.13 NMAC  Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.  Type: □ Drilling □ Workover □ Emergency □ Cavitation □ P&A □ Permanent Pit ☑ Below-grade Tank □ Closed-loop System □ Alternative  Proposed Closure Method: ☑ Waste Excavation and Removal □ Waste Removal (Closed-loop systems only) □ On-site Closure Method (Only for temporary pits and closed-loop systems) □ In-place Burial □ On-site Trench Burial □ Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
Waste Excavation and Removal Closure Plan Checklist: (19.15.17 13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.  □ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC  □ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC  □ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)  □ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  □ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

6. Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Instructions: Please indentify the facility or facilities for the disposal of liquids, for the disposal of liquids.		
facilities are required.  Disposal Facility Name:	Disposal Facility Permit Number:	
Disposal Facility Name:	Disposal Facility Permit Number:	
Will any of the proposed closed-loop system operations and associated activities o  ☐ Yes (If yes, please provide the information below) ☐ No		
Required for impacted areas which will not be used for future service and operation  Soil Backfill and Cover Design Specifications based upon the appropriate Re-vegetation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection	e requirements of Subsection H of 19.15.17.13 NMAC 1 I of 19.15.17.13 NMAC	C
17.  Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC  Instructions: Each siting criteria requires a demonstration of compliance in the provided below. Requests regarding changes to certain siting criteria may requiconsidered an exception which must be submitted to the Santa Fe Environmenta demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC	re administrative approval from the appropriate dista al Bureau office for consideration of approval. Justi	rict office or may be
Ground water is less than 50 fect below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Da	ta obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Da	ta obtained from nearby wells	<ul><li>☐ Yes ☐ No</li><li>☐ NA</li></ul>
Ground water is more than 100 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Da	ta obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other signate (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	gnificant watercourse or lakebed, sinkhole, or playa	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or churc - Visual inspection (certification) of the proposed site; Aerial photo; Satellie		☐ Yes ☐ No
Within 500 horizontal feet of a private, domestic fresh water well or spring that leavatering purposes, or within 1000 horizontal feet of any other fresh water well or - NM Office of the State Engineer - iWATERS database; Visual inspection	spring, in existence at the time of initial application.	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh wat adopted pursuant to NMSA 1978, Section 3-27-3, as amended.  - Written confirmation or verification from the municipality; Written appro		☐ Yes ☐ No
Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visu	nal inspection (certification) of the proposed site	☐ Yes ☐ No
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Minin	g and Mineral Division	☐ Yes ☐ No
<ul> <li>Within an unstable area.</li> <li>Engineering measures incorporated into the design; NM Bureau of Geolog Society; Topographic map</li> </ul>	gy & Mineral Resources; USGS; NM Geological	☐ Yes ☐ No
Within a 100-year floodplain FEMA map		☐ Yes ☐ No
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of Construction/Design Plan of Burial Trench (if applicable) based upon the a Construction/Design Plan of Temporary Pit (for in-place burial of a drying Protocols and Procedures - based upon the appropriate requirements of 19.1 Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Disposal Facility Name and Permit Number (for liquids, drilling fluids and Soil Cover Design - based upon the appropriate requirements of Subsection Re-vegetation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection	quirements of 19.15.17.10 NMAC  of Subsection F of 19.15.17.13 NMAC  oppropriate requirements of 19.15.17.11 NMAC  ppad) - based upon the appropriate requirements of 19.  5.17.13 NMAC  quirements of Subsection F of 19.15.17.13 NMAC  of Subsection F of 19.15.17.13 NMAC  drill cuttings or in case on-site closure standards cann  H of 19.15.17.13 NMAC  of 10 of 19.15.17.13 NMAC	15.17.11 NMAC

· · · · · · · · · · · · · · · · · · ·	
Operator Application Certification:  I hereby certify that the information submitted with this application is true,	accurate and complete to the best of my knowledge and belief.
Name (Print): John Chark	Title: <u>District Superintendent</u>
Signature:	Date: 12-10-08
e-mail address: clark23j@kochind.com	Telephone: _(505) 334-9111
OCD Approval: Permit Application (including closure plan)  OCD Representative Signature:  Title: Compliance	OCD Permit Number:
Closure Report (required within 60 days of closure completion): Subse Instructions: Operators are required to obtain an approved closure plan p. The closure report is required to be submitted to the division within 60 day section of the form until an approved closure plan has been obtained and	orior to implementing any closure activities and submitting the closure report.  s of the completion of the closure activities. Please do not complete this
22.  Closure Method:  Waste Excavation and Removal On-Site Closure Method A  If different from approved plan, please explain.	Iternative Closure Method
Closure Report Regarding Waste Removal Closure For Closed-loop Systemstructions: Please indentify the facility or facilities for where the liquidative facilities were utilized.  Disposal Facility Name:  Disposal Facility Name:  Were the closed-loop system operations and associated activities performed  Yes (If yes, please demonstrate compliance to the items below)  Required for impacted areas which will not be used for future service and of Site Reclamation (Photo Documentation)  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique	Disposal Facility Permit Number:  Disposal Facility Permit Number:  on or in areas that will not be used for future service and operations?
mark in the box, that the documents are attached.  Proof of Closure Notice (surface owner and division)  Proof of Deed Notice (required for on-site closure)  Plot Plan (for on-site closures and temporary pits)  Confirmation Sampling Analytical Results (if applicable)  Waste Material Sampling Analytical Results (required for on-site closures)  Disposal Facility Name and Permit Number  Soil Backfilling and Cover Installation  Re-vegetation Application Rates and Seeding Technique  Site Reclamation (Photo Documentation)	sure)  NAD:   1927   1983
25.	
Operator Closure Certification:  I hereby certify that the information and attachments submitted with this clobelief. I also certify that the closure complies with all applicable closure recommendation.	
Name (Print):	Title:
Signature:	Date:

e-mail address:\_\_

Telephone: \_\_\_

## Koch Exploration Company, LLC San Juan County, New Mexico Assets Below-Grade Tank Closure Plan

Updated: December 2, 2008

Well Name: Dryden 2
Well API Number: 30-045-24232
Well S/T/R: S22, T38N, R8W

In accordance with Rule 19.15.17.13 NMAC, the following plan describes the general closure requirements of below-grade tanks (BGT) on Koch Exploration Company, LLC (KEC) locations in San Juan County, New Mexico. This is KEC's standard procedure for closing BGTs. For those closures which do not conform to this standard closure plan, a separate closure plan will be developed and submitted to the New Mexico Oil Conservation Division (OCD). All closure activities will include proper documentation and will be submitted to the OCD within 60 days of the pit closure on a Closure Report using Division form C-144. The report will include the attachments required by form C-144.

#### General Plan Requirements

- 1. KEC shall close an existing below-grade tank that does not meet the design requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008, if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC. [19.15.17.13(A)(4)]
- 2. All piping will be rerouted to an alternative produced water storage/disposal location (e.g. surface tanks, temporary fractionation tank, etc.) The well will be temporarily shut-in until the rerouting is completed.
- 3. All produced water will be removed from the BGT following discharge-pipe rerouting. Produced water will be disposed of by injection at either Basin Disposal Inc. (Disposal #1 Well, API 30-045-26862, Permit NM-001-0005) or Key Four Corners Inc.( Sunco Disposal #1, API 30-045-28653, Permit NM-01-0009).

### Closure Method for Below-grade Tanks [19.15.17.13(E) NMAC]

- 1. KEC shall remove liquids and sludge from a below-grade tank prior to implementing a closure method and shall dispose of the liquids and sludge in a division-approved facility.
- 2. KEC shall remove the below-grade tank and either recycle, reuse, reclaim, or dispose of it in a division-approved facility (i.e. San Juan Regional Landfill operated by Waste Management under NMED Permit SWM-052426).
- 3. If there is any on-site equipment associated with a below-grade tank, then KEC shall remove the equipment, unless the equipment is required for some other purpose.
- 4. KEC shall test the soils beneath the below-grade tank to determine whether a release has occurred. KEC shall collect, at a minimum, a five point, composite sample; collect individual grab samples from any area that is wet, discolored or showing other evidence of a release; and analyze for BTEX, TPH and chlorides to demonstrate that the benzene concentration, as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 0.2 mg/kg; total BTEX concentration, as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 50 mg/kg; the TPH concentration, as determined by EPA method 418.1 or other EPA method that the division approves, does not exceed 100 mg/kg; and the chloride concentration, as determined by EPA method 300.1 or other EPA method that the division approves, does not exceed 250 mg/kg, or the background concentration,

whichever is greater. KEC shall notify the division of its results on form C-141. The division may require additional delineation upon review of the results.

Table 1: Closure Criteria for BGTs

Components	Testing Methods	Closure Limits (mg/Kg)
Benzene	EPA SW-846 Method 8021B or 8260B	0.2
BTEX	EPA SW-846 Method 8021B or 8260B	50
	EPA SW-846 Method 8015 M (Full Range)*	
TPH	or Method 418.1	100
		Greater of 250
		mg/kg or
Chlorides	EPA SW-846 Method 300.1	background
* Preferred		
Method		

- 5. If KEC or the division determines that a release has occurred, then KEC shall comply with 19.15.3.116 NMAC (report release to the OCD) and 19.15.1.19 NMAC (soils will be excavated and OCD District Office approval to haul to the Envirotech Landfarm near Bloomfield, NM, OCD Permit NM-01-0011, will be obtained).
- 6. If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Paragraph (4) of Subsection E of 19.15.17.13 NMAC, then KEC shall backfill the excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; recontour and re-vegetate the site. The division-prescribed soil cover, recontouring and re-vegetation requirements shall comply with Subsections G, H and I of 19.15.17.13 NMAC.

#### Soil Cover [19.15.17.13(H)]

Upon completion of the tank removal and any necessary soil remediation, the excavation will be backfilled with non-waste earthen material consisting of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The surface will be recontoured to match the sites existing grade and prevent ponding of water and erosion of the cover material.

#### Revegetation [19.15.17.13(I)]

For those portions of the former BGT area no longer required for production activities, KEC will seed the disturbed areas the first growing season after the BGT area is covered. Seeding will be accomplished via drilling on the contour whenever practical, or by other Division-approved methods. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted by overgrazing, fire, or other intrusion damaging to native vegetation) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintained that cover through two successive growing seasons. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

Repeat seeding or planting will be continued until successful vegetative growth occurs. *Note: KEC* assumes the seeding stipulations including mix and seeding methods specified by the Surface Management Agency (BLM, BOR, USFS, Tribal, etc.) or Land owner as part of a surface use agreement or APD are Division-approved methods unless notified by the Division of their unacceptability.

For those portions of the former pit area required for production activities, reseeding will be done at well abandonment, and following the procedure noted above.

### **Closure Notice [19.15.17.13(J) NMAC]**

- 1. KEC shall notify the surface owner by certified mail, return receipt requested, that KEC plans to close a BGT. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records is sufficient to demonstrate compliance with this requirement.
- 2. KEC shall notify the appropriate division district office verbally or by other means at least 72 hours, but not more than one week, prior to any closure operation. The notice shall include KEC's name and the location to be closed by unit letter, section, township and range. If the closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

### **Closure Report [19.15.17.13(K) NMAC]**

Within 60 days of closure completion, KEC shall submit a closure report on form C-144, with necessary attachments to document all closure activities including sampling results; information required by 19.15.17 NMAC; a plot plan; and details on back-filling, capping and covering, where applicable. In the closure report, KEC shall certify that all information in the report and attachments is correct and that KEC has complied with all applicable closure requirements and conditions specified in the approved closure plan.