District I 1625 N French Dr., Hobbs, NM 88240 District II 1301 W Grand Avenue, Artesia, NM88210 District III
1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources** Department Oil Conservation Division 1220 South St. Francis Dr.

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office. For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

$\overline{\ }$	$\overline{\cap}$	ī	0
\bigcirc	7	l	B

Pit, Closed-Loop System, Below-Grade Tank, or

Santa Fe, NM 87505

Proposed Alternative Method Permit or Closure Plan Application [] Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request Please be advised that approval of this request does not relieve theoperator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances. RCVD JUL 25'08 Operator: Energen Resources Corporation Address: 2010 Afton Place, Farmington, New Mexico 87401 OIL CONS. DIV. Facility or well name: Riddle B #224 OCD Permit Number: U/L or Qtr/Qtr I Section 27 Township 30N Range 10W County: San Juan
 Center of Proposed Design:
 Latitude
 36.77984
 Longitude
 107.86535
 NAD:
 □1927 ⋈ 1983
 Surface Owner: Federal State Private Tribal Trust or Indian Allotment Pit: Subsection F or G of 19.15.17.11 NMAC Closed-loop System: Subsection H of 19.15.17.11 NMAC Temporary: Drilling Workover ☐ Drying Pad ☐ Tanks ☐ Haul-off Bins ☐ Other _____ ☐ Permanent ☐ Emergency ☐ Cavitation ☐ Steel Pit ☐ Lined ☑ Unlined ☐ Lined ☐ Unlined Other _____ Seams: Welded Factory Other _____ String-Reinforced Volume: <u>265</u> bbl <u>165</u> yd³ Scams: Welded Factory Other Volume: bbl Dimensions: L x W x D Dimensions: Length 40 x Width 12 Below-grade tank: Subsection I of 19.15.17.11 NMAC Fencing: Subsection D of 19.15.17.11 NMAC Volume: _____bbl Chain link, six feet in height, two strands of barbed wire at top Type of fluid: Four foot height, four strands of barbed wire evenly spaced between one and Tank Construction material: four feet Secondary containment with leak detection Netting: Subsection E of 19.15.17.11 NMAC Screen Netting Other____ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off ☐ Visible sidewalls and liner ☐ Monthly inspections ☐ Visible sidewalls only Signs: Subsection C of 19.15.17.11 NMAC Other 12'x24', 2' lettering, providing Operator's name, site location, and Lincr type: Thickness _____ mil HDPE PVC emergency telephone numbers Other Signed in compliance with 19.15.3.103 NMAC Alternative Method: Administrative Approvals and Exceptions: Submittal of an exception request is required. Exceptions must be Justifications and/or demonstrations of equivalency are required. Please refer to submitted to the Santa Fe Environmental Bureau office for consideration 19.15.17 NMAC for guidance. of approval. Please check a box if one or more of the following is requested, if not leave Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval. Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

.⁴⁴ oil cons. Div. dist. 3

Oil Conservation Division

Page 1 of 4

Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.			
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site			
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No ☐ NA		
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits) Visual inspection (certification) of the proposed site; Aerial photo; Satellite image			
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality			
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No		
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No		
Within a 100-year floodplain FEMA map	Yes No		
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC			
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC	_		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (required for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9 Siting Criteria Compliance Demonstrations (required for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC			
Previously Approved Design (attach copy of design) API Number:			

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC		
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the do attached.	cuments are	
attachea. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC		
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC		
Climatological Factors Assessment		
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC		
Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC		
☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC ☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC		
Quality Control/Quality Assurance Construction and Installation Plan		
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC	1	
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC		
Nuisance or Hazardous Odors, including H ₂ S, Prevention Plan		
Emergency Response Plan		
☐ Oil Field Waste Stream Characterization ☐ Monitoring and Inspection Plan		
Erosion Control Plan		
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC		
Proposed Closure: 19,15.17,13 NMAC		
	7 Alternativa	
Type: Drilling Workover Emergency Cavitation Permanent Pit Below-grade Tank Closed-loop System] Alternative	
Proposed Closure Method: Waste Excavation and Removal		
 ☑ Waste Removal (Closed-loop systems only) ☑ On-site Closure Method (Only for temporary pits and closed-loop systems) 		
In-place Burial On-site Trench Burial		
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for cor	isideration)	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC		
Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable		
source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from		
the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau		
office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10		
NMAC for guidance.		
Ground water is less than 50 feet below the bottom of the buried waste.	☐ Yes ☐ No	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ NA	
Ground water is between 50 and 100 feet below the bottom of the buried waste	Yes No	
- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ NA	
Ground water is more than 100 feet below the bottom of the buried waste.	☐ Yes ☐ No	
NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	□ NA	
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa	☐ Yes ☐ No	
lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site		
Topographic map, Trada mapochon (vertification) of the proposed site		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes No	
- Visual inspection (certification) of the proposed site, Aerial photo; Satellite image		
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock	☐ Yes ☐ No	
watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	□ ·40 □ 110	
- NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site		
	□ V □ N-	
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	Yes No	
- Written confirmation or verification from the municipality; Written approval obtained from the municipality		
Within 500 feet of a wetland.	☐ Yes ☐ No	
- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site		
Within the area overlying a subsurface mine.	☐ Yes ☐ No	
Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division		
Within an unstable area.	□ Vaa □ Na	
 Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	☐ Yes ☐ No	
posison tohoBrahum mah		
Within a 100-year floodplain.		
- FEMA map	L	

Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the			
closure plan. Please indicate, by a check mark in the box, that the documents are attached.			
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC			
 ☐ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC ☑ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) 			
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
☑ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC			
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			
Waste Removal Closure For Closed-loop Systems That Utilize Haul-off Bins Only: (19.15.17.13.D NMAC) Instructions: Please indentify the facility			
or facilities for the disposal of liquids, drilling fluids and drill cuttings.			
Disposal Facility Name: Auga Moss / Envirotech Disposal Facility Permit Number: NM-01-0011			
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate,			
by a check mark in the box, that the documents are attached.			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC			
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Construction and Design of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC			
☐ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC ☐ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC			
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)			
Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC			
☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC			
Operator Application Certification:			
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.			
Name (Print): Kirt Sayder Title: District Engineer			
7/24/2008			
Signature: Date: 1/04/000			
77.1			
e-mail address: ksnyder@energen.com Telephone: (505) 793-7614			
OCD Approval: Permit Application (including closure plan) Closure Plan (only)			
OCD Representative Signature: B-4-98			
The state of the s			
Compliance Officer			
Title: Enviro spec OCD Permit Number:			
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC			
Closure Completion Date: 12.310.08			
Closure Method:			
Waste Excavation and Removal On-Site Closure Method Alternative Closure Method			
If different from approved plan, please explain.			
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check			
mark in the box, that the documents are attached.			
Proof of Closure Notice			
Proof of Deed Notice (if applicable)			
Plot Plan Confirmation Sampling Analytical Results			
Waste Material Sampling Analytical Results			
Disposal Facility Name and Permit Number			
Soil Backfilling and Cover Installation			
Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation)			
On-site Closure Location: Latitude Longitude NAD:1927 1983			
Operator Closure Certification:			
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and			
belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.			
Name (Print): VICKI DONGGINELL Title: REQUIDEDRY ANDLYST			
Signature: MCKL LOWOKKY Date: 01-05-09			
e-mail address: Vanabe Berkeren. an Telephone: 55.314.436			

Closed-loop Design Plan:

Our closed loop system will not entail a drying pad, temporary pit, below grade tank or sump. It will entail an above ground tank suitable for holding the cuttings and fluids for rig operations. The tank will be of sufficient volume to maintain a safe free board between disposal of the liquids and solids from rig operations.

- 1) Fencing is not required for an above ground closed-loop system.
- 2) It will be signed in compliance with 19.15.3.103 NMAC.
- 3) A frac tank will be on location to store fresh water.

Closed-loop Operating and Maintenance Plan:

The closed-loop tank will be operated and maintained; to contain liquids and solids, to aid in the prevention of contamination of fresh water sources, in order to protect public health and the environment. To attain this goal the following steps will be followed:

- 1) The liquids will be vacuumed out and disposed of at the Agua Moss Pretty Lady #1 facility (Disposal API Number 30-048-30922). Solids in the closed-loop tank will be vacuumed out and disposed of at Envirotech (Permit Number NM-01-0011) on a periodic basis to prevent over topping.
- 2) No hazardous waste, miscellaneous solid waste or debris will be discharged into or stored in the tank. Only fluids or cuttings used or generated by rig operations will be placed or stored in the tank.
- 3) The division district office will be notified within 48 hours of the discovery of compromised integrity of the closed-loop tank. Upon the discovery of the compromised tank, repairs will be enacted immediately.
- 4) All of the above operations will be inspected and a log will be signed and dated. During rig operations the inspection will be daily.

Closed-loop Closure Plan:

The closed loop tank will be closed in accordance with 19.15.17.13. This will be done by transporting cuttings and all remaining sludge to Envirotech (Permit Number NM-01-0011) following rig operations. All remaining liquids will be transported and disposed of in the Agua Moss Pretty Lady #1 facility (Disposal API number 30-048-30922). The tanks will be removed from the location as part of the rig move. At time of well abandonment, the site will be reclaimed and re-vegetated to pre-existing conditions when possible.

Closed-loop Completion:

A closed-loop tank will be set on location once drilling operations have ceased. The closed-loop tank will measure 20 ft height by 12 ft diameter (400 BBL) or 20 ft height by 10 ft 6 in diameter (300 BLL). It will be designed, operated, maintained and closed according to the attached Closed-loop Design Plan, Closed-loop Operating and Maintenance Plan, and Closed-loop Closure Plan.

Kirt Snyler
District Engineer
Energen Resources
MSSalar 8/28/2008