This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator COP					Lease	e Name	SAN .		Well No. 91		
ocation of Wel	: Unit L	etter _	В	Sec _	34	Twp _	028N	Rge _	007W	API#	30-039-07270
	Name of Reservoir or Pool			Type of Prod			Method of Prod			Prod Medium	
Upper Completion	PC				Gas			Flov	Flow		Tubing
Lower Completion	MV				Gas			Arti	Artificial Lift		Tubing
				P	re-Flow S	Shut-In	Pressu	re Data		'	
Upper	Hour, Date, Shut-In					Length of Time Shut-In			SI Press PSIG		Stabilized?(Yes or No)
Completion	6/16/2011					128 hours			229		Yes
Lower	Hour, Date, Shut-In					Length of Time Shut-In			SI Press PSIG		Stabilized?(Yes or No)
Completion	6/16/2011				-	153 hours			117		Yes
Time Lapsed Time (date/time) Since*				PRESSURE Upper zone Lower zone		Prod Zone Temperatu	е	Remarks			
6/21/2011 8·59·26 AM 0			229	229 117		69	69 zones have stabi		ed turn on pc		
6/22/2011 9 36 10 AM 25				65	1	119	69	turn on MV/	turn on MV/ complete test		
roduction rate	_										
)il:	BPOD	Based o	n:	BI	bls. In		Hrs.		_Grav		GOR
as		MC	PD; Te	st thru (O	rifice or N	leter) _					
				M	lid-Test S						
Upper Completion	Hour, Date, Shut-In				Length	Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)
Lower Completion	Hour, Date, Shut-In				Length of Time Shut-In			SI Press. PSIG			Stabilized?(Yes or No)
		**			(Contin	ue on r	everse s	side)			

a ()



Northwest New Mexico Packer-Leakage Test

Flow Test No. 2

Commenced at:		Zone Producing (Upper or Lower)									
Time	Lapsed Time	PRES	SURE	Prod Zone							
(date/time)	Since*	Upper zone	Lower zone	Temperature	Remarks						
			-								
L											
Dundersking unknight dereine											
Production rate during	test										
Oil:BPOD	Based on:	Bbls. In	Hrs.		GravGOR						
GasMCFPD; Test thru (Orifice or Meter)											
Remarks:											
I hereby certify that the information herein contained is true and complete to the best of my knowledge.											
Approved.	20	Operat									
New Mexico Qil Co	nservation Division		Ву:	By: Jason Moberg							
By Chan	4//		Title:	Title: Multi-Skilled Operator							
			_ 1106	Title. Ividiti-okilied Operator							
Title: SUPERVISOR I	DISTRICT # 3		_ Date: _	Date: Thursday, July 07, 2011							

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the
- while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for atmosphere due to lack of a pipeline connection the flow period shall be three hours

- Flow Test No 2 shall be conducted even though no leak was indicated during Flow Test No 1 Procedure for Flow Test No 2 is to be the same as for Flow Test No 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone

The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3