This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Oil Conservation Division

Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR					Leas	se Name	SUNF	RAY				Well No8	М	
Location of Well	: Unit	Letter _	Р	Sec	05	Twp _	029N	R	ge	W800	_ API#	30-045-29893		
	Name of Reservoir or Pool				Type of Prod				Method of Prod			Prod Medium		
Upper Completion	MV			Gas				Artificial Lift			Tubing			
Lower Completion	DK				Gas				Flow			Tubing		
				F	re-Flow	Shut-In	Pressu	re Data	a					
Upper	Hour, Date, Shut-In				Length of Time Shut-In				SI Press PSIG			Stabilized?(Yes or No)		
Completion	6/16/2011				-	324 hours				174		Yes		
Lower		te, Shut-Ir				of Time S	Shut-In		SI Pres	s. PSIG		Stabilized?(Yes or No)		
Completion				324 hours						191	Yes			
					FI	ow Tes	t No. 1			na				
Commenced at	t: /29/	2011 12:	00:10 PI	Л		Z	one Pro	ducing	(Upper	or Lowe	er): LO\	VER		
Time		Lapsed Time			PRESSURE Pro			Prod	od Zone					
(date/time))		ince*		per zone		er zone		erature		Remarks			
6/29/2011 12 01:1	0 PM		0		174	1	91							
6/29/2011 12:16:3	0 PM		0		174	1	04							
Production rate	during	test												
Oil:	BPOD	Based o	n:	В	bls. In _		Hrs.	*	(Grav		GOR		
Gas		MCF	PD; Tes	st thru (C	Orifice or I	Meter)								
					Aid Took	Ch4 lm	D	D	_					
Upper Completion	Hour, Da	ate, Shut-Ir	<u></u>	Ŋ	/lid-Test Length	of Time S		ire Data		s PSIG		Stabilized?(Yes or No)		
Lower Completion	Hour, Da	ate, Shut-Ir	l		Length of Time Shut-In				SI Press. PSIG			Stabilized?(Yes or No)		
					(Contin		overes a	nido)	<u> </u>		l.			

a sh



Flow Test No. 2

mmenced at:			Zone Pro	oducing (Uppe	er or Lower)				
Time	Lapsed Time	PRES	SURE	Prod Zone					
(date/time)	Since*	Upper zone	Lower zone	Temperature)	Remarks			
•									
			<u></u>						
duction rate during	j test			•					
BPOD Based on:		Bbls. In	Hrs.		Grav.	GOR			
5	MCFPD; Test th	nru (Orifice or M	leter)						
marks.									
ereby certify that th	e information herein o	contained is true	and complete	to the best of	f my knowled	ge.			
proved:		20	Opera	tor: BR					
New Mexico QiÍ Conservation Division			By:						
y Char IP			-	: Multi-Skilled Operator					
e SUPERVISOR DISTRICT # 3				Thursday, July 07, 2011					
oroved: New Mexico Oil Co	20	Opera By: Title:	tor: BR Dennis She Multi-Skilled	ets I Operator	ge.				

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified 155
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- For Flow Test No 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well Note if, on an initial packer leakage test, a gas well is being flowed to the
- atmosphere due to lack of a pipeline connection the flow period shall be three hours

- Flow Test No 2 shall be conducted even though no leak was indicated during Flow Test No 1 Procedure for Flow Test No 2 is to be the same as for Flow Test No 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone
- The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)

Following completion of Flow Test No 1, the well shall again be shut-in, in accordance with Paragraph 3