

Current Schematic

ConocoPhillips

Well Name: SAN JUAN 28-6 UNIT #68

API/UWI 3003907058	Surface Legal Location NMPM,013-027N-006W	Field Name BLANCO P.C. SOUTH (GAS)	License No.	State/Province NEW MEXICO	Well Configuration Type	Edit
Ground Elevation (ft) 6,335.00	Original KB/RT Elevation (ft) 6,345.00	KB-Ground Distance (ft) 10.00	KB-Casing Flange Distance (ft)	KB-Tubing Hanger Distance (ft)		

Well Config: - Original Hole, 9/12/2011 12:30:21 PM

ftKB (MD)	Schematic - Actual	Frm Final
0		
10		
171		
172		
175		
1,090		
2,322		
2,542		OJO ALAMO, 2,322
2,892		KIRTLAND, 2,542
3,047		FRUITLAND, 2,892
3,060		
3,090		
3,091		PICTURED CLIFFS, 3,047
3,116		
3,135		
3,203		
3,215		
3,254		
3,255		
3,264		
3,305		
4,633		
4,636		
4,688		
4,813		CLIFF HOUSE, 4,688
4,906		
5,172		MENELEE, 4,813
5,200		
5,312		
5,313		POINT LOOKOUT, 5,200
5,354		
5,371		
5,420		
5,427		
5,428		
5,482		
5,483		
5,484		

Surface Casing Cement, 10-172, 8/15/1957, Cement w/ 200 sx of regular cement, 2% gel, and 100# Flowcel. Circulated cement to surface.

Surface, 10 3/4in, 10.192in, 10 ftKB, Adjusted set depth for 10' KB., 172 ftKB

Tubing, 1 1/4in, 2.30lbs/ft, 10 ftKB, 3,090 ftKB
Tubing, 2 3/8in, 4.70lbs/ft, J-55, 10 ftKB, 4,632 ftKB

Pictured Cliffs, 9/3/1957, Frac'd PC w/ 33,000 gals of treated water and 40,000# of 10/20 sand.
Seating Nipple, 1 1/4in, 2.30lbs/ft, 3,090 ftKB, 3,091 ftKB

Pictured Cliffs, 3,060-3,116, 9/3/1957

Liner top @ 3203'

Intermediate Casing Cement, 1,090-3,255, 8/26/1957, Cement w/ 225 sx of poz regular cement, 4% gel, and 1/4# Flocele. Followed w/ 50 sx. neat cement. TOC @ 1090' by TS 8/26/1957.

Intermediate, 7 5/8in, 6.969in, 10 ftKB, 3,255 ftKB

LEWIS, 3,135

Packer Baker Model "N-1", 2 3/8in, 4.70lbs/ft, J-55, 4,632 ftKB, 4,636 ftKB

Cliffhouse, 9/3/1957, Frac'd CH w/ 60,000 gals of treated water and 60,000# of 40/80 sand.

Cliffhouse, 4,688-4,906, 9/3/1957

CLIFF HOUSE, 4,688

Tubing "NU", 2 3/8in, 4.70lbs/ft, J-55, 4,636 ftKB, 5,312 ftKB

MENELEE, 4,813

Point Lookout, 9/3/1957, Frac'd PL w/ 62,000 gals of treated water and 60,000# of 20/40 sand.

Point Lookout, 5,172-5,354, 9/3/1957

POINT LOOKOUT, 5,200

F Nipple, 2 3/8in, 4.70lbs/ft, J-55, 5,312 ftKB, 5,313 ftKB

PBTD, 5,420

Production Liner Cement, 3,305-5,483, 9/1/1957, Cement w/ 150 sx of poz cement w/ 4% gel. Followed w/ 150 sx regular cement. TOC @ 3305' by TS 9/1/1957.

Production Liner, 5 1/2in, 4.950in, 3,203 ftKB, 5,483 ftKB

MANCOS, 5,371

TD, 5,484, 9/1/1957

Bottom Plug, 5,483-5,484, 9/1/1957