# NEW MEXICO OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised June 10, 2003

Operator		DEVO	ENERG'	Y		Lease I	Name		NEBU	Well No	329
Location Of Well:	Unit Letter	0	Sec	24	Twp	31N	_Rge	7W	_API # 30-0 _	453	2248

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	PICTURED CLIFFS	GAS	FLOW	CASING
Lower Completion	DAKOTA	GAS	FLOW	TUBING

## Pre-Flow Shut-In Pressure Data

Upper	Hour, Date,Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	6/7/11 5:30 PM	45 hrs	515	YES
Lower	Hour, Date,Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	6/7/11 5:30 PM	94 hrs	95	YES

#### Flow Test No. 1

·		T	riow lest No				
Upper	r Lower):	oducing (Upper o	OPM Zone Pr	6/7/11 2:30	late)*	ommenced at (hour, d	
	Remarks	Prod. Zone	essure	Pr	Lasped Time	Time Lasped Time	
		Тетр.	Lower Compl.	Upper Compl.	Since*	(Hour, Date)	
Set packer shut in well		60	0	0	0	6/7/2011 17:30	
turned on upper completion	t	60	92	515	45	6/9/2011 14:30	
pressure crossed over		60	95	71	24	6/10/2011 14:30	
turned on lower completion	turned on lower completion		95	69	6/11/2011 15:30 25		
	-						

Production Rate During Test

Oil: BOPD based on Bbls. In Hrs. Grav. GOR

Gas: 1 Mil MCFPD; Test thru (Orifice or Meter): Meter

Mid-Test Shut-In Pressure Data

	Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or NO)
	Completion				
ſ	Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or NO)
Ì	Completion				

(Continue on reverse side)

Ca

### NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Flow Test No. 2

Commenced at (hour, date)* Zone Producing (Upper or Lower):									
Time	Lasped Time	Pres	sure	Prod. Zone	Remarks				
(Hour, Date)	Since*	Upper Compl.	Lower Compl.	Temp.					
<del></del>									
Ļ	D . 10 . m								
Production I	Rate During Test								
0.1	DODD I	1	DIL T	17	C	con			
Oil:	BOPD based	d on	Bois. In	Hrs	Grav.	COR			
		MCEDD W	(O : C . N )						
Gas:		MCFPD; Test thru	(Orifice or Meter):						
Remarks:									
	.611		1 1	.1 1 . 6 1					
I nereny cert	ify that the information	nerem contained is t	tue and complete to	the best of my kno	wieage.				
ζ.									
A	+	0	1-3 20	12 Op	erator	DEVON ENERGY			
Appoved	To a file	West Y		100 Ope	erator	DEVON ENERGI			
New Mexico	Oil Conservation Divisio	n							
	~ '/	7.1							
D	1 / 1	5////		Tıtle	Lease	a and a			
Ву	Donut	Oil 9 Coo	lm = = = 1 =	. I ITIE	~ ~~~	-7 -4 00/01			
m . i	Deputy	Oil & Gas		20 1 4					
Title		District #	<del>'3</del>	E-mail A	Address				
			•	ъ.					
				Date					

## Northwest New Mexico Packer Leakage Test Instructions

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the indway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).