Form 3160-5 (February 2005)

(Instructions on page 2)

**UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT DEC -1 2011

FORM APPROVED OMB No 1004-0137 Expires March 31, 2007

SUNDRY NOTICES AND REPORTS ON WEILINGTON Field Office				5. Lease Serial No SF-078766	
Do not use this form for proposals to drill or to re-enter and Manageme				6 If Indian, Allottee or Tribe Name	
abandoned well. Use Form 3160-3 (APD) for such proposals.				, , , , , , , , , , , , , , , , , , ,	
SUBMIT IN TRIPLICATE – Other instructions on page 2				7 If Unit of CA/Agreement, Name and/or No	
1 Type of Well				Rosa Unit	
Oıl Well Gas Well Other				8. Well Name and No Rosa Unit #256A	
2 Name of Operator				9 API Well No	
Williams Production Company, LLC  3a Address  3b. Phone No (include)			ea code)	30-039-27652  10 Field and Pool or Exploratory Area	
PO Box 640 Aztec, NM 87410 505-333-1808				Basin Fruitland Coal	
4 Location of Well (Footage, Sec., T.,R.,M., or Survey Description) SHL 1302' FNL & 1586' FWL BHL: 52' FNL & 58' FEL SEC 25 31N 6W				11 Country or Parish, State Rio Arriba, NM	
12 CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA					
TYPE OF SUBMISSION TYPE OF ACTION					
Notice of Intent		Production (Start/Resume)		rt/Resume)	Water Shut-Off
Notice of Intent Alter Casing	Fracture Treat		Reclamation		Well Integrity
Casing Repair	New Construct	ıon	Recomplete		Other Completion
Subsequent Report Change Plans	Plug and Aband	don Temporarily Abandon			
Final Abandonment Notice Convert to Plug Back Water Dispos					
duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)  10/24/11- MIRU HWS #15 for sidetrack prep. RIH and set RBP @ 2706' RDMO location  10/28/11- MIRU AWS #222  10/29/11- Install pipe rams, blind rams, choke manifold and TIW valves, test 7" casing, 250# low f/5 min and 1500# Fig. 16/20 min, all test good  10/30/11- RIH and set whipstock. Retrieve RBP @ 2706', Set RBP @ 2720'  10/31/11- Retrieve RBP @ 2720', Set RBP @ 2677'  11/1/11 to 11/2/11- Mill window from 2660' to 2673'. Drill 6-1/4" curve from 2673' to 3460'					
14 I hereby certify that the foregoing is true and correct Name (Printed/Typed)					
* ***			Permit Suprv		
Signature Date 12/1/11					
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by					
			Title	ı	Date
Conditions of approval, if any, are attached Approval of this notice does not warran certify that the applicant holds legal or equitable title to those rights in the subject leaving which would entitle the applicant to conduct operations thereon					
Title 18 U S C Section 1001 and Title 43 U S C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction					
ACCEPTED FOR RECORD					

NMOCD

DEC 0 2 2011

## ROSA UNIT #256A- Page 2

11/3/11 to 11/6/11- Drill 6-1/4" lateral from 3460' to 6095'. TD 6-1/4" @ 6095' (3229' TVD) on 11/6/11

<u>11/7/11-</u> Run 70 jts 4-1/2", 11 6#, J-55, LT&C, perforated casing (28, 0.50" holes p/ft) and 10 jts 4-1/2", 11.6#, J-55, LT&C non-perforated casing. Set @ 6095' (3229' TVD), TOL @ 2678'. Top perf @ 3146', bottom perf @ 6090'. Casing was not cemented

11/8/11 - RDMO AWS #222

11/11/11 - MIRU AWS #450 to CO lateral

11/12/11 to 11/24/11- CO Lateral

11/25/11- POOH with whipstock assy. Retrieved RBP @ 2677'

11/27/11-land 2-3/8", 4.7 #, J-55, EUE 8rd tubing with 200' capillary string @ 3162' as follows : 99 JTS, SN 1.78" @ 3130', 1 JT mud anchor with ½ Muleshoe @ 3162'.

 $\underline{11/28/11}$ - Run Pump and Rods as follows: 2-1/2 x 1-1/2 x 16' RWAC HVR sand Pro Pump, 4-  $\frac{1}{4}$ " sinker bars, 120  $\frac{3}{4}$ " Rods, 2-6', 4' Pony Rods, 3' Pony rods,1-1/4"x22' Polished Rod with 8'x1-1/2" Liner.