District I 162£JN French Dr , Hobbs NM 88240

1301 W Grand Ave , Artesia, NM 88210 District III 1000 Rio Brazos Rd, Aztec, NM 87410

District IV

State of New Mexico Energy Minerals and Natural Resources

Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

July 21, 2008

Form C-144

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the

1220 S St Francis Dr , Santa Fe, NM 87505	appropriate NMOCD District Office				
	Pit, Closed-Loop System, Below-Grade Tank, or				
Proposed Alternative Method Permit or Closure Plan Application					
Type of action: X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Modification to an existing permit Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method					
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.					
Operator. Burlington Resources Oil					
Address PO Box 4289, Farmington					
Facility or well name: SADIE WES					
API Number.	30-045- 35 305 OCD Permit Number				
U/L or Qtr/Qtr N(SE/SW) Section Center of Proposed Design Latitude Surface Owner X Federal					
Lined Unlined Liner String-Reinforced Liner Seams Welded Factor String-Reinforced Liner Seams Subsection Type of Operation P&A X	P.C.U.D. 14M & '1.2				
X Lined Unlined Liner Liner Seams X Welded X Fac	type Thickness 20 mil X LLDPE HDPE PVD Other ctory Other				
Below-grade tank: Subsection I Volume bb Tank Construction material Secondary containment with leak det Visible sidewalls and liner Liner Type Thickness					
Submittal of an exception request is requ	urred Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval				

Fencing: Subsection D of 19 15 17 11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet				
Alternate Please specify				
Netting: Subsection E of 19 15 17 11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)				
Signs: Subsection C of 19 15 17 11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19 15 3 103 NMAC				
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required Please refer to 19 15 17 NMAC for guidance Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s) Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration of approval (Fencing/BGT Liner) Exception(s) Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval				
Siting Criteria (regarding permitting) 19.15 17 10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.				
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - IWATERS database search; USGS, Data obtained from nearby wells	Yes	□No		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	□No		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No		
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo, Satellite image	□NA			
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits)	☐Yes ☐NA	□No		
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No		
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site. Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended	Yes	□No		
 Written confirmation or verification from the municipality. Written approval obtained from the municipality Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	Yes	□No		
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	□No		
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society, Topographic map	Yes	No		
Within a 100-year floodplain - FEMA map	Yes	No		

Form C-144 Oil Conservation Division Page 2 of 5

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment ChecklistSubsection B of 19 15 17 9 NMAC			
Instructions Each of the following items must be attached to the application Please indicate, by a check mark in the box, that the documents are attached			
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19 15 17 9 NMAC			
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19 15 17 9			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC			
Design Plan - based upon the appropriate requirements of 19 15 17 11 NMAC			
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15.17 12 NMAC			
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15 17 9 NMAC and 19 15 17 13 NMAC			
Previously Approved Design (attach copy of design) API or Permit			
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19 15 17 9 NMAC Instructions Each of the following items must be attached to the application Please indicate, by a check mark in the box, that the documents are attached Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19 15 17 9			
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19 15 17 10 NMAC			
X Design Plan - based upon the appropriate requirements of 19 15 17 11 NMAC			
X Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC			
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15 17 9 NMAC and 19 15 17 13 NMAC			
Previously Approved Design (attach copy of design) API			
Previously Approved Operating and Maintenance Plan API			
13			
Permanent Pits Permit Application Checklist: Subsection B of 19 15 17 9 NMAC			
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.			
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19 15 17 9 NMAC			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC			
Climatological Factors Assessment			
Certified Engineering Design Plans - based upon the appropriate requirements of 19 15 17 11 NMAC			
Dike Protection and Structural Integrity Design based upon the appropriate requirements of 19 15 17 11 NMAC			
Leak Detection Design - based upon the appropriate requirements of 19 15 17 11 NMAC			
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19 15 17 11 NMAC Quality Control/Quality Assurance Construction and Installation Plan			
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC			
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19 15 17.11 NMAC			
Nuisance or Hazardous Odors, including H2S, Prevention Plan			
Emergency Response Plan			
Oil Field Waste Stream Characterization			
Monitoring and Inspection Plan			
Erosion Control Plan			
Closure Plan - based upon the appropriate requirements of Subsection C of 19 15 17 9 NMAC and 19 15 17 13 NMAC			
14			
<u>Proposed Closure:</u> 19 15 17 13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.			
Type Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank X Closed-loop System			
☐ Alternative Proposed Closure Method ☐ Waste Excavation and Removal			
X Waste Removal (Closed-loop systems only)			
On-site Closure Method (only for temporary pits and closed-loop systems)			
In-place Burial On-site Trench			
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)			
15			
Waste Excavation and Removal Closure Plan Checklist (19 15 17 13 NMAC) Instructions: Each of the following items must be attached to the closure plan.			
Please indicate, by a check mark in the box, that the documents are attached.			
Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC			
 Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15 17 13 NMAC 			
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC			
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15.17.13 NMAC			
L Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15.17.15 NWAC			

Form C-144 Oil Conservation Division Page 3 of 5

16 Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:(19 15 17 13 D NMAC)					
Instructions Please identify the facility or facilities for the disposal of liquids, drilling fli facilities are reaured	uds and drill cuttings Use attachment if more than two				
Disposal Facility Name Envirotech / JFJ Landfarm % IEI Di					
Disposal Facility Name Basin Disposal Facility Di	sposal Facility Permit #. NM-01-005				
Will any of the proposed closed-loop system operations and associated activities Yes (If yes, please provide the information No	s occur on or in areas that will nbe used for future	service and			
Required for impacted areas which will not be used for future service and operations Soil Backfill and Cover Design Specification - based upon the appropriate requirements of Subsection H of 19 15 17 13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15 17 13 NMAC					
Siting Criteria (Regarding on-site closure methods only: 19 15 17 10 NMAC					
Instructions Each siting criteria requires a demonstration of compliance in the closure plan Recor certain siting criteria may require administrative approval from the appropriate district office or ma office for consideration of approval Justifications and/or demonstrations of equivalency are required.	ly be considered an exception which must be submitted to the Sc				
Ground water is less than 50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search, USGS Data obtain	ed from nearby wells	Yes No			
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search, USGS, Data obtained		Yes No			
Ground water is more than 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search, USGS, Data obtain	ed from nearby wells	Yes No			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other signification (measured from the ordinary high-water mark)	Yes No				
- Topographic map, Visual inspection (certification) of the proposed site					
Within 300 feet from a permanent residence, school, hospital, institution, or church in ex - Visual inspection (certification) of the proposed site, Aerial photo, satellite image	stence at the time of initial application	Yes No			
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than f purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existen - NM Office of the State Engineer - iWATERS database, Visual inspection (certifical	ce at the time of the initial application				
Within incorporated municipal boundaries or within a defined municipal fresh water well figures until to NMSA 1978, Section 3-27-3, as amended	ield covered under a municipal ordinance adopted	Yes No			
- Written confirmation or verification from the municipality, Written approval obtained from the municipality Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site		Yes No			
Within the area overlying a subsurface mine - Written confiramtion or verification or map from the NM EMNRD-Mining and Min		Yes No			
Within an unstable area - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources, USGS, NM Geological Society,		Yes No			
Topographic map Within a 100-year floodplain - FEMA map		Yes No			
On-Site Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of by a check mark in the box, that the documents are attached.	f the following items must bee attached to the clo	sure plan. Please indicate,			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC					
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19 15 17.13 NMAC					
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19 15 17 11 NMAC					
Construction/Design Plan of Temporary Pit (for in place burial of a dryii	• • • • • • • • • • • • • • • • • • • •	of 19 15 17 11 NMAC			
Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC					
Confirmation Sampling Plan (if applicable) - based upon the appropriate	•	AC			
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19 15 17.13 NMAC					
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC					
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC					
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15 17 13 NMAC					

Form C-144 Oil Conservation Division Page 4 of 5

19 Operator Application Certification:				
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief				
Name (Print) Jamie Goodwin Title Regulatory Technician				
Signature 10mu 60001 Date 1511				
e-mail address jamie goodwin@conocophillips.com Telephone 505-326-9784				
OCD Approval: Permit Application (including elfsure plan) Glosure Plan (only) GCD Conditions (see attachment) OCD Representative Signature: Approval Date: GCD Permit Number:				
Title: OCD Permit Number:				
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Instructions Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed. Closure Completion Date:				
22				
Closure Method: Waste Excavation and Removal On-site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain				
23				
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities				
were utilized. Disposal Facility Permit Number Disposal Facility Permit Number				
Disposal Facility Name Disposal Facility Permit Number				
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?				
Yes (If yes, please demonstrate compliane to the items below)				
Required for impacted areas which will not be used for future service and operations Site Reclamation (Photo Documentation)				
Soil Backfilling and Cover Installation				
Re-vegetation Application Rates and Seeding Technique				
24 Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in				
the box, that the documents are attached. Proof of Closure Notice (surface owner and division)				
Proof of Deed Notice (required for on-site closure)				
Plot Plan (for on-site closures and temporary pits)				
Confirmation Sampling Analytical Results (if applicable)				
Waste Material Sampling Analytical Results (if applicable)				
Disposal Facility Name and Permit Number				
Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique				
Site Reclamation (Photo Documentation)				
On-site Closure Location Latitude. Longitude NAD 1927 1983				
25 Operator Closure Certification:				
I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief I also certify that				
the closure complies with all applicable closure requirements and conditions specified in the approved closure plan				
Name (Print) Title				
Signature Date				
e-mail address Telephone				

Form C-144 Oil Conservation Division Page 5 of 5

Burlington Resources Oil & Gas Company, LP

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Burlington Resources Oil & Gas Company, LP may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- 1 Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- 2. Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3 In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed Loop Closure Plan:

1. Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) within 6 months from the date that the drilling rig is released.

2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	02
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. BR shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rımrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)

Purity

Source No. two (better quality)

Purity

Source No. two (better quality)

Purity

80 percent

Germination

63 percent

Percent PLS

20 percent

Percent PLS

50 percent

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 ib. PLS