District I 1625 N. French Dr., Hobbs. NM 88240 District II 1301 W Grand Ave , Artesia, NM 88210 District III 1000 Rio Brazos Rd, Aztec, NM 87410

1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 July 21, 2008

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

9608

District IV

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action:	Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
	X Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
	Modification to an existing permit
	Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of hability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances

Operator: ConocoPhillips Company	OGRID#: <u>217817</u>			
Address: PO Box 4289, Farmington, NM 87499				
Facility or well name: SAN JUAN 29-6 UNIT 61M				
API Number: 30-039-30985 OCD Permit Numb	per·			
U/L or Qtr/Qtr: K(NE/SW) Section: 19 Township: 29N Range:	6W County: Rio Arriba			
Center of Proposed Design: Latitude: 36.709354 °N Longitude:	107.507203 °W NAD: ☐ 1927 X 1983			
Surface Owner: Federal State X Private Tribal Trust or India	an Allotment			
String-Reinforced	RCVD FEB 17'12 OIL CONS. DIV. DIST. 3 HDPE PVC Other bbl Dimensions L x W x D			
Closed-loop System: Subsection H of 19.15.17.11 NMAC Type of Operation: P&A Drilling a new well Workover or Drilling (Applies to notice of intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other Lined Unlined Liner type: Thickness mil LLDPE Liner Seams: Welded Factory Other	o activities which require prior approval of a permit or HDPE PVD Other			
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: bbl Type of fluid: Tank Construction material: Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Liner Type: Thickness mil HDPE PVC Other				
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Enviro	onmental Bureau office for consideration of approval.			

Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institt Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate Please specify	ttion or churck	ı)
Netting: Subsection E of 19.15.17 11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)		
Signs: Subsection C of 19.15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC		
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: X Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration pit for Pre-set) Exception(s). Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	deration of app	roval.
Siting Criteria (regarding permitting) 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - IWATERS database search; USGS; Data obtained from nearby wells	Yes	No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	□No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	No
(Applies to temporary, emergency, or cavitation pits and below-grade tanks)	NA	
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image		—
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits)	Yes NA	∐No
 Visual inspection (certification) of the proposed site; Aerial photo; Satellite image Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. 	Yes	No
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site.		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality, Written approval obtained from the municipality	Yes	No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	No
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	Yes	No
Within a 100-year floodplain - FEMA map	Yes	No

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment ChecklistSubsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19 15.17.9
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15.17 11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17 9 NMAC and 19 15.17.13 NMAC
Previously Approved Design (attach copy of design) API or Permit
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19 15 17.9 NMAC Instructions. Each of the following items must be attached to the application Please indicate, by a check mark in the box, that the documents are attached.
Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC
Design Plan - based upon the appropriate requirements of 19.15 17.11 NMAC
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC
Previously Approved Design (attach copy of design) API
Previously Approved Operating and Maintenance Plan API
13
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17 9 NMAC
String Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19 15.17 11 NMAC
Dike Protection and Structural Integrity Design: based upon the appropriate requirements of 19.15.17.11 NMAC
Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC
Quality Control/Quality Assurance Construction and Installation Plan
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15 17.11 NMAC
Nuisance or Hazardous Odors, including H2S, Prevention Plan
Emergency Response Plan
Oil Field Waste Stream Characterization
Monitoring and Inspection Plan Erosion Control Plan
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15 17.9 NMAC and 19.15.17.13 NMAC
Proposed Closure: 19.15.17.13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type: Drilling Workover Emergency X Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative
Proposed Closure Method: Waste Excavation and Removal
Waste Removal (Closed-loop systems only)
On-site Closure Method (only for temporary pits and closed-loop systems)
In-place Burial On-site Trench
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following tiems must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15 17.13 NMAC

Form C-144 Oil Conservation Division Page 3 of 5

16 Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel	Tanks or Haul-off Bins Only:(19 15.17.13.D NMAC)				
Instructions Please identify the facility or facilities for the disposal of liquids, drilling fl facilities are required.					
	isposal Facility Permit #: NM-01-0011 / NM-01-0	010B			
Disposal Facility Name: Basin Disposal Facility D	isposal Facility Permit #: NM-01-005				
Will any of the proposed closed-loop system operations and associated activities Yes (If yes, please provide the information No	es occur on or in areas that will nbe used for future	service and			
Required for impacted areas which will not be used for future service and operations. Soil Backfill and Cover Design Specification - based upon the appropriate Re-vegetation Plan - based upon the appropriate requirements of Subsection Site Reclamation Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the appropriate requirements of Subsection Plan - based upon the ap	on I of 19 15 17 13 NMAC	MAC			
Siting Criteria (Regarding on-site closure methods only: 19 15 17 10 NMAC Instructions Each string criteria requires a demonstration of compliance in the closure plan Reco certain siting criteria may require administrative approval from the appropriate district office or m office for consideration of approval Justifications and/or demonstrations of equivalency are required.	ay be considered an exception which must be submitted to the Sa				
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - IWATERS database search, USGS. Data obtain	ned from nearby wells	Yes No			
Ground water is between 50 and 100 feet below the bottom of the buried waste		Yes No			
- NM Office of the State Engineer - tWATERS database search, USGS, Data obtain	ed from nearby wells	N/A			
Ground water is more than 100 feet below the bottom of the buried waste.		Yes No			
- NM Office of the State Engineer - tWATERS database search; USGS; Data obtain	ed from nearby wells	□N/A			
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significations (measured from the ordinary high-water mark).	int watercourse or lakebed. sinkhole, or playa lake	☐Yes ☐No			
- Topographic map, Visual inspection (certification) of the proposed site		гл., гл.,			
Within 300 feet from a permanent residence, school, hospital, institution, or church in ea - Visual inspection (certification) of the proposed site: Aerial photo, satellite image	ustence at the time of initial application.	Yes No			
· · ·	Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal fee of any other fresh water well or spring, in existence at the time of the initial application				
Within incorporated municipal boundaries or within a defined municipal fresh water well pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtain	·	Yes No			
Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map, Topographic map: Visual inspe	. ,	Yes No			
Within the area overlying a subsurface mine.	, , ,	Yes No			
- Written confirantion or verification or map from the NM EMNRD-Mining and Mi	neral Division				
Within an unstable area. - Engineering measures incorporated into the design, NM Bureau of Geology & Mir Topographic map	neral Resources; USGS, NM Geological Society.	∐Yes ∐No			
Within a 100-year floodplain FEMA map		Yes No			
On-Site Closure Plan Checklist: (19 15.17.13 NMAC) Instructions: Each of by a check mark in the box, that the documents are attached.	of the following items must bee attached to the clo	sure plan. Please indicate,			
Siting Criteria Compliance Demonstrations - based upon the appropriat	e requirements of 19.15.17.10 NMAC	1			
Proof of Surface Owner Notice - based upon the appropriate requireme	nts of Subsection F of 19.15.17.13 NMAC				
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC					
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC					
X Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC					
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC					
X Disposal Facility Name and Permit Number (for liquids, drilling fluids		s cannot be achieved)			
Soil Cover Design - based upon the appropriate requirements of Subsec	_				
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC					
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15.17.13 NMAC					

Page 4 of 5

Form C-144 Oil Conservation Division

19 Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.
Name (Print): Title:
Signature: Date:
e-mail address Telephone:
OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 2/22/2012 Title: OMD Janee Office OCD Permit Number:
Closure Report (required within 60 days of closure completion): Subsection K of 1915 17 13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed Closure Completion Date: 3/30/2011
Coourt completion Date:
Closure Method: Waste Excavation and Removal On-site Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized. Disposal Facility Name: Disposal Facility Permit Number: Disposal Facility Permit Number: Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations? Yes (If yes, please demonstrate complilane to the items below)
Required for impacted areas which will not be used for future service and operations Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (if applicable) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude: Longitude: NAD 1927 1983
25
Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is ture, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.
Name (Print) Jamie Goody, Title: Regulatory Technician
Signature Date 2/16/12
e-mail address: jamie.l.goodwin@conocophillips.com Telephone: 505-326-9784

ConocoPhillips Company Cavitation Pit for Closed-Loop Locations

Design:

ConocoPhillips Company will use a cavitation pit plan when the surface casing will be pre-set on closed-loop locations. The drill cuttings will be stockpiled on the surface.

Operations and Maintenance:

The cavitation pit will be operated and maintained as follows:

- 1. Only Fresh water and air will be used in the drilling of the surface casing.
- 2. The Cement used will be: Neat Cement with no additives.
- 3. All of the fluids will be removed within 48hrs after drilling.
- 4. A representative five point composite sample will be taken of the drill cuttings, after the setting of the surface casing is complete, using sampling tools and all samples will be tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the testing criteria is not met, all contents will be dug and hauled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	02
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

5. The NMOCD will be notified via email of the test results of the cavitation surface as follows:

Components	Tests Method	Limit (mg/Kg)	Results
Benzene	EPA SW-846 8021B or 8260B	0.2	ND
BTEX	EPA SW-846 8021B or 8260B	50	162
TPH	EPA SW-846 418.1	2500	107
GRO/DRO	EPA SW-846 8015M	500	ND
Chlorides	EPA 300.1	500	20

Closure Plan:

- The NMOCD will be notified of the sample results and the intent to start the closure process 3-7 days prior to the drill cuttings being transported, moved, or distributed on location.
- 2. In the event the criteria are not met, all solids and liquids will be removed and disposed of at Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B).
- 3. Testing results will be submitted with the Closure Report of the well locations Closed-Loop Permit on Form C-144.

ConocoPhillips is aware that approval of this plan does not relieve ConocoPhillips of liability should operations result in pollution of surface water, ground water, or the environment. Nor does approval relieve ConocoPhillips of its responsibility to comply with any other applicable governmental authority's rules and regulations.



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	ConocoPhillips	Project#:	96052-1706
Sample ID:	CL Preset Cuttings	. Date Reported:	03-31-11
Laboratory Number:	57753	Date Sampled:	03-30-11
Chain of Custody No:	9540	Date Received:	03-30-11
Sample Matrix:	Soil	Date Extracted:	03-30-11
Preservative:	Cool	Date Analyzed:	03-31-11
Condition:	Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)	
Gasoline Range (C5 - C10)	ND	0.2	
Diesel Range (C10 - C28)	ND	0.1	
Total Petroleum Hydrocarbons	ND		

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

San Juan 29-6 #61M

Analyst

Review

Ph (505) 632-0615 Fr (800) 362-1879 Fx (505) 632-1865 lab@envirotech-inc.com envirotech-inc.com



EPA Method 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Quality Assurance Report

Client:	QA/QC		Project #:		N/A
Sample ID:	03-31-11 QA/0	C	Date Reported:		03-31-11
Laboratory Number:	57736		Date Sampled:		N/A
Sample Matrix:	Methylene Chlori	de	Date Received:		N/A
Preservative:	N/A		Date Analyzed:		03-31-11
Condition:	N/A		Analysis Reques	sted:	TPH
	I-Cal Date	I-Cal RF:	C-Cal RF:	% Difference	Accept Range
Gasoline Range C5 - C10	03-31-11	9.9960E+002	1.0000E+003	0.04%	0 - 15%
Diesel Range C10 - C28	03-31-11	9.9960E+002	1.0000E+003	0.04%	0 - 15%
Blank Conc. (mg/L - mg/K	g)	Concentration		Detection Limit	
Gasoline Range C5 - C10	· · · · · · · · · · · · · · · · · · ·	ND		0.2	•
Diesel Range C10 - C28		ND		0.1	
Duplicate Conc. (mg/Kg)	Sample	Duplicate	% Différence	Accept Range	, ,
Gasoline Range C5 - C10	ND	ND	0.0%	0 - 30%	•
Diesel Range C10 - C28	ND	ND	0.0%	0 - 30%	
Spike Conc. (mg/Kg)	Sample	Spike Added	Spike Result	% Recovery	- Accept. Range
Gasoline Range C5 - C10	ND	250	202	80.8%	75 - 125%
Diesel Range C10 - C28	ND	250	262	105%	75 - 125%

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

QA/QC for Samples 57736, 57745, 57747-57753

Revie

5796 US Highway 64, Farmington, NM 87401

Ph (505) 632-0615 Fr (800) 362-1879 Fx (505) 632-1865 lab@envirotech-inc.com envirotech-inc.com



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	ConocoPhillips	Project #:	96052-1706
Sample ID:	CL Preset Cuttings	Date Reported:	03-31-11
Laboratory Number:	57753	Date Sampled:	03-30-11
Chain of Custody:	9540	Date Received:	03-30-11
Sample Matrix:	Soil	Date Analyzed:	03-30-11
Preservative:	Cool	Date Extracted:	03-30-11
Condition:	Intact	Analysis Requested:	BTEX
		Dilution:	10

	Dilduon:	
Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	(ND)	0.9
Toluene	2.5	1.0
Ethylbenzene	7.9	1.0
p,m-Xylene	132	1.2
o-Xylene	19.4	0.9
Total BTFX	162	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	111 %
	1,4-difluorobenzene	113 %
	Bromochlorobenzene	110 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

San Juan 29-6 #61M

Analyst

Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A		Project #:		N/A
Sample ID:	0330BBLK QA/Q0		Date Reported:		03-31-11
Laboratory Number:	577 36		Date Sampled:		N/A
Sample Matrix:	Soil		Date Received:		N/A
Preservative:	N/A		Date Analyzed:		03-30-11
Condition:	N/A		Analysis:		BTEX
			Dilution:		10
Calibration and	I-Cal RF:	C-Cal RF:	%Diff	Blank	Detect
Detection Limits (ug/L)		P177 - 174 - 176 - NOVA - 1	ge 0 ÷ 15%	Conc	Cimit
Benzene	4.4478E+006	4.4567E+006	0.2%	ND	0.1
Toluene	1.5897E+006	1.5928E+006	0.2%	ND	0.1
Ethylbenzene	1.2398E+006	1.2423E+006	0.2%	ND	0.1
p,m-Xylene	2.7234E+006	2.7288E+006	0.2%	ND	0.1
o-Xylene	1.0122E+006	1.0142E+006	0.2%	ND	0.1

Duplicate Conc. (ug/Kg)	Sample Du	plicate	%Diff.	Accept Range	Detect. Limit
Benzene	ND	ND	0.0%	0 - 30%	0.9
Toluene	ND	ND	0.0%	0 - 30%	1.0
Ethylbenzene	ND	ND	0.0%	0 - 30%	1.0
p,m-Xylene	2.3	2.5	8.7%	0 - 30%	1.2
o-Xylene	3.6	3.5	2.8%	0 - 30%	0.9

Spike Conc. (ug/Kg)	Sample Amo	unt Spiked Spil	ked Sample %	Recovery	Accept Range
Benzene	ND	500	549	110%	39 - 150
Toluene	ND	500	543	109%	46 - 148
Ethylbenzene	ND	500	515	103%	32 - 160
p,m-Xylene	2.3	1000	1,060	106%	46 - 148
o-Xylene	3.6	500	521	103%	46 - 148

ND - Parameter not detected at the stated detection limit.

Dilution: Spike and spiked sample concentration represent a dilution proportional to sample dilution.

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 57736, 57745-57753

Review



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:	ConocoPhillips	Project #:	96052-1706
Sample ID:	CL Preset Cuttings	Date Reported:	03/31/11
Laboratory Number:	57753	Date Sampled:	03/30/11
Chain of Custody No:	9540	Date Received:	03/30/11
Sample Matrix:	Soil	Date Extracted:	03/31/11
Preservative:	Cool	Date Analyzed:	03/31/11
Condition:	Intact	Analysis Needed:	TPH-418.1

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons



59.9

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments: San Juan 29-6 #61M

Review

Ph (505)632-0615 Fr (800) 362-1879 Fx (505) 632-1865 lab@envirotech-inc.com envirotech-inc.com



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS QUALITY ASSURANCE REPORT

Client:	QA/QC	Project #:	N/A
Sample ID:	· QA/QC	Date Reported:	03/31/11
Laboratory Number:	03-31-TPH.QA/QC 57753	Date Sampled:	N/A
Sample Matrix:	Freon-113	Date Analyzed:	03/31/11
Preservative:	N/A	Date Extracted:	03/31/11
Condition:	N/A	Analysis Needed:	TPH

Calibration	I-Cal Date	C-Cal Date				Accept Range
	03/01/11	03/31/11	1,660	1,670	0.6%	+/- 10%

Blank Conc. (mg/Kg)	Concentration	Detection Limit	
TPH	ND	59.9	

Duplicate Conc. (mg/Kg)	Sample	Duplicate	% Difference	Accept. Range
TPH	107	127	18.7%	+/- 30%

Spike Conc. (mg/Kg)	Sample	Spike Added	Spike Result	% Recovery	Accept Range
TPH	107	2,000	1,860	88.3%	80 - 120%

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis of Water

and Waste, USEPA Storet No. 4551, 1978.

Comments:

QA/QC for Samples 57745, 57747-57753



Chloride

Client: ConocoPhillips Project #: 96052-1706 Sample ID: **CL Preset Cuttings** Date Reported: 03/31/11 Lab ID#: 57753 Date Sampled: 03/30/11 Sample Matrix: Soil Date Received: 03/30/11 Preservative: Cool Date Analyzed: 03/31/11 Condition: Intact Chain of Custody: 9540

Parameter

Concentration (mg/Kg)

Total Chloride

20

Reference:

U.S.E.P.A., 4500B, "Methods for Chemical Analysis of Water and Wastes", 1983. Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

San Juan 29-6 #61M

Analyst

Review