

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.	30-043-21117
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No. LG-3925	
7. Lease Name or Unit Agreement Name Lybrook H36-2307	
8. Well Number 01H	
9. OGRID Number 282327	
10. Pool name or Wildcat Lybrook Gallup	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 7265 GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐
2. Name of Operator
Encana Oil & Gas (USA) Inc.
3. Address of Operator
370 17th Street, Suite 1700 Denver, CO 80202
4. Well Location
SHL: Unit Letter: H 1550 feet from the NORTH line and 280 feet from the EAST line
BHL: Unit Letter: E 1550 feet from the NORTH line and 330 feet from the WEST line
Section 36 Township 23N Range 7W NMPM Sandoval County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Utilized synthetic oil-based mud system., kicked off 4,374' lateral at 5057' TVD/MD KOP on 01/16/12. Set production string on 02/02/12 and 02/03/12. Installed external swellable casing packers on 02/03/12.

Lateral hole diameter: 7.875", production string diameter: 5.5", production string weight and grade 17 ppf I/L80 LTC. Depth of 7.875" hole from 4452' to 9985' MD. Casing shoe set at 9952' MD and float collar set at 9932' MD. Production liner set from 4552' to 9952' MD.

DATE TO REACHED?

Set 18 external swellable casing packers for isolation of production string at: (1) 9701' (2) 9423' (3) 9147' (4) 8869' (5) 8591' (6) 8313' (7) 8035' (8) 7758' (9) 7480' (10) 7246' (11) 7013' (12) 6779' (13) 6547' (14) 6314' (15) 6079' (16) 5845' (17) 5612' (18) 4671'.

Rig released 02/05/12. *AV*

RCVD FEB 17 '12
OIL CONS. DIV.

Spud Date: 12/08/11

Rig Release Date: 02/05/12

DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Brenda R. Linster* TITLE Regulatory Advisor
Type or print name: Brenda R. Linster E-mail address: brenda.linster@encana.com

DATE 02/15/12
PHONE: 720-876-3989

For State Use Only

APPROVED BY: *Brd Bell*
Conditions of Approval (if any):

Deputy Oil & Gas Inspector,
District #3

DATE 2-22-12

AV