

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

ConocoPhillips

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Surface: Unit E (SW/NW), 2020' FNL & 750' FWL, Section 24, T32N, R12W, NMPM

Bottom: Unit L (NW/SW), 2110' FSL & 760' FWL, Section 24, T32N, R12W, NMPM

RECEIVED

FEB 28 2012

Bureau of Land Management
Farmington Field Office

5. Lease Number
SF-078147
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
RCVD MAR 1 '12
OIL CONS. DIV.
DIST. 3
8. Well Name & Number
MOORE LS 5B
9. API Well No.
30-045-35266
10. Field and Pool
BLANCO MV / BASIN DK
11. County and State
San Juan, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other - Casing Report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

RCVD MAR 1 '12

☐ Final Abandonment

☐ Plugging

☐ Non-Routine Fracturing

OIL CONS. DIV.

☐ Casing Repair

☐ Water Shut off

DIST. 3

☐ Altering Casing

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

12/17/11 MIRU AWS 730. NU BOPE. PT csg to 600#/30min @ 17:00hrs on 12/18/11 Test - OK. PU & TIH w/ 8 3/4" bit. Tagged @ 275' & DO cmt to 324'. Drilled ahead to 5288' - Inter TD reached 12/24/11. Circ. hole & RIH w/ 125jts, 7", 23#, J-55 LT & C csg set @ 5271', w/ ST @ 2495'. 1st Stage: Pre-flushed w/ 10bbls GW, 2bbls FW. Pumped scavenger w/ 19sx(57cf-10bbls=3.02yld) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS Lead w/ 290sx(618cf-110bbls=2.13yld) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS. Tail w/ 121sx(167cf-30bbls=1.38yld) Type III cmt w/ 1% CaCl, 0.25 pps celloflake, & 0.2% FL-52. Dropped plug & displaced w/ 120bbls FW. Shut down. Bumped plug @ 05:59hrs 12/27/11. Circ. 50bbls cmt to surface WOC 2nd Stage: Preflushed w/ 10bbls of FW, w/ 10bbls of GW & 10bbls of FW. Pumped scavenger w/ 19sx(57cf-10bbls=3.02yld) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS Lead w/ 411sx(875cf-156bbls=2.13yld) Premium Lite w/ 3% CaCl, 0.25 pps celloflake, 5pps LCM-1, 0.4% FL-52, 8% bentonite, & 0.4% SMS Shut dwn Dropped plug & displaced w/ 98bbls of FW. Plug down @ 12.47hrs. Circ. 50bbls cmt to surface. WOC. TIH, & tagged & DO ST @ 2495'. PT 7" csg to 1500#/30min @ 00:30hrs on 12/28/11. Test - OK Drilled w/ 6 1/4", tagged @ 5220' & DO cmt to 5271'. TD reached @ 7929' on 12/29/11. Circ. hole & RIH w/ 184jts, L-80, 4 1/2", 11.6#, LT & C csg set @ 7925'. RU to cmt Pre-flushed w/ 10bbls GW, 2bbls of FW Pumped scavenger 9sx(28cf-5bbls=3.10yld) Premium lite HS FM, 0.25pps celloflake, 0.3% CD-32, 6.25pps LCM-1, & 1%FL-52. Tail w/232sx(459cf-82bbls=1.98yld) Premium lite HS FM, 0.25 pps celloflake 0.3% CD-32, 6.25pps LCM-1 & 1% FL-52 Dropped plug & displaced w/ 123bbls-FW Bumped plug. Plug down @ 20.15hrs on 12/30/11. RD cmt. WOC. ND BOPE. NU WH RD RR @ 02:30hrs on 12/31/11.

PT will be conducted by Completion Rig. Results & TOC will appear on next report.

14. I hereby certify that the foregoing is true and correct.

Signed

Marie E. Jaramillo

Title Staff Regulatory Tech.

Date 01/03/12

(This space for Federal or State Office use)

APPROVED BY

Title

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOCD

