District 7
1625 N French Dr , Hobbs, NM 88240
District II
1301 W Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S St Francis Dr , Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office

The state of the s
Proposed Alternative Method Permit or Closure Plan Application Type of action. Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Modification to an existing permit Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances
OperatorMcElvain Oil & Gas Properties, IncOGRID #22044
Pit: Subsection F or G of 19.15 17.11 NMAC RCVD SEP 12 '08 Temporary.
Closed-loop System: Subsection H of 19 15 17 11 NMAC Type of Operation P&A Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other Lined Unlined Liner type: Thickness mil LLDPE HDPE PVC Other Liner Seams Welded Factory Other
Below-grade tank: Subsection I of 19 15 17 11 NMAC Volume95

Submittal of an exception request is required Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval

Fencing: Subsection D of 19 15.17 11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate Please specify4' field fence w/top rail	hospital,						
Netting: Subsection E of 19.15.17 11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting OtherExpanded Metal Monthly inspections (If netting or screening is not physically feasible)							
Signs: Subsection C of 19.15 17 11 NMAC ☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers ☐ Signed in compliance with 19.15.3 103 NMAC							
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required Please refer to 19 15 17 NMAC for guidance Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau consideration of approval Exception(s) Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval	office for						
Siting Criteria (regarding permitting): 19 15 17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of a Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying above-grade tanks associated with a closed-loop system.	priate district pproval.						
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☒ No						
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map, Visual inspection (certification) of the proposed site	☐ Yes ☑ No						
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application (Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo, Satellite image	☐ Yes ☐ No ☑ NA						
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits) - Visual inspection (certification) of the proposed site, Aerial photo, Satellite image	☐ Yes ☐ No ☑ NA						
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application - NM Office of the State Engineer - iWATERS database search, Visual inspection (certification) of the proposed site	☐ Yes ⊠ No						
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality, Written approval obtained from the municipality	☐ Yes ☑ No						
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site	☐ Yes ☑ No						
Within the area overlying a subsurface mine - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☑ No						
Within an unstable area. - Engineering measures incorporated into the design, NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society; Topographic map	☐ Yes ☑ No						
Within a 100-year floodplain. - FEMA map							

Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19 15 17 9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19 15 17 9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19 15.17 9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15.17 10 NMAC Design Plan - based upon the appropriate requirements of 19 15 17.11 NMAC
 ☑ Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17.12 NMAC ☑ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15 17 9 NMAC and 19 15.17 13 NMAC
Previously Approved Design (attach copy of design) API Number: or Permit Number:
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19 15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19 15 17 9 Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19 15 17 10 NMAC Design Plan - based upon the appropriate requirements of 19 15.17 11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15.17 9 NMAC
and 19.15 17 13 NMAC
Previously Approved Design (attach copy of design) API Number:
Previously Approved Operating and Maintenance Plan API Number(Applies only to closed-loop system that use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)
13
Permanent Pits Permit Application Checklist: Subsection B of 19 15 17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are
attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19 15.17.9 NMAC
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC
☐ Climatological Factors Assessment ☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19 15 17 11 NMAC
Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC
Leak Detection Design - based upon the appropriate requirements of 19.15 17 11 NMAC
☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15 17 11 NMAC ☐ Quality Control/Quality Assurance Construction and Installation Plan
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15.17.12 NMAC
Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19 15 17.11 NMAC
 Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan
Oil Field Waste Stream Characterization
☐ Monitoring and Inspection Plan ☐ Erosion Control Plan
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17 9 NMAC and 19 15 17 13 NMAC
Proposed Closure: 19 15 17.13 NMAC
Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.
Type Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only)
On-site Closure Method (Only for temporary pits and closed-loop systems)
☐ In-place Burial ☐ On-site Trench Burial ☐ Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)
15
Waste Excavation and Removal Closure Plan Checklist: (19 15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.
Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
☐ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) ☐ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15 17.13 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15 17 13 NMAC

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19 15 17.13.1 Instructions: Please indentify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if the facilities are required.	
facilities are required. Disposal Facility Name Disposal Facility Permit Number	
Disposal Facility Name Disposal Facility Permit Number	
Will any of the proposed closed-loop system operations and associated activities occur on or in areas that will not be used for future ser Yes (If yes, please provide the information below) No	
Required for impacted areas which will not be used for future service and operations: Soil Backfill and Cover Design Specifications based upon the appropriate requirements of Subsection H of 19.15 17 13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17 13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC	c
Siting Criteria (regarding on-site closure methods only): 19.15.17 10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sout provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate dist considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Just demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.	rict office or may be
Ground water is less than 50 feet below the bottom of the buried waste - NM Office of the State Engineer - IWATERS database search, USGS, Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search, USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search, USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map, Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. - Visual inspection (certification) of the proposed site, Aerial photo; Satellite image	☐ Yes ☐ No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	Yes No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality, Written approval obtained from the municipality	☐ Yes ☐ No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map, Topographic map, Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within the area overlying a subsurface mine - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS, NM Geological Society, Topographic map	☐ Yes ☐ No
Within a 100-year floodplain - FEMA map	☐ Yes ☐ No
On-Site Closure Plan Checklist: (19 15 17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15 17.11 NMAC Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19 Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards canr Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC	15 17 11 NMAC

Operator Application Certification:
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.
Name (Print): Deborah K Powell Title: _Engineering Tech Supervisor
Signature Date: 9-11-08
e-mail address:DebbyP@McElvain.com
20. OCD Approval: Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment)
OCD Representative Signature: Approval Date: 3/28/2012
Title: OCD Permit Number:
Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.
Closure Completion Date:
Closure Method: Waste Excavation and Removal On-Site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please indentify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than
two facilities were utilized. Disposal Facility Name:
Disposal Facility Name Disposal Facility Permit Number: Disposal Facility Permit Number:
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations? Yes (If yes, please demonstrate compliance to the items below)
Required for impacted areas which will not be used for future service and operations: Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique
Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-site closure) Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location. Latitude Longitude NAD: 1927 1983
25 Operator Closure Certification:
I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan
Name (Print) Title
Signature: Date
e-mail address: Telephone

- District I PO Box 1980, Hobbs, NM 88241-1980

Oistrict II PO Drawer DD, Artesia, NM 88211-0719

District III 1000 Rio Brazos Rd., Aztec, NM 87410

District IV PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico Energy, Munerals & Natural Resources Department


OIL CONSERVATION DIVISION - PO Box 2088 Santa Fe. NM 87504-2088

Form C-102 Revised February 21, 1994 Instructions on back Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

TAD	I Number		*Pool		T	SHEADE DEDI	¹Pool Name							
30-045		-122		200	FULCHER KUTZ PICTURED CLIFFS									
Property Code 35260			Property Name "Well Number WILDWOOD 1											
'0GRID 2204			"Operator Name" "Elevation McELVAIN OIL & GAS PROPERTIES 5517"											
				1	O Surface	Location								
UL or lot no. H	Section 5	Yournehite 29N	Youreship Range Lot John Feat from the Hortr/South line Feet from the East/Ne						AST ARRIE					
		11 6	Bottom	Hole L	ocation I	f Different	From Surf	ace						
UL or lot no.	Section	Township	Ranga	Lat Ian	Feat from the	North/South line	Feet from the	East/Was	it line	County				
** Deducated Acres 159.94 Acres - NE/4 *** Consolidation Code *** Order No.														
NO ALLOW	NABLE W					ON UNTIL ALL EEN APPROVED			EN CON	SOLIDATED				



New Mexico Office of the State Engineer POD Reports and Downloads

	Towr	nship:	29N Range: 13W	Sections:	4,5,6	6,7,8,9	
	NAD27	X:	Y:	Zone:		•	Search Radius:
County:		-	Basin: SJ(San Juan)	-		Num	ber: Suffix:
Owner Na	ame: (Fir	st)	(Last)			0	Non-Domestic
(COMP)	OD / Surfac	e Data	Report Avg				
			Clear Form	iWATERS	Mer	nu _{**}	<u>{Help</u> s

WATER COLUMN REPORT 08/25/2008

(dr	ıarter	s are	e 1=1	W	2=	NE 3	3=SW 4=SE))				
(qu	ıarter	s are	e big	gge	est	to	smallest))		Depth	Depth	Water (in
POD Number	Tws	Rng	Sec	Ø	đ	Œ.	Zone	x	Y	Well	Water	Column
SJ 02328	_ 29N	13W	04	3	3					40	10	30
SJ 02899	29N	13W	04	3	3	3				45		
SJ 02730	29N	13W	04	3	3	3				40	16	24
SJ 02912	29N	13W	04	3	3	3				50		
SJ 03203	29N	13W	05	2	4	4				59	20	39
SJ 02728	29N	13W	05	4	2	4				52	12	40
SJ 03234	29N	13W	05	4	2	4				60	20	40
SJ 01444	29N	13W	05	4	4	2				55	10	45
SJ 02931	29N	13W	06	4	3	2				50	12	38
SJ 02134	29N	13W	80	2	2					33	4	29
SJ 03346	29N	13W	80	4	3	4				80	30	50
SJ 01333	29N	13W	09	1	1					38	20	18
SJ 01038	_ 29N	13W	09	1	1					42	10	32
SJ 01487	29N	13W	09	1	1					26	10	16
SJ 01556	29N	13W	09	1	1	3				27	10	17
SJ 03457	29N	13W	09	1	1	3				29	9	20
SJ 02386	29N	13W	09	1	1	4				30	10	20
SJ 02594	29N	13W	09	1	1	4				44	17	27
SJ 01779	_ 29N	13W	09	1	4					31	11	20
SJ 02209	29N	13W	09	1	4	1						
SJ 00512	29N	13W	09	1	4	1				41	15	26
SJ 00957	_ 29N	13W	09	4	3					74	20	54
SJ 00894	_ 29N	13W	09	4	3	1				30	15	15
SJ 02712	_ 29N	13W	09	4	3	3				90	50	40
SJ 02367	29N	13W	09	4	3	4				50	20	30

Record Count: 25

New Mexico Office of the State Engineer POD Reports and Downloads

Range: 13W Township: 30N Sections: 31,32,33 Y: NAD27, X: Search Radius: Zone: Basin: SJ(San Juan) County: Number: Suffix: Owner Name: (First) (Last) Non-Domestic Domestic All POD / Surface Data Report Avg Depth to Water Report Water Column Report Help Clear Form iWATERS Menu

WATER COLUMN REPORT 08/25/2008


(quarters are 1=NW 2=NE 3=SW 4=SE)

	(quarter	s are b	iggest to	smalles	t)		Depth	Depth	Water (in
POD Number	Tws	Rng Sec	gqq	Zone	x	Y	Well	Water	Column
SJ 01150	30N	13W 32	1 4				37	16	21
SJ 00156	30N	13W 32	3				44	18	26
SJ 00217	30N	13W 32	3				40	10	30
SJ 01359	30N	13W 32	3 1				25	10	15

Record Count: 4


San Juan Mines, Mills And Quarries Web Map


Mines, Mi	lls & Quarries Commodity Groups
Δ	Aggregate & Stone Mines
♦	Coal Mines
*	Industrial Minerals Mines
♥	Industrial Minerals Mills
Ø	Metal Mines and Mill Concentrate
	Potash Mines & Refineries
3	Smelters & Refinery Ops.
*	Uranium Minas


















Legend

McElvain Well & 200' Radius

McElvain Well & 300' Radius

McElvain Well & 500' Radius


Source: USGS 1:24,000 Scale Topographic Map Series San Juan Basin New Mexico Township 29N 13W Section 5




Aerial Source: NM Resource Geographic Information System Program made available by the University of New Mexico and the State of New Mexico 2005-2006 vintage Digital Orthophoto Quarter-Quadrangles were derived from the New Mexico Statewide Orthophotography Project. Source imagery flown at 35,000' above average ground.

San Juan Basin New Mexico Township 29N 13W Section 5

REMOSENO	107	71.90	Said Indiana	80-11-4	41	T	Π	8
0-0510 GW072110		1 100		DOGO HOUSE	4-1	+-		1
~~~	329			_V4 CDCDD 21 1 CDCDD 2144-1	4 1			1
BACKIES	91/L				]			
		GBL DOUBL			]			
2000 200 12	STATE OFFICE	NASKA OL BESON D HOLDSCOMUSE V BROWSELVAN IN JHE DHOMA	MOUL IS O	CONTRACTOR		-		
ara Arrestana	3 83VA181	2 1890sb	stee 223	30.E	1	- [		
		00		d				B
					щ		ш	
ı								





## **Siting Criteria Compliance Demonstrations**

Wildwood #1 well is not located in an unstable area. The location is not over a mine and is not on the side of a hill. The location of the excavated pit material is not located within 300' of any continuously flowing watercourse or 200' from any other water course.

# McElvain Oil & Gas Properties, Inc. San Juan Basin Below Grade Tank Design and Construction

In accordance with Rule 19.15.17 NMAC the following describes the as-built construction of the Below Grade Tank on the McElvain Oil & Gas Properties, Inc (MOG) Wildwood #1 well located in the SWNE of Sec 34, T29N, 13W.

### **As-built Installation:**

- 1. The existing tank pit consists of an approximate 15 foot by 15 foot by 2 foot metal shored hole into which a 12 foot by 5 foot single walled, double bottom, steel, 95 bbl tank with leak detection is placed.
- 2. The tank walls are open for visual inspection to identify the occurrence of leaks.
- 3. The below grade tank has an expanded metal cover.
- 4. The tank pit is surrounded by a 30ft X 30ft X 2ft berm that is contained within a 50 ft X 140 ft berm that encloses the tank battery to prevent overflow or surface water run-on.
- 5. A general location sign is displayed on site.
- 6. The pit tank is fenced with 4 foot field fence with a top rail.

# McElvain Oil & Gas Properties, Inc. San Juan Basin Below Grade Tank Maintenance and Operating Plan

In accordance with Rule 19.15.17 NMAC the following describes the below grade tank operation and maintenance plan for the McElvain Oil & Gas Properties, Inc (MOG) on the Wildwood #1 well located in the SWNE of Sec 5, T29N, 13W.

#### General Plan:

- 1. MOG shall operate and maintain the below grade tank to contain liquids and solids and prevent contamination of fresh water to protect the public health and environment.
- 2. MOG shall not allow a below grade tank to overflow or allow surface water run-on to enter the below grade tank.
- 3. MOG shall continuously remove any visible or measurable layer of oil from the fluid surface of a below grade tank in an effort to prevent significant accumulation of oil over time.
- 4. MOG shall inspect the below grade tank monthly and maintain a written record of each inspection for five years.
- 5. MOG shall maintain adequate freeboard to prevent overtopping of the below grade tank.

# McElvain Oil & Gas Properties, Inc. San Juan Basin Closure Plan

In accordance with Rule 19.15.17.1 NMAC the following procedure describes the closure plan for the McElvain Oil & Gas Properties, Inc (MOG) below grade tank on the Wildwood #1 well located in the SWNE of Sec 5, T29N, 13W

### **Closure Requirements:**

- 1. MOG shall close the below grade tank within the time periods provided in 19.15.17.13 NMAC or by an earlier date that the division requires because of imminent danger to fresh water, public health, or the environment.
- 2. MOG shall close an existing below grade tank that does not meet the requirements of Paragraph (1) through (4) of Subsection I of 19.15.17.11 NMAC or is not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC within five years after June 16, 2008 if not retrofitted to comply with Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC.
- 3. MOG shall close a permitted below grade tank within 60 days of cessation of the below ground tank's operation or as required by the transitional provisions of Subsection B of 19.15.17.17 NMAC in accordance with a closure plan that the appropriate division district office approves. The closure report will be filed on C-144.
- 4. All liquids will be removed from the temporary permit prior to closure and the liquids disposed of in a division approved facility.
- 5. MOG shall remove the below grade tank and dispose of it in a division approved facility or recycle, reuse, or reclaim it in a manner that the appropriate division district office approves.
- 6. MOG will remove any on-site equipment associated with the below grade tank unless the equipment is required for some other purpose.
- 7. MOG shall test the soils beneath the below grade tank to determine whether a release has occurred. MOG shall collect a five point composite sample and individual grab samples from any area that is wet, discolored, or showing other evidence of a release. The samples will be analyzed for BTEX, TPH, and chlorides to demonstrate that the benzene concentration as determined by EPA SW-846 methods 8021B or 8260B or other EPA method that the division approves, does not exceed 50 mg/kg; the TPH concentration as determined by EPA method 418.1 or other EPA method that the division approves does not exceed 100 mg/kg; and the chloride concentration as determined by EPA

- method 300.1 or other EPA method that the division approves does not exceed 250 mg/kg or the background concentration, whichever is greater. MOG shall notify the division of its results on form C-141.
- 8. If MOG or the division determines that a release has occurred, then MOG shall comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC as appropriate.
- 9. If contamination is confirmed by field sampling. MOG will follow the Guidelines For Remediation Of Leaks, Spills, and Releases NMOCD August 1993 when remediating identified contaminants.
- 10. If the sampling program demonstrates that a release has not occurred or that any release does not exceed the concentrations specified in Paragraph (4) of Subsection E of 19.15.17.13 NMAC, then MOG shall backfill the excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; re-contour, and re-vegetate the site.
- 11. Notice of closure will be given to the Aztec Division office between 72 hours and one week of closure via email or verbally. The notification of closure will include the following:
  - · Operator's name
  - · Location by Unit Letter, Section Township, and Range.
  - · Well name and API number
- 12. All closure activities will include proper documentation and be available for review upon request and will be submitted to OCD within 60 days of closure of the blow grade tank. The closure report will be filed on C-144 and incorporate the following:
  - · Details on capping and covering where applicable
  - · Inspection reports
  - · Sampling results
- 13. The site will be re-contoured to match the surrounding area. Natural drainages will be unimpeded and erosion control will be utilized where necessary.
- 14. MOG shall seed the disturbed areas the first growing season with a division approved seed mixture after pit closure. Seeding will be accomplished by drilling on the contour whenever possible or by other division approved methods. Repeat seeding or planting will be continued until successful vegetative growth occurs.
- 15. A minimum of four feet of cover shall be achieved and the cover shall include one foot of suitable material to establish vegetation at the site, or the thickness of the topsoil native to the area, whichever is greater.

16. The surface owner shall be notified of MOG's closing of the below grade tank as per the approved closure plan using certified mail with return receipt requested.