District I.
1625 N French Dr , Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S St Francis Dr , Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

District Office.			
Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application			
Type of action: Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Modification to an existing permit Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method			
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request			
lease be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the nvironment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.			
Operator: Questar Exploration and Production Company OGRID #: 23846			
Address. 1050 17 th Street, Suite 500, Denver, Colorado 80265			
Facility or well name: Lindrith #110E			
API Number. 30-039-23134 OCD Permit Number			
U/L or Qtr/Qtr C Section 10 Township 26N Range 7W County. Rio Arrıba			
Center of Proposed Design. Latitude <u>36.50529 North</u> Longitude <u>107.56560 West</u> NAD: ⊠1927 ☐ 1983			
Surface Owner: ☑ Federal ☐ State ☐ Private ☐ Tribal Trust or Indian Allotment			
2.			
☐ <u>Pit</u> : Subsection F or G of 19.15.17.11 NMAC			
Temporary:			
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A			
☐ Lined ☐ Unlined Liner type: Thicknessmul ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other			
☐ String-Reinforced			
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D			
3 Closed-loop System: Subsection H of 19 15.17.11 NMAC			
Type of Operation: DRA Deilling a new well D Westerver or Deilling (Applies to activities which require prior approved of a permit or notice of			
intent)			
☐ Drying Pad ☐ Above Ground Steel Tanks ☐ Haul-off Bins ☐ Other			
☐ Lined ☐ Unlined Liner type. Thickness mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other			
Type of Operation. F&A Diffing a new wen Workover of Diffing (Applies to activities which require prior approval of a perint of notice of intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other Lined Unlined Liner type. Thickness mil LLDPE HDPE PVC Other			
4 Polony grade tonky. Subsection Lef 19.15.17.11 NIMAC.			
Welow-grade tank: Subsection I of 19.15.17.11 NMAC Volume: 53 bbl Type of fluid: Produced water			
Volume: 53 bbl Type of fluid: Produced water			
Tank Construction material: Fiberglass			
Volume: 53 bbl Type of fluid: Produced water Tank Construction material: Fiberglass Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off			
☐ Visible sidewalls and liner ☒ Visible sidewalls only ☐ Other			
Liner type Thicknessmil			
5			

Alternative Method:

Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify Four foot height, wire mesh with T-posts			
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting □ Other □ Monthly inspections (If netting or screening is not physically feasible)			
8. Signs: Subsection C of 19.15.17.11 NMAC ☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers ☐ Signed in compliance with 19.15.3.103 NMAC			
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau consideration of approval Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	office for		
Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accept material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the approoffice or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying above-grade tanks associated with a closed-loop system.	priate district pproval.		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark) - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No		
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No ☐ NA		
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No		
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No		
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	Yes No		
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No		
Within a 100-year floodplain FEMA map	☐ Yes ☐ No		

Temporary Pits, Emergency Pits, and Below-grade Tanks Pelnstructions: Each of the following items must be attached to attached. Hydrogeologic Report (Below-grade Tanks) - based upon Hydrogeologic Data (Temporary and Emergency Pits) - based upon to Siting Criteria Compliance Demonstrations - based upon to Design Plan - based upon the appropriate requirements of Operating and Maintenance Plan - based upon the appropriate Closure Plan (Please complete Boxes 14 through 18, if apparent 19.15.17.13 NMAC Previously Approved Design (attach copy of design)	the application. Please indicate, by a character than the requirements of Paragraph (4) of Subpased upon the requirements of Paragraph (5) the appropriate requirements of 19.15.17.16 (19.15.17.11 NMAC) or the requirements of 19.15.17.12 NMAC opplicable) - based upon the appropriate requirements.	pseck mark in the box, that the documents are osection B of 19.15.17.9 NMAC (2) of Subsection B of 19.15.17.9 NMAC 10 NMAC
Closed-loop Systems Permit Application Attachment Checkl Instructions: Each of the following items must be attached to attached. Geologic and Hydrogeologic Data (only for on-site closur Siting Criteria Compliance Demonstrations (only for on-s Design Plan - based upon the appropriate requirements of Operating and Maintenance Plan - based upon the appropriate Closure Plan (Please complete Boxes 14 through 18, if ap and 19.15.17.13 NMAC	the application. Please indicate, by a charge in based upon the requirements of Paragosite closure) - based upon the appropriate of 19.15.17 11 NMAC priate requirements of 19.15.17.12 NMAC	graph (3) of Subsection B of 19 15.17.9 requirements of 19.15.17 10 NMAC
	API Number.	
Previously Approved Operating and Maintenance Plan A	API Number:	(Applies only to closed-loop system that use
ahove ground steel tanks or haul-off bins and propose to implem	nent waste removal for closure)	
Permanent Pits Permit Application Checklist: Subsection B Instructions: Each of the following items must be attached to a attached. Hydrogeologic Report - based upon the requirements of P Siting Criteria Compliance Demonstrations - based upon to Climatological Factors Assessment Certified Engineering Design Plans - based upon the approphic Dike Protection and Structural Integrity Design - based upon the appropriate requi Liner Specifications and Compatibility Assessment - base Quality Control/Quality Assurance Construction and Instation Operating and Maintenance Plan - based upon the appropriate report Freeboard and Overtopping Prevention Plan - based upon Nuisance or Hazardous Odors, including H ₂ S, Prevention Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan Erosion Control Plan Closure Plan - based upon the appropriate requirements of	Paragraph (1) of Subsection B of 19.15.17. the appropriate requirements of 19.15.17. Tropriate requirements of 19.15.17.11 NMA pon the appropriate requirements of 19.15.17.11 NMAC ed upon the appropriate requirements of 19.15.17.11 NMAC ed upon the appropriate requirements of 19.15.17.12 NMAC at the appropriate requirements of 19.15.17.12 NMAC in the appropriate requirements of 19.15.17.19 NMAC in the appropriate requirements of 1	9.9 NMAC 10 NMAC AC 5.17.11 NMAC 9.15.17.11 NMAC 9.11 NMAC
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 to Type: ☐ Drilling ☐ Workover ☐ Emergency ☐ Cavitation ☐ Alternative Proposed Closure Method: ☐ Waste Excavation and Removal ☐ Waste Removal (Closed-loop sy	n 🗌 P&A 📗 Permanent Pit 🛛 Below	-
☐ On-site Closure Method (Only fo☐ In-place Burial ☐	for temporary pits and closed-loop systems On-site Trench Burial	s) Fe Environmental Bureau for consideration)
Waste Excavation and Removal Closure Plan Checklist: (19. closure plan. Please indicate, by a check mark in the box, that □ Protocols and Procedures - based upon the appropriate req □ Confirmation Sampling Plan (if applicable) - based upon ti □ Disposal Facility Name and Permit Number (for liquids, d □ Soil Backfill and Cover Design Specifications - based upon □ Re-vegetation Plan - based upon the appropriate requirements □ Site Reclamation Plan - based upon the appropriate requirements	the documents are attached. quirements of 19.15.17 13 NMAC the appropriate requirements of Subsection drilling fluids and drill cuttings) on the appropriate requirements of Subsection tents of Subsection I of 19.15.17.13 NMAG	on F of 19.15.17.13 NMAC stion H of 19.15.17.13 NMAC C

16. Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks Instructions: Please indentify the facility or facilities for the disposal of liquids, drilling fluid facilities are required.	s or Haul-off Bins Only: (19 15.17.13.D ds and drill cuttings. Use attachment if m	NMAC) nore than two
Disposal Facility Name: Disposal Fa	acility Permit Number:	
Disposal Facility Name: Disposal Fa	acility Permit Number:	
Will any of the proposed closed-loop system operations and associated activities occur on or in Yes (If yes, please provide the information below) No	areas that will not be used for future serv	ice and operations?
Required for impacted areas which will not be used for future service and operations: Soil Backfill and Cover Design Specifications based upon the appropriate requirement Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.1' Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.1	7.13 NMAC	
17. Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan provided below. Requests regarding changes to certain siting criteria may require administrate considered an exception which must be submitted to the Santa Fe Environmental Bureau off demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance	ative approval from the appropriate distri fice for consideration of approval. Justifi	ict office or may be
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search, USGS; Data obtained from the state of th	om nearby wells	Yes No
Ground water is between 50 and 100 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from	om nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from the buried waste.	om nearby wells	☐ Yes ☐ No ☐ NA
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant water lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	ercourse or lakebed, sinkhole, or playa	Yes No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	e at the time of initial application.	☐ Yes ☐ No
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five howatering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in exist. NM Office of the State Engineer - iWATERS database; Visual inspection (certification)	stence at the time of initial application.	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field cadopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained for		☐ Yes ☐ No
Within 500 feet of a wetland US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection	(certification) of the proposed site	☐ Yes ☐ No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral		Yes No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Society; Topographic map 	Resources; USGS; NM Geological	☐ Yes ☐ No
Within a 100-year floodplain FEMA map		☐ Yes ☐ No
Dn-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection For Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMA Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection For Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings of Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17 Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17	19.15.17.10 NMAC F of 19.15.17.13 NMAC quirements of 19.15.17.11 NMAC pon the appropriate requirements of 19.15 C Subsection F of 19.15.17.13 NMAC or in case on-site closure standards cannot 7.13 NMAC	5.17.11 NMAC
Re-vegetation Plan - based upon the appropriate requirements of Subsection 1 of 19.15.17 Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.		

Operator Application Certification: I hereby certify that the information submitted with this application	n is true, accurate and complete to the best of my knowledge and belief
Name (Print): Sarah Boxley	Title: Permit Agent
Signature: Larah Boyley	Date: 17/17/08
e-mail address Sarah.Boxley@questar.com	Telephone: (303) 672-6916
OCD Approval: Permit Application (including closure plan) OCD Representative Signature: Title:	Closure Plan (only) OCD Conditions (see attachment) Approval Date: 405/2012 OCD Permit Number:
	re plan prior to implementing any closure activities and submitting the closure report. n 60 days of the completion of the closure activities. Please do not complete this
Closure Method: Waste Excavation and Removal On-Site Closure Method If different from approved plan, please explain.	☐ Alternative Closure Method ☐ Waste Removal (Closed-loop systems only)
Instructions: Please indentify the facility or facilities for where the two facilities were utilized. Disposal Facility Name: Disposal Facility Name:	Disposal Facility Permit Number:
Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique	e ana operations.
Closure Report Attachment Checklist: Instructions: Each of the mark in the box, that the documents are attached. Proof of Closure Notice (surface owner and division) Proof of Deed Notice (required for on-site closure) Plot Plan (for on-site closures and temporary pits) Confirmation Sampling Analytical Results (if applicable) Waste Material Sampling Analytical Results (required for on-Disposal Facility Name and Permit Number Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique Site Reclamation (Photo Documentation) On-site Closure Location: Latitude	e following items must be attached to the closure report. Please indicate, by a check site closure) Longitude NAD:
25. Operator Closure Certification:	
I hereby certify that the information and attachments submitted with	this closure report is true, accurate and complete to the best of my knowledge and sure requirements and conditions specified in the approved closure plan.
Name (Print):	
Signature:	Date:
o-mail address:	Telephone

Questar Exploration and Production Company

Lindrith #110E U/L: C, Section 10, T. 26 N., R. 7 W. Rio Arriba County, New Mexico

BELOW-GRADE TANK CLOSURE PLAN

As stipulated in Rule 19.15.17.13 NMAC, the following information adheres to the requirements established in closing below-grade tanks (BGTs) on Questar Exploration and Production Company (QEP) well sites. This plan will address the standard protocols and procedures for closure of BGTs.

QEP proposes to close its existing BGTs that do not meet the requirements of Paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC or are not included in Paragraph (5) of Subsection I of 19.15.17.11 NMAC in accordance with this closure plan and the transitional provisions of Subsection E of 19.15.17.17 NMAC, or within five (5) years after the effective date (June 16, 2008) of 19.15.17 NMAC.

The following outline addresses all requirements for closure of QEP's BGTs:

- 1. Prior notification of QEP's intent to close the BGT will follow 19.15.17.13J (1) and (2).
 - a. QEP will notify the surface owner by certified mail, return receipt requested, of closure plans. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records is sufficient to demonstrate compliance with this requirement.
 - b. Notification will also be given to the division District III office verbally or by other means at least 72 hours, but not more than one (1) week, prior to any closure operation. The notice will include the operator's name and the well's name, number, and API number, in addition to the well's legal description, including the unit letter, section, township, and range.
- 2. QEP will remove liquids and sludge from the BGT prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD's division-approved facility. A list of QEP's approved disposal facilities are below:

Fluid disposal: Key Energy Services
Sunco well #1
U/L=E, SWNW, Section 2, T29N-R12W
San Juan, New Mexico
Permit #NM-01-0009

Basin Disposal Inc.
Basin Disposal well #1
U/L=F, SWNW, Section 3, T29N-R11W
San Juan, New Mexico
Permit #NM-01-0005

Solid disposal: Envirotech Land Farm
Disposal Facility
Section 6, T26N-R10W, County Road #7175
San Juan, New Mexico
Permit #NM-01-0011

- 3. QEP will remove the BGT from the pit and place it at ground level adjacent to the original BGT site.
- 4. QEP will hook up necessary equipment and piping for temporary tank use. At this time, any on-site equipment not necessary to the operation of the tank will be removed from the site.
- 5. QEP will test the soils beneath the original BGT location to determine whether a release has occurred. At a minimum, a five (5) point composite sample will be collected in addition to individual grab samples from areas that are wet, discolored, or showing other evidence of a release. The samples will be analyzed for BTEX, TPH, and chlorides to demonstrate that they do not exceed certain concentrations. The testing methods and closure standards for those constituents are as follows:

Constituents	Testing Method	Closure Standards (mg/Kg)
Benzene	US EPA SW-846 methods 8021B or 8260B	0.2
total BTEX	US EPA SW-846 methods 8021B or 8260B	50
ТРН	US EPA method 418.1	100
Chlorides	US EPA method 300.1	250 or background

Notes: mg/Kg = milligram per kilogram; BTEX = benzene, toluene, ethylbenzene, and total xylenes; TPH = total petroleum hydrocarbons. Other EPA methods that the division approves may be applied to all constituents listed. The Chlorides closure standards will be determined by whichever concentration level is greatest.

6. QEP will notify the division District III office of the soil test results on Form C-141. It is understood that the NMOCD may require additional delineation upon review of the results.

- 7. If it is determined that a release has occurred, then QEP will comply with 19.15.3.116 NMAC and 19.15.1.19 NMAC, as appropriate.
- 8. If the confirmation sampling demonstrates that a release has not occurred or that any release does not exceed the concentrations specified above, then QEP will backfill the excavation with compacted, non-waste containing, earthen material; construct a division-prescribed soil cover; re-contour the site; and move the fiberglass tank onto the newly-backfilled and compacted site. The division-prescribed soil cover, re-contouring, and revegetation requirements shall comply with Subsections G, H, and I of 19.15.17.13 NMAC.
- 9. Reclamation will follow 19.15.17.13G (1) and (2).
 - a. The BGT location and all areas associated with the BGT, including associated access roads, if applicable, will be reclaimed to a safe and stable condition that blends with the surrounding undisturbed area. It is understood that QEP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Subsection H of 19.15.17.13 NMAC and re-contour the location and associated areas to a contour that approximates the original contour and blends with the surrounding topography.
 - b. Re-vegetation will not be completed at the time the BGT pit is reclaimed but will instead be applied for as part of the P&A process when the well is plugged and abandoned.
- 10. Soil cover will follow 19.15.17.13H (1) and (3).
 - a. The soil cover for closures where the BGT has been removed or contaminated soil has been remediated to the NMOCD's satisfaction will consist of the background thickness of topsoil or one (1) foot of suitable material to establish vegetation at the site, whichever is greater.
 - b. The soil cover will be constructed to the site's existing grade, and all possible efforts will be conducted to prevent ponding of water and erosion of the cover material.
- 11. Within 60 days of closure completion, QEP will submit a closure report on NMOCD's Form C-144, with necessary attachments to document all closure activities, including sampling results; information required by 19.15.17 NMAC; and details on backfilling, capping, and covering, where applicable. QEP will certify that all information in the report and attachments is correct and that QEP has complied with all applicable closure requirements and conditions specified in the approved closure plan.