

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-045-26726
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. V-1729
7. Lease Name or Unit Agreement Name Bryan Simpson
8. Well No. #1
9. Pool name or Wildcat Bisti Lower Gallup

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator

Elm Ridge Resources, Inc.

3. Address of Operator

PO Box 156 Bloomfield, NM 87413

4. Well Location

Unit Letter D : 330' Feet From The North Line and 330 Feet From The West Line  
Section 32 Township 25N Range 11W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
6565 GLE

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent date, including estimated date of starting any proposed work) SEE RULE 1103

Elm Ridge Exploration Co LLC has plugged and abandoned the above well as of April 11, 2012 as follows: **(Plug #1)** Mix and pump 20 sks of Type B cement from 3890' to 3713'. **(Plug #2)** Mix and pump 18 sks of Type B cement from 2017' to 1858'. **(Plug #3)** Mix and pump 20 sks of Type B cement from 1608' to 1431'. **(Plug #4)** Mix and pump 60 sks of Type B cement from 1293' to 793'. **(Plug #5)** Mix and pump 62 sks of Type B cement from 535' to surface with good returns on cement. Installed marker with 44 sks of cement, ~~No~~ cement to surface in 8 5/8" casing. Plugging was not witnessed by the OCD.

Approved for plugging of wellbore only  
Liability under bond is retained pending  
Receipt of C-103 (Subsequent Report of Well  
Plugging) which may be found @ OCD web page  
under forms.  
www.emnrd.state.us/ocd

RCVD APR 16 '12  
OIL CONS. DIV.  
DIST. 3

SIGNATURE

*Nicole Alley*  
Nicole Alley

TITLE

Administrative Specialist

DATE

04/12/12

TYPE OR PRINT NAME

TELEPHONE NO. 505-632-3476 ext. 203

(This space for State Use)

APPROVED BY

*Bel Pelt*

TITLE

Deputy Oil & Gas Inspector,  
District #3

DATE

4/24/12

CONDITIONS OF APPROVAL, IF ANY

A