Submit 5 Copies 10 Appropriate L Office		State of New Mexico		Form C-103	
District I		Minerals and Natural Resou	irces	May 27, 2004	
1625 N. French Dr., Hobbs, NM 8 District II			20.045	API NO. -31830	
1301 W. Grand Ave., Artesia, NM	00210	ONSERVATION DIVISI		cate Type of Lease	
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 8	87410	20 South St. Francis Dr/		STATE STEELS	
District IV		Santa Fe, NM 87505	6. Stat	e Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, 1 87505	NM		B-1088	39-30	
SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name					
(DO NOT USE THIS FORM FOR	R PROPOSALS TO DRILL O	OR TO DEEPEN OR PEUG BACK T		mer B Com A	
DIFFERENT RESERVOIR. USE PROPOSALS.)	E "APPLICATION FOR PER	MIT" (FORM C-101) FOR SUCH			
1. Type of Well: Oil Well	☐ Gas Well 🖂	Other Ann	8. Wel م	l Number 200S	
2. Name of Operator		200,	5 9. OG	RID Number 14538	
Burlington Resources Oil & Gas Company LP					
3. Address of Operator	'		(19) (4, 1))	ol name or Wildcat	
3401 E. 30 th Street, Farm	ington, NM 8/402		Ba Ba	sin Fruitland Coal	
4. Well Location			~ 1)		
Unit Letter A		om the North line and			
Section 2 Township 30N Range 9W NMPM County San Juan					
11. Elevation (Show whether DR, RKB, RT, GR, etc.)					
Pit or Below-grade Tank Application or Closure					
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water					
Pit Liner Thickness:	mil Below-Grade	Tank: Volume	bbls; Construction	Material	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
			•		
	OF INTENTION 7			ENT REPORT OF:	
PERFORM REMEDIAL WO		-	IAL WORK	☐ ALTERING CASING ☐	
TEMPORARILY ABANDON		_	NCE DRILLING O		
PULL OR ALTER CASING	☐ MULTIPLE C	OMPL CASING	CEMENT JOB	\boxtimes	
OTHER:		☐ OTHER:	7" Casing	Report 🛛	
			letails, and give pe	rtinent dates, including estimated date	
	osed work). SEE RUL	E 1103. For Multiple Comple	tions: Attach well	bore diagram of proposed completion	
or recompletion.		0.4051 70.0			
		t @ 105'. D/O cement &			
	@ 2495'. TD was reached 3/21/05. Circ. hole & ran logs. TOH. NU BOP. RIH w/ 58 jts of 7" 20 #, J-55, ST & C				
casing set @ 2493. Pumped preflush of 10 bbls FW, 2 bbls mudflush ahead of Scavenger cement- 9 sx (27 cf – 4.8					
				enger cement- $9 \text{ sx } (27 \text{ cf} - 4.8 \text{ cm})$	
bbls slurry) at 11.0 #, Ty	ype III w/ 3% CaCl	2, .25 #/sx Flocele, 5 #/sx	k LCM-1, .4% I	enger cement- 9 sx (27 cf – 4.8 Fl-52, .4% SMS, 8% GEL. Then	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sx	ype III w/ 3% CaCl x (645 cf – 115 bbls	2, .25 #/sx Flocele, 5 #/sx slurry) Premium Lite Cl	k LCM-1, .4% I ass B w/ 3% Ca	enger cement- 9 sx (27 cf – 4.8 Fl-52 , .4% SMS, 8% GEL. Then aCl2,	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sx .25 #/sx Cello-flake. Tai	ype III w/ 3% CaCl x (645 cf – 115 bbls iled w/ 90 sx (124 c	2, .25 #/sx Flocele, 5 #/sx slurry) Premium Lite Cl ef – 22 bbls slurry) Type I	x LCM-1, .4% I ass B w/ 3% Ca III cement w/ .2	enger cement- 9 sx (27 cf – 4.8 Fl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2.	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sx .25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs	ype III w/ 3% CaCl x (645 cf – 115 bbls iled w/ 90 sx (124 c 3/21/05. Circ. 49 b	2, .25 #/sx Flocele, 5 #/sx slurry) Premium Lite Cl ef – 22 bbls slurry) Type I	x LCM-1, .4% I ass B w/ 3% Ca III cement w/ .2	enger cement- 9 sx (27 cf – 4.8 Fl-52 , .4% SMS, 8% GEL. Then aCl2,	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sx .25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ 0	ype III w/ 3% CaCl x (645 cf – 115 bbls iled w/ 90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05.	2, .25 #/sx Flocele, 5 #/sx s slurry) Premium Lite Clef – 22 bbls slurry) Type lbls of cement to surface.	ass B w/ 3% Ca III cement w/ .2 RD cement hea	enger cement- 9 sx (27 cf – 4.8 Fl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2.	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sx .25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ 0	ype III w/ 3% CaCl x (645 cf – 115 bbls iled w/ 90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05.	2, .25 #/sx Flocele, 5 #/sx slurry) Premium Lite Cl ef – 22 bbls slurry) Type I	ass B w/ 3% Ca III cement w/ .2 RD cement hea	enger cement- 9 sx (27 cf – 4.8 Fl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2.	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sx .25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ 0	ype III w/ 3% CaCl x (645 cf – 115 bbls iled w/ 90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05.	2, .25 #/sx Flocele, 5 #/sx s slurry) Premium Lite Clef – 22 bbls slurry) Type lbls of cement to surface.	ass B w/ 3% Ca III cement w/ .2 RD cement hea	enger cement- 9 sx (27 cf – 4.8 Fl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2.	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sx .25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ 0	ype III w/ 3% CaCl x (645 cf – 115 bbls iled w/ 90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05.	2, .25 #/sx Flocele, 5 #/sx s slurry) Premium Lite Clef – 22 bbls slurry) Type lbls of cement to surface.	ass B w/ 3% Ca III cement w/ .2 RD cement hea	enger cement- 9 sx (27 cf – 4.8 Fl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2.	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sx .25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ 0 Will conduct casing PT	ype III w/ 3% CaCl x (645 cf – 115 bble iled w/ 90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05. with completion rig	2, .25 #/sx Flocele, 5 #/sx slurry) Premium Lite Cl of – 22 bbls slurry) Type I bls of cement to surface. It is before completion begin	ass B w/ 3% Ca III cement w/ .2 RD cement heans.	enger cement- 9 sx (27 cf – 4.8 Fl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2. d, NU BOP & manifold, blooie	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sx .25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ 0 Will conduct casing PT	ype III w/ 3% CaCl x (645 cf – 115 bbls iled w/ 90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05. with completion rig	2, .25 #/sx Flocele, 5 #/sx s slurry) Premium Lite Cl of – 22 bbls slurry) Type I bls of cement to surface. I g before completion begin	ass B w/ 3% Ca III cement w/ .2 RD cement heans.	enger cement- 9 sx (27 cf – 4.8 Fl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2.	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sx .25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ 0 Will conduct casing PT	ype III w/ 3% CaCl x (645 cf – 115 bbls iled w/ 90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05. with completion rig	2, .25 #/sx Flocele, 5 #/sx s slurry) Premium Lite Cl of – 22 bbls slurry) Type I bls of cement to surface. It is before completion begin and complete to the best of my less NMOCD guidelines , a general	x LCM-1, .4% I ass B w/ 3% Ca III cement w/ .2 RD cement heans.	enger cement- 9 sx (27 cf – 4.8 Gl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2. d, NU BOP & manifold, blooie	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sy .25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ 0 Will conduct casing PT I hereby certify that the inforgrade tank has been/will be constructed by the construction of the co	ype III w/ 3% CaCl x (645 cf - 115 bbls iled w/ 90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05. with completion right runtion above is true ar ructed or closed according	2, .25 #/sx Flocele, 5 #/sx s slurry) Premium Lite Clef – 22 bbls slurry) Type I bls of cement to surface. It is before completion begin and complete to the best of my left of NMOCD guidelines , a general of the surface. The surface is surface in the surface is surface. The surface is surface in the surface is surface. The surface is surface in the surface is surface in the surface is surface. The surface is surface in the surface is surface in the surface is surface. The surface is surface in the surface is surface. The surface is surface in the surface is surface in the surface is surface. The surface is surface is surface in the surface is surface. The surface is surface in the surface is surface in the surface is surface. The surface is surface in the surface is surface in the surface is surface. The surface is surface in the surface is surface in the surface is surface. The surface is surface in the surface in the surface is surface in the sur	A LCM-1, .4% I ass B w/ 3% Ca III cement w/ .2 RD cement heat hs. Chowledge and belipermit or an (attainty Associate December 1)	enger cement- 9 sx (27 cf – 4.8 Gl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2. d, NU BOP & manifold, blooie ief. I further certify that any pit or below-ched) alternative OCD-approved plan	
bbls slurry) at 11.0 #, Tycemented lead w/ 303 sz25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ G Will conduct casing PT I hereby certify that the inforgrade tank has been/will be constructed by the construction of the co	ype III w/3% CaCl x (645 cf - 115 bbls iled w/90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05. with completion rig ructed or closed according	2, .25 #/sx Flocele, 5 #/sx s slurry) Premium Lite Cl of – 22 bbls slurry) Type I bls of cement to surface. I g before completion begin ad complete to the best of my l to NMOCD guidelines , a general mail address: PThompson@	A LCM-1, .4% I ass B w/ 3% Ca III cement w/ .2 RD cement heats. Conowledge and believe or an (attainty Associate Debr-inc.com	enger cement- 9 sx (27 cf – 4.8 Fl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2. d, NU BOP & manifold, blooie ief. I further certify that any pit or below-ched) alternative OCD-approved plan ATE 3/24/05 Telephone No. 505-326-9503	
bbls slurry) at 11.0 #, Ty cemented lead w/ 303 sy .25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ 0 Will conduct casing PT I hereby certify that the inforgrade tank has been/will be constructed by the construction of the co	ype III w/ 3% CaCl x (645 cf - 115 bbls iled w/ 90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05. with completion right runtion above is true ar ructed or closed according	2, .25 #/sx Flocele, 5 #/sx s slurry) Premium Lite Cl of – 22 bbls slurry) Type I bls of cement to surface. I g before completion begin ad complete to the best of my l to NMOCD guidelines , a general mail address: PThompson@	A LCM-1, .4% I ass B w/ 3% Ca III cement w/ .2 RD cement heats. Conowledge and believe or an (attainty Associate Debr-inc.com	enger cement- 9 sx (27 cf – 4.8 Fl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2. d, NU BOP & manifold, blooie ief. I further certify that any pit or below-ched) alternative OCD-approved plan ATE 3/24/05 Telephone No. 505-326-9503	
bbls slurry) at 11.0 #, Tycemented lead w/ 303 sz25 #/sx Cello-flake. Tai Bump plug @ 2232 hrs line, RD & released @ G Will conduct casing PT I hereby certify that the inforgrade tank has been/will be constructed by the construction of the co	ype III w/ 3% CaCl x (645 cf – 115 bbls iled w/ 90 sx (124 c 3/21/05. Circ. 49 b 0445 3/22/05. with completion rig mation above is true ar ructed or closed according mathematical according	2, .25 #/sx Flocele, 5 #/sx s slurry) Premium Lite Clef – 22 bbls slurry) Type I bls of cement to surface. It is bls of cement	A LCM-1, .4% I ass B w/ 3% Ca III cement w/ .2 RD cement heat hs. Chowledge and belipermit or an (attainty Associate December 1)	enger cement- 9 sx (27 cf – 4.8 Gl-52, .4% SMS, 8% GEL. Then aCl2, 5 #/sx Cello-flake, 3% CaCl2. d, NU BOP & manifold, blooie dief. I further certify that any pit or below-iched) alternative OCD-approved plan ATE 3/24/05 Telephone No. 505-326-9503 APR - 1 2005	