<u>Uistrict I</u> 1625 N. French Dr., Hobbs, NM 88240

State of New Mexico Energy Minerals and Natural Resources

Form C-144 July 21, 2008

District II

1301 W Grand Ave , Artesia, NM 88210

District III

1000 Rio Brazos Rd, Aztec, NM 87410

District IV

1220 S St Francis Dr., Santa Fe. NM 87505

Department Oil Conservation Division 1220 South St. Francis Dr.

Santa Fe, NM 87505

For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office.

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

Pit, Closed-Loop System, Below-Grade Tank, or Proposed Alternative Method Permit or Closure Plan Application

Type of action:

Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method

Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method

Modification to an existing permit

Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.

Operator: ConocoPhillips Company	OGRID#: 217817
Address: PO Box 4289, Farmington, NM 87499	
Facility or well name: MUDGE B 20M	
API Number: OCD Permit Number	er:
U/L or Qtr/Qtr: G(SW/NE) Section: 8 Township: 31N Range: 1	11W County: SAN JUAN
Center of Proposed Design: Latitude: 36.91377 °N Longitude:	108.00972 °W NAD: ☐ 1927 X 1983
Surface Owner: X Federal State Private Tribal Trust or India	n Allotment
String-Reinforced	RCVD APR 20 '12 UIL CUNS. DIV.
notice of intent) Drying Pad Above Ground Steel Tanks Haul-off Bins Other	activities which require prior approval of a permit or HDPE PVD Other
Below-grade tank: Subsection I of 19.15.17.11 NMAC Volume: bbl Type of fluid: Tank Construction material: Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and auto Visible sidewalls and liner Visible sidewalls only Other Liner Type: Thickness mil HDPE PVC Other	omatic overflow shut-off
Submittal of an exception request is required Exceptions must be submitted to the Santa Fe Enviror	nmental Bureau office for consideration of approval

Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pit, temporary pits, and below-grade tanks) Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church) Four foot height, four strands of barbed wire evenly spaced between one and four feet Alternate. Please specify				
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks) Screen Netting Other Monthly inspections (If netting or screening is not physically feasible)				
Signs: Subsection C of 19.15.17.11 NMAC 12" X 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers X Signed in compliance with 19.15.3.103 NMAC				
Administrative Approvals and Exceptions: Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance. Please check a box if one or more of the following is requested, if not leave blank: X Administrative approval(s): Requests must be submitted to the appropriate division district of the Santa Fe Environmental Bureau office for consideration of approval. (Cavitation pit for Pre-set) Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.				
Siting Criteria (regarding permitting) 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau Office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above grade-tanks associated with a closed-loop system.		į		
Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells				
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	Yes	□No		
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.	Yes	□No		
(Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image				
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applied to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐Yes ☐NA	□No		
Within 500 horizonal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.	Yes	□No		
- NM Office of the State Engineer - 1WATERS database search; Visual inspection (certification) of the proposed site.				
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes	∐No		
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	Yes	□No		
Within the area overlying a subsurface mine Written confirmation or verification or map from the NM EMNRD - Mining and Mineral Division	Yes	□No		
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map				
Within a 100-year floodplain	Yes	□No		

Form C-144 Oil Conservation Division Page 2 of 5

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist Subsection B of 19.15.17.9 NMAC Instructions Each of the following items must be attached to the application Please indicate, by a check mark in the box, that the documents are attached.				
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC				
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC				
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of				
19.15.17.9 NMAC and 19.15.17.13 NMAC				
Previously Approved Design (attach-copy of design) API or Permit				
12				
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17 9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9				
Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC				
Design Plan - based upon the appropriate requirements of 19 15.17.11 NMAC				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17 12 NMAC				
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17 9				
NMAC and 19.15.17.13 NMAC				
Previously Approved Design (attach copy of design) API				
Previously Approved Operating and Maintenance Plan API				
13				
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC				
Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.				
Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19.15.17.9 NMAC				
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC				
Climatological Factors Assessment				
Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17 11 NMAC				
Dike Protection and Structural Integrity Design. based upon the appropriate requirements of 19.15.17.11 NMAC				
Leak Detection Design - based upon the appropriate requirements of 19.15.17 11 NMAC				
Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC				
Quality Control/Quality Assurance Construction and Installation Plan				
Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC				
Nuisance or Hazardous Odors, including H2S, Prevention Plan				
Emergency Response Plan				
Oil Field Waste Stream Characterization				
Monitoring and Inspection Plan				
Erosion Control Plan				
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17 9 NMAC and 19.15.17.13 NMAC				
Proposed Closure: 19.15 17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.				
Type: Drilling Workover Emergency X Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative				
Proposed Closure Method: Waste Excavation and Removal				
Waste Removal (Closed-loop systems only)				
On-site Closure Method (only for temporary pits and closed-loop systems)				
In-place Burial On-site Trench				
Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)				
15				
Waste Excavation and Removal Closure Plan Checklist (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan.				
Please indicate, by a check mark in the box, that the documents are attached.				
Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC				
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC				
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC				
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC				
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC				
La bite recommendation and consequent the appropriate requirements of businession of or 17-13-17-13 (Militie				

Form C-144 Oil Conservation Division

Page 3 of 5

16		
Waste Removal Closure For Closed-loop Systems That Utilize Above Grou Instructions Please identify the facility or facilities for the disposal of liquids, a facilities are required.		
Disposal Facility Name: Envirotech / JFJ Landfarm % IEI	Disposal Facility Permit #: NM-01-0011 / NM-01-	-0010B
Disposal Facility Name: Basin Disposal Facility	Disposal Facility Permit #: NM-01-005	· · · · · · · · · · · · · · · · · · ·
Will any of the proposed closed-loop system operations and associated Yes (If yes, please provide the information No		e service and
Required for impacted areas which will not be used for future service and opera Soil Backfill and Cover Design Specification - based upon the a Re-vegetation Plan - based upon the appropriate requirements of S	ppropriate requirements of Subsection H of 19.15 17.13	NMAC
Site Reclamation Plan - based upon the appropriate requirements	of Subsection G of 19 15 17 13 NMAC	
17 <u>Siting Criteria (Regarding on-site closure methods only:</u> 19.15 17.10 Instructions: Each siting criteria requires a demonstration of compliance in the closure picerian siting criteria may require administrative approval from the appropriate district of office for consideration of approval. Justifications and/or demonstrations of equivalency	lan. Recommendations of acceptable source material are provided belo ffice or may be considered an exception which must be submitted to the	w Requests regarding changes to Santa Fe Environmenial Bureau
Ground water is less than 50 feet below the bottom of the buried waste. - NM Office of the State Engineer - WATERS database search: USGS. D.		Yes No
Ground water is between 50 and 100 feet below the bottom of the burie	ed waste	☐Yes ☐No
- NM Office of the State Engineer - iWATERS database search, USGS, Da		N/A
Ground water is more than 100 feet below the bottom of the buried was	ste.	Yes No
- NM Office of the State Engineer - iWATERS database search; USGS; Da	ata obtained from nearby wells	□N/A
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other (measured from the ordinary high-water mark)	significant watercourse or lakebed, sinkhole, or playa lake	Yes No
- Topographic map, Visual inspection (certification) of the proposed site		
Within 300 feet from a permanent residence, school, hospital, institution, or chu - Visual inspection (certification) of the proposed site, Aerial photo; satellite	• •	∐Yes ∐No
Within 500 horizontal feet of a private, domestic fresh water well or spring that I purposes, or within 1000 horizontal fee of any other fresh water well or spring. - NM Office of the State Engineer - iWATERS database. Visual inspection Within incorporated municipal boundaries or within a defined municipal fresh water water well or spring that I will be a supplied to the supplied to	in existence at the time of the initial application. (certification) of the proposed site	Yes No
pursuant to NMSA 1978. Section 3-27-3, as amended - Written confirmation or verification from the municipality, Written appro		Lies Lino
Within 500 feet of a wetland - US Fish and Wildlife Wetland Identification map, Topographic map; Visi	ual inspection (certification) of the proposed site	Yes No
Within the area overlying a subsurface mine.		Yes No
Written confiramtion or verification or map from the NM EMNRD-Mining Within an unstable area.	g and Mineral Division	Yes No
Engineering measures incorporated into the design; NM Bureau of Geolog Topographic map	y & Mineral Resources; USGS, NM Geological Society,	
Within a 100-year floodplain FEMA map		Yes No
18 On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: by a check mark in the box, that the documents are attached.	Each of the following items must bee attached to the cl	osure plan. Please indicate,
Siting Criteria Compliance Demonstrations - based upon the app	propriate requirements of 19 15 17.10 NMAC	
Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC		
Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC		
Construction/Design Plan of Temporary Pit (for in place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC		
X Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC		
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC		
Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC		
X Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved) Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17 13 NMAC		
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC		
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC		

Form C-144 Oil Conservation Division Page 4 of 5

0perator Application	Certification:			
I hereby certify that the in	formation submitted with this application is true, accura	ate and complete to the	best of my knowledge and belief	
Name (Print)	Jamie Goodwin	Title:	Regulatory Technician	
Signature:	nmu (soodw)	Date:	4/18/12	
e-mail address.	jamie.l.goodwin@conocophillips.com	Telephone.	505-326-9784	
				
OCD Approval: OCD Representative:	Permit Application (including closure plan) Signature:	OCD Pe	y) OCD Conditions (see attachment) Approval Date: 4/24/20(7-	
Instructions: Operators a report is required to be si		implementing any clos n of the closure activition impleted.	NAC nure activities and submitting the closure report. The closure see Please do not complete this section of the form until an nure Completion Date:	
22				
Closure Method: Waste Excavation If different from a	n and Removal On-site Closure Method approved plan, please explain	Alternative Closu	re Method Waste Removal (Closed-loop systems only)	
23				
Closure Report Regardi	ng Waste Removal Closure For Closed-loop Systems tify the facility or facilities for where the liquids, drilli		cround Steel Tanks or Haul-off Bins Only: ings were disposed. Use attachment if more than two facilities	
Disposal Facility Nam	e·	Disposal Facil	ity Permit Number:	
Disposal Facility Nam	e	Disposal Facil	ty Permit Number:	
Were the closed-loop	system operations and associated activities performed o	n or in areas that will n	ot be used for future service and opeartions?	
Yes (If yes, pleas	e demonstrate complilane to the items below)	No		
	l areas which will not be used for future service and ope	erations.		
=	(Photo Documentation)			
=	nd Cover Installation			
Re-vegetation Ap	plication Rates and Seeding Technique			
the box, that the docu Proof of Closur	ments are attached. e Notice (surface owner and division)	owing items must be a	tached to the closure report. Please indicate, by a check mark in	1
=	Notice (required for on-site closure)			
	n-site closures and temporary pits)			
=	ampling Analytical Results (if applicable)			
=	Sampling Analytical Results (if applicable)			
= '	y Name and Permit Number			
<u></u>	and Cover Installation			
= *	Application Rates and Seeding Technique			
On-site Closure	n (Photo Documentation) Location: Latitude.	Longitude:	NAD	
On-site Closure	Location. Lande.	Longitude.	1721 1703	
			, William Street, Company of the Com	
	-	•	and complete to the best of my knowledge and belief. I also cert, closure plan.	ify that
Name (Print):		Title:	•	
. ,				
Signature:		Date:		
e-mail address		Telephone:		

ConocoPhillips Company

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

ConocoPhillips Company may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- 2. Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed Loop Closure Plan:

1. Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) within 6 months from the date that the drilling rig is released.

2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. COP shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)

Purity

50 percent

Germination

40 percent

Percent PLS

20 percent

Source No. two (better quality)

Purity

80 percent

Germination

63 percent

Percent PLS

50 percent

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS

ConocoPhillips Mud Preset Drill

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

ConocoPhillips may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19.15.17.11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19.15.3.103.NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows:

- Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). Reuse may include the relocating of liquids to be used in other permitted drilling operations.
- Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- 3. In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B). The liner will be disposed of at the San Juan County Landfill located on CR 3100. The drying pad will be closed within 6 months from the date that the drilling rig is released. Berms constructed from native materials will be bladed on site to the location's contour.
- 4. Any drilling materials or trash will be stored and disposed of appropriately.
- 5. The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately.

Closed Loop Closure Plan:

1. Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B). Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) within 6 months from the date that the drilling rig is released.

2. After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul.

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300.1	500

- 3. Re-contouring of location will match fit, shape, line, form and texture of the surrounding. Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4. Notification will be sent to OCD when the reclaimed area is seeded.
- 5. COP shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arriba	3.0
Indian ricegrass	Paloma or Rimrock	3.0
Slender wheatgrass	San Luis	2.0
Crested wheatgrass	Hy-crest	3.0
Bottlebrush Squirreltail	Unknown	2.0
Four-wing Saltbrush	Delar	.25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No. One (poor quality)
Purity
50 percent
Percent PLS
20 percent
Source No. two (better quality)
Purity
80 percent
Germination
63 percent
Percent PLS
50 percent
Percent PLS
50 percent

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS