This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## **Oil Conservation Division**

## Northwest New Mexico Packer-Leakage Test

Page 1 Revised June 10, 2003

Operator BR				Lease Name JICARILLA 153						Well No13	
Location of W	ell: Unit	Letter I	_ Sec _	36	Twp _	026N	R	ge	005W API	# 30-039-20119	
	Name of Reservoir or Pool			Type of Prod				Method of Prod		Prod Medium	
Upper Completion	PC			Gas				Flow		Tubing	
Lower Completion	GL-DK			Gas				Flow		Tubing	
			P	re-Flow S	Shut-In	Pressu	re Data	1			
Upper Completion	Hour, Da	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)	
	4/2/2012			223 hours				, 235		Yes	
Lower	Hour, Da	Hour, Date, Shut-In			Length of Time Shut-In			SI Press. PSIG		Stabilized?(Yes or No)	
Completion	4/2/2012			175 hours				577		Yes	
Commenced at:			ne	Zone P PRESSURE Upper zone Lower zone			Prod Zone Temperature		or Lower): LC	Remarks	
		0	Ор	235							
4/9/2012 7:37.04 AM					5 577		- 3	55 begin test open I		Jwei zone	
4/10/2012 7:39:07 AM 24			235		80	54		achieved 20% flow upper zone			
Production rat	te during t	est									
Oil:	BPOD Based on:			Bbls. In		Hrs		Grav		GOR	
Gas		MCFPD; T	est thru (O	rifice or M	leter)						
			B/	iid Taat C	No.4 la	D	Data				
Upper Completion	Hour, Date, Shut-In			Length of Time Shut-In			ire Data	SI Press PSIG		Stabilized?(Yes or No)	
Lower Completion	Hour, Date, Shut-In			Length of Time Shut-In				SI Pres	s PSIG	Stabilized?(Yes or No)	

(Continue on reverse side)

RCVD APR 17'12 OIL CONS. DIV. DIST. 3

## Flow Test No. 2

Commenced at:	:		Zone Producing (Upper or Lower)								
Time	Lapsed Time	PRES	SURE	Prod Zone							
(date/time)	Since*	Upper zone	Lower zone	Temperature	)	Remarks					
	*										
Production rate of	during test										
Oil:	BPOD Based on:	Bbls. In	Hrs.		Grav.	GOR					
Gas	MCFPD; Test th	nru (Orifice or M	eter)								
Remarks:											
	-		AN ARRAY	W W D							
I hereby certify th	nat the information herein o	ontained is true	and complete	to the best of	my knowled	lge.					
Annroyed:	4/30	20 /3	Oneral	tor: BR							
	Oil Conservation Division	20	_		222						
New Mexico	Oil Conservation Division		By:	Ronnie Gre	ene						
By:	Seputy Oil & Gas Ins	nector	Title:	Multi-Skilled	Operator						
Title:	Date:	Date: Monday, April 16, 2012									

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced Offset operators shall also be so notified
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- 4 For Flow Test No 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.

- 6 Flow Test No 2 shall be conducted even though no leak was indicated during Flow Test No 1 Procedure for Flow Test No 2 is to be the same as for Flow Test No 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)