

District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-144
July 21, 2008

For temporary pits, closed-loop systems, and below-grade tanks, submit to the appropriate NMOCD District Office.
For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

4804

Pit, Closed-Loop System, Below-Grade Tank, or
Proposed Alternative Method Permit or Closure Plan Application

- Type of action: ☒ Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method
☐ Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method
☐ Modification to an existing permit
☐ Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.

1.
Operator: EnerVest Operating, LLC OGRID #: 143199
Address: 1001 Fannin St. Ste 800 Houston, Texas 77002
Facility or well name: Jicarilla Contract 148 #32
API Number: 30-039-23655 OCD Permit Number: _____
U/L or Qtr/Qtr D Section 14 Township 25N Range 05W County: Rio Arriba
Center of Proposed Design: Latitude 36.404693 Longitude -107.334051 NAD: ☐ 1927 ☒ 1983
Surface Owner: ☐ Federal ☐ State ☐ Private ☒ Tribal Trust or Indian Allotment

2.
☐ **Pit:** Subsection F or G of 19.15.17.11 NMAC
Temporary: ☐ Drilling ☐ Workover
☐ Permanent ☐ Emergency ☐ Cavitation ☐ P&A
☐ Lined ☐ Unlined Liner type: Thickness _____ mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other _____
☐ String-Reinforced
Liner Seams: ☐ Welded ☐ Factory ☐ Other _____ Volume: _____ bbl Dimensions _____



3.
☐ **Closed-loop System:** Subsection H of 19.15.17.11 NMAC
Type of Operation: ☐ P&A ☐ Drilling a new well ☐ Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent)
☐ Drying Pad ☐ Above Ground Steel Tanks ☐ Haul-off Bins ☐ Other _____
☐ Lined ☐ Unlined Liner type: Thickness _____ mil ☐ LLDPE ☐ HDPE ☐ PVC ☐ Other _____
Liner Seams: ☐ Welded ☐ Factory ☐ Other _____

4.
☒ **Below-grade tank:** Subsection I of 19.15.17.11 NMAC
Volume: 95 bbl Type of fluid: Primarily produced water w/ compressor skid precipitation & incidental lubricating oil
Tank Construction material: Steel w/ expanded metal cover
☐ Secondary containment with leak detection ☐ Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off
☐ Visible sidewalls and liner ☐ Visible sidewalls only ☐ Other _____
Liner type: Thickness _____ mil ☐ HDPE ☐ PVC ☐ Other _____

5.
☐ **Alternative Method:**
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

6.

Fencing: Subsection D of 19.15.17.11 NMAC (*Applies to permanent pits, temporary pits, and below-grade tanks*)

- ☐ Chain link, six feet in height, two strands of barbed wire at top (*Required if located within 1000 feet of a permanent residence, school, hospital, institution or church*)
- ☐ Four foot height, four strands of barbed wire evenly spaced between one and four feet
- ☒ Alternate. Please specify 42" Hog-wire fence with 2 strands barbed-wire on top

7.

Netting: Subsection E of 19.15.17.11 NMAC (*Applies to permanent pits and permanent open top tanks*)

- ☒ Screen ☐ Netting ☐ Other _____
- ☐ Monthly inspections (If netting or screening is not physically feasible)

8.

Signs: Subsection C of 19.15.17.11 NMAC

- ☐ 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers
- ☒ Signed in compliance with 19.15.3.103 NMAC

9.

Administrative Approvals and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

- ☒ Administrative approval(s): Requests must be submitted to the appropriate division district or the Santa Fe Environmental Bureau office for consideration of approval.
- ☐ Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

10.

Siting Criteria (regarding permitting): 19.15.17.10 NMAC

Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Applicant must attach justification for request. Please refer to 19.15.17.10 NMAC for guidance. Siting criteria does not apply to drying pads or above-grade tanks associated with a closed-loop system.

Ground water is less than 50 feet below the bottom of the temporary pit, permanent pit, or below-grade tank. - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). - Topographic map; Visual inspection (certification) of the proposed site	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to temporary, emergency, or cavitation pits and below-grade tanks) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. (Applies to permanent pits) - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> NA
Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application. - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within 500 feet of a wetland. - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within the area overlying a subsurface mine. - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within an unstable area. - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Within a 100-year floodplain. - FEMA map	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No

11.

Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC**Instructions:** Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.

- ☒ Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC
☐ Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC
☒ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
☒ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
☒ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
☒ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC

☐ Previously Approved Design (attach copy of design) API Number: _____ or Permit Number: _____

12.

Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC**Instructions:** Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.

- ☐ Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19.15.17.9
☐ Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19.15.17.10 NMAC
☐ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
☐ Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC

☐ Previously Approved Design (attach copy of design) API Number: _____

☐ Previously Approved Operating and Maintenance Plan API Number: _____ (Applies only to closed-loop system that use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)

13.

Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC**Instructions:** Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.

- ☐ Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC
☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC
☐ Climatological Factors Assessment
☐ Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC
☐ Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC
☐ Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC
☐ Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC
☐ Quality Control/Quality Assurance Construction and Installation Plan
☐ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC
☐ Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC
☐ Nuisance or Hazardous Odors, including H₂S, Prevention Plan
☐ Emergency Response Plan
☐ Oil Field Waste Stream Characterization
☐ Monitoring and Inspection Plan
☐ Erosion Control Plan
☐ Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC

14.

Proposed Closure: 19.15.17.13 NMAC**Instructions:** Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.

Type: ☐ Drilling ☐ Workover ☐ Emergency ☐ Cavitation ☐ P&A ☐ Permanent Pit ☒ Below-grade Tank ☐ Closed-loop System
☐ Alternative

Proposed Closure Method: ☒ Waste Excavation and Removal
☐ Waste Removal (Closed-loop systems only)
☐ On-site Closure Method (Only for temporary pits and closed-loop systems)
☐ In-place Burial ☐ On-site Trench Burial
☐ Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)

15.

Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) **Instructions:** Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.

- ☒ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC
☒ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC
☒ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)
☒ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC
☒ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC
☒ Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

16.

Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.D NMAC)

Instructions: Please identify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two facilities are required.

Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Will any of the proposed closed-loop system operations and associated activities occur on or in areas that *will not* be used for future service and operations?

☐ Yes (If yes, please provide the information below) ☐ No

Required for impacted areas which will not be used for future service and operations:

☐ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC

☐ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

17.

Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC

Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable source material are provided below. Requests regarding changes to certain siting criteria may require administrative approval from the appropriate district office or may be considered an exception which must be submitted to the Santa Fe Environmental Bureau office for consideration of approval. Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17.10 NMAC for guidance.

Ground water is less than 50 feet below the bottom of the buried waste.

- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells

☐ Yes ☐ No

☐ NA

Ground water is between 50 and 100 feet below the bottom of the buried waste

- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells

☐ Yes ☐ No

☐ NA

Ground water is more than 100 feet below the bottom of the buried waste.

- NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells

☐ Yes ☐ No

☐ NA

Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).

- Topographic map; Visual inspection (certification) of the proposed site

☐ Yes ☐ No

Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.

- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image

☐ Yes ☐ No

Within 500 horizontal feet of a private, domestic fresh water well or spring that less than five households use for domestic or stock watering purposes, or within 1000 horizontal feet of any other fresh water well or spring, in existence at the time of initial application.

- NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site

☐ Yes ☐ No

Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended.

- Written confirmation or verification from the municipality; Written approval obtained from the municipality

☐ Yes ☐ No

Within 500 feet of a wetland.

- US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site

☐ Yes ☐ No

Within the area overlying a subsurface mine.

- Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division

☐ Yes ☐ No

Within an unstable area.

- Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map

☐ Yes ☐ No

Within a 100-year floodplain.

- FEMA map

☐ Yes ☐ No

18.

On-Site Closure Plan Checklist: (19.15.17.13 NMAC) **Instructions:** Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.

☐ Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC

☐ Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC

☐ Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of 19.15.17.11 NMAC

☐ Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.11 NMAC

☐ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC

☐ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC

☐ Waste Material Sampling Plan - based upon the appropriate requirements of Subsection F of 19.15.17.13 NMAC

☐ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)

☐ Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC

☐ Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19.15.17.13 NMAC

☐ Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19.15.17.13 NMAC

19.

Operator Application Certification:

I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.

Name (Print): Ronnie L. Young Title: Compliance Supervisor

Signature: *Ronnie L. Young* Date: 1-18-10

e-mail address: ryoung@enervest.net Telephone: 713-495-6530

20.

OCD Approval: ☒ Permit Application (including closure plan) ☐ Closure Plan (only) ☐ OCD Conditions (see attachment)

OCD Representative Signature: *Jonathan D. Kelly* Approval Date: 5/16/2012

Title: Deputy Oil & Gas Inspector,

District #3 OCD Permit Number: _____

21.

Closure Report (required within 60 days of closure completion): Subsection K of 19.15.17.13 NMAC

Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.

☐ Closure Completion Date: _____

22.

Closure Method:

☐ Waste Excavation and Removal ☐ On-Site Closure Method ☐ Alternative Closure Method ☐ Waste Removal (Closed-loop systems only)
☐ If different from approved plan, please explain.

23.

Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:

Instructions: Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.

Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Disposal Facility Name: _____ Disposal Facility Permit Number: _____

Were the closed-loop system operations and associated activities performed on or in areas that *will not* be used for future service and operations?

☐ Yes (If yes, please demonstrate compliance to the items below) ☐ No

Required for impacted areas which will not be used for future service and operations:

- ☐ Site Reclamation (Photo Documentation)
☐ Soil Backfilling and Cover Installation
☐ Re-vegetation Application Rates and Seeding Technique

24.

Closure Report Attachment Checklist: *Instructions: Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.*

- ☐ Proof of Closure Notice (surface owner and division)
☐ Proof of Deed Notice (required for on-site closure)
☐ Plot Plan (for on-site closures and temporary pits)
☐ Confirmation Sampling Analytical Results (if applicable)
☐ Waste Material Sampling Analytical Results (required for on-site closure)
☐ Disposal Facility Name and Permit Number
☐ Soil Backfilling and Cover Installation
☐ Re-vegetation Application Rates and Seeding Technique
☐ Site Reclamation (Photo Documentation)

On-site Closure Location: Latitude _____ Longitude _____ NAD: ☐ 1927 ☐ 1983

25.

Operator Closure Certification:

I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.

Name (Print): _____ Title: _____

Signature: _____ Date: _____

e-mail address: _____ Telephone: _____

Attachment to Form C-144
Below-grade Tank Permit Application

Introduction:

EnerVest Operating, LLC (EV) is submitting this permit application to operate an existing below-grade tank under the authority of 19.15.17 NMAC. The tank is not currently permitted; therefore this document serves as supporting documentation referenced in the attached Form C-144. EV operates coal bed methane production sites in San Juan County, New Mexico. The below-grade tank at this location is used to collect precipitation and residual lubrication oil from the engine skid drain system and produced water from the primary and secondary separators. Produced water from the secondary separator may have small quantities of entrained lubricating oil from the compressor cylinder. In general, emulsified lubricating oil makes up a small percentage of the overall contents of the below-grade tank.

This application is being submitted for the following well site:

Well Name: Jicarilla Contract 148 #32
API No: 30-039-23655
Location: UL D, Sec 14, 25N, 05W

The supporting documentation contained in this C-144 attachment is organized as follows:

Section I – Sitting Criteria Compliance Demonstration
Section II – Design Plan
Section III – Operating and Maintenance Plan
Section IV – Closure Plan
Section V – Hydrogeology Report

Appendices:

01 – USGS 7.5 Minute Topo Map
02 – Groundwater (water well search)
03 – Aerial Photo
04 – Municipal Boundary Map
05 – U.S. Fish & Wildlife Wetland Identification Map
06 – FEMA 100-year Floodplain map
07 – Mine Map
08 – C-102 Location Plat, Facility Inspection Sheet, Below-Grade Tank Diagram
09 – Karst Map for unstable areas

References

Section I

Sitting Criteria Compliance Demonstration

Jicarilla Apache Tribal 148 #32

API No. 30-039-23655

Sitting Criteria Compliance Demonstration

Criteria as per 19.15.17.10.(A) (1)	In Compliance	Comments
Ground water less than 50' below bottom of tank	Yes	Refer to "Site Hydrology Report" in Section V
Within 300' of continuously flowing watercourse or 200 feet of other significant watercourse, lakebed, sinkhole, or playa lake (measured from ordinary high-water mark)	No - 35 Ft from Dry Wash	Refer to Observed Setting Requirements completed by field personnel in Appendix 08
Within 300 feet of a permanent residence, school, hospital, institution, or church	Yes	Refer to Observed Setting Requirements completed by field personnel in Appendix 08
Within 500 ft of a private, domestic freshwater well or spring or within 1000 ft of freshwater well or spring in existence at time of application	Yes	Refer to Observed Setting Requirements completed by field personnel in Appendix 08
Within incorporated municipal boundary of defined municipal fresh water field	Yes	Refer to Observed Setting Requirements completed by field personnel in Appendix 08
Within 500 feet of a wetland	Yes	Refer to Observed Setting Requirements completed by field personnel in Appendix 08 and USF&W Map in Appendix 5
Within the area overlying a subsurface mine.	Yes	Refer to Observed Setting Requirements completed by field personnel in Appendix 08
Within an unstable area	Yes	Refer to Observed Setting Requirements completed by field personnel in Appendix 08 and Karst Map in Appendix 09
Within a 100-year floodplain	Yes	Refer to Observed Setting Requirements completed by field personnel in Appendix 08 and FEMA Map in Appendix 06

Section II

Design & Construction Plan

EnerVest Operating, LLC (EV)

**BELOW-GRADE TANK
DESIGN AND CONSTRUCTION SPECIFICATIONS**

Rule 19.15.17.11

- C. Enervest Operating is the official operator of record for all wells which have below-grade tanks to be addressed in this specification. All below-grade tanks are located on these leases and will be in full compliance with 19.15.16.8 regarding signage.
- D. EV will ensure a fence shall be constructed and maintained in good repair with gates that are closed and locked when responsible personnel are not on site. EV shall insure that all gates are closed and locked when responsible personnel are not on-site.

If the below-grade tank is located within 1,000 feet of a permanent residence, school, hospital, institution or church, the fence shall be a chain link security fence at least 6 feet in height with at least two strands of barbed wire on top.

If the below-grade tank is not within 1,000 feet of the above mentioned structures, the fence shall constructed to exclude livestock with at least four strands of barbed wire evenly spaced between one foot from the ground and four foot above the ground.

EV is requesting administrative approval to use a 42" Hog wire fence with 2 strands barbed-wire on top in lieu of the required four strand barbed wire fence. This will be supported with iron posting at the corners and 10 – 12 feet apart. EV believes this will offer better protection for wildlife in these tank areas.

- E. EV shall ensure an open top tank is screened with expanded 3/16" metal screen or a fully closed top, both of which are welded on the top of the tank. Such screening will be painted to blend with the below-grade tank. EV believes this is sufficient strength to protect migratory birds or other wildlife.
- I. EV will ensure all below-grade tanks will be constructed of 3/16" steel, resistant to the tank's contents and to damage from sunlight. Based on water production and road condition for access during the winter months there are a choice of three different sizes which could be used:

CAPACITY	DIAMETER	HEIGHT
125 bbl	15'	4'
120 bbl	12'	6'
100 bbl	12'	5'

This tank will contain liquids and should prevent contamination of fresh water to protect the public health and environment.

The below-grade system will include a excavated area for the tanks which will be dependent upon the size of the tank used:

- 18' x 18' x 4' High Square excavated area
- 18' Diameter x 4' High Circular excavated area
- 18' Diameter x 5' High Circular excavated area

Most of our below-grade tank systems were installed prior to June 16, 2008 and are 16.5' x 16.5' x 4' square excavated area design. As tanks are retro fitted, this will be changed to one of the above. The particular area and well conditions will determine which design best for that particular well. EV will ensure that there will be room to walk around the tank inside the containment area which will better enable our field personnel to inspect for damage to liners or incidental leaks. Please refer to tank diagram under Appendix 8 for details.

All excavated areas will be reinforced with metal walls to prevent collapse. There will be sufficient open area on all sides of the tank to witness any incidental release that may occur. Please refer to tank diagram under Appendix 8.

EV will ensure the base of any excavated area containing a below-grade tank will be level and free of rocks, debris, sharp edges or irregularities to prevent punctures, cracks or indentations of the liner or tank bottom.

EV will ensure that any geomembrane liner used shall consist of 30-mil flexible PVC or 60-mil HDPE liner or equivalent liner material. The liner shall be composed of an impervious, synthetic material that is resistant to petroleum hydrocarbons, salt and acidic and alkaline solutions and shall be resistant to ultraviolet light. The liner shall have a hydraulic conductivity no greater than 1×10^{-9} cm/sec. The liner shall be compatible with EPA SW-846 method 9090A. EV will install the liner in such a manner as to divert any possible leak for visual inspection. EV will demonstrate to the OCD that the liner complies with the specifications within Subparagraph (a) of Paragraph (4) of Section I of 19.156.17.11 NMAC and obtain approval from the division prior to the installation of the new design.

EV will ensure the fluid levels of tanks will be monitored by automatic high level alarms at 24" from the top and shut-off devise at 10 1/2 inches from the top of the tank. The tanks will be also equipped with a manual shut-off valve in the event it is needed. Please see design specification sheet of this system in this section. The majority of our below-grade tanks are within the berm around our tank battery and as so are protected from run-on water. Those outside this berm will be protected with an earthen berm which will extend at least 6" above surface ground level to divert run-on around the tank. The side walls of the excavated



area will extend at least 6" above the ground level to divert run-on water around the tank. Any possible leak will be diverted, on the liner, in such a way can be visually inspected.

EV tank design will be a single walled tank constructed to ensure that the side walls are open for visual inspection for leaks; the bottom will be elevated six inches above the ground surface and will contain a geomembrane liner, as described above, directly on the ground level of the containment area.

Once a below-grade tank which was installed prior to June 16, 2008 does not demonstrate integrity, EV shall promptly repair or remove that below-grade tank and close the tank or install a below-grade tank that is in full compliance with Paragraph 1 thru 4 of Section I of 19.15.17.11 NMAC. EV shall comply with the operational requirements of 19.15.17.12 NMAC. Please refer to tank diagram under Appendix 8 for details

Any single walled below-grade tank installed before June 16, 2008 where any portion of the tank sidewall is below the ground surface and not totally visible shall be closed, retrofited or replaced before June 15, 2013. EV will fully comply with Paragraph 1 thru 4 of Section I of 19.15.17.11 NMAC for all retrofitting or replacement of below-grade tanks.

REVISION BLOCK				
REV.	E.C.N. NO.	DESCRIPTION	DATE	APPRVD
00		INITIAL RELEASE	8/27/08	D.T.
A	N1389	ADDED TUBE END SHRINK AND POTTING	7/28/07	MJR
B	N1528	UPDATED LEAD WIRES, POTTING AND FERRULE	4/1/09	R.R.



- 1.) WETTED MATERIALS:
STEM / MOUNTING: 316/316L S.S.
FLOAT: 316L S.S.
SHAFT COLLAR: 316 S.S.
- 2.) TEMPERATURE RANGE: -40°F TO +250°F
- 3.) PRESSURE RATING: 120 PSIG
- 4.) ELECTRICAL SPECIFICATIONS:
SWITCHING VOLTAGE 240V AC/DC MAX.
SWITCHING CURRENT: 0.5 AMP MAX.
CONTACT RATING: 50VA MAX.
- 5.) MINIMUM MEDIA SP. GR. : 0.85 S.G.
- 6.) INSTALL FLOAT IN THE N.C. POSITION WITH
MAGNET UP AS SHOWN.
- 7.) OVER TRAVEL TO BE BETWEEN 1/16" AND 3/16" MAX.
UPON EITHER SWITCH CLOSURE OR OPENING.
- 8.
9. TIGHTEN SCREW ONLY 1/2 THRU PAST CONTACT
WITH STEM
- 10) APPLY SILICON SEALER AROUND SWITCHES TO
PREVENT SHOCK TO SWITCHES.
- 11) ADD ONE DROP OF LOCTITE 290 TO THE SET SCREWS OF
EACH COLLAR.

5	2	2000-2000-0006	2000-STD FLOAT	316L S.S.
4	4	0610-0500-0008	1/2" SHAFT COLLAR	316 S.S.
3	1	3000C3890-0001	SWITCH ASSEMBLY	316/316L
2	1	0199-0908-0500	ADJUSTABLE MOUNTING	316/316L
1	1	5000C3890-0001	STEM/MTG. SUB-ASSEMBLY	316/316L
ITEM	QTY	PART NUMBER	DESCRIPTION, CATALOG NO. OR FINISHED SIZE	MATL

UNLESS OTHERWISE SPECIFIED		MATERIAL #		DRAWN BY: MJR DATE: 6/26/06		INNOVATIVE SOLUTIONS, LLC 20 CHERRY HILL ROAD, NARRAGANSETT, RI 02882-1515	
DIMENSIONS ARE IN INCHES. () ARE IN MM (MILLIMETERS)		FRESH (HSA)		CHNG BY: D.T. DATE: 6/27/06		TITLE: 2 LEVEL S.S. / S.S. FLOAT	
TOLERANCES: Xs: 1 XX±.01 XXX±.005 FRACTIONS ±1/64 ANGLES±30°		HEAT		A-YING BY: D.T. DATE: 6/27/06		L500 LEVEL SENSOR	
MACHINED SURFACES BY RMS		PLATING		PROJECT NO.		SIZE: FSCM NO.	
NEXT ASSY		REMOVE ALL BURRS AND SHARP EDGES		MATERIAL: AS NOTED		UNCL NO. L500C3890-0001	
						B SCALE: 25 SHEET 1 OF 1	

Section III

Operation & Maintenance Plan

EnerVest Operating, LLC (EV)

**BELOW-GRADE TANK
OPERATIONAL REQUIREMENTS**

Rule 19.15.17.12

- A. EV will operate and maintain Below-Grade Tanks to insure the integrity of the below-grade tank, liner, liner system or berms to prevent contamination of fresh water and protect public health and the environment.

EV will not discharge or store any hazardous waste material of any kind in any Below-Grade Tank.

Any penetration of the below-grade below the liquid's surface that may occur, EV shall remove all liquid above the damage or leak line within 48 hours of the discovery. EV shall notify the appropriate district office within 48 hours of the discovery and repair the damage or replace the liner or below-grade tank.

EV will insure the metal retaining walls of the below-grade system around each tank will extend at least 6" above ground level or be equipped with a 6" earthen berm in an effort to divert run-on water around the below-grade system.

- D. EV will insure that a below-grade tank constructed and installed prior to June 16, 2008 that does not meet the requirements of 19.15.17.11 NMAC and does not demonstrate integrity or that the below-grade tank develops any conditions as identified in 19.15.17.12 NMAC shall close the existing below-grade tank pursuant to the closure requirements of 19.15.17.13 NMAC and install a below-grade tank that is in full compliance with our approved design. Please see below-grade system diagram in Appendix 8 for details.

EV will insure all Below-grade tanks will be equipped with automatic high-level alarm which sounds at 24" and than shut off devise to insure that flow will shut off at the freeboard height of 10 1/2 inches.

The majority of our below-grade tanks are within the berm around our tank battery and as so are protected from run-on water. Those outside this berm will be protected with an earthen berm which will extend at least 6" above surface ground level to divert run-on around the tank.

EV will remove any visible or measurable layer of oil from the fluid surface of a below-grade tank.

With any below-grade tank, installed before June 16, 2008, that is retrofitted or replaced with another tank, EV will insure that the soil beneath the removed soil is inspected for wet, discolored, or any other evidence of release, with photographic evidence. EV will report the results of all testing to the division on form C-141 and demonstrate to the division whether the evidence of contamination indicates an imminent threat to fresh water, public health, safety or the environment exists. If the division determines that the contamination does not pose an imminent threat to fresh water, public health, safety or the environment, EV shall complete the retrofit or the replacement of the below-grade tank as per our approved design program as indicated in Appendix 8. If EV or the division determines that the contamination poses an imminent threat to fresh water, public health, safety or the environment, then EV shall close the existing below-grade tank pursuant to the closure requirements of 19.17.15.13 NMAC prior to initiating the retrofit or replacement.

Table 1-1 GSE HD Single Geomembrane

TESTED PROPERTY	TEST METHOD	FREQUENCY	MINIMUM		AVERAGE		VALUE	
			30 mil	40 mil	60 mil	80 mil	100 mil	
Thickness, (minimum average) mil (mm)	ASTM D 5199	every roll	30 (0.75)	40 (1.00)	60 (1.50)	80 (2.00)	100 (2.50)	
Lowest individual reading (-10%)			27 (0.69)	36 (0.91)	54 (1.40)	72 (1.80)	90 (2.30)	
Density, g/cm ³	ASTM D 1505	200,000 lb	0.94	0.94	0.94	0.94	0.94	
Tensile Properties (each direction)	ASTM D 6693, Type IV Dumbell, 2 ipm	20,000 lb						
Strength at Break, lb/in-width (N/mm)			120 (21)	152 (26)	243 (42)	327 (57)	410 (71)	
Strength at Yield, lb/in-width (N/mm)			66 (11)	84 (14)	132 (23)	177 (30)	212 (37)	
Elongation at Break, %	G.L. 2.0 in (51 mm) G.L. 1.3 in (33 mm)		700	700	700	700	700	
Elongation at Yield, %			13	13	13	13	13	
Tear Resistance, lb (N)	ASTM D 1004	45,000 lb	21 (93)	28 (124)	42 (186)	58 (257)	73 (324)	
Puncture Resistance, lb (N)	ASTM D 4833	45,000 lb	65 (289)	85 (378)	125 (556)	160 (711)	195 (867)	
Carbon Black Content, % (Range)	ASTM D 1 603*/421 8	20,000 lb	2.0 - 3.0	2.0 - 3.0	2.0 - 3.0	2.0 - 3.0	2.0 - 3.0	
Carbon Black Dispersion	ASTM D 5596	45,000 lb	Note ⁽¹⁾	Note ⁽¹⁾	Note ⁽¹⁾	Note ⁽¹⁾	Note ⁽¹⁾	
Notched Constant Tensile Load, hr	ASTM D 5397, Appendix	200,000 lb	1000	1000	1000	1000	1000	
Oxidative Induction Time, min	ASTM D 3895, 200°C; O ₂ , 1 atm	200,000 lb	>140	>140	>140	>140	>140	
TYPICAL ROLL DIMENSIONS								
Roll Length ⁽²⁾ , ft (m)			1,120 (341)	870 (265)	560 (171)	430 (131)	340 (104)	
Roll Width ⁽²⁾ , ft (m)			22.5 (6.9)	22.5 (6.9)	22.5 (6.9)	22.5 (6.9)	22.5 (6.9)	
Roll Area, ft ² (m ²)			25,200 (2,341)	19,575 (1,819)	12,600 (1,171)	9,675 (899)	7,650 (711)	

NOTES:

- ⁽¹⁾Dispersion only applies to near spherical agglomerates. 9 of 10 views shall be Category 1 or 2. No more than 1 view from Category 3.
- ⁽²⁾Roll lengths and widths have a tolerance of $\pm 1\%$.
- GSE HD is available in rolls weighing approximately 3,900 lb (1,769 kg).
- All GSE geomembranes have dimensional stability of $\pm 2\%$ when tested according to ASTM D 1204 and LTB of $< -77^{\circ}\text{C}$ when tested according to ASTM D 746.
- *Modified

O.R.E. SYSTEMS
P.O. Box 3677
Farmington, NM 87499
(505) 327-2161

Section IV

Closure Plan

EnerVest Operating, LLC (EV)

**BELOW-GRADE TANK
CLOSURE REQUIREMENTS**

Rule 19.15.17.13

Before June 15, 2013, EV shall close, retrofit, or replace an existing below-grade tank that has not demonstrated integrity.

EV shall close a below-grade tank within the time periods provided in 19.15.17.13 NMAC, or by an earlier date that the division requires because of imminent danger to fresh water, public health or the environment.

- A. EV shall close an existing below-grade tank that does not meet the requirements of Subsection I, paragraphs (1) through (4), of 19.15.17.11 NMAC if not retrofitted to comply with said requirements prior to any sale or change of operator to 19.15.9.9 NMAC.

Any below-grade tank installed prior to June 16, 2008 that is single walled and where any portion of the tank sidewall is below the ground surface and not visible shall equip or retrofit the below-grade tank to comply with paragraphs (1) through (4) of Subsection I of 19.15.17.11 NMAC, or close it, within 5 years after June 16, 2008.

Within 60 days of cessation of the permitted below-grade tanks operation or as required by Subsection B of 19.15.17.17 NMAC, EV shall close the below-grade tank in accordance with a closure plan that the appropriate division district office approves.

- J. Prior to implementing any closure operations EV shall research county tax records to determine the name and address of the surface owner of the properties involved. EV shall notify this surface owner via Certified U.S. Mail, return receipt requested, of their intent to close said below-grade tank.

Upon determination, EV will notify the appropriate district office prior to any closure operations beginning. Such notification shall be at least 72 hours, via U.S. Mail, prior to beginning work but not more than one week prior to beginning work. Such notice shall contain at a minimum the following:

Operators Name
Unit letter, Section, Township, & Range of well
Well name and well number
API Number of well

- E. All free standing liquids and sludge will be removed at the start of the below-grade tank closure process from the below-grade tank and disposed of in one of the below division-approved facility as indicated below:

TNT Land Farm	Permit # NM-01-0008	Liquids & Sludge
Environtech Land Farm	Permit # NM-01-0011	Solids
AguaMoss	Permit # 247130	Liquids

EV will obtain prior approval from the division to dispose, recycle, reuse, or reclaim the below-grade tanks and provide documentation of the final disposition of the below-grade tank in the closure report.

Existing liners that are removed as a result of closure will be wiped cleaned and disposed of at a solid waste facility listed below in compliance with Subparagraph (M) of Paragraph (I) of Subsection C 19.15.35.8 NMAC..

San Juan Regional Landfill	Permit # SWM 052426 or
“	Special Waster Permit # SWM052433 “sp”

If there is any on-site equipment associated with a below-grade tank, EV shall remove the equipment, unless the equipment is required for some other purpose .

Upon removal of the below-grade tank, EV will take, at a minimum, a five point composite sample from where the tank was sitting. EV shall collect individual grab samples will be taken from any area that is wet, discolored or showing other evidence of a release. All samples will be analyzed for the following:

Components	Test Method	Limits (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0.2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418.1	100
Chlorides	EPA 300.1	250 or background, whichever is greater

EV will insure that the results of all sampling shall be reported to the division on approved form C-141. EV understands that the division may require additional delineation upon review of the results.

If sampling demonstrates that concentrations specified above have NOT been exceeded, or that a release has NOT occurred, EV will backfill the excavation with compacted, non-waste containing, earthen material, construct a division prescribed soil cover, and recontour and re-vegetate the site. The division prescribed soil cover, recontouring, and re-vegetation shall comply with 19.15.17.13.

If EV or the division determines that a release has occurred, EV shall fully comply with 19.15.29 NMAC and 19.15.30 NMAC as appropriate.

- G. Once EV has closed a below-grade tank, we shall reclaim the site to a safe and stable condition that blends with the surrounding undisturbed area. When possible, EV will restore the impacted surface area to the condition that existed prior to oil and gas operations by the placement of soil cover.

If the closed area is within the confines of the pad location EV will blend the site to match the pad location as much as possible. Such activities shall prevent erosion, protect fresh water, human health and the environment. EV will obtain written agreement from the surface owner for any alternate re-vegetation proposals and submit to the division for final approval.

- H. The soil cover design will be consistent with the requirements of 19.15.17.13(H)(1) and (3). The soil cover will consist of the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater. The soil cover will be constructed to the site's existing grade and prevent ponding of water and erosion of the cover material.

- I. EV will seed the disturbed areas the first growing season after closing the below grade tank. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will be used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs. During the two growing seasons that prove viability, there shall be no artificial irrigation of the vegetation.

EV shall notify the division when it has seeded or planted and when it successfully achieves re-vegetation by U.S. Mail.

- K. Within 60 days of completion of closure operations, EV will file Form C-144, with attachments, outlining the detailed operations of the closing operations. Such attachments shall include, but not limited to, proof of surface owner and division notifications, confirmation of sampling analysis, disposal facility names and permit numbers, soil backfilling and cover installation, re-vegetation application rates and seeding techniques, and photo documentations.

Section V

Hydrogeology Report

Regional Hydrogeology Report

The San Jose Formation of Eocene age occurs in New Mexico and Colorado, and its outcrop forms the land surface over much of the eastern half of the central San Juan Basin. It overlies the Nacimiento Formation in the area generally south of the Colorado-New Mexico state line and overlies the Animas Formation in the area generally north of the State line.

The San Jose Formation was deposited in various fluvial-type environments. In general, the unit consists of an interbedded sequence of sandstone, siltstone, and variegated shale. Thickness of the San Jose Formation generally increases from west to east, ranging from 200 feet in the west and south to almost 2,700 feet in the center of the structural basin.

Ground water is associated with alluvial and fluvial sandstone aquifers. Therefore the occurrence of ground water is mainly controlled by the distribution of sandstone in the formation. The distribution of such sandstone is the results of original depositional extend plus any post-depositional modifications, namely erosion and structural deformation.

Transmissivity data for the San Jose Formation are minimal. Values of 40 and 120 feet squared per day were determined from two aquifer tests (Stone et al, 1983. table 5). The reported or measured discharge from 46 water wells completed in San Jose Formation ranges from 0.15 to 61 gallons per minute and the median is 5 gallons per minute. Most of the wells provide water for livestock and domestic use.

The San Jose Formation is a very suitable unit for recharge from precipitation because soils that form on the unit are sandy and highly permeable and therefore readily absorb precipitation. However, low annual precipitation, relatively high transpiration and evaporation rates, and deep dissection of the San Jose Formation by the San Juan River and its tributaries all tend to reduce the effective recharge to the unit.

Stone et al., 1983, Hydrogeology and Water Resources of the San Juan Basin, New Mexico; Socorro, New Mexico Bureau of Mines and Mineral Resources Hydrologic Report 6, 70 p.

Site Specific Hydro Geologic Analysis

Jicarilla Contract 148 #32 API 30-039-23655

The above referenced well is located at UL D, Sec 14, 25N, 05W at an elevation of 7002. Surface casing was set to a depth of 334' or at a depth of 6668'.

According to the Office of State Engineer, the closest water well drilled was RG 70162 about 4 miles SE of our location. Drilled to 150 feet at an elevation of 7030, it shows water encountered at 95 feet or at a depth of 6935 or 267 feet below our location.

In 1955, Pan American drilled their Jicarilla Contract 148 #1 (30-039-06039) about 300 feet West of our location. It was at an elevation of 7004 with no indication of water being encountered. Surface casing was set at 165 feet which would be at 6839. This would be 151 feet below our well.

There is a difference of 26 feet in the elevation between the RG 70162 and the #1 well. That same water bearing zone would be at 6978' at the #1 well, which is 310 feet below the casing point of our location.

In 1980, Amoco Production drilled their Jicarilla Contract 148 #24 (30-039-22524) about 300 feet West of our location. It was at an elevation of 7001 with no indication of water being encountered. Surface casing was set at 300 feet which would be at 6701. This would be 33 feet below our well.


The RG 70162 well encountered water at a depth of 6935 feet. However there is a difference of 29 feet in elevation above the #24 well. That would put this same water bearing zone at 6906 at the 24 well, which is 238 feet below the casing point of our location.

Upon researching the OCD on-line files for not only these wells but other wells in the area also, I could not locate any information of the composition of the soils nor did I find any mention of any well encountering water.


The groundwater at our well site should be greater than 100 feet at a minimum. This should allow ample protection for any groundwater in the area.

Appendix 01

U.S. 7.5 Minute TOPO Map



0 500 1000ft



Petroleum Recovery
Research Center

TOPO - Jicarilla Contract 148 #32

Figure: 01


D - Sec 14, 25N, 05W

Jan 07, 2010


API 30-039-23655

Appendix 02

Ground Water Depth



0 2000 4000ft



Petroleum Recovery
Research Center

OSE Water Wells - Jicarilla Contract 148 #32

Figure: 02

D - Sec 14, 25N, 05W

Jan 07, 2010

API 30-039-23655



New Mexico Office of the State Engineer

Water Right Summary



WR File Number: RG 70162

Primary Purpose: DOM 72-12-1 DOMESTIC ONE HOUSEHOLD

Primary Status: PMT PERMIT

Total Acres:

Total Diversion: 3

Owner: RICHARD AND NAOMI CARDENAS

Documents on File

Doc	File/Act	Status			Transaction Desc.	From/To	Acres	Diversion	Consumptive
		1	2	3					
72121	1998-07-06	PMT	LOG	PRC	RG 70162	T		3	

Point of Diversion

(NAD83 UTM in meters)

Pod Number	Source	Q Q Q	64 16 4 Sec Tws Rng	X	Y	Other Location Desc
RG 70162	Shallow			295149	4025729	

The data is furnished by the NMOSE/ISC and is accepted by the recipient with the expressed understanding that the OSE/ISC make no warranties, expressed or implied, concerning the accuracy, completeness, reliability, usability, or suitability for any particular purpose of the data.

**STATE ENGINEER OFFICE
WELL RECORD**

Section 1. GENERAL INFORMATION

(A) Owner of well Richard & Naomi Candinas Owner's Well No. RG-70162
 Street or Post Office Address P.O. Box 4368 NDCBU
 City and State Taos, NM 87571

Well was drilled under Permit No. HC-17909 and is located in the:

a. $\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$ of Section _____ Township _____ Range _____ N.M.P.M.

b. Tract No. _____ of Map No. _____ of the _____

c. Lot No. _____ of Block No. _____ of the _____
 Subdivision, recorded in _____ County.

d. X= 196000 feet, Y= 1950000 feet, N.M. Coordinate System Central Zone in
 the Gijosa Grant.

(B) Drilling Contractor Cisneros well Drilling License No. WD-1398

Address P.O. Box 57, Dursey, NM 87556

Drilling Began 7/8/98 Completed 7/10/98 Type tools 3 conc bit Size of hole 6 3/4 in.

Elevation of land surface or 7030 at well is _____ ft. Total depth of well 150' ft.

Completed well is ☒ shallow ☐ artesian. Depth to water upon completion of well 95' ft.

Section 2. PRINCIPAL WATER-BEARING STRATA

Depth in Feet		Thickness in Feet	Description of Water-Bearing Formation	Estimated Yield (gallons per minute)
From	To			
<u>0-5</u>	<u>5'</u>		<u>Top soil</u>	<u>9 gallons</u>
<u>5'</u>	<u>7'</u>		<u>Clay</u>	
<u>7'</u>	<u>35'</u>		<u>Gravel</u>	
<u>35'</u>	<u>150'</u>		<u>Clay, Gravel, Sand</u>	

Section 3. RECORD OF CASING

Diameter (inches)	Pounds per foot	Threads per in.	Depth in Feet		Length (feet)	Type of Shoe	Perforations	
			Top	Bottom			From	To
<u>4 1/2</u>			<u>0'</u>	<u>150'</u>			<u>110'</u>	<u>150'</u>

Section 4. RECORD OF MUDDING AND CEMENTING

Depth in Feet		Hole Diameter	Sacks of Mud	Cubic Feet of Cement	Method of Placement
From	To				
<u>0'</u>	<u>150'</u>	<u>6 3/4</u>	<u>2 sack</u>		<u>By Hand</u>


Section 5. PLUGGING RECORD

Plugging Contractor _____
 Address _____
 Plugging Method _____
 Date Well Plugged _____
 Plugging approved by: _____


State Engineer Representative

No.	Depth in Feet		Cubic Feet of Cement
	Top	Bottom	
<u>1</u>			
<u>2</u>			
<u>3</u>			
<u>4</u>			

Date Received 10-5-98 FOR USE OF STATE ENGINEER ONLY X= 196,000
 Quad Y= 1,950,000 FSL Central ✓
 File No. RG-70162 Use DOM Location No. Gijosa



0 500 1000ft



Petroleum Recovery
Research Center

Offset Wells - Jicarilla Contract 148 #32

Figure: 2a

D - Sec 14, 25N, 05W

Jan 07, 2010

API 30-039-23655

Hobbs, NM 88240

State of New Mexico
Energy, Minerals & Natural Resources DepartmentForm C-102
Revised August 15, 2000

Al, Artesia, NM 88210

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe NM 87505Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

, Brazos Rd., Aztec, NM 87410

ACTIV

, 040 South Pacheco, Santa Fe, NM 87505

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-039-22524	² Pool Code 72439 / 82329	³ Pool Name Blanco South Pictured Cliffs / Otero Chacra
⁴ Property Code 00740	⁵ Property Name Jicarilla Contract 148	⁶ Well Number 24
⁷ OGRID No. 000778	⁸ Operator Name BP America Production Company	⁹ Elevation 7001'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Unit D	14	25N	5W		945'	North	935'	West	Rio Arriba

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
---------------	---------	----------	-------	---------	---------------	------------------	---------------	----------------	--------

¹² Dedicated Acres 160 PC 160 Ch	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
---	-------------------------------	----------------------------------	-------------------------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

¹⁶ 					¹⁷ OPERATOR CERTIFICATION <i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief</i> Signature Printed Name Cherry Hlava Title Regulatory Analyst Date 02/05/2002
					¹⁸ SURVEYOR CERTIFICATION <i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief</i> July 29, 1980 Date of Survey Signature and Seal of Professional Surveyor Fred B. Kerr Jr. Certificate Number 1950

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

(Form C-104)
(Revised 7/1/52)

06039

REQUEST FOR ~~WELL~~ - (GAS) ALLOWABLE

New Well
~~RECEIVED~~

This form shall be submitted by the operator before an initial allowable will be assigned to any completed Oil or Gas well. Form C-104 is to be submitted in QUADRUPLICATE to the same District Office to which Form C-101 was sent. The allowable will be assigned effective 7:00 A.M. on date of completion or recompletion, provided this form is filed during calendar month of completion or recompletion. The completion date shall be that date in the case of an oil well when oil is delivered into the stock tanks. Gas must be reported on 15.025 psia at 60° Fahrenheit.

Farmington, New Mexico February 22, 1957

(Place)

(Date)

WE ARE HEREBY REQUESTING AN ALLOWABLE FOR A WELL KNOWN AS:

PAN AMERICAN PETROLEUM CORPORATION

(Company or Operator)

Jicarilla

Contract 148

(Lease)

, Well No. 1, in NW 1/4 NW 1/4,

D, Sec. 14, T25N, R. 5W, NMPM, South Blanco-Pictured Cliffs Pool

Unit Letter

Rio Arriba County. Date Spudded 11/21/55, Date Completed 11/30/55

Please indicate location:

D X	C	B	A
E	F	G	H
L	K	J	I
M	N	O	P

Elevation 7004 Total Depth 3315, P.B. 3295

Top gas pay 3248 Name of Prod. Form Pictured Cliffs

Casing Perforations: See below or

Depth to Casing shoe of Prod. String 3315

Natural Prod. Test BOPD

based on bbls. Oil in Hrs. Mins.

Test after acid or shot BOPD

Based on bbls. Oil in Hrs. Mins.

Gas Well Potential 5996 MCFPD

Size choke in inches 2" outlet

Date first oil run to tanks or gas to Transmission system:


Transporter taking Gas: Pacific Northwest Pipeline Corporation

Section 14

Casing and Cementing Record

Size Feet Sax

8-5/8"	165	125
5-1/2"	3315	100
2-3/8"	3233	



Remarks: Includes 3315' of 5 1/2" OD 5.012" ID 14LB Casing; 3233' of 2-3/8" OD 1.995" ID 4.7LB Tubing. Well fracked (three perforations 3249-3256 w/4 shots/ft; 3256-3272 w/2 shots/ft.) with 27,000 gallons water & 30,000 LB sand. Injection rate 42 BPM. Test after frac 5996 MCFPD.

I hereby certify that the information given above is true and complete to the best of my knowledge.

Approved: MAR 8 1957, 19

PAN AMERICAN PETROLEUM CORPORATION
(Company or Operator)
D. J. SCOTT

By: (Signature)

Title: Field Clerk
Send Communications regarding well to:

Name:

Address:

OIL CONSERVATION COMMISSION
Original Signed By:

By:

Title: PETROLEUM ENGINEER DIST. NO. 3

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐
well well
2. NAME OF OPERATOR
ALCO PRODUCTION COMPANY
3. ADDRESS OF OPERATOR
501 Airport Dr., Farmington, N.M. 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 945' FNL x 935' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

- | REQUEST FOR APPROVAL TO: | | SUBSEQUENT REPORT OF: |
|-----------------------------|--------------------------|--------------------------|
| TEST WATER SHUT-OFF | <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON* | <input type="checkbox"/> | <input type="checkbox"/> |
| (other) Spud and Set Casing | | |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 12 1/4" hole on 12-3-80, and drilled to 300'. Set 8 5/8" 24# surface casing at 300' on 12-4-80, and cemented with 315 sx of class "B" neat cement containing 2% CaCl₂. Good cement was circulated to the surface. Drilled a 7 7/8" hole to a depth of 4312'. Set 4 1/2" 10.5# intermediate casing on 12-9-80 at 4312', and cemented with 760 sx of class "B" neat cement containing 65/35 POZ, 6% gel, 2# medium tuf plug per sack, and .8% fluid loss additive. This was tailed in with 100 sx of class "B" neat cement. No cement was circulated to the surface. The rig was released on 12-9-80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Dist. Admin. Supvr DATE 1-19-81

(This space for Federal or State office use)


APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

MOCC


*See Instructions on Reverse Side

Appendix 03

Aerial Photo



0 500 1000ft



Petroleum Recovery
Research Center

Aerial - Jicarilla Contract 148 #32

Figure: 03


D - Sec 14, 25N, 05W

Jan 07, 2010


API 30-039-23655

Appendix 04

Municipality Boundary Map



0 2000 4000ft



Petroleum Recovery
Research Center

Municipalities - Jicarilla Contract 148 #32

Figure: 04

D - Sec 14, 25N, 05W

Jan 07, 2010

API 30-039-23655

Appendix 05

U.S. Fish & Wildlife Wetland Identification Map

Wetlands Map



Legend

Ohio_wet_scan

- 0
- 1
- Out of range

Interstate
Major Roads

- Other Road
- Interstate
- State highway
- US highway

Roads

Cities

USGS Quad Index 24K

Lower 48 Wetland Polygons

- Estuarine and Marine Deepwater
- Estuarine and Marine Wetland
- Freshwater Emergent Wetland
- Freshwater Forested/Shrub Wetland
- Freshwater Pond
- Lake
- Other
- Riverine

Lower 48 Available Wetland Data

Non-Digital

Digital

No Data

Scan

NHD Streams

Counties 100K


States 100K

South America

North America



Scale: 1:8,659




Map center: 36° 24' 17" N, 107° 20' 3" W

This map is a user generated static output from an Internet mapping site and is for general reference only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable. THIS MAP IS NOT TO BE USED FOR NAVIGATION

Appendix 06

FEMA 100-year Floodplain Map



Jicarilla Apache Tribal 151
Floodplain maps not available

Jicarilla Apache Indian Reservation
UNSTUDIED AREA



APPROXIMATE SCALE


2000 0 2000 FEET

NATIONAL FLOOD INSURANCE PROGRAM

FIRM
FLOOD INSURANCE RATE MAP

RIO ARriba COUNTY,
NEW MEXICO
UNINCORPORATED AREAS

PANEL 550 OF 1325
(SEE MAP INDEX FOR PANELS NOT PRINTED)



PANEL LOCATION

COMMUNITY-PANEL NUMBER
350049 0550 B

EFFECTIVE DATE:
JANUARY 5, 1989





Federal Emergency Management Agency

This is an official copy of a portion of the above referenced flood map. It was extracted using F-MIT On-Line. This map does not reflect changes or amendments which may have been made subsequent to the date on the title block. For the latest product information about National Flood Insurance Program flood maps check the FEMA Flood Map Store at www.msc.fema.gov

Appendix 07

Mines, Mills, & Quarries Map



Petroleum Recovery
Research Center

Mines, Mills, Quarries - Jicarilla Contract 148 #32

Figure: 07

D - Sec 14, 25N, 05W

Jan 07, 2010

API 30-039-23655

Appendix 08

**C-102 Location Plat
Facility Inspection Sheet
Below-Grade Tank Diagram**

All distances must be from the outer boundaries of the Section.


Operator AMOCO PRODUCTION COMPANY		Lease JICARILLA CONTRACT 148		Well No. 32
Unit Letter D	Section 14	Township 25N	Range 5W	County Rio Arriba
Actual Footage Location of Well: 880 feet from the North line and 1190 feet from the West line				
Ground Level Elev: 7002	Producing Formation Gallup-Dakota	Pool West Lindrith-Gallup-Dakota	Dedicated Acreage: 160 Acres	

1. Outline the acreage dedicated to the subject well by colored pencil or hatchure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☐ Yes ☒ No If answer is "yes," type of consolidation _____

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) _____

No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.

	<p>8 5/8 @ 334</p> <p>RECEIVED</p> <p>BUREAU OF LAND MANAGEMENT ADMINISTRATIVE SERVICE AREA</p> <p>14</p> <p>RECEIVED</p> <p>JUN 17 1985</p> <p>OIL CON. DIV.</p> <p>DIST. 3</p>

CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Name
B. D. Shaw

Position
Admin. Supervisor

Company
Amoco Production Company

Date
10-29-84

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief.

Date Surveyed
October 7, 1984

Registered Professional Engineer and Land Surveyor
Fred B. Kern Jr.

Certificate No. **4222**

ENERVEST OPERATING LLC

Below Grade Tank
Observed Sitting Requirements

Lease Name & Well Number Jizari 110 Contract 148-32

API No. 3003923655

Observed by Jim Cochran

Date Observed 9-15-09

MEASURED FROM THE BELOW-GRADE TANK: Yes No If not within limits, explain:

Continuously flowing water course > 300 ft. ☐ ☒ 35' South-west of Dry wash

Significant Watercourse, lakebed, sinkhole or
playa lake > 200 feet ☒ ☐ _____

Permanent Residence > 200 feet ☒ ☐ _____

School > 200 feet ☒ ☐ _____

Hospital > 200' ☒ ☐ _____

Institution or Church > 200' ☒ ☐ _____

Private, domestic fresh water well or
spring > 500 feet ☒ ☐ _____

Any other fresh water well or spring > 1000 feet ☒ ☐ _____

Within incorporated municipal boundary of
defined municipal fresh water field ☐ ☒ _____

Wetland area > 500 feet ☒ ☐ _____

Overlying a subsurface mine ☐ ☒ _____


36° 24.33 N 107° 20.04 W

Distance to watercourse or dry wash should be to nearest edge


Please include distance & direction to all waterwells and/or wetland areas

Each Below-Grade Tank needing to be permitted, needs a visual inspection
of the above Criteria as per Rule 19.15.17.10

MATERIAL SEE CHART - ASTM A653 SS GR 50 G115 OIL		BLANK SIZE 46.5 x 116.5		SURFACE AREA		WEIGHT (LBS) see chart			
DESIGN RM		THIS DRAWING IS THE EXCLUSIVE PROPERTY OF VESTEEL AND ALL RIGHTS ARE RESERVED NO PART OF THIS DRAWING MAY BE USED OR REPRODUCED IN ANY MANNER WHATSOEVER WITHOUT WRITTEN PERMISSION FROM VESTEEL, a Division of JENICSYS ENGINEERED PRODUCTS		SCALE nts		DOWN, CY.M.D. 02.02.19		LOCATION WINNIPEG	
DWN. RF				E.C.R. A6647		E.P. NO. 02-255		TYPE ACAD14	
CHKD. BA		DRAWING TITLE CONTAINMENT RING 44" WALL PANEL		SIZE		DRAWING NO.		REV. NO.	
APPD. BA		CUSTOMER		PRINTING DATE		B ES 15510		1	



13 1/2" WALL PANEL LAYOUT BEFORE FLANGING




MANUFACTURING VIEW ONLY - TRIPLE PANEL AFTER
CORR & PUNCH, BEFORE SLITTING & FLANGING

MATERIAL SPECIFICATIONS				
THICKNESS		BLANK WIDTH	WALL SHEET PART NO	WEIGHT (LBS)
NOMINAL	MINIMUM			
0.066	0.061	14.75	CW1357F	31.5


MATERIAL					BLANK SIZE		WEIGHT (LBS)	
SEE CHART - ASTM A653 SS GR50 G115 OIL					46.5x116.5 (3 pcs)		31.5	
THIS DRAWING IS THE EXCLUSIVE PROPERTY OF WESTEEL AND ALL RIGHTS ARE RESERVED. NO PART OF THIS DRAWING MAY BE USED OR REPRODUCED IN ANY MANNER WHATSOEVER WITHOUT WRITTEN PERMISSION FROM Westeel Limited					SCALE	DWN. (Y.M.D.)	LOCATION	
WESTEEL					N.T.S.	2004.11.30	WPG	
DRAWING TITLE: 13.5" FULL PANEL - 57" ONLY CONTAINMENT RING					E.C.R.	E.P. NO.	DVG TYPE	
CUSTOMER					A6834	02-255	A-2000	
PRINTING DATE (Y.M.D.)					SIZE	DRAWING NO.		REV. NO.
-					A	ES 15516		O

NO	DATE	REVISION	E.C.R.	BY	CH.

DIMENSIONS SHOWN ARE IMP	
MM UNITS SHOWN IN BRACKETS	
TOLERANCES (UNLESS OTHERWISE NOTED)	
DIMENSIONS:	
IMPERIAL (in.)	METRIC (mm)
.x ? .1	.x ? .2
.xx ? .03	.x ? 1.0
.xxx ? .010	.xx ? .50
ANGULAR: ± 1°	




44' WALL PANEL AFTER CORRUGATING AND PUNCHING




- MANUFACTURING NOTES:
1. CORRUGATION: SEE DETAIL
 2. HOLE OFF CENTER OF CORR: ± .05
 3. HOLE BURR MAX: .01
 4. CUT OFF BURR MAX: .01
 5. CORNER HOLE TO HOLE DIAGONAL: ± .15

MATERIAL SPECIFICATIONS				
THICKNESS		BLANK WIDTH	WALL SHEET PART NO	WEIGHT (lb)
NOMINAL	MINIMUM			
0.066	0.061	46.5	CW445715F	97.7
0.139	0.130	46.2	CW445710F	208.5

DIMENSIONS SHOWN ARE IMPERIAL UNITS SHOWN IN BRACKETS				TOLERANCES (UNLESS OTHERWISE NOTED)		DIMENSIONS:		MATERIAL		BLANK SIZE		SURFACE AREA		WEIGHT (LBS)	
NO		DATE		REVISION		E.C.R. BY CH.		DESND. BA		46.5 x 116.5		SCALE		DWN. (Y.M.D.)	
								DWN. RF		THIS DRAWING IS THE EXCLUSIVE PROPERTY OF VESTEEL AND ALL RIGHTS ARE RESERVED. NO PART OF THIS DRAWING MAY BE USED OR REPRODUCED IN ANY MANNER WHATSOEVER WITHOUT WRITTEN PERMISSION FROM VESTEEL, a Division of JENISYS ENGINEERED PRODUCTS		DWN. (Y.M.D.) 04.12.01		LOCATION WINNIPEG	
								CHKD. BA		DRAWING TITLE 44' FULL PANEL - 57' ONLY CONTAINMENT RING		E.C.R. A6834		TYPE A-2000	
								APPD. BA		CUSTOMER		PRINTING DATE		REV. NO.	
										SIZE B		DRAWING NO. ES 15518		0	



13 1/2" WALL PANEL LAYOUT BEFORE FLANGING




MANUFACTURING VIEW ONLY - TRIPLE PANEL AFTER
CORR & PUNCH, BEFORE SLITTING & FLANGING

MATERIAL SPECIFICATIONS				
THICKNESS		BLANK WIDTH	WALL SHEET PART NO	WEIGHT (lb)
NOMINAL	MINIMUM			
0.066	0.061	14.75	019419	31.5


				MATERIAL		BLANK SIZE		WEIGHT (LBS.)	
				SEE CHART - ASTM A653 SS GR50 G115 OIL		46.5x116.5 (3 pcs)		31.5	
				DESND.	BA	THIS DRAWING IS THE EXCLUSIVE PROPERTY OF WESTEEL AND ALL RIGHTS ARE RESERVED. NO PART OF THIS DRAWING MAY BE USED OR REPRODUCED IN ANY MANNER WHATSOEVER WITHOUT WRITTEN PERMISSION FROM Westeel Limited		SCALE	N.T.S.
				DWN.	RF	DRAWING TITLE		E.C.R.	A6834
				CHKD.	BA	9.5" FULL PANEL - 52.5" ONLY CONTAINMENT RING		DWN. (Y.M.D.)	2006.08.08
				APPD.	BA	CUSTOMER		E.P. NO.	02-255
						PRINTING DATE (Y.M.D.)		DWG TYPE	A-2000
								SIZE	A
								DRAWING NO.	019419
								REV. NO.	0

NO	DATE	REVISION	E.C.R.	BY	CH

DIMENSIONS SHOWN ARE IMP		MM		UNITS SHOWN IN BRACKETS	
TOLERANCES		(UNLESS OTHERWISE NOTED)		DIMENSIONS:	
IMPERIAL (in.)	METRIC (mm)	IMPERIAL (in.)	METRIC (mm)	IMPERIAL (in.)	METRIC (mm)
.X ? .1	X ? 2	.X ? .1	X ? 2	.X ? .1	X ? 2
.XX ? .03	.X ? 1.0	.XX ? .03	.X ? 1.0	.XX ? .03	.X ? 1.0
.XXX ? .010	.XXX ? .50	.XXX ? .010	.XXX ? .50	.XXX ? .010	.XXX ? .50
ANGULAR ± 1°					



21 1/2' WALL PANEL LAYOUT BEFORE FLANGING




MANUFACTURING NOTES:

1. CORRUGATION..... SEE DETAIL
2. HOLE OFF CENTER OF CORR..... ± .05
3. HOLE BURR MAX..... .01
4. CUT OFF BURR MAX..... .01
5. CORNER HOLE TO HOLE DIAGONAL ± .15


MATERIAL SPECIFICATIONS

THICKNESS	BLANK WIDTH	WALL SHEET PART NO	WEIGHT (lb)
NOMINAL MINIMUM			
0.066 0.061	23.3	C10514	49.4



NO	DATE	REVISION	E.C.R.	BY	CH
1	06/12/06	CORRECTED HOLE PATTERN ON BOTTOM BLANK	A6898	RF	RF


DIMENSIONS SHOWN ARE IMPERIAL UNITS SHOWN IN BRACKETS	
TOLERANCES UNLESS OTHERWISE NOTED	
DIMENSIONS:	
IMPERIAL (in.)	METRIC (mm)
.X # 1	.X # 2
.X # 3	.X # 10
.X # 4	.X # 20
.X # 5	.X # 30
.X # 6	.X # 40
.X # 7	.X # 50
.X # 8	.X # 60
.X # 9	.X # 70
.X # 10	.X # 80
.X # 11	.X # 90
.X # 12	.X # 100
.X # 13	.X # 110
.X # 14	.X # 120
.X # 15	.X # 130
.X # 16	.X # 140
.X # 17	.X # 150
.X # 18	.X # 160
.X # 19	.X # 170
.X # 20	.X # 180
.X # 21	.X # 190
.X # 22	.X # 200
.X # 23	.X # 210
.X # 24	.X # 220
.X # 25	.X # 230
.X # 26	.X # 240
.X # 27	.X # 250
.X # 28	.X # 260
.X # 29	.X # 270
.X # 30	.X # 280
.X # 31	.X # 290
.X # 32	.X # 300
.X # 33	.X # 310
.X # 34	.X # 320
.X # 35	.X # 330
.X # 36	.X # 340
.X # 37	.X # 350
.X # 38	.X # 360
.X # 39	.X # 370
.X # 40	.X # 380
.X # 41	.X # 390
.X # 42	.X # 400
.X # 43	.X # 410
.X # 44	.X # 420
.X # 45	.X # 430
.X # 46	.X # 440
.X # 47	.X # 450
.X # 48	.X # 460
.X # 49	.X # 470
.X # 50	.X # 480
.X # 51	.X # 490
.X # 52	.X # 500
.X # 53	.X # 510
.X # 54	.X # 520
.X # 55	.X # 530
.X # 56	.X # 540
.X # 57	.X # 550
.X # 58	.X # 560
.X # 59	.X # 570
.X # 60	.X # 580
.X # 61	.X # 590
.X # 62	.X # 600
.X # 63	.X # 610
.X # 64	.X # 620
.X # 65	.X # 630
.X # 66	.X # 640
.X # 67	.X # 650
.X # 68	.X # 660
.X # 69	.X # 670
.X # 70	.X # 680
.X # 71	.X # 690
.X # 72	.X # 700
.X # 73	.X # 710
.X # 74	.X # 720
.X # 75	.X # 730
.X # 76	.X # 740
.X # 77	.X # 750
.X # 78	.X # 760
.X # 79	.X # 770
.X # 80	.X # 780
.X # 81	.X # 790
.X # 82	.X # 800
.X # 83	.X # 810
.X # 84	.X # 820
.X # 85	.X # 830
.X # 86	.X # 840
.X # 87	.X # 850
.X # 88	.X # 860
.X # 89	.X # 870
.X # 90	.X # 880
.X # 91	.X # 890
.X # 92	.X # 900
.X # 93	.X # 910
.X # 94	.X # 920
.X # 95	.X # 930
.X # 96	.X # 940
.X # 97	.X # 950
.X # 98	.X # 960
.X # 99	.X # 970
.X # 100	.X # 980
.X # 101	.X # 990
.X # 102	.X # 1000
.X # 103	.X # 1010
.X # 104	.X # 1020
.X # 105	.X # 1030
.X # 106	.X # 1040
.X # 107	.X # 1050
.X # 108	.X # 1060
.X # 109	.X # 1070
.X # 110	.X # 1080
.X # 111	.X # 1090
.X # 112	.X # 1100
.X # 113	.X # 1110
.X # 114	.X # 1120
.X # 115	.X # 1130
.X # 116	.X # 1140
.X # 117	.X # 1150
.X # 118	.X # 1160
.X # 119	.X # 1170
.X # 120	.X # 1180
.X # 121	.X # 1190
.X # 122	.X # 1200
.X # 123	.X # 1210
.X # 124	.X # 1220
.X # 125	.X # 1230
.X # 126	.X # 1240
.X # 127	.X # 1250
.X # 128	.X # 1260
.X # 129	.X # 1270
.X # 130	.X # 1280
.X # 131	.X # 1290
.X # 132	.X # 1300
.X # 133	.X # 1310
.X # 134	.X # 1320
.X # 135	.X # 1330
.X # 136	.X # 1340
.X # 137	.X # 1350
.X # 138	.X # 1360
.X # 139	.X # 1370
.X # 140	.X # 1380
.X # 141	.X # 1390
.X # 142	.X # 1400
.X # 143	.X # 1410
.X # 144	.X # 1420
.X # 145	.X # 1430
.X # 146	.X # 1440
.X # 147	.X # 1450
.X # 148	.X # 1460
.X # 149	.X # 1470
.X # 150	.X # 1480
.X # 151	.X # 1490
.X # 152	.X # 1500
.X # 153	.X # 1510
.X # 154	.X # 1520
.X # 155	.X # 1530
.X # 156	.X # 1540
.X # 157	.X # 1550
.X # 158	.X # 1560
.X # 159	.X # 1570
.X # 160	.X # 1580
.X # 161	.X # 1590
.X # 162	.X # 1600
.X # 163	.X # 1610
.X # 164	.X # 1620
.X # 165	.X # 1630
.X # 166	.X # 1640
.X # 167	.X # 1650
.X # 168	.X # 1660
.X # 169	.X # 1670
.X # 170	.X # 1680
.X # 171	.X # 1690
.X # 172	.X # 1700
.X # 173	.X # 1710
.X # 174	.X # 1720
.X # 175	.X # 1730
.X # 176	.X # 1740
.X # 177	.X # 1750
.X # 178	.X # 1760
.X # 179	.X # 1770
.X # 180	.X # 1780
.X # 181	.X # 1790
.X # 182	.X # 1800
.X # 183	.X # 1810
.X # 184	.X # 1820
.X # 185	.X # 1830
.X # 186	.X # 1840
.X # 187	.X # 1850
.X # 188	.X # 1860
.X # 189	.X # 1870
.X # 190	.X # 1880
.X # 191	.X # 1890
.X # 192	.X # 1900
.X # 193	.X # 1910
.X # 194	.X # 1920
.X # 195	.X # 1930
.X # 196	.X # 1940
.X # 197	.X # 1950
.X # 198	.X # 1960
.X # 199	.X # 1970
.X # 200	.X # 1980
.X # 201	.X # 1990
.X # 202	.X # 2000
.X # 203	.X # 2010
.X # 204	.X # 2020
.X # 205	.X # 2030
.X # 206	.X # 2040
.X # 207	.X # 2050
.X # 208	.X # 2060
.X # 209	.X # 2070
.X # 210	.X # 2080
.X # 211	.X # 2090
.X # 212	.X # 2100
.X # 213	.X # 2110
.X # 214	.X # 2120
.X # 215	.X # 2130
.X # 216	.X # 2140
.X # 217	.X # 2150
.X # 218	.X # 2160
.X # 219	.X # 2170
.X # 220	.X # 2180
.X # 221	.X # 2190
.X # 222	.X # 2200
.X # 223	.X # 2210
.X # 224	.X # 2220
.X # 225	.X # 2230
.X # 226	.X # 2240
.X # 227	.X # 2250
.X # 228	.X # 2260
.X # 229	.X # 2270
.X # 230	.X # 2280
.X # 231	.X # 2290
.X # 232	.X # 2300
.X # 233	.X # 2310
.X # 234	.X # 2320
.X # 235	.X # 2330
.X # 236	.X # 2340
.X # 237	.X # 2350
.X # 238	.X # 2360
.X # 239	.X # 2370
.X # 240	.X # 2380
.X # 241	.X # 2390
.X # 242	.X # 2400
.X # 243	.X # 2410
.X # 244	.X # 2420
.X # 245	.X # 2430
.X # 246	.X # 2440
.X # 247	.X # 2450
.X # 248	.X # 2460
.X # 249	.X # 2470
.X # 250	.X # 2480
.X # 251	.X # 2490
.X # 252	.X # 2500
.X # 253	.X # 2510
.X # 254	.X # 2520
.X # 255	.X # 2530
.X # 256	.X # 2540
.X # 257	.X # 2550
.X # 258	.X # 2560
.X # 259	.X # 2570
.X # 260	.X # 2580
.X # 261	.X # 2590
.X # 262	.X # 2600
.X # 263	.X # 2610
.X # 264	.X # 2620
.X # 265	.X # 2630
.X # 266	.X # 2640
.X # 267	.X # 2650
.X # 268	.X # 2660
.X # 269	.X # 2670
.X # 270	.X # 2680
.X # 271	.X # 2690
.X # 272	.X # 2700
.X # 273	.X # 2710
.X # 274	.X # 2720
.X # 275	.X # 2730
.X # 276	.X # 2740
.X # 277	.X # 2750
.X # 278	.X # 2760
.X # 279	.X # 2770
.X # 280	.X # 2780
.X # 281	.X # 2790
.X # 282	.X # 2800
.X # 283	.X # 2810
.X # 284	.X # 2820
.X # 285	.X # 2830
.X # 286	.X # 2840
.X # 287	.X # 2850
.X # 288	.X # 2860
.X # 289	.X # 2870
.X # 290	.X # 2880
.X # 291	.X # 2890
.X # 292	.X # 2900
.X # 293	.X # 2910
.X # 294	.X # 2920
.X # 295	.X # 2930
.X # 296	.X # 2940
.X # 297	.X # 2950
.X # 298	.X # 2960
.X # 299	.X # 2970
.X # 300	.X # 2980
.X # 301	.X # 2990
.X # 302	.X # 3000
.X # 303	.X # 3010
.X # 304	.X # 3020
.X # 305	.X # 3030
.X # 306	.X # 3040
.X # 307	.X # 3050
.X # 308	.X # 3060
.X # 309	.X # 3070
.X # 310	.X # 3080
.X # 311	.X # 3090
.X # 312	.X # 3100
.X # 313	.X # 3110
.X # 314	.X # 3120
.X # 315	.X # 3130
.X # 316	.X # 3140
.X # 317	.X # 3150
.X # 318	.X # 3160
.X # 319	.X # 3170
.X # 320	.X # 3180
.X # 321	.X # 3190
.X # 322	.X # 3200
.X # 323	.X # 3210
.X # 324	.X # 3220
.X # 325	.X # 3230
.X # 326	.X # 3240
.X # 327	.X # 3250
.X # 328	.X # 3260
.X # 329	.X # 3270
.X # 330	.X # 3280
.X # 331	.X # 3290
.X # 332	.X # 3300
.X # 333	.X # 3310
.X # 334	.X # 3320
.X # 335	.X # 3330
.X # 336	.X # 3340
.X # 337	.X # 3350
.X # 338	.X # 3360
.X # 339	.X # 3370
.X # 340	.X # 3380
.X # 341	.X # 3390
.X # 342	.X # 3400
.X # 343	.X # 3410
.X # 344	.X # 3420
.X # 345	.X # 3430
.X # 346	.X # 3440
.X # 347	.X # 3450
.X # 348	.X # 3460
.X # 349	.X # 3470
.X # 350	.X # 3480
.X # 351	.X # 3490
.X # 352	.X # 3500
.X # 353	.X # 3510
.X # 354	.X # 3520
.X # 355	.X # 3530
.X # 356	.X # 3540
.X # 357	.X # 3550
.X # 358	.X # 3560
.X # 359	.X # 3570
.X # 360	.X # 3580
.X # 361	.X # 3590
.X # 362	.X # 3600
.X # 363	.X # 3610
.X # 364	.X # 3620
.X # 365	.X # 3630
.X # 366	.X # 3640
.X # 367	.X # 3650
.X # 368	.X # 3660
.X # 369	.X # 3670
.X # 370	.X # 3680
.X # 371	.X # 3690
.X # 372	.X # 3700
.X # 373	.X # 3710
.X # 374	.X # 3720
.X # 375	.X # 3730
.X # 376	.X # 3740
.X # 377	.X # 3750
.X # 378	.X # 3760
.X # 379	.X # 3770
.X # 380	.X # 3780
.X # 381	.X # 3790
.X # 382	.X # 3800
.X # 383	.X # 3810
.X # 384	.X # 3820
.X # 385	.X # 3830
.X # 386	.X # 3840
.X # 387	.X # 3850
.X # 388	.X # 3860
.X # 389	.X # 3870
.X # 390	.X # 3880




INSTALLATION INSTRUCTIONS & SITE REQUIREMENTS

1. EXCAVATE AS PER ABOVE
2. FOR BEST RESULTS, BACKFILL WITH CLEAN PEA GRAVEL (OR EQUIVALENT FREE FLOWING MATERIAL) EVENLY AROUND THE STRUCTURE, TAKING CARE NOT TO FILL IN ANY ONE AREA VERY HIGH RELATIVE TO OTHER AREAS, SO AS TO MAINTAIN THE STRUCTURE AS ROUND. WORKING AROUND THE STRUCTURE IN APPROXIMATELY 6" LIFTS IS RECOMMENDED. (NOTE: ALTERNATIVE MATERIALS CAN BE USED BUT CARE MUST BE TAKEN TO INSURE THAT THE EXTERNAL PRESSURES ACTING ON THE STRUCTURE REMAIN UNIFORM. IF NATIVE SOIL IS USED AS A BACKFILL MATERIAL, IT SHOULD BE UNIFORM IN CONSISTENCY, AND BE FREE OF LARGE ROCKS OR UNBROKEN CLUMPS, WHICH COULD RESULT IN UNEVEN LOADING).
3. THE COMPLETED STRUCTURE SHOULD EXTEND APPROXIMATELY 8" ABOVE GRADE
4. TO INSURE STRUCTURAL INTEGRITY, UNEVEN EXTERNAL WALL PRESSURE IS TO BE AVOIDED. NO VEHICLES OR OTHER SOURCES OF POINT LOADING SHOULD BE PERMITTED WITHIN THE EFFECTIVE ZONE (AS ILLUSTRATED).
5. WESTEEL IS NOT LIABLE FOR ANY DAMAGES OR INJURIES RESULTING FROM ANY FAILURE DUE TO IMPROPER INSTALLATION, IMPROPER SITE CONDITIONS, OR INADEQUATE MAINTENANCE OF THE SITE.

NOTE: THIS SYSTEM IS NOT DESIGNED FOR THE SECONDARY CONTAINMENT OF LIQUIDS, RATHER, TO ALLOW FOR INSPECTION OF THE TANK.






ENERVEST OPERATING, LLC

Proposed Alternative Fencing

Below-Grade Tank Construction

42" Hogwire Fence with 2 strands barbed-wire on top






EnerVest Operating, LLC
Western Division

Below-Grade Tank System

Gravity Fed - Produced Water





Below-Grade System Components

Tank Size		Excavation Areas
Capacity	Dia x Height	
125 Bbl	15' x 4'	18' x 18' x 4' Square
120 Bbl	12' x 6'	18' x 4' Circular
100 Bbl	12' x 5'	18' x 5' Circular

Tank size dependent upon water production & road conditions
Excavation Area size dependent upon tank size

Appendix 09

Karst Map



Petroleum Recovery
Research Center

Karst - Jicarilla Contract 148 #32

Figure: 09

D - Sec 14, 25N, 05W

Jan 07, 2010

API 30-039-23655

REFERENCES

Wetland Map:

U. S. Fish and Wildlife Service
National Wetlands Inventory
Wetlands Mapper
www.fws.gov/wetlands/data/mapper

Floodplains map:

Federal Emergency Management Agency
National Flood Insurance Program
FIRM (Flood Insurance Rate Map)
Map Service Center
<http://msc.fema.gov/webapp/wcs/stores/servlet/FemaWelcomeView?storeId=10001&catalogId=10001&langId=-1>

Depth to Ground Water: Individual water well documentation.

State of New Mexico
Office of the State Engineer
New Mexico Water Rights Reporting System
http://www.ose.state.nm.us/waters_db_index.html

Subsurface Mines:

EMNRD
Mining & Minerals Division
Mines, Mills & Quarries Commodity Group
<http://www.emnrd.state.nm.us/MMD/index.htm>

Regional Hydrogeology:

Stone et al., 1983, Hydrogeology and Water Resources of the San Juan Basin, New Mexico; Socorro, New Mexico Bureau of Mines and Mineral Resources Hydrologic Report 6, 70 p.

Base Maps:

Petroleum Recovery Research Center
PRRC PitRule Web Mapping Portal
USGS Topo
TerraServer – US
www.pitrule.source3.com