

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
 Sundry Notices and Reports on Wells

1. Type of Well

Oil Well

2. Name of Operator

Central Resources, Inc., c/o NMOCD Aztec District Office

3. Address & Phone No. of Operator

1000 Rio Brazos Road, Aztec, NM 87410 505-334-6178


4. Location of Well, Footage, Sec., T, R, M

1450' FNL and 1250' FWL, Section 24, T-31-N, R-17-W

2005 APR 6 PM 12 02

RECEIVED

070 FARMINGTON NM



5. **Lease Number**
BIA #14-20-603-2022
6. **If Indian, All. or Tribe Name**
Navajo
7. **Unit Agreement Name**
Horseshoe Gallup
8. **Well Name & Number**
HSGU #287
9. **API Well No.**
30-045-21923
10. **Field and Pool**
Horseshoe Gallup
11. **County & State**
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**Type of Submission**☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment**Type of Action**☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other -☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection**13. Describe Proposed or Completed Operations**

A-Plus Well Service Plugged and Abandoned the above well NMSA 1978, Section 13-1-127, Purchase Agreement: 415210700028; Purchase Document: 05-199-000321.

2/14/05 MOL and RU rig. Check pressures: 0# tubing, 0# casing, 0# bradenhead. ND wellhead. NU BOP. TOH and LD 52 joints 2.875" tubing. PU 47 joints A+ workstring and round trip 5.5" casing scraper to 1485'. TIH with 5.5" DHS CR and set at 1485'. Circulate casing clean with 36 bbls of water.

2/15/05 Pressure test 5.5" casing to 500#, held OK. Plug #1 with CR at 1485', spot 40 sxs Type III cement (53 cf) inside the 5.5" casing above the CR up to 1107' to isolate the Gallup interval. TOH and LD tubing. Plug #2 with 29 sxs Type III cement (38 cf), pumped down the 5.5" casing from 192' to surface, circulate good cement out bradenhead. ND BOP. Dig out and cut off wellhead. Found cement down 20' in 5.5" casing and at the surface in the annulus. Mix 12 sxs cement to fill casing and install P&A marker. RD and MOL. H. Villanueva, NMOCD was on location.

SIGNATURE

William F. Clark

Contractor

February 28, 2005

(This space for Federal or State Office use)

APPROVED BY

Title

CONDITION OF APPROVAL, if any:

 Date
 ACCEPTED FOR RECORD

APR 08 2005

NMOCD

 FARMINGTON FIELD OFFICE
 BY SN