Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED OMB No. 1004-0135 Expires July 31, 1996

5. Lease Serial No.

NMSF - 079365-A

	form for proposals to Use Form 3160-3 (APD			If Indian, Allottee or Tribe I	Vame
SUBMIT IN TRIPL 1. Type of Well	CATE – Other instru	ictions on reverse	e side	. If Unit or CA/Agreement, N ED Lincon Unit NMNM 7	
Oil Well X Gas Well 2. Name of Operator	Other	56		. Well Name and No.	
•	like Pippin LLC (Agen	3b. Phone No. (include	2000	. API Well No. 0-039-27844	
c/o: Pippin, 3104 N. Sullivan, F 4. Location of Well (Footage, Sec., T.	, R., M., or Survey Description	505- \$27-45 73	7. 3 V.	Field and Pool, or Explorato	-
660' FNL 2355' FEL (B) Sec	. 22 12/N RUBVV	A CONTRACTOR	2600	County or Parish, State Arriba County, Nev	v Mexico
12. CHECK APPROPRIATE BOX	K(ES) TO INDICATE NAT	URE OF NOTICE, RE	PORT, OR OTHE	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (Sta	art/Resume)	
Subsequent Report	Casing Repair	New Construction	Recomplete	Other SF	PUD & E & INTER.
Final Abandonment Notice	Change Plans Convert to Injection	Plug and Abandon Plug Back	☐ Temporarily A ☐ Water Disposa		
13. Describe Proposed or Completed Operatic If the proposal is to deepen directionally Attach the Bond under which the work Following completion of the involved operating has been completed. Final Abe determined that the site is ready for final inspe-	or recomplete horizontally, give s will be performed or provide the erations. If the operation results in andonment Notices shall be filed of	subsurface locations and measu Bond No. on file with BLM/ a multiple completion or rec	ured and true vertical of /BIA. Required subseque completion in a new int	depths of all pertinent markers an zent reports shall be filed within terval, a Form 3160-4 shall be fil	d zones 30 days ed once

Spudded 12-1/4" hole @ 11:00 PM on 3/23/05. Drilled to 386'. TIH w/9-5/8" 32.3# H-40 ST&C csg & set @ 386'. Cemented csg w/90 sx (163 cf) PRB-11 cmt w/6% salt, 0.3% Versaset, 2% Calseal, 2% econolite, 5#/sx gilsonite, 0.25#/sx flocele mixed @ 13.5 ppg w/yield of 1.81 cuft/sx. Tail w/100 sx (118 cf) standard Type II cmt w/2% Cacl2, 0.25#/sx flocele mixed @ 15.6 ppg & yield of 1.18 cf/sx. Circ. 17 bbls cmt to pit. Pressure test csg to 500 psi/ for 30 min - OK.

Drilled 8-3/4" hole to 2731'. TIH w/7" 20# J-55 ST&C csg & set @ 2731' on 3/27/05. Cemented csg w/306 sx (685 cf) PremiumPlus Type III cmt w/2% Calseal, 2% Econolite, 6% Salt, 0.3% Versaset, 5#/sx gilsonite, 0.25#/sx Flocele mixed @ 12.5 ppg & yield of 2.24 cf/sx. Tail w/135 sx (244 cf) PremiumPlus Type III cmt w/2% Calseal, 6% salt, 0.3% Versaset, 0.25#/sx Flocele, 5#/sx gilsonite, & 2% Econolite, mixed at 13.5 ppg, & yield of 1.81 cf/sx. Circ. 35 bbls cmt to pit. Pressure test csg to 1000 psi/ for 30 min - OK.

Conditions of approval, if any, are attached. Approval of this notice does no certify that the applicant holds legal or equitable title to those rights in the swhich would entitle the applicant to conduct operations thereon.			FARMINGTUN FIELD UFFICE		
Approved by	Title	Date	APR n 4 2005		
THIS SPA	CE FOR FEDERAL OR ST	TATE USE			
Signature Witho the apin	Date	March 28, 2005	ACCEPTED END RECORD		
Mike Pippin	Petr. Engr. (Agent)				
Name (Printed/Typed)	Title	Title			
14. I hereby certify that the foregoing is true and correct					

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.