RECEIVED

Form 3160-5 (February 2005)

UNITED STATES DEPARTMENT OF THE INTERIOR JUN 14 2012

FORM APPROVED


BUREAU OF LAND MANAGEMENT Farmington Field Office

OMB No. 1004-0137 Expires: March 31, 2007

Bureau of Land Managemerial No.						
SUNDRY NOTICES AND REPORTS ON WELLS			NMSF-078765			
Do not use this form for proposals to drill or to re-enter an			6. If Indian, Allottee or Tribe Name			
abandoned well. Use Form 316	0-3 (APD) for suc	ch proposals.				
SUBMIT IN TRIPLICATI	E – Other instructions	on page 2.	7. If Unit of CA/Agreement, Name and/or No.			
1 Type of Well			Rosa Unit			
			8. Well Name and No.			
	ther		Rosa Unit #60B			
Name of Operator WPX Energy Production, LLC	T		9. API Well No. 30-045-34251			
3a. Address PO Box 640 Aztec, NM 87410	3b. Phone No. (incluation 505-333-1806	le area code)	10 Field and Pool or Exploratory Area BLANCO MV/BASIN MANCOS/BASIN DK			
4. Location of Well (Footage, Sec., T.,R.,M., or Survey			11. Country or Parish, State			
	R6W NMPM		San Juan, NM			
12. CHECK THE APPROPRIATE	E BOX(ES) TO INDICA	TE NATURE OF NOTICE, R	EPORT OR OTH	IER DATA		
TYPE OF SUBMISSION		TYPE OF ACTION				
Notice of Intent Acidize	Deepen	Production (Sta	rt/Resume)	Water Shut-Off		
Alter Casing	Fracture Treat	Reclamation		Well Integrity		
Subsequent Report Casing Repair	New Construction	on Recomplete		Other /Reallocation		
Change Plans	Plug and Aband	on Temporarily Ab	pandon			
Final Abandonment Notice Convert to Injection Plug Back Water Disposal						
all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) WPX ran a completion profiler tool for allocation purposes on the Rosa Unit #060B. Based on the results obtained, WPX proposes the following allocation:						
Mesaverde	37%			Others are the second of the second		
				RCVD JUN 18'12		
Mancos 32%				OIL CONS. DIV.		
Dakota 31%				DIST. 3		
Total	100%					
14. I hereby certify that the foregoing is true and correct Name (<i>Printed/Typed</i>) Ben Mitchell		Title Regulatory Specialist				
Signature & Male						
Signature / E / C / C Date 6/13/2012 THIS SPACE FOR FEDERAL OR STATE OFFICE USE						
Approved by						
Soe Herrit		Title Geo		Date 6-15-12		
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.						
Title 18 U S.C. Section 1001 and Title 43 U.S.C. Section 12 United States any false, fictitious or fraudulent statements of			y to make to any de	epartment or agency of the		

(Instructions on page 2)

Williams Production Company Rosa Unit #60B







Company | Williams Production Company

Well Name | Rosa Unit #60B

Field | Blanco Mesaverde/Basin Dakota

Location | San Juan County, New Mexico

Customer Name | Michael Andrews

Date of Survey | May 11, 2012

Date of Analysis | May 17, 2012

Logging Engineer | Loren Healy

Analyst | Derrick George

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful misconduct on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.





Table of Contents

Survey Objectives
Logging Procedures
Well Information
Tool String
Well Log History
Results
Brief Description of Process
Model Results With Recorded Data
Production Rates At Surface Conditions
Flow Model at Downhole Conditions With Comparison of Theoretical Response to Recorded Data
Overlay of all Log Data
Apparent Fluid Velocity Derived from Spinner
Spinner Calibration Plots Relationship between R.P.S. and Fluid Velocity (fpm)
Well Information
Parameters used for Analysis
Definitions





Survey Objectives

- Identify the source of water production.
- Identify gas producing intervals.
- Quantitative production profile.

Logging Procedures

Date ::	Time	Comment
05/11	07:00	Arrive on location
05/11	06:00	Gauge run start
05/11	07:00	Gauge run stop
05/11	07:38	Program Completion Profile String
05/11	07:58	Start GIH pass
05/11	08:19	Stop GIH pass
05/11	08:20	Start logging passes
05/11	11:54	Stop logging passes
05/11	11:54	Start out of well pass
05/11	12:15	Stop out of well pass
05/11	12:24	Start download
05/11	12:44	Stop download
05/11	13:00	Rig down

Interval Logged:

[From 5,103 to 8,108 ft.]

60 ft/min 90 ft/min 120 ft/min





Well Information

Casing:

5.5" 17.0 lb/ft

surface to 8,224 ft

Tubing:

2.375" 4.7 lb/ft

surface to 4,811 ft

Perforations:

5,105; 5,107; 5,109; 5,172; 5,176; 5,186; 5,189; 5,192; 5,195; 5,217; 5,219; 5,235; 5,237; 5,240; 5,251; 5,254; 5,295; 5,297; 5,320; 5,322; 5,363; 5,367; 5,392; 5,394; 5,398; 5,402; 5,406; 5,409; 5,412; 5,416; 5,422; 5,426; 5,432; 5,439; 5,445; 5,450; 5,453; 5,462; 5,466; 5,470; 5,474; 5,483; 5,487; 5,490; 5,493; 5,511; 5,516; 5,518; 5,520; 5,523; 5,527; 5,531; 5,534; 5,537; 5,541; 5,545; 5,594; 5,596; 5,614; 5,616;

5,620; 5,622; 5,624; 5,628 ft (Stage 9 - Cliff House/Menefee)

5,681; 5,684; 5,689; 5,690; 5,693; 5,696; 5,699; 5,702; 5,711; 5,715; 5,718; 5,721; 5,724; 5,730; 5,733; 5,736; 5,742; 5,751; 5,753; 5,758; 5,762; 5,765; 5,768; 5,771; 5,775; 5,780; 5,784; 5,788; 5,799; 5,806; 5,817; 5,823; 5,829; 5,833; 5,836; 5,844; 5,854; 5,862; 5,864; 5,880; 5,882; 5,885; 5,888; 5,890; 5,898; 5,906; 5,908; 5,914; 5,916; 5,918; 5,924; 5,928; 5,934; 5,938 ft (Stage 8 - Point Lookout)

6,545; 6,560; 6,575; 6,590; 6,605; 6,620; 6,635; 6,650; 6,665; 6,680; 6,695; 6,710; 6,725; 6,740 ft (Stage 7 - Mancos)

6,805; 6,815; 6,825; 6,835; 6,845; 6,855; 6,865; 6,875; 6,885; 6,895 ft (Stage 6 - Mancos)

6,930; 6,940; 6,964; 6,988; 7,008; 7,014; 7,058; 7,064; 7,070; 7,074 ft (Stage 5 - Mancos)

7,150; 7,160; 7,170; 7,190; 7,200; 7,210; 7,250; 7,260; 7,270 ft (Stage 4 - Mancos)

7,415; 7,425; 7,435; 7,445; 7,455; 7,465; 7,485; 7,495; 7,505; 7,515; 7,525; 7,535 ft (Stage 3 - Mancos)

7,670-7,671; 7,673-7,674; 7,676-7,677; 7,679-7,680; 7,682-7,683; 7,685-7,686; 7,687-7,688 ft (Stage 2 - Mancos)

7,920; 7,924; 7,928; 7,932; 7,940; 7,950; 7,960; 7,970; 7,975; 7,980; 7,986; 7,992; 7,997; 8,002; 8,012; 8,022; 8,032; 8,037; 8,042; 8,047; 8,052 ft (Stage 1 - Dakota)





Flowing tubing pressure at the time of logging: 67 - 72 psi

Daily average surface production reported at the time of logging:

gas: 252 - 371 Mscf/d

water: N/A bpd

Tool String

The 1 11/16" Completion Profiler string comprised the following sensors:

Battery housing; RS-232/CCL; Memory/CPU; Gamma Ray; Pressure/Temperature Combo; Centralizer; Induction Collar Locator; Fluid Density; Centralizer; Spinner Flowmeter.

Well Log History

Log Date	Type of Survey
08/04/08	SpectraScan
08/19/08	SpectraScan
08/27/08	SpectraScan
09/11/08	SpectraScan
09/23/08	SpectraScan
10/04/08	SpectraScan
06/22/09	SpectraScan
10/21/09	Completion Profiler
07/01/10	Completion Profiler
06/04/11	Completion Profiler





Results

The following table summarizes the production from each frac stage.

	ts.	6		GAS / WATER PR				745
				Flow Rates	Reported at STI	P		
Zone	Inte	rvals	Q-Gas	Qp-Gas	Percent of	Q-Water	Qp-Water	Percent of
feet			MCFD	MCFD	Total	BFPD	BFPD	Total
Surface	to	5105	395 Mcf/d		100 %	1 bpd		100 %
	, ,	Stage 9	- Cliff House/Mene	efee	20 %	4	To to	14 %
5105	to	5628	395 Mcf/d	77 Mcf/d		1 bpd	0 bpd	
	:	Stąg	e 8 - Point Lookou	t	17 %			29 %
5681	to	5938	318 Mcf/d	68 Mcf/d		1 bpd	0 bpd	
y	,	· · · · · · · · · · · · · · · · · · ·	tage 7 - Mancos		13 %	, , ,	*** ** ***	6 %
6545	to	6740	250 Mcf/d	50 Mcf/d		1 bpd	0 bpd	
	. * .	S	tage 6 - Mancos		0 %		* * * * * * * * * * * * * * * * * * * *	0 %
6805	to	6895	200 Mcf/d	1 Mcf/d		1 bpd	0 bpd	
;	1	` ∴ S	tage 5 - Mancos	, y	0 %	· · · · · · · · · · · · · · · · · · ·	7 H T NO	0 %
6930	to	7074	199 Mcf/d	1 Mcf/d		1 bpd	0 bpd	
		\$	tage 4 - Mancos		0 %		, 10 , Na	0`%
7150	to	7270	199 Mcf/d	1 Mcf/d		1 bpd	0 bpd	
	. 4	, S	tage 3 - Manços	<i>3</i>	13 %		14 1 14 14 14 14 14 14 14 14 14 14 14 14	13 %
7415	to	7535	198 Mcf/d	52 Mcf/d		1 bpd	0 bpd	
	1,	S	tage 2 - Mancos		6%			6%
7670	to	7688	146 Mcf/d	25 Mcf/d		1 bpd	0 bpd	
, , , , , , , , , , , , , , , , , , ,	*, 5,	* . S	tage 1 - Dakota -		31 %	7 - 3 - 5 - 4 - 4 - 5 - 5 - 5 - 5 - 5 - 5 - 5	Calendary Some of the second	
7920	to	8052	122 Mcf/d	122 Mcf/d	† ************************************	0 bpd	0 bpd	1