

Submit Copy to Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

AMENDED

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-045-35315
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator Encana Oil & Gas (USA) Inc.		6. State Oil & Gas Lease No. V-1509
3. Address of Operator 370 17 th Street, Suite 1700 Denver, CO 80202		7. Lease Name or Unit Agreement Name Good Times P32-2410
4. Well Location SHL: Unit Letter <u>P</u> : <u>990</u> feet from the <u>S</u> line and <u>330</u> feet from the <u>E</u> line BHL: Unit Letter <u>M</u> : <u>991</u> feet from the <u>S</u> line and <u>379</u> feet from the <u>W</u> line Section 32 Township 24N Range 10W NMPM San Juan County		8. Well Number 01H
		9. OGRID Number 282327
		10. Pool name or Wildcat South Bisti-Gallup
		CONFIDENTIAL
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6615 GR		

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: **AMENDED** ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Utilized synthetic oil-based mud system., kicked off 4212' lateral at 3948' TVD/MD KOP on 02/19/12. TD reached 02/27/12. TD at 8800' MD/4471' TVD. Set production liner and installed external swellable casing packers on 02/29/12.

Lateral hole diameter: 8.5", production string diameter: 5.5", production string weight and grade 17 ppf I/L80 LTC. Depth of 8.5" hole from 3763' to 8800' MD. Casing shoe set at 8788' MD and float collar set at 8777' MD. Production liner set from 3532' to 8788' MD.

Set 18 external swellable casing packers for isolation of production string at: (1) 8547' (2) 8313' (3) 8080' (4) 7845' (5) 7612' (6) 7377' (7) 7145' (8) 6912' (9) 6678' (10) 6446' (11) 6212' (12) 5978' (13) 5701' (14) 5423' (15) 5144' (16) 4866' (17) 4588' (18) 3781'.

Rig released 03/01/2012.

RCVD JUN 14 '12

OIL CONS. DIV.

Spud Date: 02/09/12

Rig Release Date: 03/01/12

DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Amanda Cavoto TITLE Engineering Technician
Type or print name: Amanda Cavoto E-mail address: amanda.cavoto@encana.com

DATE 06/12/12
PHONE: 720-876-3437

For State Use Only

APPROVED BY: [Signature] TITLE Deputy Oil & Gas Inspector DATE 6/18/12
Conditions of Approval (if any): Av District # 3