District I 1625 N French Dr., Hobbs, NM 88240

District II 1301 W Grand Ave , Artesia, NM 88210

1000 Rio Brazos Rd, Aztec, NM 87410

District 1V

1220 S St Francis Dr , Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

July 21, 2008 For temporary pits, closed-loop sytems, and below-grade tanks, submit to the appropriate NMOCD District Office

Form C-144

For permanent pits and exceptions submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office

Pit, Closed-Loop System, Below-Grade Tank, or			
Proposed Alternative Method Permit or Closure Plan Application			
Type of action. X Permit of a pit, closed-loop system, below-grade tank, or proposed alternative method Closure of a pit, closed-loop system, below-grade tank, or proposed alternative method Modification to an existing permit Closure plan only submitted for an existing permitted or non-permitted pit, closed-loop system, below-grade tank, or proposed alternative method			
Instructions: Please submit one application (Form C-144) per individual pit, closed-loop system, below-grade tank or alternative request Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations of ordinances.			
Operator Burlington Resources Oil & Gas Company, LP OGRID#. 14538 Address: PO Box 4289, Farmington, NM 87499			
Facility or well name SAN JUAN 29-7 UNIT 56C			
API Number OCD Permit Number			
U/L or Qtr/Qtr. P(SE/SE) Section 15 Township: 29N Range 7W County: Rio Arriba Center of Proposed Design Latitude 36.72178 °N Longitude: 107.55312 °W NAD: 1927 x 1983 Surface Owner: x Federal State Private Tribal Trust or Indian Allotment			
Pit: Subsection F or G of 19 15 17 11 NMAC Temporary Drilling Workover OIL CONS. DIV. Permanent Emergency Cavitation P&A Lined Unlined Liner type Thickness mil LLDPE HDPE PVC Other String-Reinforced Liner Seams Welded Factory Other Volume bbl Dimensions L x W x D			
X Closed-loop System: Subsection H of 19 15 17 11 NMAC Type of Operation P&A X Drilling a new well Workover or Drilling (Applies to activities which require prior approval of a permit or notice of intent) X Drying Pad X Above Ground Steel Tanks Haul-off Bins Other X Lined Unlined Liner type Thickness 20 mil X LLDPE HDPE PVD Other			
Liner Seams X Welded X Factory Other .			
Below-grade tank: Subsection I of 19 15 17 11 NMAC Volume bbl Type of fluid Tank Construction material			
Secondary containment with leak detection Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off Visible sidewalls and liner Visible sidewalls only Other Liner Type Fhickness mil HDPE PVC Other			
5 Alternative Method:			
Submittal of an exception request is required Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval			

Form C-144

Oil Conservation Division

Page 1 of 5

Temporary Pits, Emergency Pits and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19 15 17 9 NMAC			
Instructions Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached			
Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19 15 17 9 NMAC			
Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19 15 17 9			
Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC			
Design Plan - based upon the appropriate requirements of 19 15 17 11 NMAC			
Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC			
Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of			
19 15 17 9 NMAC and 19 15 17 13 NMAC			
Previously Approved Design (attach copy of design) API or Permit			
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19 15 17 9 NMAC Instructions Leach of the following items must be attached to the application Please indicate, by a check mark in the box, that the documents are attached Geologic and Hydrogeologic Data (only for on-site closure) - based upon the requirements of Paragraph (3) of Subsection B of 19 15 17 9 Siting Criteria Compliance Demonstrations (only for on-site closure) - based upon the appropriate requirements of 19 15 17 10 NMAC X Design Plan - based upon the appropriate requirements of 19 15 17 11 NMAC			
X Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC			
X Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19 15 17 9			
NMAC and 19 15 17 13 NMAC			
Previously Approved Design (attach copy of design) API			
Previously Approved Operating and Maintenance Plan API			
The readily approved operating and wantenance rain.			
Permanent Pits Permit Application Checklist: Subsection B of 19 15 17 9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report - based upon the requirements of Paragraph (I) of Subsection B of 19 15 17 9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19 15 17 10 NMAC Climatological Factors Assessment Certified Engineering Design Plans - based upon the appropriate requirements of 19 15 17 11 NMAC Dike Protection and Structural Integrity Design based upon the appropriate requirements of 19 15 17 11 NMAC Leak Detection Design - based upon the appropriate requirements of 19 15 17 11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19 15 17 11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19 15 17 12 NMAC Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19 15 17 11 NMAC Nuisance or Hazardous Odors, including H2S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization Monitoring and Inspection Plan			
Erosion Control Plan Closure Plan - based upon the appropriate requirements of Subsection C of 19 15 17 9 NMAC and 19 15 17 13 NMAC			
Proposed Closure: 19 15 17 13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan. Type Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Closed-loop System Alternative Proposed Closure Method Waste Excavation and Removal X Waste Removal (Closed-loop systems only) On-site Closure Method (only for temporary pits and closed-loop systems) In-place Burial On-site Trench Alternative Closure Method (Exceptions must be submitted to the Santa Fe Environmental Bureau for consideration)			
15			
Waste Excavation and Removal Closure Plan Checklist: (19 15 17 13 NMAC) Instructions: Each of the following items must be attached to the closure plan			
Please indicate, by a check mark in the box, that the documents are attached. Protocols and Procedures - based upon the appropriate requirements of 19 15 17 13 NMAC			
Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection F of 19 15 17 13 NMAC			
Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings)			
Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19 15 17 13 NMAC			
Re-vegetation Plan - based upon the appropriate requirements of Subsection I of 19 15 17 13 NMAC			
Site Reclamation Plan - based upon the appropriate requirements of Subsection G of 19 15 17 13 NMAC			
1 Lat and a second their concerning the physical requirements of proposition of the 17 15 11/11/10			

Form C-144 Oil Conservation Division Page 3 of 5

19 Operator Application Certification:			
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief			
Name (Print) Iamie Goodwin Title Regulatory Technician			
Signature (1000WI) Date 4/9/12			
e-mail address Jamie I goodwin@conocophillips com Telephone 1 \$05-326-9784			
20 OCD Approval. Permit Application (including closure plan) Closure Plan (only) OCD Conditions (see attachment) OCD Representative Signature: Approval Date: 4/2/2512			
Title: OM Jauce Office Och Permit Number:			
Closure Report (required within 60 days of closure completion): Subsection K of 19 15 17 13 NMAC Instructions Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed Closure Completion Date:			
Closure Method: Waste Excavation and Removal On-site Closure Method Alternative Closure Method Waste Removal (Closed-loop systems only) If different from approved plan, please explain			
23			
Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only. Instructions Please identify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities			
were utilized Disposal Facility Name Disposal Facility Permit Number			
Disposal Facility Name Disposal Facility Permit Number			
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations?			
Yes (If yes, please demonstrate compliane to the items below)			
Required for impacted areas which will not be used for future service and operations			
Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation			
Re-vegetation Application Rates and Seeding Technique			
24			
Closure Report Attachment Checklist: Instructions. Each of the following items must be attached to the closure report. Please indicate, by a check mark in the box, that the documents are attached.			
Proof of Closure Notice (surface owner and division)			
Proof of Deed Notice (required for on-site closure)			
Plot Plan (for on-site closures and temporary pits)			
Confirmation Sampling Analytical Results (if applicable)			
Waste Material Sampling Analytical Results (if applicable)			
Disposal Facility Name and Permit Number			
Soil Backfilling and Cover Installation Re-vegetation Application Rates and Seeding Technique			
Site Reclamation (Photo Documentation)			
On-site Closure Location Latitude Longitude NAD 1927 1983			
Operator Closure Certification: I hereby certify that the information and attachments submitted with this closure report is tine, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.			
Name (Print) Title			
Signature Date			
e-mail address Telephone			

Burlington Resources Oil & Gas Company, LP

Closed Loop Design:

The closed loop design will not incorporate a temporary pit or below grade tank. The plan will utilize an above grade tank suitable for holding the cuttings and fluids generated during drilling operations. The volume of the tank shall be of a sufficient volume to maintain an adequate free board for periodic removal and disposal of cuttings and fluids.

Burlington Resources Oil & Gas Company, LP may incorporate the use of a 20 mil, string reinforced, LLDPE liner with factory welded seams to line the drying pad in order to minimize the volume of fluids to be disposed of. The drying pad will be designed to prevent contamination of fresh water, protect public health and the environment, and have sumps to facilitate the collection of liquids derived from drilling cuttings, as specified per subsection H of 19 15 17 11. The cuttings pad will be constructed above grade and containment will be through the use of earthen berms of sufficient height to contain the cuttings and prevent run-off of surface water or fluids. The drying pad area will replace the area of the drill site previously designated for the reserve pit. It will be signed in compliance with 19 15 3.103 NMAC. Frac tanks will be utilized on site for fresh water storage.

Closed Loop Operations and Maintenance:

The closed loop system will be operated and maintained for solids and liquid containment to prevent ground water contamination as follows

- 1 Any free liquids will be recovered and reused or disposed of at the Basin Disposal Facility (Permit # NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) Reuse may include the relocating of liquids to be used in other permitted drilling operations
- 2 Drill solids will be recovered from location and hauled to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) periodically as required to maintain a safe free board in the cuttings tank. No onsite trench burial of cuttings will occur.
- In the event a drying pad is utilized, the cuttings will be picked up and transported to Basin Disposal Facility (Permit #NM-01-005) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit # NM-01-0010B) The liner will be disposed of at the San Juan County Landfill located on CR 3100 The drying pad will be closed within 6 months from the date that the drilling rig is released Berms constructed from native materials will be bladed on site to the location's contour
- 4 Any drilling materials or trash will be stored and disposed of appropriately
- The NMOCD will be notified within 48 hours of the discovery of compromised integrity of the closed loop containment. Any required repairs will commence immediately

Closed Loop Closure Plan:

Upon completion of the drilling operations, all solids and liquids will be removed and disposed of to Envirotech (Permit #NM-01-0011) and/or Basin Disposal Facility (Permit #NM-01-005) and/or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) Equipment shall also be removed from location. In the event a drying pad is utilized, the solids contained on the pad shall remain on site to allow sufficient drying and will then be transported to Envirotech (Permit #NM-01-0011) or JFJ Landfarm % Industrial Ecosystem Inc. (Permit #NM-01-0010B) within 6 months from the date that the drilling rig is released

2 After the drying pad is removed the surface below will be visually inspected for any contamination. If contamination is discovered a five point composite sample will be taken of the drying pad area using sampling tools and all samples tested per Subsection B of 19.15.17.13(B)(1)(b). In the event that the criteria are not met, all contents will be handled per Subparagraph (a) of Paragraph (1) of Subsection B of 19.15.17.13 i.e., Dig and haul

Components	Tests Method	Limit (mg/Kg)
Benzene	EPA SW-846 8021B or 8260B	0 2
BTEX	EPA SW-846 8021B or 8260B	50
TPH	EPA SW-846 418 1	2500
GRO/DRO	EPA SW-846 8015M	500
Chlorides	EPA 300 1	500

- Re-contouring of location will match fit, shape, line, form and texture of the surrounding Re-shaping will include drainage control, prevent ponding, and prevent erosion. Natural drainages will be unimpeded and water bars and/or silt traps will be place in areas where needed to prevent erosion on a large scale. Final re-contour shall have a uniform appearance with smooth surface, fitting the natural landscape.
- 4 Notification will be sent to OCD when the reclaimed area is seeded
- BR shall seed the disturbed areas the first growing season after the operator closes the drying pad. Seeding will be accomplished via drilling on the contour whenever practical or by other division-approved methods. BLM or Forest Service stipulated seed mixes will used on federal lands. Vegetative cover will equal 70% of the native perennial vegetative cover (un-impacted) consisting of at least three native plant species, including at least one grass, but not including noxious weeds, and maintain that cover through two successive growing seasons. Repeat seeding or planting will be continued until successful vegetative growth occurs.

Туре	Variety or Cultivator	PLS/A
Western wheatgrass	Arrıba	3 0
Indian ricegrass	Paloma or Rımrock	3 0
Slender wheatgrass	San Luis	2 0
Crested wheatgrass	Hy-crest	3 0
Bottlebrush Squirreltail	Unknown	20
Four-wing Saltbrush	Delar	25

Species shall be planted in pounds of pure live seed per acre: Present Pure Live Seed (PLS) = Purity X Germination/100 Two lots of seed can be compared on the basis of PLS as follows:

Source No One (poor quality)
Purity
50 percent
Germination
40 percent
Percent PLS
20 percent

Source No two (better quality)
Purity
80 percent
Germination
63 percent
Percent PLS
50 percent

5 lb. bulk seed required to make 2 lb. bulk seed required to make

1 lb. PLS 1 lb. PLS